



MOSEK Command Line Tools

Release 8.0.0.94

MOSEK ApS

2017

1	Introduction	1
1.1	Why the Command Line Tools?	1
1.2	License agreement	1
2	Installation	3
3	The Command Line Tool	5
3.1	Introduction	5
3.2	Command Line Example	5
3.3	Command Line Arguments	8
3.4	The Parameter File	10
4	The MOSEK-bundled AMPL shell	11
4.1	Invoking the AMPL shell	11
4.2	An example	11
4.3	Determining the outcome of an optimization	13
4.4	Optimizer options	14
4.5	Constraint and variable names	14
4.6	Which solution is returned to AMPL	15
4.7	Hot-start	15
4.8	The infeasibility report	17
4.9	Sensitivity analysis	17
4.10	Using the command line version of the AMPL interface	18
5	Problem Formulation and Solutions	21
5.1	Linear Optimization	21
5.2	Conic Quadratic Optimization	24
5.3	Semidefinite Optimization	26
5.4	Quadratic and Quadratically Constrained Optimization	28
5.5	General Convex Optimization	29
6	The Optimizers for Continuous Problems	31
6.1	Presolve	31
6.2	Linear Optimization	33
6.3	Conic Optimization	39
6.4	Nonlinear Convex Optimization	40
6.5	Using Multiple Threads in an Optimizer	41
7	The Optimizer for Mixed-integer Problems	43
7.1	Some Concepts and Facts Related to Mixed-integer Optimization	43
7.2	The Mixed-integer Optimizer	44
7.3	Termination Criterion	44
7.4	Parameters Affecting the Termination of the Integer Optimizer.	45
7.5	How to Speed Up the Solution Process	45
7.6	Understanding Solution Quality	46

8	Problem Analyzer	47
8.1	General Characteristics	48
8.2	Objective	49
8.3	Linear Constraints	49
8.4	Constraint and Variable Bounds	50
8.5	Quadratic Constraints	50
8.6	Conic Constraints	50
9	Analyzing Infeasible Problems	51
9.1	Example: Primal Infeasibility	51
9.2	Locating the cause of Primal Infeasibility	52
9.3	Locating the Cause of Dual Infeasibility	52
9.4	The Infeasibility Report	53
9.5	Theory Concerning Infeasible Problems	56
9.6	The Certificate of Primal Infeasibility	56
9.7	The certificate of dual infeasibility	57
10	Sensitivity Analysis	61
10.1	Sensitivity Analysis for Linear Problems	61
10.2	Sensitivity Analysis with MOSEK	67
11	API Reference	71
11.1	Parameters	71
11.2	Response codes	119
11.3	Enumerations	140
12	Supported File Formats	167
12.1	The LP File Format	168
12.2	The MPS File Format	173
12.3	The OPF Format	185
12.4	The CBF Format	194
12.5	The XML (OSiL) Format	209
12.6	The Task Format	209
12.7	The JSON Format	209
12.8	The Solution File Format	216
13	Interface changes	219
13.1	Compatibility	219
13.2	Parameters	219
13.3	Constants	221
13.4	Response Codes	225
	Bibliography	227
	API Index	229

INTRODUCTION

The **MOSEK** Optimization Suite 8.0.0.94 is a powerful software package capable of solving large-scale optimization problems of the following kind:

- linear,
- convex quadratic,
- conic quadratic (also known as second-order cone),
- semidefinite,
- and general convex.

Integer constrained variables are supported for all problem classes except for semidefinite and general convex problems. In order to obtain an overview of features in the **MOSEK** Optimization Suite consult the [product introduction](#) guide.

1.1 Why the Command Line Tools?

The **MOSEK** capabilities can be accessed from the command line without the need to use any programming language. The user can input optimization problems using files in a variety of *formats*, or via the AMPL language shell.

1.2 License agreement

Before using the **MOSEK** software, please read the license agreement available in the distribution at <MSKHOME>/mosek/8/mosek-eula.pdf or on the **MOSEK** website <https://mosek.com/sales/license-agreement>.

MOSEK uses some third-party open-source libraries. Their license details follows.

zlib

MOSEK includes the *zlib* library obtained from the [zlib website](#). The license agreement for *zlib* is shown in [Listing 1.1](#).

Listing 1.1: *zlib* license.

```
zlib.h -- interface of the 'zlib' general purpose compression library
version 1.2.7, May 2nd, 2012

Copyright (C) 1995-2012 Jean-loup Gailly and Mark Adler

This software is provided 'as-is', without any express or implied
warranty. In no event will the authors be held liable for any damages
```

arising from the use of this software.

Permission is granted to anyone to use this software for any purpose, including commercial applications, and to alter it and redistribute it freely, subject to the following restrictions:

1. The origin of this software must not be misrepresented; you must not claim that you wrote the original software. If you use this software in a product, an acknowledgment in the product documentation would be appreciated but is not required.
2. Altered source versions must be plainly marked as such, and must not be misrepresented as being the original software.
3. This notice may not be removed or altered from any source distribution.

Jean-loup Gailly
jloup@gzip.org

Mark Adler
madler@alumni.caltech.edu

fplib

MOSEK includes the floating point formatting library developed by David M. Gay obtained from the [netlib website](#). The license agreement for *fplib* is shown in [Listing 1.2](#).

Listing 1.2: *fplib* license.

```
/*
 *
 * The author of this software is David M. Gay.
 *
 * Copyright (c) 1991, 2000, 2001 by Lucent Technologies.
 *
 * Permission to use, copy, modify, and distribute this software for any
 * purpose without fee is hereby granted, provided that this entire notice
 * is included in all copies of any software which is or includes a copy
 * or modification of this software and in all copies of the supporting
 * documentation for such software.
 *
 * THIS SOFTWARE IS BEING PROVIDED "AS IS", WITHOUT ANY EXPRESS OR IMPLIED
 * WARRANTY. IN PARTICULAR, NEITHER THE AUTHOR NOR LUCENT MAKES ANY
 * REPRESENTATION OR WARRANTY OF ANY KIND CONCERNING THE MERCHANTABILITY
 * OF THIS SOFTWARE OR ITS FITNESS FOR ANY PARTICULAR PURPOSE.
 */
```

INSTALLATION

After installing **MOSEK** Optimization Suite as described in the [Installation Guide](#) then the command line tool is ready for use.

THE COMMAND LINE TOOL

3.1 Introduction

The **MOSEK** command line tool is used to solve optimization problems from the operating system command line. It is invoked as follows

```
mosek [options] [filename]
```

where both [options] and [filename] are optional arguments:

- [options] consists of command line arguments that modify the behavior of **MOSEK**. They are listed in Section 3.3.
- filename is a file describing the optimization problem. The **MOSEK** command line accepts files in any of the *supported file formats* or in the AMPL *nl* file.

If no arguments are given, **MOSEK** will return its version and platform, i.e.

```
andrea@Bistrup:~$ mosek/8/tools/platform/linux64x86/bin/mosek

MOSEK Version 8.0.0.32(BETA) (Build date: 2016-7-12 10:29:26)
Copyright (c) MOSEK ApS, Denmark. WWW: mosek.com
Platform: Linux/64-X86

*** No input file specified. No optimization is performed.

Return code - 0 [MSK_RES_OK]
```

3.2 Command Line Example

In this section there are some examples on how to use the **MOSEK** command line. Please refer to Section 3.3 for the complete list of available command line options.

3.2.1 Solve an Optimization Problem

The simplest case is to solve a problem stored in file, say `lo1.mps`:

```
mosek lo1.mps
```

The solver will

- read `lo1.mps` from disk,
- solve the problem and
- store the relevant solution files (see 12.8) if any solution exists.

These steps are clear from the solver output in the following listing.

```

MOSEK Version 8.0.0.34(BETA) (Build date: 2016-8-24 00:51:13)
Copyright (c) MOSEK ApS, Denmark. WWW: mosek.com
Platform: Linux/64-X86

Open file '/home/andrea/mosek/8/tools/examples/data/lo1.mps'
Reading started.
Using 'obj' as objective vector
Read 13 number of A nonzeros in 0.00 seconds.
Using 'rhs' as rhs vector
Using 'bound' as bound vector
Reading terminated. Time: 0.00

Read summary
  Type           : LO (linear optimization problem)
  Objective sense : max
  Scalar variables : 4
  Matrix variables : 0
  Constraints      : 3
  Cones           : 0
  Time            : 0.0

Problem
  Name           : lo1
  Objective sense : max
  Type           : LO (linear optimization problem)
  Constraints     : 3
  Cones          : 0
  Scalar variables : 4
  Matrix variables : 0
  Integer variables : 0

Optimizer started.
Interior-point optimizer started.
Presolve started.
Linear dependency checker started.
Linear dependency checker terminated.
Eliminator started.
Freed constraints in eliminator : 0
Eliminator terminated.
Eliminator - tries          : 1           time           : 0.00
Lin. dep. - tries          : 1           time           : 0.00
Lin. dep. - number         : 0
Presolve terminated. Time: 0.00
Optimizer - threads         : 2
Optimizer - solved problem  : the primal
Optimizer - Constraints     : 3
Optimizer - Cones          : 0
Optimizer - Scalar variables : 6           conic           : 0
Optimizer - Semi-definite variables: 0       scalarized        : 0
Factor - setup time        : 0.00         dense det. time   : 0.00
Factor - ML order time     : 0.00         GP order time     : 0.00
Factor - nonzeros before factor : 6       after factor      : 6
Factor - dense dim.        : 0           flops             : 1.06e+02
ITE PFEAS   DFEAS   GFEAS   PRSTATUS   POBJ          DOBJ          MU          TIME
0  8.0e+00  3.2e+00  3.5e+00  1.00e+00  1.000000000e+01  0.000000000e+00  1.0e+00  0.01
1  4.2e+00  2.5e+00  4.7e-01  0.00e+00  3.093970927e+01  2.766058702e+01  2.6e+00  0.01
2  4.2e-01  2.5e-01  4.6e-02  -1.82e-02  6.511676243e+01  6.308843559e+01  2.6e-01  0.01
3  3.6e-02  2.1e-02  3.9e-03  5.84e-01  8.096141239e+01  8.061962333e+01  2.2e-02  0.01
4  1.5e-05  9.1e-06  1.7e-06  9.43e-01  8.333280389e+01  8.333241803e+01  9.2e-06  0.01
5  1.5e-09  9.1e-10  1.7e-10  1.00e+00  8.333333328e+01  8.333333324e+01  9.2e-10  0.01
Basis identification started.

```

```

Primal basis identification phase started.
ITER      TIME
0         0.00
Primal basis identification phase terminated. Time: 0.00
Dual basis identification phase started.
ITER      TIME
0         0.00
Dual basis identification phase terminated. Time: 0.00
Basis identification terminated. Time: 0.00
Interior-point optimizer terminated. Time: 0.01.

Optimizer terminated. Time: 0.02

Interior-point solution summary
  Problem status : PRIMAL_AND_DUAL_FEASIBLE
  Solution status : OPTIMAL
  Primal.  obj: 8.3333333280e+01    nrm: 5e+01    Viol.  con: 1e-08    var: 0e+00
  Dual.    obj: 8.3333333242e+01    nrm: 4e+00    Viol.  con: 2e-10    var: 5e-09

Basic solution summary
  Problem status : PRIMAL_AND_DUAL_FEASIBLE
  Solution status : OPTIMAL
  Primal.  obj: 8.3333333333e+01    nrm: 5e+01    Viol.  con: 7e-15    var: 0e+00
  Dual.    obj: 8.3333333245e+01    nrm: 4e+00    Viol.  con: 2e-10    var: 5e-09

Optimizer summary
Optimizer          -                time: 0.02
  Interior-point    - iterations : 5      time: 0.01
    Basis identification -          time: 0.00
      Primal        - iterations : 0      time: 0.00
      Dual          - iterations : 0      time: 0.00
      Clean primal   - iterations : 0      time: 0.00
      Clean dual     - iterations : 0      time: 0.00
  Simplex          -                time: 0.00
    Primal simplex   - iterations : 0      time: 0.00
    Dual simplex     - iterations : 0      time: 0.00
    Mixed integer    - relaxations: 0      time: 0.00

Open file '/home/andrea/mosek/8/tools/examples/data/lo1.sol'
Start writing.
done writing. Time: 0.00

Open file '/home/andrea/mosek/8/tools/examples/data/lo1.bas'
Start writing.
done writing. Time: 0.00

Return code - 0  [MSK_RES_OK]

```

3.2.2 Change a Solver Parameter

Using the `-d` option it is possible to set the solver parameters. The next command shows how to switch off the presolver and solve a problem stored in a file called `lo1.opf`.

```
mosek -d MSK_IPAR_PREOLVE_USE MSK_OFF lo1.opf
```

If multiple parameters must be specified, option `-d` must be repeated for each one. For instance say also the time limit must be set:

```
mosek -d MSK_IPAR_PREOLVE_USE MSK_OFF -d MSK_DPAR_OPTIMIZER_MAX_TIME 1.0 lo1.opf
```

Please refer to [11.1.1](#) for the complete list of available solver parameters.

3.2.3 Convert a File

The **MOSEK** command line can also be used to convert between two file formats supported by **MOSEK**. This can be achieved using the `-out` option. Moreover using `-x` the solver will not actually solve the problem.

Warning: The target file type must support the problem type of the source file, otherwise the conversion will be partial.

For instance in case a MPS file must be converted in a more readable OPF format, the following line can be used

```
mosek -x -out lo1.opf lo1.mps
```

The output produced is

```
MOSEK Version 8.0.0.34(BETA) (Build date: 2016-8-24 00:51:13)
Copyright (c) MOSEK ApS, Denmark. WWW: mosek.com
Platform: Linux/64-X86

Open file '/home/andrea/mosek/8/tools/examples/data/lo1.mps'
Reading started.
Using 'obj' as objective vector
Read 13 number of A nonzeros in 0.00 seconds.
Using 'rhs' as rhs vector
Using 'bound' as bound vector
Reading terminated. Time: 0.01

Read summary
  Type           : LO (linear optimization problem)
  Objective sense : max
  Scalar variables : 4
  Matrix variables : 0
  Constraints      : 3
  Cones           : 0
  Time            : 0.0

Open file 'lo1.opf'
Start writing.
done writing. Time: 0.00

Return code - 0  [MSK_RES_OK]
```

Note: The output clearly shows how the solver does not actually solve the given problem.

3.3 Command Line Arguments

The following list shows the available command-line arguments for **MOSEK**:

- `-anapro`
Analyze the problem data.
- `-anasoli <name>`
Analyze the initial solution name e.g. `-anasoli bas`.
- `-anasolo <name>`
Analyze the final solution name e.g. `-anasolo itg`.

- a
 MOSEK is started in AMPL mode.
- basi <name>
 Input basis solution file name.
- baso <name>
 Output basis solution file name.
- d <name> <value>
 Define the value **value** for the **MOSEK** parameter **name**.
- dbgmem <name>
 Name of memory debug file.
- f
 Complete license information is printed.
- h, -?
 Help.
- inti <name>
 Input integer solution file name.
- into <name>
 Output integer solution file name.
- itri <name>
 Input interior point solution file name.
- itro <name>
 Output interior point solution file name.
- info <name>
 Infeasible subproblem output file name.
- infrepo <name>
 Feasibility reparation output file.
- l, -L <dir>
 dir is the directory where the **MOSEK** license file is located (typically named `mosek.lic`).
- max
 The problem is maximized.
- min
 The problem is minimized.
- n
 Ignore errors in subsequent parameter settings.
- out <name>
 Write the task to a data file named *name*. See Section 12.
- p <name>, -pari <name>
 Name of the input parameter file.
- paro <name>
 Name of the output parameter file.
- r
 If the option is present, the program returns -1 if an error occurred otherwise 0.
- removeitg
 Removes all integer constraints after reading the problem.
- rout <name>
 If the option is present, the program writes the return code to file *name*.

- q <name>
Name of a optional log file.
- sen <file>
Perform sensitivity analysis based on file.
- silent
As little information as possible is send to the terminal.
- toconic
Translate to conic form after reading.
- v
MOSEK version is printed and no optimization is performed.
- w
If this options is on, then **MOSEK** will wait for a license.
- x
Do not run the optimizer. Useful for converting between file formats.
- List all possible parameters.

3.4 The Parameter File

Occasionally system or algorithmic parameters in **MOSEK** should be changed be the user. One way of changing parameters is to use a so-called parameter file which is a plain text file. It can for example can have the format

```
BEGIN MOSEK
% This is a comment.
% The subsequent line tells MOSEK that an optimal
% basis should be computed by the interior-point optimizer.
MSK_IPAR_INTPNT_BASIS      MSK_BI_ALWAYS
MSK_DPAR_INTPNT_TOL_PFEAS  1.0e-9
END MOSEK
```

Note that the file begins with the line `BEGIN MOSEK` and is terminated with the line `END MOSEK`, this is required. Moreover, everything that appears after an `%` is considered to be a comment and is ignored. Similarly, empty lines are ignored. The important lines are those which begins with a valid **MOSEK** parameter name such as `MSK_IPAR_INTPNT_BASIS`. Immediately after parameter name follows the new value for the parameter. All the **MOSEK** parameter names are listed in Section 11.1.

Using the parameter file

The parameter file can be given any name, but let us assume it has the name `mosek.par`. If **MOSEK** should use the parameter settings in that file, then `-p` should be on the command line when **MOSEK** is invoked. An example of such a command line is

```
mosek -p mosek.par afiro.mps
```

Command-line parameters override those from the parameter file in case of repetition. For instance

```
mosek -p mosek.par -d MSK_IPAR_NUM_THREAD 1 -d MSK_DPAR_INTPNT_TOL_PFEAS 1.0e-8 afiro.mps
```

will set the `MSK_IPAR_NUM_THREADS` parameter to one, while the the `MSK_DPAR_INTPNT_TOL_PFEAS` will be set to 10^{-8} , using the value provided on the command line.

f.. _doc.cmd.ampl:

THE MOSEK-BUNDLED AMPL SHELL

AMPL is a modeling language for specifying linear and nonlinear optimization models in a natural way. AMPL also makes it easy to solve the problem and e.g. display the solution or part of it.

We will not discuss the specifics of the AMPL language here but instead refer the reader to [FGK03], <http://ampl.com/BOOK/download.html> and the AMPL website <http://www.ampl.com>.

AMPL cannot solve optimization problems by itself but requires a link to an appropriate optimizer such as **MOSEK**. The **MOSEK** distribution includes

- an AMPL link which makes it possible to use **MOSEK** as an optimizer within AMPL,
- the official AMPL interpreter repackaged `mampl` that uses the **MOSEK** license manager instead of the standard AMPL one.

Warning: It is possible to specify problems in AMPL that cannot be solved by **MOSEK**. The optimization problem must be a smooth convex optimization problem as discussed in Section 5.

Note: To use **MOSEK** from AMPL you need to correctly setup the system path to the **MOSEK** command line tool.

4.1 Invoking the AMPL shell

The **MOSEK** distribution by default comes with the AMPL shell included. Assuming `MSKHOME` is the folder in which **MOSEK** has been installed, it is located under

```
{MSKHOME}/mosek/8/tools/platform/{PLATFORM}/bin/
```

for Linux and OSX users (`PLATFORM` must be among `linux64x86`, `osx64x86`), and under

```
{MSKHOME}\mosek\8\tools\platform\{PLATFORM}\bin\
```

for Windows users (`PLATFORM` must be among `win32x86`, `win64x86`).

To invoke the AMPL shell included in the **MOSEK** distribution type:

```
mampl
```

4.2 An example

In many instances, you can successfully apply **MOSEK** simply by specifying the model and data, setting the solver option to **MOSEK**, and typing `solve`.

The problem we want to solve is a simple linear optimization problem. The AMPL formulation is in [Listing 4.1](#).

Listing 4.1: An example of optimization problem using AMPL language.

```

set NUTR ordered;
set FOOD ordered;

param cost {FOOD} >= 0;
param f_min {FOOD} >= 0, default 0;
param f_max {j in FOOD} >= f_min[j], default Infinity;

param n_min {NUTR} >= 0, default 0;
param n_max {i in NUTR} >= n_min[i], default Infinity;

param amt {NUTR,FOOD} >= 0;

# -----

var Buy {j in FOOD} >= f_min[j], <= f_max[j];

# -----

minimize Total_Cost: sum {j in FOOD} cost[j] * Buy[j];

minimize Nutr_Amt {i in NUTR}: sum {j in FOOD} amt[i,j] * Buy[j];

# -----

subject to Diet {i in NUTR}:
    n_min[i] <= sum {j in FOOD} amt[i,j] * Buy[j] <= n_max[i];

```

We can specify the input data using an input file again following the AMPL language, as reported in [Listing 4.2](#).

Listing 4.2: An example of data for an optimization problem using AMPL language.

```

param:  FOOD:      cost  f_min  f_max :=
  "Quarter Pounder w/ Cheese"  1.84  .    .
  "McLean Deluxe w/ Cheese"    2.19  .    .
  "Big Mac"                    1.84  .    .
  "Filet-O-Fish"               1.44  .    .
  "McGrilled Chicken"          2.29  .    .
  "Fries, small"               .77   .    .
  "Sausage McMuffin"           1.29  .    .
  "1% Lowfat Milk"             .60   .    .
  "Orange Juice"              .72   .    . ;

param:  NUTR:      n_min  n_max :=
  Cal      2000  .
  Carbo    350   375
  Protein   55   .
  VitA     100   .
  VitC     100   .
  Calc     100   .
  Iron     100   . ;

param amt (tr):

```

	Cal	Carbo	Protein	VitA	VitC	Calc	Iron	:=
"Quarter Pounder w/ Cheese"	510	34	28	15	6	30	20	
"McLean Deluxe w/ Cheese"	370	35	24	15	10	20	20	
"Big Mac"	500	42	25	6	2	25	20	
"Filet-O-Fish"	370	38	14	2	0	15	10	

"McGrilled Chicken"	400	42	31	8	15	15	8
"Fries, small"	220	26	3	0	15	0	2
"Sausage McMuffin"	345	27	15	4	0	20	15
"1% Lowfat Milk"	110	12	9	10	4	30	0
"Orange Juice"	80	20	1	2	120	2	2 ;

First to invoke the AMPL shell type:

```
mampl
```

when the AMPL shell has started type the commands:

```
ampl: model diet.mod;
ampl: data diet.dat;
ampl: option solver mosek;
ampl: solve;
```

The resulting output is:

```
MOSEK finished.
Problem status   - PRIMAL_AND_DUAL_FEASIBLE
Solution status  - OPTIMAL
Primal objective - 14.8557377
Dual objective   - 14.8557377

Objective = Total_Cost
```

4.3 Determining the outcome of an optimization

The AMPL parameter `solve_result_num` is used to indicate the outcome of the optimization process. It is used as follows

```
ampl: display solve_result_num
```

Please refer to table [Table 4.1](#) for possible values of this parameter.

Table 4.1: Interpretation of `solve_result_num`.

Value	Message
0	the solution is optimal.
100	suboptimal primal solution.
101	superoptimal (dual feasible) solution.
150	the solution is near optimal.
200	primal infeasible problem.
300	dual infeasible problem.
400	too many iterations.
500	solution status is unknown.
501	ill-posed problem, solution status is unknown.
> 501	Mapped MOSEK response code. See note below.

Note: **MOSEK** response codes are mapped on AMPL return code greater than 501. In order to get the actual response code the base value 501 must be subtracted. For example: say the AMPL return code is 502, then it corresponds to **MOSEK** response code 1.

4.4 Optimizer options

4.4.1 The MOSEK parameter database

The **MOSEK** optimizer has options and parameters controlling such things as the termination criterion and which optimizer is used. These parameters can be modified within AMPL as shown in the example below:

```
ampl: model diet.mod;
ampl: data diet.dat;
ampl: option solver mosek;
ampl: option mosek_options
ampl? 'msk_ipar_optimizer = msk_optimizer_primal_simplex \
ampl? msk_ipar_sim_max_iterations = 100000';
ampl: solve;
```

In the example above a string called `mosek_options` is created which contains the parameter settings. Each parameter setting has the format

```
parameter name = value
```

where `parameter name` can be any valid **MOSEK** parameter name. See Section 11.1 for a description of all valid **MOSEK** parameters.

An alternative way of specifying the options is

```
ampl: option mosek_options
ampl? 'msk_ipar_optimizer = msk_optimizer_primal_simplex'
ampl? 'msk_ipar_sim_max_iterations = 100000';
```

New options can also be appended to an existing option string as shown below

```
ampl: option mosek_options $mosek_options
ampl? ' msk_ipar_sim_print_freq = 0 msk_ipar_sim_max_iterations = 1000';
```

The expression `$mosek_options` expands to the current value of the option. Line two in the example appends an additional value `msk_ipar_sim_max_iterations` to the option string.

4.4.2 Options

outlev

Controls the amount of printed output. 0 means no printed output and a higher value means more printed output. An example of setting `outlev` is as follows:

```
ampl: option mosek_options 'outlev=2';
```

wantsol

We refer the reader to the AMPL manual [\[FGK03\]](#) for details about this option.

4.5 Constraint and variable names

AMPL assigns meaningful names to all the constraints and variables. Since **MOSEK** uses item names in error and log messages, it may be useful to pass the AMPL names to **MOSEK**.

Using the command

```
ampl: option auxfiles rc;
```

before the

```
ampl: solve;
```

command makes **MOSEK** obtain the constraint and variable names automatically.

4.6 Which solution is returned to AMPL

The **MOSEK** optimizer can produce three types of solutions: basic, integer, and interior point solutions. For nonlinear problems only an interior solution is available. For linear optimization problems optimized by the interior-point optimizer with basis identification turned on both a basic and an interior point solution are calculated. The simplex algorithm produces only a basic solution. Whenever both an interior and a basic solution are available, the basic solution is returned. For problems containing integer variables, the integer solution is returned to AMPL.

4.7 Hot-start

Frequently, a sequence of optimization problems is solved where each problem differs only slightly from the previous problem. In that case it may be advantageous to use the previous optimal solution to warm-start the optimizer. Such a facility is available in **MOSEK** only when the simplex optimizer is used.

The warm-start facility exploits the AMPL variable suffix `sstatus` to communicate the optimal basis back to AMPL, and AMPL uses this facility to communicate an initial basis to **MOSEK**. The following example demonstrates this feature.

```
ampl: model diet.mod;
ampl: data diet.dat;
ampl: option solver mosek;
ampl: option mosek_options
ampl? 'msk_ipar_optimizer = msk_optimizer_primal_simplex outlev=2';
ampl: solve;
ampl: display Buy.sstatus;
ampl: solve;
```

The resulting output is:

```
Accepted: msk_ipar_optimizer          = MSK_OPTIMIZER_PRIMAL_SIMPLEX
Accepted: outlev                      = 2

Computer  - Platform                  : Linux/64-X86
Computer  - CPU type                  : Intel-P4
MOSEK     - task name                  :
MOSEK     - objective sense            : min
MOSEK     - problem type               : LO (linear optimization problem)
MOSEK     - constraints                 : 7                variables          : 9
MOSEK     - integer variables          : 0

Optimizer started.
Simplex optimizer started.
Presolve started.
Linear dependency checker started.
Linear dependency checker terminated.
Presolve   - Stk. size (kb) : 0
Eliminator - tries          : 0                time                  : 0.00
```

```

Eliminator - elim's          : 0
Lin. dep. - tries           : 1          time          : 0.00
Lin. dep. - number          : 0
Presolve terminated. Time: 0.00
Primal simplex optimizer started.
Primal simplex optimizer setup started.
Primal simplex optimizer setup terminated.
Optimizer - solved problem    : the primal
Optimizer - constraints       : 7          variables      : 9
Optimizer - hotstart         : no
ITER      DEGITER(%)  PFEAS      DFEAS      POBJ          DOBJ          TIME
↪      TOTTIME
0          0.00        1.40e+03   NA          1.2586666667e+01   NA          0.00
↪      0.01
3          0.00        0.00e+00   NA          1.4855737705e+01   NA          0.00
↪      0.01
Primal simplex optimizer terminated.
Simplex optimizer terminated. Time: 0.00.
Optimizer terminated. Time: 0.01
Return code - 0 [MSK_RES_OK]
MOSEK finished.
Problem status   : PRIMAL_AND_DUAL_FEASIBLE
Solution status  : OPTIMAL
Primal objective : 14.8557377
Dual objective   : 14.8557377

Objective = Total_Cost
Buy.sstatus [*] :=
'Quarter Pounder w/ Cheese' bas
'McLean Deluxe w/ Cheese' low
'Big Mac' low
Filet-O-Fish low
'McGrilled Chicken' low
'Fries, small' bas
'Sausage McMuffin' low
'1% Lowfat Milk' bas
'Orange Juice' low
;
Accepted: msk_ipar_optimizer          = MSK_OPTIMIZER_PRIMAL_SIMPLEX
Accepted: outlev                      = 2
Basic solution
Problem status : UNKNOWN
Solution status : UNKNOWN
Primal - objective: 1.4855737705e+01   eq. infeas.: 3.97e+03 max bound infeas.: 2.00e+03
Dual   - objective: 0.0000000000e+00   eq. infeas.: 7.14e-01 max bound infeas.: 0.00e+00

Computer - Platform          : Linux/64-X86
Computer - CPU type         : Intel-P4
MOSEK    - task name        :
MOSEK    - objective sense   : min
MOSEK    - problem type      : LO (linear optimization problem)
MOSEK    - constraints       : 7          variables      : 9
MOSEK    - integer variables : 0
Optimizer started.
Simplex optimizer started.
Presolve started.
Presolve - Stk. size (kb) : 0
Eliminator - tries         : 0          time          : 0.00
Eliminator - elim's        : 0
Lin. dep. - tries         : 0          time          : 0.00
Lin. dep. - number        : 0
Presolve terminated. Time: 0.00
Primal simplex optimizer started.

```

```

Primal simplex optimizer setup started.
Primal simplex optimizer setup terminated.
Optimizer - solved problem      : the primal
Optimizer - constraints         : 7          variables           : 9
Optimizer - hotstart           : yes
Optimizer - Num. basic         : 7          Basis rank           : 7
Optimizer - Valid bas. fac.    : no
ITER      DEGITER(%)  PFEAS      DFEAS      POBJ      DOBJ      TIME
↪      TOTTIME
0         0.00        0.00e+00   NA        1.4855737705e+01   NA        0.00
↪      0.01
0         0.00        0.00e+00   NA        1.4855737705e+01   NA        0.00
↪      0.01
Primal simplex optimizer terminated.
Simplex optimizer terminated. Time: 0.00.
Optimizer terminated. Time: 0.01
Return code - 0 [MSK_RES_OK]
MOSEK finished.
Problem status   : PRIMAL_AND_DUAL_FEASIBLE
Solution status  : OPTIMAL
Primal objective : 14.8557377
Dual objective   : 14.8557377

Objective = Total_Cost

```

Please note that the second solve takes fewer iterations since the previous optimal basis is reused.

4.8 The infeasibility report

For linear optimization problems without any integer constrained variables **MOSEK** can generate an infeasibility report automatically. The report provides important information about the infeasibility.

The generation of the infeasibility report is turned on using the parameter setting

```

option auxfiles rc;
option mosek_options 'msk_ipar_infeas_report_auto=msk_on';

```

For further details about infeasibility report see Section 9.

4.9 Sensitivity analysis

MOSEK can calculate sensitivity information for the objective and constraints. To enable sensitivity information set the option:

```
sensitivity = 1
```

Results are returned in variable/constraint suffixes as follows:

- **.down** Smallest value of objective coefficient/right hand side before the optimal basis changes.
- **.up** Largest value of objective coefficient/right hand side before the optimal basis changes.
- **.current** Current value of objective coefficient/right hand side.

For ranged constraints sensitivity information is returned only for the lower bound.

The example below returns sensitivity information on the `diet` model.

```
ampl: model diet.mod;
ampl: data diet.dat;
ampl: option solver mosek;
ampl: option mosek_options 'sensitivity=1';

ampl: solve;
#display sensitivity information and current solution.
ampl: display _var.down,_var.current,_var.up,_var;
#display sensitivity information and optimal dual values.
ampl: display _con.down,_con.current,_con.up,_con;
```

The resulting output is:

```
Return code - 0 [MSK_RES_OK]
MOSEK finished.
Problem status : PRIMAL_AND_DUAL_FEASIBLE
Solution status : OPTIMAL
Primal objective : 14.8557377
Dual objective : 14.8557377

suffix up OUT;
suffix down OUT;
suffix current OUT;
Objective = Total_Cost
:  _var.down _var.current      _var.up      _var      :=
1  1.37385   1.84             1.86075    4.38525
2  1.8677    2.19             Infinity    0
3  1.82085   1.84             Infinity    0
4  1.35466   1.44             Infinity    0
5  1.57633   2.29             Infinity    0
6  0.094     0.77             0.794851   6.14754
7  1.22759   1.29             Infinity    0
8  0.57559   0.6             0.910769   3.42213
9  0.657279  0.72             Infinity    0
;
ampl: display _con.down,_con.current,_con.up,_con;
:  _con.down _con.current _con.up _con      :=
1  -Infinity      2000      3965.37  0
2      297.6       350       375      0.0277049
3  -Infinity       55       172.029  0
4      63.0531     100       195.388  0.0267541
5  -Infinity      100       132.213  0
6  -Infinity      100       234.221  0
7      17.6923     100       142.821  0.0248361
;
```

4.10 Using the command line version of the AMPL interface

AMPL can generate a data file containing all the optimization problem and all relevant information which can then be read and solved by the **MOSEK** command line tool.

When the problem has been loaded into AMPL, the commands

```
ampl: option auxfiles rc;
ampl: write bprob;
```

will make AMPL write the appropriate data files, i.e.

```
prob.nl  
prob.col  
prob.row
```

Then the problem can be solved using the command line version of **MOSEK** as follows

```
mosek prob.nl outlev=10 -a
```

The *-a* command line option indicates that **MOSEK** is invoked in AMPL mode. When **MOSEK** is invoked in AMPL mode the normal **MOSEK** command line options should appear *after* the *-a* option except for the file name which should be the first argument. As the above example demonstrates **MOSEK** accepts command line options as specified by the AMPL **convention**. Which command line arguments **MOSEK** accepts in AMPL mode can be viewed by executing

```
mosek -- -a
```

For linear, quadratic and quadratic constrained problems a text file representation of the problem can be obtained using one of the commands

```
mosek prob.nl -a -x -out prob.mps  
mosek prob.nl -a -x -out prob.opf  
mosek prob.nl -a -x -out prob.lp
```


PROBLEM FORMULATION AND SOLUTIONS

In this chapter we will discuss the following issues:

- The formal definitions of the problem types that **MOSEK** can solve.
- The solution information produced by **MOSEK**.
- The information produced by **MOSEK** if the problem is infeasible.

5.1 Linear Optimization

A linear optimization problem can be written as

$$\begin{array}{ll} \text{minimize} & c^T x + c^f \\ \text{subject to} & \begin{array}{ll} l^c \leq & Ax \leq u^c, \\ l^x \leq & x \leq u^x, \end{array} \end{array} \quad (5.1)$$

where

- m is the number of constraints.
- n is the number of decision variables.
- $x \in \mathbb{R}^n$ is a vector of decision variables.
- $c \in \mathbb{R}^n$ is the linear part of the objective function.
- $A \in \mathbb{R}^{m \times n}$ is the constraint matrix.
- $l^c \in \mathbb{R}^m$ is the lower limit on the activity for the constraints.
- $u^c \in \mathbb{R}^m$ is the upper limit on the activity for the constraints.
- $l^x \in \mathbb{R}^n$ is the lower limit on the activity for the variables.
- $u^x \in \mathbb{R}^n$ is the upper limit on the activity for the variables.

A primal solution (x) is *(primal) feasible* if it satisfies all constraints in (5.1). If (5.1) has at least one primal feasible solution, then (5.1) is said to be (primal) feasible.

In case (5.1) does not have a feasible solution, the problem is said to be *(primal) infeasible*.

5.1.1 Duality for Linear Optimization

Corresponding to the primal problem (5.1), there is a dual problem

$$\begin{array}{ll} \text{maximize} & (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\ \text{subject to} & \begin{array}{ll} A^T y + s_l^x - s_u^x & = c, \\ -y + s_l^c - s_u^c & = 0, \\ s_l^c, s_u^c, s_l^x, s_u^x & \geq 0. \end{array} \end{array} \quad (5.2)$$

If a bound in the primal problem is plus or minus infinity, the corresponding dual variable is fixed at 0, and we use the convention that the product of the bound value and the corresponding dual variable is 0. E.g.

$$l_j^x = -\infty \quad \Rightarrow \quad (s_l^x)_j = 0 \text{ and } l_j^x \cdot (s_l^x)_j = 0.$$

This is equivalent to removing variable $(s_l^x)_j$ from the dual problem. A solution

$$(y, s_l^c, s_u^c, s_l^x, s_u^x)$$

to the dual problem is feasible if it satisfies all the constraints in (5.2). If (5.2) has at least one feasible solution, then (5.2) is *(dual) feasible*, otherwise the problem is *(dual) infeasible*.

A Primal-dual Feasible Solution

A solution

$$(x, y, s_l^c, s_u^c, s_l^x, s_u^x)$$

is denoted a *primal-dual feasible solution*, if (x) is a solution to the primal problem (5.1) and $(y, s_l^c, s_u^c, s_l^x, s_u^x)$ is a solution to the corresponding dual problem (5.2).

The Duality Gap

Let

$$(x^*, y^*, (s_l^c)^*, (s_u^c)^*, (s_l^x)^*, (s_u^x)^*)$$

be a primal-dual feasible solution, and let

$$(x^c)^* := Ax^*.$$

For a primal-dual feasible solution we define the *duality gap* as the difference between the primal and the dual objective value,

$$\begin{aligned} c^T x^* + c^f - \{ & (l^c)^T (s_l^c)^* - (u^c)^T (s_u^c)^* + (l^x)^T (s_l^x)^* - (u^x)^T (s_u^x)^* + c^f \} \\ &= \sum_{i=0}^{m-1} [(s_l^c)^* ((x_i^c)^* - l_i^c) + (s_u^c)^* (u_i^c - (x_i^c)^*)] \\ &+ \sum_{j=0}^{n-1} [(s_l^x)^* (x_j - l_j^x) + (s_u^x)^* (u_j^x - x_j^*)] \geq 0 \end{aligned} \quad (5.3)$$

where the first relation can be obtained by transposing and multiplying the dual constraints (5.2) by x^* and $(x^c)^*$ respectively, and the second relation comes from the fact that each term in each sum is nonnegative. It follows that the primal objective will always be greater than or equal to the dual objective.

An Optimal Solution

It is well-known that a linear optimization problem has an optimal solution if and only if there exist feasible primal and dual solutions so that the duality gap is zero, or, equivalently, that the *complementarity conditions*

$$\begin{aligned} (s_l^c)^* ((x_i^c)^* - l_i^c) &= 0, & i = 0, \dots, m-1, \\ (s_u^c)^* (u_i^c - (x_i^c)^*) &= 0, & i = 0, \dots, m-1, \\ (s_l^x)^* (x_j - l_j^x) &= 0, & j = 0, \dots, n-1, \\ (s_u^x)^* (u_j^x - x_j^*) &= 0, & j = 0, \dots, n-1, \end{aligned}$$

are satisfied.

If (5.1) has an optimal solution and **MOSEK** solves the problem successfully, both the primal and dual solution are reported, including a status indicating the exact state of the solution.

5.1.2 Infeasibility for Linear Optimization

Primal Infeasible Problems

If the problem (5.1) is infeasible (has no feasible solution), **MOSEK** will report a certificate of primal infeasibility: The dual solution reported is the certificate of infeasibility, and the primal solution is undefined.

A certificate of primal infeasibility is a feasible solution to the modified dual problem

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x \\ & \text{subject to} && A^T y + s_l^x - s_u^x = 0, \\ & && -y + s_l^c - s_u^c = 0, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0, \end{aligned} \tag{5.4}$$

such that the objective value is strictly positive, i.e. a solution

$$(y^*, (s_l^c)^*, (s_u^c)^*, (s_l^x)^*, (s_u^x)^*)$$

to (5.4) so that

$$(l^c)^T (s_l^c)^* - (u^c)^T (s_u^c)^* + (l^x)^T (s_l^x)^* - (u^x)^T (s_u^x)^* > 0.$$

Such a solution implies that (5.4) is unbounded, and that its dual is infeasible. As the constraints to the dual of (5.4) are identical to the constraints of problem (5.1), we thus have that problem (5.1) is also infeasible.

Dual Infeasible Problems

If the problem (5.2) is infeasible (has no feasible solution), **MOSEK** will report a certificate of dual infeasibility: The primal solution reported is the certificate of infeasibility, and the dual solution is undefined.

A certificate of dual infeasibility is a feasible solution to the modified primal problem

$$\begin{aligned} & \text{minimize} && c^T x \\ & \text{subject to} && \hat{l}^c \leq Ax \leq \hat{u}^c, \\ & && \hat{l}^x \leq x \leq \hat{u}^x, \end{aligned} \tag{5.5}$$

where

$$\hat{l}_i^c = \begin{cases} 0 & \text{if } l_i^c > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_i^c := \begin{cases} 0 & \text{if } u_i^c < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

and

$$\hat{l}_j^x = \begin{cases} 0 & \text{if } l_j^x > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_j^x := \begin{cases} 0 & \text{if } u_j^x < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

such that

$$c^T x < 0.$$

Such a solution implies that (5.5) is unbounded, and that its dual is infeasible. As the constraints to the dual of (5.5) are identical to the constraints of problem (5.2), we thus have that problem (5.2) is also infeasible.

Primal and Dual Infeasible Case

In case that both the primal problem (5.1) and the dual problem (5.2) are infeasible, **MOSEK** will report only one of the two possible certificates — which one is not defined (**MOSEK** returns the first certificate found).

Minimalization vs. Maximalization

When the objective sense of problem (5.1) is maximization, i.e.

$$\begin{array}{llll}
\text{maximize} & & c^T x + c^f \\
\text{subject to} & l^c \leq & Ax & \leq u^c, \\
& l^x \leq & x & \leq u^x,
\end{array}$$

the objective sense of the dual problem changes to minimization, and the domain of all dual variables changes sign in comparison to (5.2). The dual problem thus takes the form

$$\begin{array}{ll}
\text{minimize} & (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\
\text{subject to} & \\
& A^T y + s_l^x - s_u^x = c, \\
& -y + s_l^c - s_u^c = 0, \\
& s_l^c, s_u^c, s_l^x, s_u^x \leq 0.
\end{array}$$

This means that the duality gap, defined in (5.3) as the primal minus the dual objective value, becomes nonpositive. It follows that the dual objective will always be greater than or equal to the primal objective. The primal infeasibility certificate will be reported by **MOSEK** as a solution to the system

$$\begin{array}{l}
A^T y + s_l^x - s_u^x = 0, \\
-y + s_l^c - s_u^c = 0, \\
s_l^c, s_u^c, s_l^x, s_u^x \leq 0,
\end{array} \tag{5.6}$$

such that the objective value is strictly negative

$$(l^c)^T (s_l^c)^* - (u^c)^T (s_u^c)^* + (l^x)^T (s_l^x)^* - (u^x)^T (s_u^x)^* < 0.$$

Similarly, the certificate of dual infeasibility is an x satisfying the requirements of (5.5) such that $c^T x > 0$.

5.2 Conic Quadratic Optimization

Conic quadratic optimization is an extension of linear optimization (see Section 5.1) allowing conic domains to be specified for subsets of the problem variables. A conic quadratic optimization problem can be written as

$$\begin{array}{llll}
\text{minimize} & & c^T x + c^f \\
\text{subject to} & l^c \leq & Ax & \leq u^c, \\
& l^x \leq & x & \leq u^x, \\
& & x \in \mathcal{K},
\end{array} \tag{5.7}$$

where set \mathcal{K} is a Cartesian product of convex cones, namely $\mathcal{K} = \mathcal{K}_1 \times \cdots \times \mathcal{K}_p$. Having the domain restriction, $x \in \mathcal{K}$, is thus equivalent to

$$x^t \in \mathcal{K}_t \subseteq \mathbb{R}^{n_t},$$

where $x = (x^1, \dots, x^p)$ is a partition of the problem variables. Please note that the n -dimensional Euclidean space \mathbb{R}^n is a cone itself, so simple linear variables are still allowed.

MOSEK supports only a limited number of cones, specifically:

- The \mathbb{R}^n set.
- The quadratic cone:

$$\mathcal{Q}^n = \left\{ x \in \mathbb{R}^n : x_1 \geq \sqrt{\sum_{j=2}^n x_j^2} \right\}.$$

- The rotated quadratic cone:

$$\mathcal{Q}_r^n = \left\{ x \in \mathbb{R}^n : 2x_1x_2 \geq \sum_{j=3}^n x_j^2, \quad x_1 \geq 0, \quad x_2 \geq 0 \right\}.$$

Although these cones may seem to provide only limited expressive power they can be used to model a wide range of problems as demonstrated in [MOSEKApS12].

5.2.1 Duality for Conic Quadratic Optimization

The dual problem corresponding to the conic quadratic optimization problem (5.7) is given by

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\ & \text{subject to} && \\ & && A^T y + s_l^x - s_u^x + s_n^x = c \\ & && -y + s_l^c - s_u^c = 0, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0, \\ & && s_n^x \in \mathcal{K}^*, \end{aligned} \tag{5.8}$$

where the dual cone \mathcal{K}^* is a Cartesian product of the cones

$$\mathcal{K}^* = \mathcal{K}_1^* \times \cdots \times \mathcal{K}_p^*,$$

where each \mathcal{K}_t^* is the dual cone of \mathcal{K}_t . For the cone types **MOSEK** can handle, the relation between the primal and dual cone is given as follows:

- The \mathbb{R}^n set:

$$\mathcal{K}_t = \mathbb{R}^{n_t} \quad \Leftrightarrow \quad \mathcal{K}_t^* = \{s \in \mathbb{R}^{n_t} : s = 0\}.$$

- The quadratic cone:

$$\mathcal{K}_t = \mathcal{Q}^{n_t} \quad \Leftrightarrow \quad \mathcal{K}_t^* = \mathcal{Q}^{n_t} = \left\{ s \in \mathbb{R}^{n_t} : s_1 \geq \sqrt{\sum_{j=2}^{n_t} s_j^2} \right\}.$$

- The rotated quadratic cone:

$$\mathcal{K}_t = \mathcal{Q}_r^{n_t} \quad \Leftrightarrow \quad \mathcal{K}_t^* = \mathcal{Q}_r^{n_t} = \left\{ s \in \mathbb{R}^{n_t} : 2s_1s_2 \geq \sum_{j=3}^{n_t} s_j^2, \quad s_1 \geq 0, \quad s_2 \geq 0 \right\}.$$

Please note that the dual problem of the dual problem is identical to the original primal problem.

5.2.2 Infeasibility for Conic Quadratic Optimization

In case **MOSEK** finds a problem to be infeasible it reports a certificate of infeasibility. This works exactly as for linear problems (see Section 5.1.2).

Primal Infeasible Problems

If the problem (5.7) is infeasible, **MOSEK** will report a certificate of primal infeasibility: The dual solution reported is the certificate of infeasibility, and the primal solution is undefined.

A certificate of primal infeasibility is a feasible solution to the problem

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x \\ & \text{subject to} && \\ & && A^T y + s_l^x - s_u^x + s_n^x = 0, \\ & && -y + s_l^c - s_u^c = 0, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0, \\ & && s_n^x \in \mathcal{K}^*, \end{aligned}$$

such that the objective value is strictly positive.

Dual infeasible problems

If the problem (5.8) is infeasible, **MOSEK** will report a certificate of dual infeasibility: The primal solution reported is the certificate of infeasibility, and the dual solution is undefined.

A certificate of dual infeasibility is a feasible solution to the problem

$$\begin{aligned} & \text{minimize} && c^T x \\ & \text{subject to} && \hat{l}^c \leq Ax \leq \hat{u}^c, \\ & && \hat{l}^x \leq x \leq \hat{u}^x, \\ & && x \in \mathcal{K}, \end{aligned}$$

where

$$\hat{l}_i^c = \begin{cases} 0 & \text{if } l_i^c > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_i^c := \begin{cases} 0 & \text{if } u_i^c < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

and

$$\hat{l}_j^x = \begin{cases} 0 & \text{if } l_j^x > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_j^x := \begin{cases} 0 & \text{if } u_j^x < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

such that the objective value is strictly negative.

5.3 Semidefinite Optimization

Semidefinite optimization is an extension of conic quadratic optimization (see Section 5.2) allowing positive semidefinite matrix variables to be used in addition to the usual scalar variables. A semidefinite optimization problem can be written as

$$\begin{aligned} & \text{minimize} && \sum_{j=0}^{n-1} c_j x_j + \sum_{j=0}^{p-1} \langle \bar{C}_j, \bar{X}_j \rangle + c^f \\ & \text{subject to} && \begin{aligned} l_i^c &\leq && \sum_{j=0}^{n-1} a_{ij} x_j + \sum_{j=0}^{p-1} \langle \bar{A}_{ij}, \bar{X}_j \rangle &\leq u_i^c, & i = 0, \dots, m-1 \\ l_j^x &\leq && x_j &\leq u_j^x, & j = 0, \dots, n-1 \\ &&& x \in \mathcal{K}, \bar{X}_j \in \mathcal{S}_+^{r_j}, && j = 0, \dots, p-1 \end{aligned} \end{aligned} \quad (5.9)$$

where the problem has p symmetric positive semidefinite variables $\bar{X}_j \in \mathcal{S}_+^{r_j}$ of dimension r_j with symmetric coefficient matrices $\bar{C}_j \in \mathcal{S}^{r_j}$ and $\bar{A}_{ij} \in \mathcal{S}^{r_j}$. We use standard notation for the matrix inner product, i.e., for $U, V \in \mathbb{R}^{m \times n}$ we have

$$\langle U, V \rangle := \sum_{i=0}^{m-1} \sum_{j=0}^{n-1} U_{ij} V_{ij}.$$

With semidefinite optimization we can model a wide range of problems as demonstrated in [MOSEKApS12].

5.3.1 Duality for Semidefinite Optimization

The dual problem corresponding to the semidefinite optimization problem (5.9) is given by

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\ & \text{subject to} && \begin{aligned} c - A^T y + s_u^x - s_l^x &= s_n^x, \\ \bar{C}_j - \sum_{i=0}^m y_i \bar{A}_{ij} &= \bar{S}_j, & j = 0, \dots, p-1 \\ s_l^c - s_u^c &= y, \\ s_l^c, s_u^c, s_l^x, s_u^x &\geq 0, \\ s_n^x &\in \mathcal{K}^*, \quad \bar{S}_j \in \mathcal{S}_+^{r_j}, & j = 0, \dots, p-1 \end{aligned} \end{aligned} \quad (5.10)$$

where $A \in \mathbb{R}^{m \times n}$, $A_{ij} = a_{ij}$, which is similar to the dual problem for conic quadratic optimization (see Section 5.2.1), except for the addition of dual constraints

$$\left(\overline{C}_j - \sum_{i=0}^m y_i \overline{A}_{ij} \right) \in \mathcal{S}_+^{r_j}.$$

Note that the dual of the dual problem is identical to the original primal problem.

5.3.2 Infeasibility for Semidefinite Optimization

In case **MOSEK** finds a problem to be infeasible it reports a certificate of the infeasibility. This works exactly as for linear problems (see Section 5.1.2).

Primal Infeasible Problems

If the problem (5.9) is infeasible, **MOSEK** will report a certificate of primal infeasibility: The dual solution reported is a certificate of infeasibility, and the primal solution is undefined.

A certificate of primal infeasibility is a feasible solution to the problem

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x \\ & \text{subject to} && \\ & && A^T y + s_l^x - s_u^x + s_n^x = 0, \\ & && \sum_{i=0}^{m-1} y_i \overline{A}_{ij} + \overline{S}_j = 0, && j = 0, \dots, p-1 \\ & && -y + s_l^c - s_u^c = 0, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0, \\ & && s_n^x \in \mathcal{K}^*, \quad \overline{S}_j \in \mathcal{S}_+^{r_j}, && j = 0, \dots, p-1 \end{aligned}$$

such that the objective value is strictly positive.

Dual Infeasible Problems

If the problem (5.10) is infeasible, **MOSEK** will report a certificate of dual infeasibility: The primal solution reported is the certificate of infeasibility, and the dual solution is undefined.

A certificate of dual infeasibility is a feasible solution to the problem

$$\begin{aligned} & \text{minimize} && \sum_{j=0}^{n-1} c_j x_j + \sum_{j=0}^{p-1} \langle \overline{C}_j, \overline{X}_j \rangle \\ & \text{subject to} && \hat{l}_i^c \leq \sum_{j=1}^n a_{ij} x_j + \sum_{j=0}^{p-1} \langle \overline{A}_{ij}, \overline{X}_j \rangle \leq \hat{u}_i^c, \quad i = 0, \dots, m-1 \\ & && \hat{l}^x \leq \begin{matrix} x \\ \overline{X}_j \end{matrix} \leq \hat{u}^x, \\ & && x \in \mathcal{K}, \quad \overline{X}_j \in \mathcal{S}_+^{r_j}, && j = 0, \dots, p-1 \end{aligned}$$

where

$$\hat{l}_i^c = \begin{cases} 0 & \text{if } l_i^c > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_i^c := \begin{cases} 0 & \text{if } u_i^c < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

and

$$\hat{l}_j^x = \begin{cases} 0 & \text{if } l_j^x > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_j^x := \begin{cases} 0 & \text{if } u_j^x < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

such that the objective value is strictly negative.

5.4 Quadratic and Quadratically Constrained Optimization

A convex quadratic and quadratically constrained optimization problem is an optimization problem of the form

$$\begin{aligned} & \text{minimize} && \frac{1}{2}x^T Q^o x + c^T x + c^f \\ & \text{subject to} && \begin{aligned} l_k^c &\leq \frac{1}{2}x^T Q^k x + \sum_{j=0}^{n-1} a_{kj} x_j &\leq u_k^c, & k = 0, \dots, m-1, \\ l_j^x &\leq x_j &\leq u_j^x, & j = 0, \dots, n-1, \end{aligned} \end{aligned} \quad (5.11)$$

where Q^o and all Q^k are symmetric matrices. Moreover for convexity, Q^o must be a positive semidefinite matrix and Q^k must satisfy

$$\begin{aligned} -\infty < l_k^c &\Rightarrow Q^k \text{ is negative semidefinite,} \\ u_k^c < \infty &\Rightarrow Q^k \text{ is positive semidefinite,} \\ -\infty < l_k^c \leq u_k^c < \infty &\Rightarrow Q^k = 0. \end{aligned}$$

The convexity requirement is very important and **MOSEK** checks whether it is fulfilled.

5.4.1 A Recommendation

Any convex quadratic optimization problem can be reformulated as a conic quadratic optimization problem, see [MOSEKApS12] and in particular [And13]. In fact **MOSEK** does such conversion internally as a part of the solution process for the following reasons:

- the conic optimizer is numerically more robust than the one for quadratic problems.
- the conic optimizer is usually faster because quadratic cones are simpler than quadratic functions, even though the conic reformulation usually has more constraints and variables than the original quadratic formulation.
- it is easy to dualize the conic formulation if deemed worthwhile potentially leading to (huge) computational savings.

However, instead of relying on the automatic reformulation we recommend to formulate the problem as conic problem from scratch because:

- it saves the computational overhead of the reformulation including the convexity check. A conic problem is convex by construction and hence no convexity check is needed for conic problems.
- usually the modeller can do a better reformulation than the automatic method because the modeller can exploit the knowledge of what is being modelled.

To summarize we recommend to formulate quadratic problems and in particular quadratically constrained problems directly in conic form.

5.4.2 Duality for Quadratic and Quadratically Constrained Optimization

The dual problem corresponding to the quadratic and quadratically constrained optimization problem (5.11) is given by

$$\begin{aligned} & \text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + \frac{1}{2}x^T \left\{ \sum_{k=0}^{m-1} y_k Q^k - Q^o \right\} x + c^f \\ & \text{subject to} && \begin{aligned} A^T y + s_l^x - s_u^x + \left\{ \sum_{k=0}^{m-1} y_k Q^k - Q^o \right\} x &= c, \\ -y + s_l^c - s_u^c &= 0, \\ s_l^c, s_u^c, s_l^x, s_u^x &\geq 0. \end{aligned} \end{aligned} \quad (5.12)$$

The dual problem is related to the dual problem for linear optimization (see Section 5.1.1), but depends on the variable x which in general can not be eliminated. In the solutions reported by **MOSEK**, the value of x is the same for the primal problem (5.11) and the dual problem (5.12).

5.4.3 Infeasibility for Quadratic and Quadratically Constrained Optimization

In case **MOSEK** finds a problem to be infeasible it reports a certificate of infeasibility. This works exactly as for linear problems (see Section 5.1.2).

Primal Infeasible Problems

If the problem (5.11) with all $Q^k = 0$ is infeasible, **MOSEK** will report a certificate of primal infeasibility. As the constraints are the same as for a linear problem, the certificate of infeasibility is the same as for linear optimization (see Section 5.1.2.1).

Dual Infeasible Problems

If the problem (5.12) with all $Q^k = 0$ is infeasible, **MOSEK** will report a certificate of dual infeasibility. The primal solution reported is the certificate of infeasibility, and the dual solution is undefined.

A certificate of dual infeasibility is a feasible solution to the problem

$$\begin{array}{ll} \text{minimize} & c^T x \\ \text{subject to} & \hat{l}^c \leq Ax \leq \hat{u}^c, \\ & 0 \leq Q^o x \leq 0, \\ & \hat{l}^x \leq x \leq \hat{u}^x, \end{array}$$

where

$$\hat{l}_i^c = \begin{cases} 0 & \text{if } l_i^c > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_i^c := \begin{cases} 0 & \text{if } u_i^c < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

and

$$\hat{l}_j^x = \begin{cases} 0 & \text{if } l_j^x > -\infty, \\ -\infty & \text{otherwise,} \end{cases} \quad \text{and} \quad \hat{u}_j^x := \begin{cases} 0 & \text{if } u_j^x < \infty, \\ \infty & \text{otherwise,} \end{cases}$$

such that the objective value is strictly negative.

5.5 General Convex Optimization

MOSEK is capable of solving smooth (twice differentiable) convex nonlinear optimization problems of the form

$$\begin{array}{ll} \text{minimize} & f(x) + c^T x + c^f \\ \text{subject to} & l^c \leq g(x) + Ax \leq u^c, \\ & l^x \leq x \leq u^x, \end{array}$$

where

- m is the number of constraints.
- n is the number of decision variables.
- $x \in \mathbb{R}^n$ is a vector of decision variables.
- $c \in \mathbb{R}^n$ is the linear part objective function.
- $A \in \mathbb{R}^{m \times n}$ is the constraint matrix.
- $l^c \in \mathbb{R}^m$ is the lower limit on the activity for the constraints.
- $u^c \in \mathbb{R}^m$ is the upper limit on the activity for the constraints.
- $l^x \in \mathbb{R}^n$ is the lower limit on the activity for the variables.

- $u^x \in \mathbb{R}^n$ is the upper limit on the activity for the variables.
- $f : \mathbb{R}^n \rightarrow \mathbb{R}$ is a nonlinear function.
- $g : \mathbb{R}^n \rightarrow \mathbb{R}^m$ is a nonlinear vector function.

This means that the i -th constraint has the form

$$l_i^c \leq g_i(x) + \sum_{j=1}^n a_{ij}x_j \leq u_i^c.$$

The linear term Ax is included in $g(x)$ since it can be handled much more efficiently as a separate entity when optimizing.

The nonlinear functions f and g must be smooth in all $x \in [l^x; u^x]$. Moreover, $f(x)$ must be a convex function and $g_i(x)$ must satisfy

$$\begin{aligned} -\infty < l_i^c &\Rightarrow g_i(x) \text{ is concave,} \\ u_i^c < \infty &\Rightarrow g_i(x) \text{ is convex,} \\ -\infty < l_i^c \leq u_i^c < \infty &\Rightarrow g_i(x) = 0. \end{aligned}$$

5.5.1 Duality for General convex Optimization

Similar to the linear case, **MOSEK** reports dual information in the general nonlinear case. Indeed in this case the Lagrange function is defined by

$$\begin{aligned} L(x, s_l^c, s_u^c, s_l^x, s_u^x) &:= f(x) + c^T x + c^f \\ &\quad - (s_l^c)^T (g(x) + Ax - l^c) - (s_u^c)^T (u^c - g(x) - Ax) \\ &\quad - (s_l^x)^T (x - l^x) - (s_u^x)^T (u^x - x), \end{aligned}$$

and the dual problem is given by

$$\begin{aligned} &\text{maximize} && L(x, s_l^c, s_u^c, s_l^x, s_u^x) \\ &\text{subject to} && \nabla_x L(x, s_l^c, s_u^c, s_l^x, s_u^x)^T = 0, \\ &&& s_l^c, s_u^c, s_l^x, s_u^x \geq 0, \end{aligned}$$

which is equivalent to

$$\begin{aligned} &\text{maximize} && (l^c)^T s_l^c - (u^c)^T s_u^c + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\ &&& + f(x) - g(x)^T y - (\nabla f(x)^T - \nabla g(x)^T y)^T x \\ &\text{subject to} && A^T y + s_l^x - s_u^x - (\nabla f(x)^T - \nabla g(x)^T y) = c, \\ &&& -y + s_l^c - s_u^c = 0, \\ &&& s_l^c, s_u^c, s_l^x, s_u^x \geq 0. \end{aligned}$$

In this context we use the following definition for scalar functions

$$\nabla f(x) = \left[\frac{\partial f(x)}{\partial x_1}, \dots, \frac{\partial f(x)}{\partial x_n} \right],$$

and accordingly for vector functions

$$\nabla g(x) = \begin{bmatrix} \nabla g_1(x) \\ \vdots \\ \nabla g_m(x) \end{bmatrix}.$$

THE OPTIMIZERS FOR CONTINUOUS PROBLEMS

The most essential part of **MOSEK** is the optimizers. Each optimizer is designed to solve a particular class of problems, i.e. linear, conic, or general nonlinear problems. The purpose of the present chapter is to discuss which optimizers are available for the continuous problem classes and how the performance of an optimizer can be tuned, if needed. This chapter deals with the optimizers for *continuous problems* with no integer variables.

When the optimizer is called, it roughly performs the following steps:

1. *Presolve*: Preprocessing to reduce the size of the problem.
2. *Dualizer*: Choosing whether to solve the primal or the dual form of the problem.
3. *Scaling*: Scaling the problem for better numerical stability.
4. *Optimize*: Solve the problem using selected method.

The first three preprocessing steps are transparent to the user, but useful to know about for tuning purposes. In general, the purpose of the preprocessing steps is to make the actual optimization more efficient and robust.

Using multiple threads

The interior-point optimizers in **MOSEK** have been parallelized. This means that if you solve linear, quadratic, conic, or general convex optimization problem using the interior-point optimizer, you can take advantage of multiple CPU's.

By default **MOSEK** will automatically select the number of threads to be employed when solving the problem. However, the number of threads employed can be changed by setting the parameter `MSK_IPAR_NUM_THREADS`. This should never exceed the number of cores on the computer.

The speed-up obtained when using multiple threads is highly problem and hardware dependent, and consequently, it is advisable to compare single threaded and multi threaded performance for the given problem type to determine the optimal settings.

For small problems, using multiple threads is not be worthwhile and may even be counter productive.

6.1 Presolve

Before an optimizer actually performs the optimization the problem is preprocessed using the so-called presolve. The purpose of the presolve is to

1. remove redundant constraints,
2. eliminate fixed variables,
3. remove linear dependencies,
4. substitute out (implied) free variables, and

5. reduce the size of the optimization problem in general.

After the presolved problem has been optimized the solution is automatically postsolved so that the returned solution is valid for the original problem. Hence, the presolve is completely transparent. For further details about the presolve phase, please see [AA95] and [AGMX96].

It is possible to fine-tune the behavior of the presolve or to turn it off entirely. If presolve consumes too much time or memory compared to the reduction in problem size gained it may be disabled. This is done by setting the parameter `MSK_IPAR_PRESOLVE_USE` to `MSK_PRESOLVE_MODE_OFF`.

The two most time-consuming steps of the presolve are

- the eliminator, and
- the linear dependency check.

Therefore, in some cases it is worthwhile to disable one or both of these.

Numerical issues in the presolve

During the presolve the problem is reformulated so that it hopefully solves faster. However, in rare cases the presolved problem may be harder to solve than the original problem. The presolve may also be infeasible although the original problem is not.

If it is suspected that presolved problem is much harder to solve than the original then it is suggested to first turn the eliminator off by setting the parameter `MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_NUM_TRIES` to 0. If that does not help, then trying to turn presolve off may help.

Since all computations are done in finite precision then the presolve employs some tolerances when concluding a variable is fixed or constraint is redundant. If it happens that **MOSEK** incorrectly concludes a problem is primal or dual infeasible, then it is worthwhile to try to reduce the parameters `MSK_DPAR_PRESOLVE_TOL_X` and `MSK_DPAR_PRESOLVE_TOL_S`. However, if reducing the parameters actually helps then this should be taken as an indication that the problem is badly formulated.

Eliminator

The purpose of the eliminator is to eliminate free and implied free variables from the problem using substitution. For instance, given the constraints

$$\begin{aligned} y &= \sum_j x_j, \\ y, x &\geq 0, \end{aligned}$$

y is an implied free variable that can be substituted out of the problem, if deemed worthwhile. If the eliminator consumes too much time or memory compared to the reduction in problem size gained it may be disabled. This can be done by setting the parameter `MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_NUM_TRIES` to 0. In rare cases the eliminator may cause that the problem becomes much hard to solve.

Linear dependency checker

The purpose of the linear dependency check is to remove linear dependencies among the linear equalities. For instance, the three linear equalities

$$\begin{aligned} x_1 + x_2 + x_3 &= 1, \\ x_1 + 0.5x_2 &= 0.5, \\ 0.5x_2 + x_3 &= 0.5 \end{aligned}$$

contain exactly one linear dependency. This implies that one of the constraints can be dropped without changing the set of feasible solutions. Removing linear dependencies is in general a good idea since it reduces the size of the problem. Moreover, the linear dependencies are likely to introduce numerical problems in the optimization phase.

It is best practise to build models without linear dependencies. If the linear dependencies are removed at the modeling stage, the linear dependency check can safely be disabled by setting the parameter `MSK_IPAR_PRESOLVE_LINDEP_USE` to `MSK_OFF`.

Dualizer

All linear, conic, and convex optimization problems have an equivalent dual problem associated with them. **MOSEK** has built-in heuristics to determine if it is most efficient to solve the primal or dual problem. The form (primal or dual) solved is displayed in the **MOSEK** log. Should the internal heuristics not choose the most efficient form of the problem it may be worthwhile to set the dualizer manually by setting the parameters:

- `MSK_IPAR_INTPNT_SOLVE_FORM`: In case of the interior-point optimizer.
- `MSK_IPAR_SIM_SOLVE_FORM`: In case of the simplex optimizer.

Note that currently only linear problems may be dualized.

Scaling

Problems containing data with large and/or small coefficients, say $1.0e + 9$ or $1.0e - 7$, are often hard to solve. Significant digits may be truncated in calculations with finite precision, which can result in the optimizer relying on inaccurate calculations. Since computers work in finite precision, extreme coefficients should be avoided. In general, data around the same *order of magnitude* is preferred, and we will refer to a problem, satisfying this loose property, as being *well-scaled*. If the problem is not well scaled, **MOSEK** will try to scale (multiply) constraints and variables by suitable constants. **MOSEK** solves the scaled problem to improve the numerical properties.

The scaling process is transparent, i.e. the solution to the original problem is reported. It is important to be aware that the optimizer terminates when the termination criterion is met on the scaled problem, therefore significant primal or dual infeasibilities may occur after unscaling for badly scaled problems. The best solution of this issue is to reformulate the problem, making it better scaled.

By default **MOSEK** heuristically chooses a suitable scaling. The scaling for interior-point and simplex optimizers can be controlled with the parameters `MSK_IPAR_INTPNT_SCALING` and `MSK_IPAR_SIM_SCALING` respectively.

6.2 Linear Optimization

6.2.1 Optimizer Selection

Two different types of optimizers are available for linear problems: The default is an interior-point method, and the alternatives are simplex methods. The optimizer can be selected using the parameter `MSK_IPAR_OPTIMIZER`.

6.2.2 The Interior-point Optimizer

The purpose of this section is to provide information about the algorithm employed in **MOSEK** interior-point optimizer.

In order to keep the discussion simple it is assumed that **MOSEK** solves linear optimization problems of standard form

$$\begin{aligned} &\text{minimize} && c^T x \\ &\text{subject to} && Ax = b, \\ &&& x \geq 0. \end{aligned} \tag{6.1}$$

This is in fact what happens inside **MOSEK**; for efficiency reasons **MOSEK** converts the problem to standard form before solving, then converts it back to the input form when reporting the solution.

Since it is not known beforehand whether problem (6.1) has an optimal solution, is primal infeasible or is dual infeasible, the optimization algorithm must deal with all three situations. This is the reason that **MOSEK** solves the so-called homogeneous model

$$\begin{aligned} Ax - b\tau &= 0, \\ A^T y + s - c\tau &= 0, \\ -c^T x + b^T y - \kappa &= 0, \\ x, s, \tau, \kappa &\geq 0, \end{aligned} \tag{6.2}$$

where y and s correspond to the dual variables in (6.1), and τ and κ are two additional scalar variables. Note that the homogeneous model (6.2) always has solution since

$$(x, y, s, \tau, \kappa) = (0, 0, 0, 0, 0)$$

is a solution, although not a very interesting one.

Any solution

$$(x^*, y^*, s^*, \tau^*, \kappa^*)$$

to the homogeneous model (6.2) satisfies

$$x_j^* s_j^* = 0 \text{ and } \tau^* \kappa^* = 0.$$

Moreover, there is always a solution that has the property

$$\tau^* + \kappa^* > 0.$$

First, assume that $\tau^* > 0$. It follows that

$$\begin{aligned} A \frac{x^*}{\tau^*} &= b, \\ A^T \frac{y^*}{\tau^*} + \frac{s^*}{\tau^*} &= c, \\ -c^T \frac{x^*}{\tau^*} + b^T \frac{y^*}{\tau^*} &= 0, \\ x^*, s^*, \tau^*, \kappa^* &\geq 0. \end{aligned}$$

This shows that $\frac{x^*}{\tau^*}$ is a primal optimal solution and $(\frac{y^*}{\tau^*}, \frac{s^*}{\tau^*})$ is a dual optimal solution; this is reported as the optimal interior-point solution since

$$(x, y, s) = \left\{ \frac{x^*}{\tau^*}, \frac{y^*}{\tau^*}, \frac{s^*}{\tau^*} \right\}$$

is a primal-dual optimal solution.

On other hand, if $\kappa^* > 0$ then

$$\begin{aligned} Ax^* &= 0, \\ A^T y^* + s^* &= 0, \\ -c^T x^* + b^T y^* &= \kappa^*, \\ x^*, s^*, \tau^*, \kappa^* &\geq 0. \end{aligned}$$

This implies that at least one of

$$-c^T x^* > 0 \tag{6.3}$$

or

$$b^T y^* > 0 \tag{6.4}$$

is satisfied. If (6.3) is satisfied then x^* is a certificate of dual infeasibility, whereas if (6.4) is satisfied then y^* is a certificate of dual infeasibility.

In summary, by computing an appropriate solution to the homogeneous model, all information required for a solution to the original problem is obtained. A solution to the homogeneous model can be computed using a primal-dual interior-point algorithm [And09].

Interior-point Termination Criterion

For efficiency reasons it is not practical to solve the homogeneous model exactly. Hence, an exact optimal solution or an exact infeasibility certificate cannot be computed and a reasonable termination criterion has to be employed.

In every iteration, k , of the interior-point algorithm a trial solution

$$(x^k, y^k, s^k, \tau^k, \kappa^k)$$

to homogeneous model is generated where

$$x^k, s^k, \tau^k, \kappa^k > 0.$$

Whenever the trial solution satisfies the criterion

$$\begin{aligned} \left\| A \frac{x^k}{\tau^k} - b \right\|_{\infty} &\leq \epsilon_p (1 + \|b\|_{\infty}), \\ \left\| A^T \frac{y^k}{\tau^k} + \frac{s^k}{\tau^k} - c \right\|_{\infty} &\leq \epsilon_d (1 + \|c\|_{\infty}), \text{ and} \\ \min \left(\frac{(x^k)^T s^k}{(\tau^k)^2}, \left| \frac{c^T x^k}{\tau^k} - \frac{b^T y^k}{\tau^k} \right| \right) &\leq \epsilon_g \max \left(1, \frac{\min(|c^T x^k|, |b^T y^k|)}{\tau^k} \right), \end{aligned} \quad (6.5)$$

the interior-point optimizer is terminated and

$$\frac{(x^k, y^k, s^k)}{\tau^k}$$

is reported as the primal-dual optimal solution. The interpretation of (6.5) is that the optimizer is terminated if

- $\frac{x^k}{\tau^k}$ is approximately primal feasible,
- $\left\{ \frac{y^k}{\tau^k}, \frac{s^k}{\tau^k} \right\}$ is approximately dual feasible, and
- the duality gap is almost zero.

On the other hand, if the trial solution satisfies

$$-\epsilon_i c^T x^k > \frac{\|c\|_{\infty}}{\max(1, \|b\|_{\infty})} \|Ax^k\|_{\infty}$$

then the problem is declared dual infeasible and x^k is reported as a certificate of dual infeasibility. The motivation for this stopping criterion is as follows: First assume that $\|Ax^k\|_{\infty} = 0$; then x^k is an exact certificate of dual infeasibility. Next assume that this is not the case, i.e.

$$\|Ax^k\|_{\infty} > 0,$$

and define

$$\bar{x} := \epsilon_i \frac{\max(1, \|b\|_{\infty})}{\|Ax^k\|_{\infty} \|c\|_{\infty}} x^k.$$

It is easy to verify that

$$\|A\bar{x}\|_{\infty} = \epsilon_i \frac{\max(1, \|b\|_{\infty})}{\|c\|_{\infty}} \text{ and } -c^T \bar{x} > 1,$$

which shows \bar{x} is an approximate certificate of dual infeasibility where ϵ_i controls the quality of the approximation. A smaller value means a better approximation.

Finally, if

$$\epsilon_i b^T y^k > \frac{\|b\|_{\infty}}{\max(1, \|c\|_{\infty})} \|A^T y^k + s^k\|_{\infty}$$

then y^k is reported as a certificate of primal infeasibility.

It is possible to adjust the tolerances ε_p , ε_d , ε_g and ε_i using parameters; see Table 6.1 for details.

Table 6.1: Parameters employed in termination criterion

ToleranceParameter	name
ε_p	<i>MSK_DPAR_INTPNT_TOL_PFEAS</i>
ε_d	<i>MSK_DPAR_INTPNT_TOL_DFEAS</i>
ε_g	<i>MSK_DPAR_INTPNT_TOL_REL_GAP</i>
ε_i	<i>MSK_DPAR_INTPNT_TOL_INFEAS</i>

The default values of the termination tolerances are chosen such that for a majority of problems appearing in practice it is not possible to achieve much better accuracy. Therefore, tightening the tolerances usually is not worthwhile. However, an inspection of (6.5) reveals that quality of the solution is dependent on $\|b\|_\infty$ and $\|c\|_\infty$; the smaller the norms are, the better the solution accuracy.

The interior-point method as implemented by **MOSEK** will converge toward optimality and primal and dual feasibility at the same rate [And09]. This means that if the optimizer is stopped prematurely then it is very unlikely that either the primal or dual solution is feasible. Another consequence is that in most cases all the tolerances, ε_p , ε_d and ε_g , have to be relaxed together to achieve an effect.

In some cases the interior-point method terminates having found a solution not too far from meeting the optimality condition (6.5). A solution is defined as *near optimal* if scaling ε_p , ε_d and ε_g by any number $\varepsilon_n \in [1.0, +\infty]$ conditions (6.5) are satisfied.

A near optimal solution is therefore of lower quality but still potentially valuable. If for instance the solver stalls, i.e. it can make no more significant progress towards the optimal solution, a near optimal solution could be available and be good enough for the user.

The basis identification discussed in Section 6.2.2.2 requires an optimal solution to work well; hence basis identification should be turned off if the termination criterion is relaxed.

To conclude the discussion in this section, relaxing the termination criterion is usually not worthwhile.

Basis Identification

An interior-point optimizer does not return an optimal basic solution unless the problem has a unique primal and dual optimal solution. Therefore, the interior-point optimizer has an optional post-processing step that computes an optimal basic solution starting from the optimal interior-point solution. More information about the basis identification procedure may be found in [AY96]. In the following we provide an overall idea of the procedure.

There are some cases in which a basic solution could be more valuable:

- a basic solution is often more accurate than an interior-point solution,
- a basic solution can be used to warm-start the simplex algorithm in case of reoptimization,
- a basic solution is in general more sparse, i.e. more variables are fixed to zero. This is particularly appealing when solving continuous relaxation of mixed integer problems, as well as in all applications in which sparser solutions are preferred.

To illustrate how the basis identification routine works, we use the following trivial example:

$$\begin{array}{ll} \text{minimize} & x + y \\ \text{subject to} & x + y = 1, \\ & x, y \geq 0. \end{array}$$

It is easy to see that all feasible solutions are also optimal. In particular, there are two basic solutions namely

$$\begin{array}{ll} (x_1^*, y_1^*) &= (1, 0), \\ (x_2^*, y_2^*) &= (0, 1). \end{array}$$

The interior point algorithm will actually converge to the center of the optimal set, i.e. to $(x^*, y^*) = (1/2, 1/2)$ (to see this in **MOSEK** deactivate *Presolve*).

In practice, when the algorithm gets close to the optimal solution, it is possible to construct in polynomial time an initial basis for the simplex algorithm from the current interior point solution. This basis is used to warm-start the simplex algorithm that will provide the optimal basic solution.

In most cases the constructed basis is optimal, or very few iterations are required by the simplex algorithm to make it optimal and hence the final *clean* phase be short. However, in some cases for nasty problems e.g. ill-conditioned problems the additional simplex clean up phase may take of lot a time.

By default **MOSEK** performs a basis identification. However, if a basic solution is not needed, the basis identification procedure can be turned off. The parameters

- `MSK_IPAR_INTPNT_BASIS`,
- `MSK_IPAR_BI_IGNORE_MAX_ITER`, and
- `MSK_IPAR_BI_IGNORE_NUM_ERROR`

control when basis identification is performed.

The type of simplex algorithm to be used can be tuned by the `MSK_IPAR_BI_CLEAN_OPTIMIZER` parameter i.e. primal or dual simplex, and the maximum number of iterations can be set by the `MSK_IPAR_BI_MAX_ITERATIONS`.

Finally, it should be mentioned that there is no guarantee on which basic solution will be returned.

The Interior-point Log

Below is a typical log output from the interior-point optimizer presented:

Optimizer	- threads	:	1						
Optimizer	- solved problem	:	the dual						
Optimizer	- Constraints	:	2						
Optimizer	- Cones	:	0						
Optimizer	- Scalar variables	:	6	conic	:	0			
Optimizer	- Semi-definite variables:	:	0	scalarized	:	0			
Factor	- setup time	:	0.00	dense det. time	:	0.00			
Factor	- ML order time	:	0.00	GP order time	:	0.00			
Factor	- nonzeros before factor	:	3	after factor	:	3			
Factor	- dense dim.	:	0	flops	:	7.00e+001			
ITE	PFEAS	DFEAS	GFEAS	PRSTATUS	POBJ	DOBJ	MU	TIME	
0	1.0e+000	8.6e+000	6.1e+000	1.00e+000	0.000000000e+000	-2.208000000e+003	1.0e+000	0.00	
1	1.1e+000	2.5e+000	1.6e-001	0.00e+000	-7.901380925e+003	-7.394611417e+003	2.5e+000	0.00	
2	1.4e-001	3.4e-001	2.1e-002	8.36e-001	-8.113031650e+003	-8.055866001e+003	3.3e-001	0.00	
3	2.4e-002	5.8e-002	3.6e-003	1.27e+000	-7.777530698e+003	-7.766471080e+003	5.7e-002	0.01	
4	1.3e-004	3.2e-004	2.0e-005	1.08e+000	-7.668323435e+003	-7.668207177e+003	3.2e-004	0.01	
5	1.3e-008	3.2e-008	2.0e-009	1.00e+000	-7.668000027e+003	-7.668000015e+003	3.2e-008	0.01	
6	1.3e-012	3.2e-012	2.0e-013	1.00e+000	-7.667999994e+003	-7.667999994e+003	3.2e-012	0.01	

The first line displays the number of threads used by the optimizer and second line tells that the optimizer chose to solve the dual problem rather than the primal problem. The next line displays the problem dimensions as seen by the optimizer, and the `Factor...` lines show various statistics. This is followed by the iteration log.

Using the same notation as in Section 6.2.2 the columns of the iteration log have the following meaning:

- ITE: Iteration index.
- PFEAS: $\|Ax^k - b\tau^k\|_\infty$. The numbers in this column should converge monotonically towards zero but may stall at low level due to rounding errors.
- DFEAS: $\|A^T y^k + s^k - c\tau^k\|_\infty$. The numbers in this column should converge monotonically toward zero but may stall at low level due to rounding errors.

- **GFEAS**: $|-c^T x^k + b^T y^k - \kappa^k|$. The numbers in this column should converge monotonically toward zero but may stall at low level due to rounding errors.
- **PRSTATUS**: This number converges to 1 if the problem has an optimal solution whereas it converges to -1 if that is not the case.
- **POBJ**: $c^T x^k / \tau^k$. An estimate for the primal objective value.
- **DOBJ**: $b^T y^k / \tau^k$. An estimate for the dual objective value.
- **MU**: $\frac{(x^k)^T s^k + \tau^k \kappa^k}{n+1}$. The numbers in this column should always converge monotonically to zero.
- **TIME**: Time spend since the optimization started.

6.2.3 The simplex Based Optimizer

An alternative to the interior-point optimizer is the simplex optimizer.

The simplex optimizer uses a different method that allows exploiting an initial guess for the optimal solution to reduce the solution time. Depending on the problem it may be faster or slower to use an initial guess; see section 6.2.4 for a discussion.

MOSEK provides both a primal and a dual variant of the simplex optimizer — we will return to this later.

Simplex Termination Criterion

The simplex optimizer terminates when it finds an optimal basic solution or an infeasibility certificate. A basic solution is optimal when it is primal and dual feasible; see Section 5.1 and 5.1.1 for a definition of the primal and dual problem. Due to the fact that computations are performed in finite precision **MOSEK** allows violation of primal and dual feasibility within certain tolerances. The user can control the allowed primal and dual tolerances with the parameters `MSK_DPAR_BASIS_TOL_X` and `MSK_DPAR_BASIS_TOL_S`.

Starting From an Existing Solution

When using the simplex optimizer it may be possible to reuse an existing solution and thereby reduce the solution time significantly. When a simplex optimizer starts from an existing solution it is said to perform a *warm-start*. If the user is solving a sequence of optimization problems by solving the problem, making modifications, and solving again, **MOSEK** will warm-start automatically.

Setting the parameter `MSK_IPAR_OPTIMIZER` to `MSK_OPTIMIZER_FREE_SIMPLEX` instructs **MOSEK** to select automatically between the primal and the dual simplex optimizers. Hence, **MOSEK** tries to choose the best optimizer for the given problem and the available solution.

By default **MOSEK** uses presolve when performing a warm-start. If the optimizer only needs very few iterations to find the optimal solution it may be better to turn off the presolve.

Numerical Difficulties in the Simplex Optimizers

Though **MOSEK** is designed to minimize numerical instability, completely avoiding it is impossible when working in finite precision. **MOSEK** counts a “numerical unexpected behavior” event inside the optimizer as a *set-back*. The user can define how many set-backs the optimizer accepts; if that number is exceeded, the optimization will be aborted. Set-backs are implemented to avoid long sequences where the optimizer tries to recover from an unstable situation.

Set-backs are, for example, repeated singularities when factorizing the basis matrix, repeated loss of feasibility, degeneracy problems (no progress in objective) and other events indicating numerical difficulties. If the simplex optimizer encounters a lot of set-backs the problem is usually badly scaled; in such

a situation try to reformulate into a better scaled problem. Then, if a lot of set-backs still occur, trying one or more of the following suggestions may be worthwhile:

- Raise tolerances for allowed primal or dual feasibility: Hence, increase the value of
 - `MSK_DPAR_BASIS_TOL_X`, and
 - `MSK_DPAR_BASIS_TOL_S`.
- Raise or lower pivot tolerance: Change the `MSK_DPAR_SIMPLEX_ABS_TOL_PIV` parameter.
- Switch optimizer: Try another optimizer.
- Switch off crash: Set both `MSK_IPAR_SIM_PRIMAL_CRASH` and `MSK_IPAR_SIM_DUAL_CRASH` to 0.
- Experiment with other pricing strategies: Try different values for the parameters
 - `MSK_IPAR_SIM_PRIMAL_SELECTION` and
 - `MSK_IPAR_SIM_DUAL_SELECTION`.
- If you are using warm-starts, in rare cases switching off this feature may improve stability. This is controlled by the `MSK_IPAR_SIM_HOTSTART` parameter.
- Increase maximum set backs allowed controlled by `MSK_IPAR_SIM_MAX_NUM_SETBACKS`.
- If the problem repeatedly becomes infeasible try switching off the special degeneracy handling. See the parameter `MSK_IPAR_SIM_DEGEN` for details.

6.2.4 The Interior-point or the Simplex Optimizer?

Given a linear optimization problem, which optimizer is the best: The primal simplex, the dual simplex or the interior-point optimizer?

It is impossible to provide a general answer to this question. However, the interior-point optimizer behaves more predictably: it tends to use between 20 and 100 iterations, almost independently of problem size, but cannot perform warm-start, while simplex can take advantage of an initial solution, but is less predictable for cold-start. The interior-point optimizer is used by default.

6.2.5 The Primal or the Dual Simplex Variant?

MOSEK provides both a primal and a dual simplex optimizer. Predicting which simplex optimizer is faster is impossible, however, in recent years the dual optimizer has seen several algorithmic and computational improvements, which, in our experience, makes it faster on average than the primal simplex optimizer. Still, it depends much on the problem structure and size.

Setting the `MSK_IPAR_OPTIMIZER` parameter to `MSK_OPTIMIZER_FREE_SIMPLEX` instructs **MOSEK** to choose which simplex optimizer to use automatically.

To summarize, if you want to know which optimizer is faster for a given problem type, you should try all the optimizers.

6.3 Conic Optimization

6.3.1 The Interior-point Optimizer

For conic optimization problems only an interior-point type optimizer is available. The interior-point optimizer is an implementation of the so-called homogeneous and self-dual algorithm. For a detailed description of the algorithm, please see [\[ART03\]](#).

Interior-point Termination Criteria

The parameters controlling when the conic interior-point optimizer terminates are shown in Table 6.2.

Table 6.2: Parameters employed in termination criterion.

Parameter name	Purpose
<i>MSK_DPAR_INTPNT_CO_TOL_PFEAS</i>	Controls primal feasibility
<i>MSK_DPAR_INTPNT_CO_TOL_DFEAS</i>	Controls dual feasibility
<i>MSK_DPAR_INTPNT_CO_TOL_REL_GAP</i>	Controls relative gap
<i>MSK_DPAR_INTPNT_TOL_INFEAS</i>	Controls when the problem is declared infeasible
<i>MSK_DPAR_INTPNT_CO_TOL_MU_RED</i>	Controls when the complementarity is reduced enough

6.4 Nonlinear Convex Optimization

6.4.1 The Interior-point Optimizer

For quadratic, quadratically constrained, and general convex optimization problems an interior-point type optimizer is available. The interior-point optimizer is an implementation of the homogeneous and self-dual algorithm. For a detailed description of the algorithm, please see [AY98], [AY99].

The Convexity Requirement

Continuous nonlinear problems are required to be convex. For quadratic problems **MOSEK** test this requirement before optimizing. Specifying a non-convex problem results in an error message.

The following parameters are available to control the convexity check:

- *MSK_IPAR_CHECK_CONVEXITY*: Turn convexity check on/off.
- *MSK_DPAR_CHECK_CONVEXITY_REL_TOL*: Tolerance for convexity check.
- *MSK_IPAR_LOG_CHECK_CONVEXITY*: Turn on more log information for debugging.

The Differentiability Requirement

The nonlinear optimizer in **MOSEK** requires both first order and second order derivatives. This of course implies care should be taken when solving problems involving non-differentiable functions.

For instance, the function

$$f(x) = x^2$$

is differentiable everywhere whereas the function

$$f(x) = \sqrt{x}$$

is only differentiable for $x > 0$. In order to make sure that **MOSEK** evaluates the functions at points where they are differentiable, the function domains must be defined by setting appropriate variable bounds.

In general, if a variable is not ranged **MOSEK** will only evaluate that variable at points strictly within the bounds. Hence, imposing the bound

$$x \geq 0$$

in the case of \sqrt{x} is sufficient to guarantee that the function will only be evaluated in points where it is differentiable.

However, if a function is differentiable on a closed range, specifying the variable bounds is not sufficient. Consider the function

$$f(x) = \frac{1}{x} + \frac{1}{1-x}. \quad (6.6)$$

In this case the bounds

$$0 \leq x \leq 1$$

will not guarantee that **MOSEK** only evaluates the function for x between 0 and 1. To force **MOSEK** to strictly satisfy both bounds on ranged variables set the parameter `MSK_IPAR_INTPNT_STARTING_POINT` to `MSK_STARTING_POINT_SATISFY_BOUNDS`.

For efficiency reasons it may be better to reformulate the problem than to force **MOSEK** to observe ranged bounds strictly. For instance, (6.6) can be reformulated as follows

$$\begin{aligned} f(x) &= \frac{1}{x} + \frac{1}{y} \\ 0 &= 1 - x - y \\ 0 &\leq x \\ 0 &\leq y. \end{aligned}$$

Interior-point Termination Criteria

The parameters controlling when the general convex interior-point optimizer terminates are shown in Table 6.3.

Table 6.3: Parameters employed in termination criteria.

Parameter name	Purpose
<code>MSK_DPAR_INTPNT_NL_TOL_PFEAS</code>	Controls primal feasibility
<code>MSK_DPAR_INTPNT_NL_TOL_DFEAS</code>	Controls dual feasibility
<code>MSK_DPAR_INTPNT_NL_TOL_REL_GAP</code>	Controls relative gap
<code>MSK_DPAR_INTPNT_TOL_INFEAS</code>	Controls when the problem is declared infeasible
<code>MSK_DPAR_INTPNT_NL_TOL_MU_RED</code>	Controls when the complementarity is reduced enough

6.5 Using Multiple Threads in an Optimizer

If multiple cores are available then it is possible for **MOSEK** to take advantage of them to speed up the computation. However, please note the speedup achieved is going to be dependent on the problem characteristics e.g. the size of problem. Typically for smallish problems no speedup is obtained by exploiting multiple cores. In fact forcing **MOSEK** to use one core can increase speed because parallel overhead is avoided.

6.5.1 Thread Safety

The **MOSEK** API is thread-safe provided that a task is only modified or accessed from one thread at any given time. Also accessing two or more separate tasks from threads at the same time is safe. Sharing an environment between threads is safe.

6.5.2 Determinism

The optimizers are run-to-run deterministic which means if a problem is solved twice on the same computer using the same parameter setting and exactly the same input then exactly the same results is obtained. One qualification is that no time limits must be imposed because the time taken to perform an operation on a computer is dependent on many factors such as the current workload.

6.5.3 The Parallelized Interior-point Optimizer

By default the interior-point optimizer exploits multiple cores using multithreading. Hence, big tasks such as large dense matrix multiplication may be divided into several independent smaller tasks that can be computed independently. However, there is a computational overhead associated with exploiting multiple threads e.g. cost of the additional coordination etc. Therefore, it may be advantageous to turn off the multithreading for smallish problem using the parameter `MSK_IPAR_INTPNT_MULTI_THREAD`.

Moreover, when the interior-point optimizer is allowed to exploit multiple threads, then the parameter `MSK_IPAR_NUM_THREADS` controls the maximum number of threads (and therefore the number of cores) that **MOSEK** will employ.

THE OPTIMIZER FOR MIXED-INTEGER PROBLEMS

A problem is a mixed-integer optimization problem when one or more of the variables are constrained to be integer valued. **MOSEK** can solve mixed-integer

- linear,
- quadratic and quadratically constrained, and
- conic quadratic

problems.

Readers unfamiliar with integer optimization are recommended to consult some relevant literature, e.g. the book [Wol98] by Wolsey.

7.1 Some Concepts and Facts Related to Mixed-integer Optimization

It is important to understand that in a worst-case scenario, the time required to solve integer optimization problems grows exponentially with the size of the problem. For instance, assume that a problem contains n binary variables, then the time required to solve the problem in the worst case may be proportional to 2^n . The value of 2^n is huge even for moderate values of n .

In practice this implies that the focus should be on computing a near optimal solution quickly rather than on locating an optimal solution. Even if the problem is only solved approximately, it is important to know how far the approximate solution is from an optimal one. In order to say something about the quality of an approximate solution the concept of *relaxation* is important.

The mixed-integer optimization problem

$$\begin{aligned} z^* = \quad & \text{minimize} && c^T x \\ & \text{subject to} && Ax = b, \\ & && x \geq 0 \\ & && x_j \in \mathbb{Z}, \quad \forall j \in \mathcal{J}, \end{aligned} \tag{7.1}$$

has the continuous relaxation

$$\begin{aligned} \underline{z} = \quad & \text{minimize} && c^T x \\ & \text{subject to} && Ax = b, \\ & && x \geq 0 \end{aligned} \tag{7.2}$$

The continuous relaxation is identical to the mixed-integer problem with the restriction that some variables must be integers removed.

There are two important observations about the continuous relaxation. First, the continuous relaxation is usually much faster to optimize than the mixed-integer problem. Secondly if \hat{x} is any feasible solution to (7.1) and

$$\bar{z} := c^T \hat{x}$$

then

$$\underline{z} \leq z^* \leq \bar{z}.$$

This is an important observation since if it is only possible to find a near optimal solution within a reasonable time frame then the quality of the solution can nevertheless be evaluated. The value \underline{z} is a lower bound on the optimal objective value. This implies that the obtained solution is no further away from the optimum than $\bar{z} - \underline{z}$ in terms of the objective value.

Whenever a mixed-integer problem is solved **MOSEK** reports this lower bound so that the quality of the reported solution can be evaluated.

7.2 The Mixed-integer Optimizer

The mixed-integer optimizer can handle problems with linear, quadratic objective and constraints and conic constraints. However, a problem can not contain both quadratic objective or constraints and conic constraints.

The mixed-integer optimizer is specialized for solving linear and conic optimization problems. It can also solve pure quadratic and quadratically constrained problems; these problems are automatically converted to conic problems before being solved.

The mixed-integer optimizer is run-to-run deterministic. This means that if a problem is solved twice on the same computer with identical options then the obtained solution will be bit-for-bit identical for the two runs. However, if a time limit is set then this may not be case since the time taken to solve a problem is not deterministic. The mixed-integer optimizer is parallelized i.e. it can exploit multiple cores during the optimization.

The solution process can be split into these phases:

1. **Presolve:** In this phase the optimizer tries to reduce the size of the problem and improve the formulation using preprocessing techniques. The presolve stage can be turned off using the `MSK_IPAR_PRESOLVE_USE` parameter
2. **Cut generation:** Valid inequalities (cuts) are added to improve the lower bound
3. **Heuristic:** Using heuristics the optimizer tries to guess a good feasible solution. Heuristics can be controlled by the parameter `MSK_IPAR_MIO_HEURISTIC_LEVEL`
4. **Search:** The optimal solution is located by branching on integer variables

7.3 Termination Criterion

In general, it is time consuming to find an exact feasible and optimal solution to an integer optimization problem, though in many practical cases it may be possible to find a sufficiently good solution. Therefore, the mixed-integer optimizer employs a relaxed feasibility and optimality criterion to determine when a satisfactory solution is located.

A candidate solution that is feasible for the continuous relaxation is said to be an integer feasible solution if the criterion

$$\min(x_j - \lfloor x_j \rfloor, \lceil x_j \rceil - x_j) \leq \delta_1 \quad \forall j \in \mathcal{J}$$

is satisfied, meaning that x_j is at most δ_1 from the nearest integer.

Whenever the integer optimizer locates an integer feasible solution it will check if the criterion

$$\bar{z} - \underline{z} \leq \max(\delta_2, \delta_3 \max(10^{-10}, |\bar{z}|))$$

is satisfied. If this is the case, the integer optimizer terminates and reports the integer feasible solution as an optimal solution. Please note that \underline{z} is a valid lower bound determined by the integer optimizer during the solution process, i.e.

$$\underline{z} \leq z^*.$$

The lower bound \underline{z} normally increases during the solution process.

7.3.1 Relaxed Termination

If an optimal solution cannot be located within a reasonable time, it may be advantageous to employ a relaxed termination criterion after some time. Whenever the integer optimizer locates an integer feasible solution and has spent at least the number of seconds defined by the `MSK_DPAR_MIO_DISABLE_TERM_TIME` parameter on solving the problem, it will check whether the criterion

$$\bar{z} - \underline{z} \leq \max(\delta_4, \delta_5 \max(10^{-10}, |\bar{z}|))$$

is satisfied. If it is satisfied, the optimizer will report that the candidate solution is **near optimal** and then terminate. Please note that since this criterion depends on timing, the optimizer will not be run to run deterministic.

7.4 Parameters Affecting the Termination of the Integer Optimizer.

All δ tolerances can be adjusted using suitable parameters — see Table 7.1.

Table 7.1: Tolerances for the mixed-integer optimizer.

Tolerance	Parameter name
δ_1	<code>MSK_DPAR_MIO_TOL_ABS_RELAX_INT</code>
δ_2	<code>MSK_DPAR_MIO_TOL_ABS_GAP</code>
δ_3	<code>MSK_DPAR_MIO_TOL_REL_GAP</code>
δ_4	<code>MSK_DPAR_MIO_NEAR_TOL_ABS_GAP</code>
δ_5	<code>MSK_DPAR_MIO_NEAR_TOL_REL_GAP</code>

In Table 7.2 some other parameters affecting the integer optimizer termination criterion are shown. Please note that if the effect of a parameter is delayed, the associated termination criterion is applied only after some time, specified by the `MSK_DPAR_MIO_DISABLE_TERM_TIME` parameter.

Table 7.2: Other parameters affecting the integer optimizer termination criterion.

Parameter name	De- layed	Explanation
<code>MSK_IPAR_MIO_MAX_NUM_BRANCHES</code>	Yes	Maximum number of branches allowed.
<code>MSK_IPAR_MIO_MAX_NUM_RELAXS</code>	Yes	Maximum number of relaxations allowed.
<code>MSK_IPAR_MIO_MAX_NUM_SOLUTIONS</code>	Yes	Maximum number of feasible integer solutions allowed.

7.5 How to Speed Up the Solution Process

As mentioned previously, in many cases it is not possible to find an optimal solution to an integer optimization problem in a reasonable amount of time. Some suggestions to reduce the solution time are:

- Relax the termination criterion: In case the run time is not acceptable, the first thing to do is to relax the termination criterion — see Section 7.3 for details.
- Specify a good initial solution: In many cases a good feasible solution is either known or easily computed using problem specific knowledge. If a good feasible solution is known, it is usually worthwhile to use this as a starting point for the integer optimizer.
- Improve the formulation: A mixed-integer optimization problem may be impossible to solve in one form and quite easy in another form. However, it is beyond the scope of this manual to discuss good formulations for mixed-integer problems. For discussions on this topic see for example [\[Wol98\]](#).

7.6 Understanding Solution Quality

To determine the quality of the solution one should check the following:

- The solution status key returned by **MOSEK**
- The *optimality gap*: A measure of how much the located solution can deviate from the optimal solution to the problem
- Feasibility. How much the solution violates the constraints of the problem

The *optimality gap* is a measure for how close the solution is to the optimal solution. The optimality gap is given by

$$\epsilon = |(\text{objective value of feasible solution}) - (\text{objective bound})|.$$

The objective value of the solution is guaranteed to be within ϵ of the optimal solution.

The optimality gap can be retrieved through the solution item `MSK_DINF_MIO_OBJ_ABS_GAP`. Often it is more meaningful to look at the optimality gap normalized with the magnitude of the solution. The relative optimality gap is available in `MSK_DINF_MIO_OBJ_REL_GAP`.

PROBLEM ANALYZER

The problem analyzer prints a detailed survey of the

- linear constraints and objective
- quadratic constraints
- conic constraints
- variables

of the model.

In the initial stages of model formulation the problem analyzer may be used as a quick way of verifying that the model has been built or imported correctly. In later stages it can help revealing special structures within the model that may be used to tune the optimizer's performance or to identify the causes of numerical difficulties.

The problem analyzer is run from the command line using the *-anapro* argument and produces something similar to the following (this is the problem analyzer's survey of the *aflow30a* problem from the MIPLIB 2003 collection.)

Analyzing the problem

Constraints		Bounds		Variables	
upper bd:	421	ranged	: all	cont:	421
fixed :	58			bin :	421

Objective, min cx

range: min c :	0.00000	min c >0:	11.0000	max c :	500.000
distrib:	c	vars			
	0	421			
	[11, 100)	150			
	[100, 500]	271			

Constraint matrix A has

479 rows (constraints)
842 columns (variables)
2091 (0.518449%) nonzero entries (coefficients)

Row nonzeros, A_i

range: min A_i:	2 (0.23753%)	max A_i:	34 (4.038%)
distrib:	A_i	rows	rows% acc%
	2	421	87.89 87.89
	[8, 15]	20	4.18 92.07
	[16, 31]	30	6.26 98.33
	[32, 34]	8	1.67 100.00

```

Column nonzeros, A|j
  range: min A|j: 2 (0.417537%)    max A|j: 3 (0.626305%)
distrib:      A|j      cols      cols%      acc%
              2        435        51.66        51.66
              3        407        48.34        100.00

A nonzeros, A(ij)
  range: min |A(ij)|: 1.00000    max |A(ij)|: 100.000
distrib:      A(ij)      coeffs
              [1, 10)      1670
              [10, 100]     421

```

```

-----
Constraint bounds, lb <= Ax <= ub
distrib:      |b|      lbs      ub
              0      421
              [1, 10]      58      58

```

```

Variable bounds, lb <= x <= ub
distrib:      |b|      lbs      ub
              0      842
              [1, 10)      421
              [10, 100]     421

```

The survey is divided into six different sections, each described below. To keep the presentation short with focus on key elements the analyzer generally attempts to display information on issues relevant for the current model only: E.g., if the model does not have any conic constraints (this is the case in the example above) or any integer variables, those parts of the analysis will not appear.

8.1 General Characteristics

The first part of the survey consists of a brief summary of the model's linear and quadratic constraints (indexed by i) and variables (indexed by j). The summary is divided into three subsections:

Constraints

- **upper bd** The number of upper bounded constraints, $\sum_{j=0}^{n-1} a_{ij}x_j \leq u_i^c$
- **lower bd** The number of lower bounded constraints, $l_i^c \leq \sum_{j=0}^{n-1} a_{ij}x_j$
- **ranged** The number of ranged constraints, $l_i^c \leq \sum_{j=0}^{n-1} a_{ij}x_j \leq u_i^c$
- **fixed** The number of fixed constraints, $l_i^c = \sum_{j=0}^{n-1} a_{ij}x_j = u_i^c$
- **free** The number of free constraints

Bounds

- **upper bd** The number of upper bounded variables, $x_j \leq u_j^x$
- **lower bd** The number of lower bounded variables, $l_k^x \leq x_j$
- **ranged** The number of ranged variables, $l_k^x \leq x_j \leq u_j^x$
- **fixed** The number of fixed variables, $l_k^x = x_j = u_j^x$

- **free** The number of free variables

Variables

- **cont** The number of continuous variables, $x_j \in \mathbb{R}$
- **bin** The number of binary variables, $x_j \in \{0, 1\}$
- **int** The number of general integer variables, $x_j \in \mathbb{Z}$

Only constraints, bounds and domains actually in the model will be reported on; if all entities in a section turn out to be of the same kind, the number will be replaced by **all** for brevity.

8.2 Objective

The second part of the survey focuses on (the linear part of) the objective, summarizing the optimization sense and the coefficients' absolute value range and distribution. The number of 0 (zero) coefficients is singled out (if any such variables are in the problem).

The range is displayed using three terms:

- **min |c|** The minimum absolute value among all coefficients
- **min |c|>0** The minimum absolute value among the nonzero coefficients
- **max |c|** The maximum absolute value among the coefficients

If some of these extrema turn out to be equal, the display is shortened accordingly:

- If **min |c|** is greater than zero, the **min |c|>0** term is obsolete and will not be displayed
- If only one or two different coefficients occur this will be displayed using **all** and an explicit listing of the coefficients

The absolute value distribution is displayed as a table summarizing the numbers by orders of magnitude (with a ratio of 10). Again, the number of variables with a coefficient of 0 (if any) is singled out. Each line of the table is headed by an interval (half-open intervals including their lower bounds), and is followed by the number of variables with their objective coefficient in this interval. Intervals with no elements are skipped.

8.3 Linear Constraints

The third part of the survey displays information on the nonzero coefficients of the linear constraint matrix.

Following a brief summary of the matrix dimensions and the number of nonzero coefficients in total, three sections provide further details on how the nonzero coefficients are distributed by row-wise count (**A|j**), by column-wise count (**A|i**), and by absolute value (**|A(ij)|**). Each section is headed by a brief display of the distribution's range (**min** and **max**), and for the row/column-wise counts the corresponding densities are displayed too (in parentheses).

The distribution tables single out three particularly interesting counts: zero, one, and two nonzeros per row/column; the remaining row/column nonzeros are displayed by orders of magnitude (ratio 2). For each interval the relative and accumulated relative counts are also displayed.

Note that constraints may have both linear and quadratic terms, but the empty rows and columns reported in this part of the survey relate to the linear terms only. If empty rows and/or columns are found in the linear constraint matrix, the problem is analyzed further in order to determine if the corresponding constraints have any quadratic terms or the corresponding variables are used in conic or quadratic constraints.

The distribution of the absolute values, $|A(ij)|$, is displayed just as for the objective coefficients described above.

8.4 Constraint and Variable Bounds

The fourth part of the survey displays distributions for the absolute values of the finite lower and upper bounds for both constraints and variables. The number of bounds at 0 is singled out and, otherwise, displayed by orders of magnitude (with a ratio of 10).

8.5 Quadratic Constraints

The fifth part of the survey displays distributions for the nonzero elements in the gradient of the quadratic constraints, i.e. the nonzero row counts for the column vectors Qx . The table is similar to the tables for the linear constraints' nonzero row and column counts described in the survey's third part.

Note: Quadratic constraints may also have a linear part, but that will be included in the linear constraints survey; this means that if a problem has one or more pure quadratic constraints, part three of the survey will report an equal number of linear constraint rows with 0 (zero) nonzeros. Likewise, variables that appear in quadratic terms only will be reported as empty columns (0 nonzeros) in the linear constraint report.

8.6 Conic Constraints

The last part of the survey summarizes the model's conic constraints. For each of the two types of cones, quadratic and rotated quadratic, the total number of cones are reported, and the distribution of the cones' dimensions are displayed using intervals. Cone dimensions of 2, 3, and 4 are singled out.

ANALYZING INFEASIBLE PROBLEMS

When developing and implementing a new optimization model, the first attempts will often be either infeasible, due to specification of inconsistent constraints, or unbounded, if important constraints have been left out.

In this section we will

- go over an example demonstrating how to locate infeasible constraints using the **MOSEK** infeasibility report tool,
- discuss in more general terms which properties may cause infeasibilities, and
- present the more formal theory of infeasible and unbounded problems.

9.1 Example: Primal Infeasibility

A problem is said to be *primal infeasible* if no solution exists that satisfies all the constraints of the problem.

As an example of a primal infeasible problem consider the problem of minimizing the cost of transportation between a number of production plants and stores: Each plant produces a fixed number of goods, and each store has a fixed demand that must be met. Supply, demand and cost of transportation per unit are given in Fig. 9.1.




Fig. 9.1: Supply, demand and cost of transportation.

The problem represented in Fig. 9.1 is infeasible, since the total demand

$$2300 = 1100 + 200 + 500 + 500$$

exceeds the total supply

$$2200 = 200 + 1000 + 1000$$

If we denote the number of transported goods from plant i to store j by x_{ij} , the problem can be formulated as the LP:

$$\begin{array}{llllllllllll}
 \text{minimize} & x_{11} & + & 2x_{12} & + & 5x_{23} & + & 2x_{24} & + & x_{31} & + & 2x_{33} & + & x_{34} \\
 \text{subject to} & x_{11} & + & x_{12} & & & & & & & & & & \leq 200, \\
 & & & & & x_{23} & + & x_{24} & & & & & & \leq 1000, \\
 & & & & & & & & x_{31} & + & x_{33} & + & x_{34} & \leq 1000, \\
 & x_{11} & & & & & & & + & x_{31} & & & & = 1100, \quad (9.1) \\
 & & x_{12} & & & & & & & & & & & = 200, \\
 & & & x_{23} & + & & & & & & x_{33} & & & = 500, \\
 & & & & & x_{24} & + & & & & & x_{34} & = 500, \\
 & x_{ij} & \geq 0.
 \end{array}$$

Solving problem (9.1) using **MOSEK** will result in a solution, a solution status and a problem status. Among the log output from the execution of **MOSEK** on the above problem are the lines:

```

Basic solution
Problem status : PRIMAL_INFEASIBLE
Solution status : PRIMAL_INFEASIBLE_CER

```

The first line indicates that the problem status is primal infeasible. The second line says that a *certificate of the infeasibility* was found. The certificate is returned in place of the solution to the problem.

9.2 Locating the cause of Primal Infeasibility

Usually a primal infeasible problem status is caused by a mistake in formulating the problem and therefore the question arises: *What is the cause of the infeasible status?* When trying to answer this question, it is often advantageous to follow these steps:

- Remove the objective function. This does not change the infeasibility status but simplifies the problem, eliminating any possibility of issues related to the objective function.
- Consider whether your problem has some necessary conditions for feasibility and examine if these are satisfied, e.g. total supply should be greater than or equal to total demand.
- Verify that coefficients and bounds are reasonably sized in your problem.

If the problem is still primal infeasible, some of the constraints must be relaxed or removed completely. The **MOSEK** infeasibility report (Section 9.4) may assist you in finding the constraints causing the infeasibility.

Possible ways of relaxing your problem include:

- Increasing (decreasing) upper (lower) bounds on variables and constraints.
- Removing suspected constraints from the problem.

Returning to the transportation example, we discover that removing the fifth constraint

$$x_{12} = 200$$

makes the problem feasible.

9.3 Locating the Cause of Dual Infeasibility

A problem may also be *dual infeasible*. In this case the primal problem is often unbounded, meaning that feasible solutions exist such that the objective tends towards infinity. An example of a dual infeasible

and primal unbounded problem is:

$$\begin{array}{ll}\text{minimize} & x_1 \\ \text{subject to} & x_1 \leq 5.\end{array}$$

To resolve a dual infeasibility the primal problem must be made more restricted by

- Adding upper or lower bounds on variables or constraints.
- Removing variables.
- Changing the objective.

9.3.1 A cautionary note

The problem

$$\begin{array}{ll}\text{minimize} & 0 \\ \text{subject to} & 0 \leq x_1, \\ & x_j \leq x_{j+1}, \quad j = 1, \dots, n-1, \\ & x_n \leq -1\end{array}$$

is clearly infeasible. Moreover, if any one of the constraints is dropped, then the problem becomes feasible.

This illustrates the worst case scenario where all, or at least a significant portion of the constraints are involved in causing infeasibility. Hence, it may not always be easy or possible to pinpoint a few constraints responsible for infeasibility.

9.4 The Infeasibility Report

MOSEK includes functionality for diagnosing the cause of a primal or a dual infeasibility. It can be turned on by setting the `MSK_IPAR_INFEAS_REPORT_AUTO` to `MSK_ON`. This causes **MOSEK** to print a report on variables and constraints involved in the infeasibility.

The `MSK_IPAR_INFEAS_REPORT_LEVEL` parameter controls the amount of information presented in the infeasibility report. The default value is 1.

9.4.1 Example: Primal Infeasibility

We will keep working with the problem (9.1) written in LP format:

Listing 9.1: The code for problem (9.1).

```
\
\ An example of an infeasible linear problem.
\
minimize
  obj: + 1 x11 + 2 x12
        + 5 x23 + 2 x24
        + 1 x31 + 2 x33 + 1 x34
st
  s0: + x11 + x12          <= 200
  s1: + x23 + x24          <= 1000
  s2: + x31 + x33 + x34    <= 1000
  d1: + x11 + x31          = 1100
  d2: + x12                = 200
  d3: + x23 + x33          = 500
  d4: + x24 + x34          = 500
bounds
end
```

Using the command line (please remember it accepts options following the C API format)

```
mosek -d MSK_IPAR_INFEAS_REPORT_AUTO MSK_ON infeas.lp
```

MOSEK produces the following infeasibility report:

MOSEK PRIMAL INFEASIBILITY REPORT.

Problem status: The problem is primal infeasible

The following constraints are involved in the primal infeasibility.

Index	Name	Lower bound	Upper bound	Dual lower	Dual upper
0	s0	NONE	2.000000e+002	0.000000e+000	1.000000e+000
2	s2	NONE	1.000000e+003	0.000000e+000	1.000000e+000
3	d1	1.100000e+003	1.100000e+003	1.000000e+000	0.000000e+000
4	d2	2.000000e+002	2.000000e+002	1.000000e+000	0.000000e+000

The following bound constraints are involved in the infeasibility.

Index	Name	Lower bound	Upper bound	Dual lower	Dual upper
8	x33	0.000000e+000	NONE	1.000000e+000	0.000000e+000
10	x34	0.000000e+000	NONE	1.000000e+000	0.000000e+000

The infeasibility report is divided into two sections corresponding to constraints and variables. It is a selection of those lines from the problem solution (in this case the file `infeas.sol`), which are important in understanding primal infeasibility. In this case the constraints `s0`, `s2`, `d1`, `d2` and variables `x33`, `x34` are of importance.

The columns `Dual lower` and `Dual upper` contain the values of dual variables s_l^c , s_u^c , s_l^x and s_u^x in the primal infeasibility certificate (see Section 5.1.2.1). Only the non-zero ones, which contribute to the optimization objective and thus are important for infeasibility, are shown.

It is also possible to obtain the infeasible subproblem. The command line

```
mosek -d MSK_IPAR_INFEAS_REPORT_AUTO MSK_ON infeas.lp -info rinfeas.lp
```

produces the files `rinfeas.bas.inf.lp`. In this case the content of the file `rinfeas.bas.inf.lp` is

```
minimize
obj:  + 0 x11 + 0 x12 + 0 x13 + 0 x21 + 0 x22 + 0 x23
      + 0 x31 + 0 x32 + 0 x33 + 0 x24 + 0 x34
subject to
s0:  + x11 + x12 <= 2e+02
s2:  + x31 + x33 + x34 <= 1e+03
d1:  + x11 + x31 = 1.1e+03
d2:  + x12 = 2e+02
bounds
x11 free
x12 free
x13 free
x21 free
x22 free
x23 free
x31 free
x32 free
0 <= x33 <= +infinity
x24 free
0 <= x34 <= +infinity
end
```

which is an optimization problem. This problem is identical to (9.1), except that the objective and some of the constraints and bounds have been removed. Executing the command

```
mosek -d MSK_IPAR_INFEAS_REPORT_AUTO MSK_ON rinfeas.bas.inf.lp
```

demonstrates that the reduced problem is **primal infeasible**. Since the reduced problem is usually smaller than original problem, it should be easier to locate the cause of infeasibility in this rather than in the original (9.1).

9.4.2 Example: Dual Infeasibility

The following problem is dual to (9.1) and therefore it is dual infeasible.

Listing 9.2: The dual of problem (9.1).

```
maximize + 200 y1 + 1000 y2 + 1000 y3 + 1100 y4 + 200 y5 + 500 y6 + 500 y7
subject to
  x11: y1+y4 < 1
  x12: y1+y5 < 2
  x23: y2+y6 < 5
  x24: y2+y7 < 2
  x31: y3+y4 < 1
  x33: y3+y6 < 2
  x34: y3+y7 < 1
bounds
  -inf <= y1 < 0
  -inf <= y2 < 0
  -inf <= y3 < 0
  y4 free
  y5 free
  y6 free
  y7 free
end
```

This can be verified by proving that

$$(y_1, \dots, y_7) = (-1, 0, -1, 1, 1, 0, 0)$$

is a certificate of dual infeasibility (see Section 5.1.2.2) as we can see from this report:

```
MOSEK DUAL INFEASIBILITY REPORT.

Problem status: The problem is dual infeasible

The following constraints are involved in the infeasibility.

Index   Name      Activity      Objective      Lower bound      Upper bound
5       x33       -1.000000e+00  2.000000e+02   NONE             2.000000e+00
6       x34       -1.000000e+00  1.100000e+03   NONE             1.000000e+00

The following variables are involved in the infeasibility.

Index   Name      Activity      Objective      Lower bound      Upper bound
0       y1       -1.000000e+00  2.000000e+02   NONE             0.000000e+00
2       y3       -1.000000e+00  1.000000e+03   NONE             0.000000e+00
3       y4       1.000000e+00   1.100000e+03   NONE             NONE
4       y5       1.000000e+00   2.000000e+02   NONE             NONE

Interior-point solution summary
Problem status : DUAL_INFEASIBLE
Solution status : DUAL_INFEASIBLE_CER
Primal.  obj: 1.0000000000e+02   nrm: 1e+00   Viol.  con: 0e+00   var: 0e+00
```

Let y^* denote the reported primal solution. **MOSEK** states

- that the problem is *dual infeasible*,
- that the reported solution is a certificate of dual infeasibility, and
- that the infeasibility measure for y^* is approximately zero.

Since the original objective was maximization, we have that $c^T y^* > 0$. See Section 5.1.2 for how to interpret the parameter values in the infeasibility report for a linear program. We see that the variables $y1$, $y3$, $y4$, $y5$ and the constraints $x33$ and $x34$ contribute to infeasibility with non-zero values in the Activity column.

One possible strategy to *fix* the infeasibility is to modify the problem so that the certificate of infeasibility becomes invalid. In this case we could do one the following things:

- Add a lower bound on $y3$. This will directly invalidate the certificate of dual infeasibility.
- Increase the object coefficient of $y3$. Changing the coefficients sufficiently will invalidate the inequality $c^T y^* > 0$ and thus the certificate.
- Add lower bounds on $x11$ or $x31$. This will directly invalidate the certificate of infeasibility.

Please note that modifying the problem to invalidate the reported certificate does *not* imply that the problem becomes dual feasible — the reason for infeasibility may simply *move*, resulting a problem that is still infeasible, but for a different reason.

More often, the reported certificate can be used to give a hint about errors or inconsistencies in the model that produced the problem.

9.5 Theory Concerning Infeasible Problems

This section discusses the theory of infeasibility certificates and how **MOSEK** uses a certificate to produce an infeasibility report. In general, **MOSEK** solves the problem

$$\begin{array}{llll} \text{minimize} & & c^T x + c^f & \\ \text{subject to} & l^c \leq & Ax & \leq u^c, \\ & l^x \leq & x & \leq u^x \end{array} \quad (9.2)$$

where the corresponding dual problem is

$$\begin{array}{ll} \text{maximize} & (l^c)^T s_l^c - (u^c)^T s_u^c \\ & + (l^x)^T s_l^x - (u^x)^T s_u^x + c^f \\ \text{subject to} & A^T y + s_l^x - s_u^x = c, \\ & -y + s_l^c - s_u^c = 0, \\ & s_l^c, s_u^c, s_l^x, s_u^x \leq 0. \end{array} \quad (9.3)$$

We use the convention that for any bound that is not finite, the corresponding dual variable is fixed at zero (and thus will have no influence on the dual problem). For example

$$l_j^x = -\infty \quad \Rightarrow \quad (s_l^x)_j = 0$$

9.6 The Certificate of Primal Infeasibility

A certificate of primal infeasibility is *any* solution to the homogenized dual problem

$$\begin{array}{ll} \text{maximize} & (l^c)^T s_l^c - (u^c)^T s_u^c \\ & + (l^x)^T s_l^x - (u^x)^T s_u^x \\ \text{subject to} & A^T y + s_l^x - s_u^x = 0, \\ & -y + s_l^c - s_u^c = 0, \\ & s_l^c, s_u^c, s_l^x, s_u^x \leq 0. \end{array}$$

with a positive objective value. That is, $(s_l^{c*}, s_u^{c*}, s_l^{x*}, s_u^{x*})$ is a certificate of primal infeasibility if

$$(l^c)^T s_l^{c*} - (u^c)^T s_u^{c*} + (l^x)^T s_l^{x*} - (u^x)^T s_u^{x*} > 0$$

and

$$\begin{aligned} A^T y + s_l^{x*} - s_u^{x*} &= 0, \\ -y + s_l^{c*} - s_u^{c*} &= 0, \\ s_l^{c*}, s_u^{c*}, s_l^{x*}, s_u^{x*} &\leq 0. \end{aligned}$$

The well-known *Farkas Lemma* tells us that (9.2) is infeasible if and only if a certificate of primal infeasibility exists.

Let $(s_l^{c*}, s_u^{c*}, s_l^{x*}, s_u^{x*})$ be a certificate of primal infeasibility then

$$(s_l^{c*})_i > 0 ((s_u^{c*})_i > 0)$$

implies that the lower (upper) bound on the i th constraint is important for the infeasibility. Furthermore,

$$(s_l^{x*})_j > 0 ((s_u^{x*})_j > 0)$$

implies that the lower (upper) bound on the j th variable is important for the infeasibility.

9.7 The certificate of dual infeasibility

A certificate of dual infeasibility is *any* solution to the problem

$$\begin{aligned} &\text{minimize} && c^T x \\ &\text{subject to} && \bar{l}^c \leq Ax \leq \bar{u}^c, \\ &&& \bar{l}^x \leq x \leq \bar{u}^x \end{aligned}$$

with negative objective value, where we use the definitions

$$\bar{l}_i^c := \begin{cases} 0, & l_i^c > -\infty, \\ -\infty, & \text{otherwise,} \end{cases}, \quad \bar{u}_i^c := \begin{cases} 0, & u_i^c < \infty, \\ \infty, & \text{otherwise,} \end{cases}$$

and

$$\bar{l}_i^x := \begin{cases} 0, & l_i^x > -\infty, \\ -\infty, & \text{otherwise,} \end{cases} \quad \text{and} \quad \bar{u}_i^x := \begin{cases} 0, & u_i^x < \infty, \\ \infty, & \text{otherwise.} \end{cases}$$

Stated differently, a certificate of dual infeasibility is any x^* such that

$$\begin{aligned} c^T x^* &< 0, \\ \bar{l}^c &\leq Ax^* \leq \bar{u}^c, \\ \bar{l}^x &\leq x^* \leq \bar{u}^x \end{aligned} \tag{9.4}$$

The well-known Farkas Lemma tells us that (9.3) is infeasible if and only if a certificate of dual infeasibility exists.

Note that if x^* is a certificate of dual infeasibility then for any j such that

$$x_j^* \leq 0,$$

variable j is involved in the dual infeasibility.

Given the assumption that all weights are 1 then the command

```
mosek -primalrepair -d MSK_IPAR_LOG_FEAS_REPAIR 3 feasrepair.lp
```

will form the repaired problem and solve it. The parameter `MSK_IPAR_LOG_FEAS_REPAIR` controls the amount of log output from the repair. A value of 2 causes the optimal repair to be printed out.

The output from running the above command is:

```

Copyright (c) MOSEK ApS, Denmark. WWW: mosek.com

Open file 'feasrepair.lp'

Read summary
Type           : LO (linear optimization problem)
Objective sense : min
Constraints     : 4
Scalar variables : 2
Matrix variables : 0
Time           : 0.0

Computer
Platform       : Windows/64-X86
Cores          : 4

Problem
Name           :
Objective sense : min
Type           : LO (linear optimization problem)
Constraints     : 4
Cones          : 0
Scalar variables : 2
Matrix variables : 0
Integer variables : 0

Primal feasibility repair started.
Optimizer started.
Interior-point optimizer started.
Presolve started.
Linear dependency checker started.
Linear dependency checker terminated.
Eliminator started.
Total number of eliminations : 2
Eliminator terminated.
Eliminator - tries          : 1          time          : 0.00
Eliminator - elim's        : 2
Lin. dep. - tries          : 1          time          : 0.00
Lin. dep. - number         : 0
Presolve terminated. Time: 0.00
Optimizer - threads         : 1
Optimizer - solved problem  : the primal
Optimizer - Constraints     : 2
Optimizer - Cones          : 0
Optimizer - Scalar variables : 6          conic          : 0
Optimizer - Semi-definite variables: 0      scalarized       : 0
Factor - setup time         : 0.00        dense det. time  : 0.00
Factor - ML order time      : 0.00        GP order time    : 0.00
Factor - nonzeros before factor : 3        after factor     : 3
Factor - dense dim.         : 0          flops            : 5.40e+001
ITE PFEAS  DFEAS  GFEAS  PRSTATUS  POBJ          DOBJ          MU          TIME
0  2.7e+001  1.0e+000  4.8e+000  1.00e+000  4.195228609e+000  0.000000000e+000  1.0e+000  0.00
1  2.4e+001  8.6e-001  1.5e+000  0.00e+000  1.227497414e+001  1.504971820e+001  2.6e+000  0.00
2  2.6e+000  9.7e-002  1.7e-001  -6.19e-001  4.363064729e+001  4.648523094e+001  3.0e-001  0.00
3  4.7e-001  1.7e-002  3.1e-002  1.24e+000  4.256803136e+001  4.298540657e+001  5.2e-002  0.00
4  8.7e-004  3.2e-005  5.7e-005  1.08e+000  4.249989892e+001  4.250078747e+001  9.7e-005  0.00
5  8.7e-008  3.2e-009  5.7e-009  1.00e+000  4.249999999e+001  4.250000008e+001  9.7e-009  0.00
6  8.7e-012  3.2e-013  5.7e-013  1.00e+000  4.250000000e+001  4.250000000e+001  9.7e-013  0.00
Basis identification started.
Primal basis identification phase started.
ITER      TIME
0          0.00
Primal basis identification phase terminated. Time: 0.00

```

```

Dual basis identification phase started.
ITER      TIME
0         0.00
Dual basis identification phase terminated. Time: 0.00
Basis identification terminated. Time: 0.00
Interior-point optimizer terminated. Time: 0.00.

Optimizer terminated. Time: 0.03
Basic solution summary
Problem status : PRIMAL_AND_DUAL_FEASIBLE
Solution status : OPTIMAL
Primal.  obj: 4.2500000000e+001  Viol.  con: 1e-013  var: 0e+000
Dual.    obj: 4.2500000000e+001  Viol.  con: 0e+000  var: 5e-013
Optimal objective value of the penalty problem: 4.250000000000e+001

Repairing bounds.
Increasing the upper bound -2.25e+001 on constraint 'c4' (3) with 1.35e+002.
Decreasing the lower bound 6.50e+002 on variable 'x2' (4) with 2.00e+001.
Primal feasibility repair terminated.
Optimizer started.
Interior-point optimizer started.
Presolve started.
Presolve terminated. Time: 0.00
Interior-point optimizer terminated. Time: 0.00.

Optimizer terminated. Time: 0.00

Interior-point solution summary
Problem status : PRIMAL_AND_DUAL_FEASIBLE
Solution status : OPTIMAL
Primal.  obj: -5.6700000000e+003  Viol.  con: 0e+000  var: 0e+000
Dual.    obj: -5.6700000000e+003  Viol.  con: 0e+000  var: 0e+000

Basic solution summary
Problem status : PRIMAL_AND_DUAL_FEASIBLE
Solution status : OPTIMAL
Primal.  obj: -5.6700000000e+003  Viol.  con: 0e+000  var: 0e+000
Dual.    obj: -5.6700000000e+003  Viol.  con: 0e+000  var: 0e+000

Optimizer summary
Optimizer          -                time: 0.00
Interior-point    - iterations : 0      time: 0.00
Basis identification -                time: 0.00
Primal           - iterations : 0      time: 0.00
Dual             - iterations : 0      time: 0.00
Clean primal     - iterations : 0      time: 0.00
Clean dual       - iterations : 0      time: 0.00
Clean primal-dual - iterations : 0      time: 0.00
Simplex          -                time: 0.00
Primal simplex   - iterations : 0      time: 0.00
Dual simplex     - iterations : 0      time: 0.00
Primal-dual simplex - iterations : 0      time: 0.00
Mixed integer    - relaxations: 0      time: 0.00

```

reports the optimal repair. In this case it is to increase the upper bound on constraint c4 by 1.35e2 and decrease the lower bound on variable x2 by 20.

SENSITIVITY ANALYSIS

Given an optimization problem it is often useful to obtain information about how the optimal objective value changes when the problem parameters are perturbed. E.g, assume that a bound represents the capacity of a machine. Now, it may be possible to expand the capacity for a certain cost and hence it is worthwhile knowing what the value of additional capacity is. This is precisely the type of questions the sensitivity analysis deals with.

Analyzing how the optimal objective value changes when the problem data is changed is called *sensitivity analysis*.

References

The book [Chv83] discusses the classical sensitivity analysis in Chapter 10 whereas the book [RTV97] presents a modern introduction to sensitivity analysis. Finally, it is recommended to read the short paper [Wal00] to avoid some of the pitfalls associated with sensitivity analysis.

Warning: Currently, sensitivity analysis is only available for continuous linear optimization problems. Moreover, **MOSEK** can only deal with perturbations of bounds and objective function coefficients.

10.1 Sensitivity Analysis for Linear Problems

10.1.1 The Optimal Objective Value Function

Assume that we are given the problem

$$\begin{aligned} z(l^c, u^c, l^x, u^x, c) = & \text{minimize} && c^T x \\ & \text{subject to} && l^c \leq Ax \leq u^c, \\ & && l^x \leq x \leq u^x, \end{aligned} \quad (10.1)$$

and we want to know how the optimal objective value changes as l_i^c is perturbed. To answer this question we define the perturbed problem for l_i^c as follows

$$\begin{aligned} f_{l_i^c}(\beta) = & \text{minimize} && c^T x \\ & \text{subject to} && l^c + \beta e_i \leq Ax \leq u^c, \\ & && l^x \leq x \leq u^x, \end{aligned}$$

where e_i is the i -th column of the identity matrix. The function

$$f_{l_i^c}(\beta) \quad (10.2)$$

shows the optimal objective value as a function of β . Please note that a change in β corresponds to a perturbation in l_i^c and hence (10.2) shows the optimal objective value as a function of varying l_i^c with the other bounds fixed.

It is possible to prove that the function (10.2) is a piecewise linear and convex function, i.e. its graph may look like in Fig. 10.1 and Fig. 10.2.




Fig. 10.1: $\beta = 0$ is in the interior of linearity interval.

Clearly, if the function $f_{l_i^c}(\beta)$ does not change much when β is changed, then we can conclude that the optimal objective value is insensitive to changes in l_i^c . Therefore, we are interested in the rate of change in $f_{l_i^c}(\beta)$ for small changes in β — specifically the gradient

$$f'_{l_i^c}(0),$$

which is called the *shadow price* related to l_i^c . The shadow price specifies how the objective value changes for small changes of β around zero. Moreover, we are interested in the *linearity interval*

$$\beta \in [\beta_1, \beta_2]$$

for which

$$f'_{l_i^c}(\beta) = f'_{l_i^c}(0).$$

Since $f_{l_i^c}$ is not a smooth function $f'_{l_i^c}$ may not be defined at 0, as illustrated in Fig. 10.2. In this case we can define a left and a right shadow price and a left and a right linearity interval.

The function $f_{l_i^c}$ considered only changes in l_i^c . We can define similar functions for the remaining parameters of the z defined in (10.1) as well:

$$\begin{aligned} f_{l_i^c}(\beta) &= z(l^c + \beta e_i, u^c, l^x, u^x, c), & i &= 1, \dots, m, \\ f_{u_i^c}(\beta) &= z(l^c, u^c + \beta e_i, l^x, u^x, c), & i &= 1, \dots, m, \\ f_{l_j^x}(\beta) &= z(l^c, u^c, l^x + \beta e_j, u^x, c), & j &= 1, \dots, n, \\ f_{u_j^x}(\beta) &= z(l^c, u^c, l^x, u^x + \beta e_j, c), & j &= 1, \dots, n, \\ f_{c_j}(\beta) &= z(l^c, u^c, l^x, u^x, c + \beta e_j), & j &= 1, \dots, n. \end{aligned}$$

Given these definitions it should be clear how linearity intervals and shadow prices are defined for the parameters u_i^c etc.

Fig. 10.2: $\beta = 0$ is a breakpoint.

Equality Constraints

In **MOSEK** a constraint can be specified as either an equality constraint or a ranged constraint. If some constraint e_i^c is an equality constraint, we define the optimal value function for this constraint as

$$f_{e_i^c}(\beta) = z(l^c + \beta e_i, u^c + \beta e_i, l^x, u^x, c)$$

Thus for an equality constraint the upper and the lower bounds (which are equal) are perturbed simultaneously. Therefore, **MOSEK** will handle sensitivity analysis differently for a ranged constraint with $l_i^c = u_i^c$ and for an equality constraint.

10.1.2 The Basis Type Sensitivity Analysis

The classical sensitivity analysis discussed in most textbooks about linear optimization, e.g. [Chv83], is based on an optimal basic solution or, equivalently, on an optimal basis. This method may produce misleading results [RTV97] but is **computationally cheap**. Therefore, and for historical reasons, this method is available in **MOSEK**.

We will now briefly discuss the basis type sensitivity analysis. Given an optimal basic solution which provides a partition of variables into basic and non-basic variables, the basis type sensitivity analysis computes the linearity interval $[\beta_1, \beta_2]$ so that the basis remains optimal for the perturbed problem. A shadow price associated with the linearity interval is also computed. However, it is well-known that an optimal basic solution may not be unique and therefore the result depends on the optimal basic solution employed in the sensitivity analysis. This implies that the computed interval is only a subset of the largest interval for which the shadow price is constant. Furthermore, the optimal objective value function might have a breakpoint for $\beta = 0$. In this case the basis type sensitivity method will only provide a subset of either the left or the right linearity interval.

In summary, the basis type sensitivity analysis is computationally cheap but does not provide complete information. Hence, the results of the basis type sensitivity analysis should be used with care.

10.1.3 The Optimal Partition Type Sensitivity Analysis

Another method for computing the complete linearity interval is called the *optimal partition type sensitivity analysis*. The main drawback of the optimal partition type sensitivity analysis is that it is computationally expensive compared to the basis type analysis. This type of sensitivity analysis is currently provided as an experimental feature in **MOSEK**.

Given the optimal primal and dual solutions to (10.1), i.e. x^* and $((s_l^c)^*, (s_u^c)^*, (s_l^x)^*, (s_u^x)^*)$ the optimal objective value is given by

$$z^* := c^T x^*.$$

The left and right shadow prices σ_1 and σ_2 for l_i^c are given by this pair of optimization problems:

$$\begin{aligned} \sigma_1 = & \text{minimize} && e_i^T s_l^c \\ & \text{subject to} && A^T(s_l^c - s_u^c) + s_l^x - s_u^x = c, \\ & && (l^c)^T(s_l^c) - (u^c)^T(s_u^c) + (l^x)^T(s_l^x) - (u^x)^T(s_u^x) = z^*, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0 \end{aligned}$$

and

$$\begin{aligned} \sigma_2 = & \text{maximize} && e_i^T s_l^c \\ & \text{subject to} && A^T(s_l^c - s_u^c) + s_l^x - s_u^x = c, \\ & && (l^c)^T(s_l^c) - (u^c)^T(s_u^c) + (l^x)^T(s_l^x) - (u^x)^T(s_u^x) = z^*, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0. \end{aligned}$$

These two optimization problems make it easy to interpret the shadow price. Indeed, if $((s_l^c)^*, (s_u^c)^*, (s_l^x)^*, (s_u^x)^*)$ is an arbitrary optimal solution then

$$(s_l^c)^* \in [\sigma_1, \sigma_2].$$

Next, the linearity interval $[\beta_1, \beta_2]$ for l_i^c is computed by solving the two optimization problems

$$\begin{aligned} \beta_1 = & \text{minimize} && \beta \\ & \text{subject to} && l^c + \beta e_i \leq Ax \leq u^c, \\ & && c^T x - \sigma_1 \beta = z^*, \\ & && l^x \leq x \leq u^x, \end{aligned}$$

and

$$\begin{aligned} \beta_2 = & \text{maximize} && \beta \\ & \text{subject to} && l^c + \beta e_i \leq Ax \leq u^c, \\ & && c^T x - \sigma_2 \beta = z^*, \\ & && l^x \leq x \leq u^x. \end{aligned}$$

The linearity intervals and shadow prices for u_i^c , l_j^x , and u_j^x are computed similarly to l_i^c .

The left and right shadow prices for c_j denoted σ_1 and σ_2 respectively are computed as follows:

$$\begin{aligned} \sigma_1 = & \text{minimize} && e_j^T x \\ & \text{subject to} && l^c + \beta e_i \leq Ax \leq u^c, \\ & && c^T x = z^*, \\ & && l^x \leq x \leq u^x, \end{aligned}$$

and

$$\begin{aligned} \sigma_2 = & \text{maximize} && e_j^T x \\ & \text{subject to} && l^c + \beta e_i \leq Ax \leq u^c, \\ & && c^T x = z^*, \\ & && l^x \leq x \leq u^x. \end{aligned}$$

Once again the above two optimization problems make it easy to interpret the shadow prices. Indeed, if x^* is an arbitrary primal optimal solution, then

$$x_j^* \in [\sigma_1, \sigma_2].$$

The linearity interval $[\beta_1, \beta_2]$ for a c_j is computed as follows:

$$\begin{aligned} \beta_1 = & \text{minimize} && \beta \\ & \text{subject to} && A^T(s_l^c - s_u^c) + s_l^x - s_u^x = c + \beta e_j, \\ & && (l^c)^T(s_l^c) - (u^c)^T(s_u^c) + (l^x)^T(s_l^x) - (u^x)^T(s_u^x) - \sigma_1 \beta \leq z^*, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0 \end{aligned}$$

and

$$\begin{aligned} \beta_2 = & \text{maximize} && \beta \\ & \text{subject to} && A^T(s_l^c - s_u^c) + s_l^x - s_u^x = c + \beta e_j, \\ & && (l^c)^T(s_l^c) - (u^c)^T(s_u^c) + (l^x)^T(s_l^x) - (u^x)^T(s_u^x) - \sigma_2 \beta \leq z^*, \\ & && s_l^c, s_u^c, s_l^x, s_u^x \geq 0. \end{aligned}$$

10.1.4 Example: Sensitivity Analysis

As an example we will use the following transportation problem. Consider the problem of minimizing the transportation cost between a number of production plants and stores. Each plant supplies a number of goods and each store has a given demand that must be met. Supply, demand and cost of transportation per unit are shown in Fig. 10.3.




Fig. 10.3: Supply, demand and cost of transportation.

If we denote the number of transported goods from location i to location j by x_{ij} , problem can be formulated as the linear optimization problem of minimizing

$$1x_{11} + 2x_{12} + 5x_{23} + 2x_{24} + 1x_{31} + 2x_{33} + 1x_{34}$$

subject to

$$\begin{aligned} x_{11} + x_{12} & \leq 400, \\ x_{23} + x_{24} & \leq 1200, \\ x_{31} + x_{33} + x_{34} & \leq 1000, \\ x_{11} + x_{31} & = 800, \\ x_{12} + x_{31} & = 100, \\ x_{23} + x_{33} & = 500, \\ x_{24} + x_{34} & = 500, \\ x_{11}, x_{12}, x_{23}, x_{24}, x_{31}, x_{33}, x_{34} & \geq 0. \end{aligned} \tag{10.3}$$

The sensitivity parameters are shown in Table 10.1 and Table 10.2 for the basis type analysis and in Table 10.3 and Table 10.4 for the optimal partition type analysis.

Table 10.1: Ranges and shadow prices related to bounds on constraints and variables: results for the basis type sensitivity analysis.

Con.	β_1	β_2	σ_1	σ_2
1	-300.00	0.00	3.00	3.00
2	-700.00	$+\infty$	0.00	0.00
3	-500.00	0.00	3.00	3.00
4	-0.00	500.00	4.00	4.00
5	-0.00	300.00	5.00	5.00
6	-0.00	700.00	5.00	5.00
7	-500.00	700.00	2.00	2.00
Var.	β_1	β_2	σ_1	σ_2
x_{11}	$-\infty$	300.00	0.00	0.00
x_{12}	$-\infty$	100.00	0.00	0.00
x_{23}	$-\infty$	0.00	0.00	0.00
x_{24}	$-\infty$	500.00	0.00	0.00
x_{31}	$-\infty$	500.00	0.00	0.00
x_{33}	$-\infty$	500.00	0.00	0.00
x_{34}	-0.000000	500.00	2.00	2.00

Table 10.2: Ranges and shadow prices related to bounds on constraints and variables: results for the optimal partition type sensitivity analysis.

Con.	β_1	β_2	σ_1	σ_2
1	-300.00	500.00	3.00	1.00
2	-700.00	$+\infty$	-0.00	-0.00
3	-500.00	500.00	3.00	1.00
4	-500.00	500.00	2.00	4.00
5	-100.00	300.00	3.00	5.00
6	-500.00	700.00	3.00	5.00
7	-500.00	700.00	2.00	2.00
Var.	β_1	β_2	σ_1	σ_2
x_{11}	$-\infty$	300.00	0.00	0.00
x_{12}	$-\infty$	100.00	0.00	0.00
x_{23}	$-\infty$	500.00	0.00	2.00
x_{24}	$-\infty$	500.00	0.00	0.00
x_{31}	$-\infty$	500.00	0.00	0.00
x_{33}	$-\infty$	500.00	0.00	0.00
x_{34}	$-\infty$	500.00	0.00	2.00

Table 10.3: Ranges and shadow prices related to the objective coefficients: results for the basis type sensitivity analysis.

Var.	β_1	β_2	σ_1	σ_2
c_1	$-\infty$	3.00	300.00	300.00
c_2	$-\infty$	∞	100.00	100.00
c_3	-2.00	∞	0.00	0.00
c_4	$-\infty$	2.00	500.00	500.00
c_5	-3.00	∞	500.00	500.00
c_6	$-\infty$	2.00	500.00	500.00
c_7	-2.00	∞	0.00	0.00

Table 10.4: Ranges and shadow prices related to the objective coefficients: results for the optimal partition type sensitivity analysis.

Var.	β_1	β_2	σ_1	σ_2
c_1	$-\infty$	3.00	300.00	300.00
c_2	$-\infty$	∞	100.00	100.00
c_3	-2.00	∞	0.00	0.00
c_4	$-\infty$	2.00	500.00	500.00
c_5	-3.00	∞	500.00	500.00
c_6	$-\infty$	2.00	500.00	500.00
c_7	-2.00	∞	0.00	0.00

Examining the results from the optimal partition type sensitivity analysis we see that for constraint number 1 we have $\sigma_1 = 3$, $\sigma_2 = 1$ and $\beta_1 = -300$, $\beta_2 = 500$. Therefore, we have a left linearity interval of $[-300, 0]$ and a right interval of $[0, 500]$. The corresponding left and right shadow prices are 3 and 1 respectively. This implies that if the upper bound on constraint 1 increases by

$$\beta \in [0, \beta_1] = [0, 500]$$

then the optimal objective value will decrease by the value

$$\sigma_2 \beta = 1\beta.$$

Correspondingly, if the upper bound on constraint 1 is decreased by

$$\beta \in [0, 300]$$

then the optimal objective value will increase by the value

$$\sigma_1 \beta = 3\beta.$$

10.2 Sensitivity Analysis with MOSEK

A sensitivity analysis can be performed with the **MOSEK** command line tool specifying the option `-sen`, e.g.

```
mosek myproblem.mps -sen sensitivity.ssp
```

where `sensitivity.ssp` is a file in the format described in the next section. The `ssp` file describes which parts of the problem the sensitivity analysis should be performed on, see Section 10.2.1.

By default results are written to a file named `myproblem.sen`. If necessary, this filename can be changed by setting the `MSK_SPAR_SENSITIVITY_RES_FILE_NAME` parameter. By default a basis type sensitivity analysis is performed. However, the type of sensitivity analysis (basis or optimal partition) can be changed by setting the parameter `MSK_IPAR_SENSITIVITY_TYPE` appropriately. Following values are accepted for this parameter:

- `MSK_SENSITIVITY_TYPE_BASIS`
- `MSK_SENSITIVITY_TYPE_OPTIMAL_PARTITION`

10.2.1 Sensitivity Analysis Specification File

MOSEK employs an MPS-like file format to specify on which model parameters the sensitivity analysis should be performed. As the optimal partition type sensitivity analysis can be computationally expensive it is important to limit the sensitivity analysis.

The format of the sensitivity specification file is shown in Listing 10.1, where capitalized names are keywords, and names in brackets are names of the constraints and variables to be included in the analysis.

Listing 10.1: Sensitivity analysis file specification.

```
BOUNDS CONSTRAINTS
U|L|LU [cname1]
U|L|LU [cname2] - [cname3]
BOUNDS VARIABLES
U|L|LU [vname1]
U|L|LU [vname2] - [vname3]
OBJECTIVE VARIABLES
[vname1]
[vname2] - [vname3]
```

The sensitivity specification file has three sections, i.e.

- **BOUNDS CONSTRAINTS:** Specifies on which bounds on constraints the sensitivity analysis should be performed.
- **BOUNDS VARIABLES:** Specifies on which bounds on variables the sensitivity analysis should be performed.
- **OBJECTIVE VARIABLES:** Specifies on which objective coefficients the sensitivity analysis should be performed.

A line in the body of a section must begin with a whitespace. In the **BOUNDS** sections one of the keys L, U, and LU must appear next. These keys specify whether the sensitivity analysis is performed on the lower bound, on the upper bound, or on both the lower and the upper bound respectively. Next, a single constraint (variable) or range of constraints (variables) is specified.

Recall from Section 10.1.1.1 that equality constraints are handled in a special way. Sensitivity analysis of an equality constraint can be specified with either L, U, or LU, all indicating the same, namely that upper and lower bounds (which are equal) are perturbed simultaneously.

As an example consider

```
BOUNDS CONSTRAINTS
L "cons1"
U "cons2"
LU "cons3" - "cons6"
```


which requests that sensitivity analysis is performed on the lower bound of the constraint named `cons1`, on the upper bound of the constraint named `cons2`, and on both lower and upper bound on the constraints named `cons3` to `cons6`.

It is allowed to use indexes instead of names, for instance

```
BOUNDS CONSTRAINTS
L "cons1"
U 2
LU 3 - 6
```

The character `*` indicates that the line contains a comment and is ignored.

10.2.2 Example: Sensitivity Analysis from Command Line

As an example consider problem (10.3): the sensitivity file shown below (included in the distribution among the examples).

Listing 10.2: Sensitivity file for problem (10.3).

```
* Comment 1

BOUNDS CONSTRAINTS
U "c1"          * Analyze upper bound for constraints named c1
U 2             * Analyze upper bound for constraints with index 2
U 3-5          * Analyze upper bound for constraint with index in interval [3:5]

VARIABLES CONSTRAINTS
L 2-4           * This section specifies which bounds on variables should be analyzed.
L "x11"

OBJECTIVE CONSTRAINTS
"x11"          * This section specifies which objective coefficients should be analysed.
2
```

The command

```
mosek transport.lp -sen sensitivity.ssp -d MSK_IPAR_SENSITIVITY_TYPE sensitivitytype.basis
```

produces the output file as follow

```
BOUNDS CONSTRAINTS
INDEX  NAME          BOUND  LEFTRANGE  RIGHTRANGE  LEFTPRICE  RIGHTPRICE
0      c1            UP      -6.574875e-18  5.000000e+02  1.000000e+00  1.
2      c3            UP      -6.574875e-18  5.000000e+02  1.000000e+00  1.
3      c4            FIX      -5.000000e+02  6.574875e-18  2.000000e+00  2.
4      c5            FIX      -1.000000e+02  6.574875e-18  3.000000e+00  3.
5      c6            FIX      -5.000000e+02  6.574875e-18  3.000000e+00  3.

BOUNDS VARIABLES
INDEX  NAME          BOUND  LEFTRANGE  RIGHTRANGE  LEFTPRICE  RIGHTPRICE
2      x23          L0      -6.574875e-18  5.000000e+02  2.000000e+00  2.
3      x24          L0      -inf        5.000000e+02  0.000000e+00  0.
4      x31          L0      -inf        5.000000e+02  0.000000e+00  0.
```

0	x11	L0	-inf	3.000000e+02	0.000000e+00	0.
↪000000e+00						
OBJECTIVE VARIABLES						
INDEX	NAME	LEFTRANGE	RIGHTRANGE	LEFTPRICE	└	
↪RIGHTPRICE						
0	x11	-inf	1.000000e+00	3.000000e+02	3.	
↪000000e+02						
2	x23	-2.000000e+00	+inf	0.000000e+00	0.	
↪000000e+00						

10.2.3 Controlling Log Output

Setting the parameter *MSK_IPAR_LOG_SENSITIVITY* to 1 or 0 (default) controls whether or not the results from sensitivity calculations are printed to the message stream.

The parameter *MSK_IPAR_LOG_SENSITIVITY_OPT* controls the amount of debug information on internal calculations from the sensitivity analysis.

API REFERENCE

11.1 Parameters

All parameters (alphabetical order)

- *double parameters*
- *integer parameters*
- *string parameters*

Parameters grouped by topic

Note: some parameters may appear in more than one group.

- *Conic interior-point method*
- *License manager*
- *Logging*
- *Presolve*
- *Primal simplex optimizer*
- *Dual simplex optimizer*
- *Data input/output*
- *Overall solver*
- *Data check*
- *Basis identification*
- *Simplex optimizer*
- *Output information*
- *Solution input/output*
- *Infeasibility report*
- *Nonlinear convex method*
- *Analysis*
- *Mixed-integer optimization*
- *Termination criterion*
- *Optimization system*
- *Progress call-back*
- *Interior-point method*

- *Debugging*

11.1.1 Parameters List (alphabetically)

Double Parameters

MSK_DPAR_ANA_SOL_INFEAS_TOL

If a constraint violates its bound with an amount larger than this value, the constraint name, index and violation will be printed by the solution analyzer.

Accepted Values: [0.0 ;+inf]

Default Value: 1e-6

Groups: *Analysis*

MSK_DPAR_BASIS_REL_TOL_S

Maximum relative dual bound violation allowed in an optimal basic solution.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-12

Groups: *Simplex optimizer, Termination criterion*

MSK_DPAR_BASIS_TOL_S

Maximum absolute dual bound violation in an optimal basic solution.

Accepted Values: [1.0e-9 ;+inf]

Default Value: 1.0e-6

Groups: *Simplex optimizer, Termination criterion*

MSK_DPAR_BASIS_TOL_X

Maximum absolute primal bound violation allowed in an optimal basic solution.

Accepted Values: [1.0e-9 ;+inf]

Default Value: 1.0e-6

Groups: *Simplex optimizer, Termination criterion*

MSK_DPAR_CHECK_CONVEXITY_REL_TOL

This parameter controls when the full convexity check declares a problem to be non-convex. Increasing this tolerance relaxes the criteria for declaring the problem non-convex.

A problem is declared non-convex if negative (positive) pivot elements are detected in the Cholesky factor of a matrix which is required to be PSD (NSD). This parameter controls how much this non-negativity requirement may be violated.

If d_i is the pivot element for column i , then the matrix Q is considered to not be PSD if:

$$d_i \leq -|Q_{ii}| \text{check_convexity_rel_tol}$$

Accepted Values: [0 ;+inf]

Default Value: 1e-10

Groups: *Interior-point method*

MSK_DPAR_DATA_SYM_MAT_TOL

Absolute zero tolerance for elements in in suymmetric matrixes. If any value in a symmetric matrix is smaller than this parameter in absolute terms **MOSEK** will treat the values as zero and generate a warning.

Accepted Values: [1.0e-16 ;1.0e-6]

Default Value: 1.0e-12

Groups: *Data check*

MSK_DPAR_DATA_SYM_MAT_TOL_HUGE

An element in a symmetric matrix which is larger than this value in absolute size causes an error.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e20

Groups: *Data check*

MSK_DPAR_DATA_SYM_MAT_TOL_LARGE

An element in a symmetric matrix which is larger than this value in absolute size causes a warning message to be printed.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e10

Groups: *Data check*

MSK_DPAR_DATA_TOL_AIJ

Absolute zero tolerance for elements in A . If any value A_{ij} is smaller than this parameter in absolute terms **MOSEK** will treat the values as zero and generate a warning.

Accepted Values: [1.0e-16 ;1.0e-6]

Default Value: 1.0e-12

Groups: *Data check*

MSK_DPAR_DATA_TOL_AIJ_HUGE

An element in A which is larger than this value in absolute size causes an error.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e20

Groups: *Data check*

MSK_DPAR_DATA_TOL_AIJ_LARGE

An element in A which is larger than this value in absolute size causes a warning message to be printed.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e10

Groups: *Data check*

MSK_DPAR_DATA_TOL_BOUND_INF

Any bound which in absolute value is greater than this parameter is considered infinite.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e16

Groups: *Data check*

MSK_DPAR_DATA_TOL_BOUND_WRN

If a bound value is larger than this value in absolute size, then a warning message is issued.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e8

Groups: *Data check*

MSK_DPAR_DATA_TOL_CJ_LARGE

An element in c which is larger than this value in absolute terms causes a warning message to be printed.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e8

Groups: *Data check*

MSK_DPAR_DATA_TOL_C_HUGE

An element in c which is larger than the value of this parameter in absolute terms is considered to be huge and generates an error.

Accepted Values: [0.0 ; +inf]

Default Value: 1.0e16

Groups: *Data check*

MSK_DPAR_DATA_TOL_QIJ

Absolute zero tolerance for elements in Q matrices.

Accepted Values: [0.0 ; +inf]

Default Value: 1.0e-16

Groups: *Data check*

MSK_DPAR_DATA_TOL_X

Zero tolerance for constraints and variables i.e. if the distance between the lower and upper bound is less than this value, then the lower and upper bound is considered identical.

Accepted Values: [0.0 ; +inf]

Default Value: 1.0e-8

Groups: *Data check*

MSK_DPAR_INTPNT_CO_TOL_DFEAS

Dual feasibility tolerance used by the conic interior-point optimizer.

Accepted Values: [0.0 ; 1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_CO_TOL_INFEAS

Controls when the conic interior-point optimizer declares the model primal or dual infeasible. A small number means the optimizer gets more conservative about declaring the model infeasible.

Accepted Values: [0.0 ; 1.0]

Default Value: 1.0e-10

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_CO_TOL_MU_RED

Relative complementarity gap feasibility tolerance used by the conic interior-point optimizer.

Accepted Values: [0.0 ; 1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_CO_TOL_NEAR_REL

If **MOSEK** cannot compute a solution that has the prescribed accuracy, then it will multiply the termination tolerances with value of this parameter. If the solution then satisfies the termination criteria, then the solution is denoted near optimal, near feasible and so forth.

Accepted Values: [1.0 ; +inf]

Default Value: 1000

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_CO_TOL_PFEAS

Primal feasibility tolerance used by the conic interior-point optimizer.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_CO_TOL_REL_GAP

Relative gap termination tolerance used by the conic interior-point optimizer.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-7

Groups: *Interior-point method, Termination criterion, Conic interior-point method*

MSK_DPAR_INTPNT_NL_MERIT_BAL

Controls if the complementarity and infeasibility is converging to zero at about equal rates.

Accepted Values: [0.0 ;0.99]

Default Value: 1.0e-4

Groups: *Interior-point method, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_DFEAS

Dual feasibility tolerance used when a nonlinear model is solved.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_MU_RED

Relative complementarity gap tolerance.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-12

Groups: *Interior-point method, Termination criterion, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_NEAR_REL

If the **MOSEK** nonlinear interior-point optimizer cannot compute a solution that has the prescribed accuracy, then it will multiply the termination tolerances with value of this parameter. If the solution then satisfies the termination criteria, then the solution is denoted near optimal, near feasible and so forth.

Accepted Values: [1.0 ;+inf]

Default Value: 1000.0

Groups: *Interior-point method, Termination criterion, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_PFEAS

Primal feasibility tolerance used when a nonlinear model is solved.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_REL_GAP

Relative gap termination tolerance for nonlinear problems.

Accepted Values: [1.0e-14 ;+inf]

Default Value: 1.0e-6

Groups: *Termination criterion, Interior-point method, Nonlinear convex method*

MSK_DPAR_INTPNT_NL_TOL_REL_STEP

Relative step size to the boundary for general nonlinear optimization problems.

Accepted Values: [1.0e-4 ;0.9999999]

Default Value: 0.995

Groups: *Interior-point method, Nonlinear convex method*

MSK_DPAR_INTPNT_QO_TOL_DFEAS

Dual feasibility tolerance used when the interior-point optimizer is applied to a quadratic optimization problem..

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_QO_TOL_INFEAS

Controls when the conic interior-point optimizer declares the model primal or dual infeasible. A small number means the optimizer gets more conservative about declaring the model infeasible.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-10

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_QO_TOL_MU_RED

Relative complementarity gap feasibility tolerance used when interior-point optimizer is applied to a quadratic optimization problem.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_QO_TOL_NEAR_REL

If **MOSEK** cannot compute a solution that has the prescribed accuracy, then it will multiply the termination tolerances with value of this parameter. If the solution then satisfies the termination criteria, then the solution is denoted near optimal, near feasible and so forth.

Accepted Values: [1.0 ;+inf]

Default Value: 1000

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_QO_TOL_PFEAS

Primal feasibility tolerance used when the interior-point optimizer is applied to a quadratic optimization problem.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_QO_TOL_REL_GAP

Relative gap termination tolerance used when the interior-point optimizer is applied to a quadratic optimization problem.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_TOL_DFEAS

Dual feasibility tolerance used for linear and quadratic optimization problems.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_TOL_DSAFE

Controls the initial dual starting point used by the interior-point optimizer. If the interior-point optimizer converges slowly and/or the constraint or variable bounds are very large, then it might be worthwhile to increase this value.

Accepted Values: [1.0e-4 ;+inf]

Default Value: 1.0

Groups: *Interior-point method*

MSK_DPAR_INTPNT_TOL_INFEAS

Controls when the optimizer declares the model primal or dual infeasible. A small number means the optimizer gets more conservative about declaring the model infeasible. A value of 0.0 means the optimizer must have an exact certificate of infeasibility and this is very unlikely to happen.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-10

Groups: *Interior-point method, Termination criterion, Nonlinear convex method*

MSK_DPAR_INTPNT_TOL_MU_RED

Relative complementarity gap tolerance.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-16

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_TOL_PATH

Controls how close the interior-point optimizer follows the central path. A large value of this parameter means the central is followed very closely. On numerical unstable problems it may be worthwhile to increase this parameter.

Accepted Values: [0.0 ;0.9999]

Default Value: 1.0e-8

Groups: *Interior-point method*

MSK_DPAR_INTPNT_TOL_PFEAS

Primal feasibility tolerance used for linear and quadratic optimization problems.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-8

Groups: *Interior-point method, Termination criterion*

MSK_DPAR_INTPNT_TOL_PSAFE

Controls the initial primal starting point used by the interior-point optimizer. If the interior-point optimizer converges slowly and/or the constraint or variable bounds are very large, then it may be worthwhile to increase this value.

Accepted Values: [1.0e-4 ;+inf]

Default Value: 1.0

Groups: *Interior-point method*

MSK_DPAR_INTPNT_TOL_REL_GAP

Relative gap termination tolerance.

Accepted Values: [1.0e-14 ;+inf]

Default Value: 1.0e-8

Groups: *Termination criterion, Interior-point method*

MSK_DPAR_INTPNT_TOL_REL_STEP

Relative step size to the boundary for linear and quadratic optimization problems.

Accepted Values: [1.0e-4 ;0.999999]

Default Value: 0.9999

Groups: *Interior-point method*

MSK_DPAR_INTPNT_TOL_STEP_SIZE

If the step size falls below the value of this parameter, then the interior-point optimizer assumes that it is stalled. In other words the interior-point optimizer does not make any progress and therefore it is better stop.

Accepted Values: [0.0 ;1.0]

Default Value: 1.0e-6

Groups: *Interior-point method*

MSK_DPAR_LOWER_OBJ_CUT

If either a primal or dual feasible solution is found proving that the optimal objective value is outside, the interval [*MSK_DPAR_LOWER_OBJ_CUT*, *MSK_DPAR_UPPER_OBJ_CUT*], then **MOSEK** is terminated.

Accepted Values: [-inf ;+inf]

Default Value: -1.0e30

Groups: *Termination criterion*

MSK_DPAR_LOWER_OBJ_CUT_FINITE_TRH

If the lower objective cut is less than the value of this parameter value, then the lower objective cut i.e. *MSK_DPAR_LOWER_OBJ_CUT* is treated as $-\infty$.

Accepted Values: [-inf ;+inf]

Default Value: -0.5e30

Groups: *Termination criterion*

MSK_DPAR_MIO_DISABLE_TERM_TIME

This parameter specifies the number of seconds n during which the termination criteria governed by

- *MSK_IPAR_MIO_MAX_NUM_RELAXS*
- *MSK_IPAR_MIO_MAX_NUM_BRANCHES*
- *MSK_DPAR_MIO_NEAR_TOL_ABS_GAP*
- *MSK_DPAR_MIO_NEAR_TOL_REL_GAP*

is disabled since the beginning of the optimization.

A negative value is identical to infinity i.e. the termination criteria are never checked.

Accepted Values: [-inf ;+inf]

Default Value: -1.0

Groups: *Mixed-integer optimization, Termination criterion*

MSK_DPAR_MIO_MAX_TIME

This parameter limits the maximum time spent by the mixed-integer optimizer. A negative number means infinity.

Accepted Values: `[-inf ;+inf]`

Default Value: `-1.0`

Groups: *Mixed-integer optimization, Termination criterion*

MSK_DPAR_MIO_NEAR_TOL_ABS_GAP

Relaxed absolute optimality tolerance employed by the mixed-integer optimizer. This termination criteria is delayed. See [MSK_DPAR_MIO_DISABLE_TERM_TIME](#) for details.

Accepted Values: `[0.0 ;+inf]`

Default Value: `0.0`

Groups: *Mixed-integer optimization*

MSK_DPAR_MIO_NEAR_TOL_REL_GAP

The mixed-integer optimizer is terminated when this tolerance is satisfied. This termination criteria is delayed. See [MSK_DPAR_MIO_DISABLE_TERM_TIME](#) for details.

Accepted Values: `[0.0 ;+inf]`

Default Value: `1.0e-3`

Groups: *Mixed-integer optimization, Termination criterion*

MSK_DPAR_MIO_REL_GAP_CONST

This value is used to compute the relative gap for the solution to an integer optimization problem.

Accepted Values: `[1.0e-15 ;+inf]`

Default Value: `1.0e-10`

Groups: *Mixed-integer optimization, Termination criterion*

MSK_DPAR_MIO_TOL_ABS_GAP

Absolute optimality tolerance employed by the mixed-integer optimizer.

Accepted Values: `[0.0 ;+inf]`

Default Value: `0.0`

Groups: *Mixed-integer optimization*

MSK_DPAR_MIO_TOL_ABS_RELAX_INT

Absolute relaxation tolerance of the integer constraints. I.e. $\min(|x| - \lfloor x \rfloor, \lceil x \rceil - |x|)$ is less than the tolerance then the integer restrictions assumed to be satisfied.

Accepted Values: `[1e-9 ;+inf]`

Default Value: `1.0e-5`

Groups: *Mixed-integer optimization*

MSK_DPAR_MIO_TOL_FEAS

Feasibility tolerance for mixed integer solver.

Accepted Values: `[1e-9 ;1e-3]`

Default Value: `1.0e-6`

Groups: *Mixed-integer optimization*

MSK_DPAR_MIO_TOL_REL_DUAL_BOUND_IMPROVEMENT

If the relative improvement of the dual bound is smaller than this value, the solver will terminate the root cut generation. A value of 0.0 means that the value is selected automatically.

Accepted Values: `[0.0 ;1.0]`

Default Value: 0.0

Groups: *Mixed-integer optimization*

MSK_DPAR_MIO_TOL_REL_GAP

Relative optimality tolerance employed by the mixed-integer optimizer.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-4

Groups: *Mixed-integer optimization, Termination criterion*

MSK_DPAR_OPTIMIZER_MAX_TIME

Maximum amount of time the optimizer is allowed to spent on the optimization. A negative number means infinity.

Accepted Values: [-inf ;+inf]

Default Value: -1.0

Groups: *Termination criterion*

MSK_DPAR_PREOLVE_TOL_ABS_LINDEP

Absolute tolerance employed by the linear dependency checker.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-6

Groups: *Presolve*

MSK_DPAR_PREOLVE_TOL_AIJ

Absolute zero tolerance employed for a_{ij} in the presolve.

Accepted Values: [1.0e-15 ;+inf]

Default Value: 1.0e-12

Groups: *Presolve*

MSK_DPAR_PREOLVE_TOL_REL_LINDEP

Relative tolerance employed by the linear dependency checker.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-10

Groups: *Presolve*

MSK_DPAR_PREOLVE_TOL_S

Absolute zero tolerance employed for s_i in the presolve.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-8

Groups: *Presolve*

MSK_DPAR_PREOLVE_TOL_X

Absolute zero tolerance employed for x_j in the presolve.

Accepted Values: [0.0 ;+inf]

Default Value: 1.0e-8

Groups: *Presolve*

MSK_DPAR_QCQO_REFORMULATE_REL_DROP_TOL

This parameter determines when columns are dropped in incomplete Cholesky factorization during reformulation of quadratic problems.

Accepted Values: [0 ;+inf]

Default Value: 1e-15

Groups: *Interior-point method*

MSK_DPAR_SEMIDEFINITE_TOL_APPROX

Tolerance to define a matrix to be positive semidefinite.

Accepted Values: [1.0e-15 ;+inf]

Default Value: 1.0e-10

Groups: *Data check*

MSK_DPAR_SIMPLEX_ABS_TOL_PIV

Absolute pivot tolerance employed by the simplex optimizers.

Accepted Values: [1.0e-12 ;+inf]

Default Value: 1.0e-7

Groups: *Simplex optimizer*

MSK_DPAR_SIM_LU_TOL_REL_PIV

Relative pivot tolerance employed when computing the LU factorization of the basis in the simplex optimizers and in the basis identification procedure.

A value closer to 1.0 generally improves numerical stability but typically also implies an increase in the computational work.

Accepted Values: [1.0e-6 ;0.999999]

Default Value: 0.01

Groups: *Basis identification, Simplex optimizer*

MSK_DPAR_UPPER_OBJ_CUT

If either a primal or dual feasible solution is found proving that the optimal objective value is outside, the interval [*MSK_DPAR_LOWER_OBJ_CUT*, *MSK_DPAR_UPPER_OBJ_CUT*], then **MOSEK** is terminated.

Accepted Values: [-inf ;+inf]

Default Value: 1.0e30

Groups: *Termination criterion*

MSK_DPAR_UPPER_OBJ_CUT_FINITE_TRH

If the upper objective cut is greater than the value of this parameter, then the upper objective cut *MSK_DPAR_UPPER_OBJ_CUT* is treated as ∞ .

Accepted Values: [-inf ;+inf]

Default Value: 0.5e30

Groups: *Termination criterion*

Integer Parameters

MSK_IPAR_ANA_SOL_BASIS

Controls whether the basis matrix is analyzed in solution analyzer.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Analysis*

MSK_IPAR_ANA_SOL_PRINT_VIOLATED

Controls whether a list of violated constraints is printed.

All constraints violated by more than the value set by the parameter *MSK_DPAR_ANA_SOL_INFEAS_TOL* will be printed.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Analysis*

MSK_IPAR_AUTO_SORT_A_BEFORE_OPT

Controls whether the elements in each column of *A* are sorted before an optimization is performed. This is not required but makes the optimization more deterministic.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Debugging*

MSK_IPAR_AUTO_UPDATE_SOL_INFO

Controls whether the solution information items are automatically updated after an optimization is performed.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Optimization system*

MSK_IPAR_BASIS_SOLVE_USE_PLUS_ONE

If a slack variable is in the basis, then the corresponding column in the basis is a unit vector with -1 in the right position. However, if this parameter is set to *MSK_ON*, -1 is replaced by 1.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Simplex optimizer*

MSK_IPAR_BI_CLEAN_OPTIMIZER

Controls which simplex optimizer is used in the clean-up phase.

Accepted Values: *MSK_optimizertypee*

Default Value: *MSK_OPTIMIZER_FREE*

Groups: *Basis identification, Overall solver*

MSK_IPAR_BI_IGNORE_MAX_ITER

If the parameter *MSK_IPAR_INTPNT_BASIS* has the value *MSK_BI_NO_ERROR* and the interior-point optimizer has terminated due to maximum number of iterations, then basis identification is performed if this parameter has the value *MSK_ON*.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Interior-point method, Basis identification*

MSK_IPAR_BI_IGNORE_NUM_ERROR

If the parameter *MSK_IPAR_INTPNT_BASIS* has the value *MSK_BI_NO_ERROR* and the interior-point optimizer has terminated due to a numerical problem, then basis identification is performed if this parameter has the value *MSK_ON*.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Interior-point method, Basis identification*

MSK_IPAR_BI_MAX_ITERATIONS

Controls the maximum number of simplex iterations allowed to optimize a basis after the basis identification.

Accepted Values: `[0 ;+inf]`

Default Value: `1000000`

Groups: *Basis identification, Termination criterion*

MSK_IPAR_CACHE_LICENSE

Specifies if the license is kept checked out for the lifetime of the mosek environment (*MSK_ON*) or returned to the server immediately after the optimization (*MSK_OFF*).

By default the license is checked out for the lifetime of the **MOSEK** environment by the first call to the optimizer.

Check-in and check-out of licenses have an overhead. Frequent communication with the license server should be avoided.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *License manager*

MSK_IPAR_CHECK_CONVEXITY

Specify the level of convexity check on quadratic problems

Accepted Values: *MSKcheckconvexitytypee*

Default Value: *MSK_CHECK_CONVEXITY_FULL*

Groups: *Data check, Nonlinear convex method*

MSK_IPAR_COMPRESS_STATFILE

Control compression of stat files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

MSK_IPAR_INFEAS_GENERIC_NAMES

Controls whether generic names are used when an infeasible subproblem is created.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Infeasibility report*

MSK_IPAR_INFEAS_PREFER_PRIMAL

If both certificates of primal and dual infeasibility are supplied then only the primal is used when this option is turned on.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Overall solver*

MSK_IPAR_INFEAS_REPORT_AUTO

Controls whether an infeasibility report is automatically produced after the optimization if the problem is primal or dual infeasible.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_INFEAS_REPORT_LEVEL

Controls the amount of information presented in an infeasibility report. Higher values imply more information.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Infeasibility report, Output information*

MSK_IPAR_INTPNT_BASIS

Controls whether the interior-point optimizer also computes an optimal basis.

Accepted Values: *MSKbasindtypee*

Default Value: *MSK_BI_ALWAYS*

Groups: *Interior-point method, Basis identification*

MSK_IPAR_INTPNT_DIFF_STEP

Controls whether different step sizes are allowed in the primal and dual space.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_HOTSTART

Currently not in use.

Accepted Values: *MSKintpnthotstarte*

Default Value: *MSK_INTPNT_HOTSTART_NONE*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_MAX_ITERATIONS

Controls the maximum number of iterations allowed in the interior-point optimizer.

Accepted Values: [0 ;+inf]

Default Value: 400

Groups: *Interior-point method, Termination criterion*

MSK_IPAR_INTPNT_MAX_NUM_COR

Controls the maximum number of correctors allowed by the multiple corrector procedure. A negative value means that **MOSEK** is making the choice.

Accepted Values: [-1 ;+inf]

Default Value: -1

Groups: *Interior-point method*

MSK_IPAR_INTPNT_MAX_NUM_REFINEMENT_STEPS

Maximum number of steps to be used by the iterative refinement of the search direction. A negative value implies that the optimizer chooses the maximum number of iterative refinement steps.

Accepted Values: [-inf ;+inf]

Default Value: -1

Groups: *Interior-point method*

MSK_IPAR_INTPNT_MULTI_THREAD

Controls whether the interior-point optimizers are allowed to employ multiple threads if more threads is available.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Optimization system*

MSK_IPAR_INTPNT_OFF_COL_TRH

Controls how many offending columns are detected in the Jacobian of the constraint matrix.

0	no detection
1	aggressive detection
> 1	higher values mean less aggressive detection

Accepted Values: `[0 ;+inf]`

Default Value: `40`

Groups: *Interior-point method*

MSK_IPAR_INTPNT_ORDER_METHOD

Controls the ordering strategy used by the interior-point optimizer when factorizing the Newton equation system.

Accepted Values: *MSKorderingtypee*

Default Value: *MSK_ORDER_METHOD_FREE*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_REGULARIZATION_USE

Controls whether regularization is allowed.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_SCALING

Controls how the problem is scaled before the interior-point optimizer is used.

Accepted Values: *MSKscalingtypee*

Default Value: *MSK_SCALING_FREE*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_SOLVE_FORM

Controls whether the primal or the dual problem is solved.

Accepted Values: *MSKsolveforme*

Default Value: *MSK_SOLVE_FREE*

Groups: *Interior-point method*

MSK_IPAR_INTPNT_STARTING_POINT

Starting point used by the interior-point optimizer.

Accepted Values: *MSKstartpointtypee*

Default Value: *MSK_STARTING_POINT_FREE*

Groups: *Interior-point method*

MSK_IPAR_LICENSE_DEBUG

This option is used to turn on debugging of the license manager.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *License manager*

MSK_IPAR_LICENSE_PAUSE_TIME

If *MSK_IPAR_LICENSE_WAIT* = *MSK_ON* and no license is available, then **MOSEK** sleeps a number of milliseconds between each check of whether a license has become free.

Accepted Values: [0 ;1000000]

Default Value: 100

Groups: *License manager*

MSK_IPAR_LICENSE_SUPPRESS_EXPIRE_WRNS

Controls whether license features expire warnings are suppressed.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *License manager, Output information*

MSK_IPAR_LICENSE_TRH_EXPIRY_WRN

If a license feature expires in a numbers days less than the value of this parameter then a warning will be issued.

Accepted Values: [0 ;+inf]

Default Value: 7

MSK_IPAR_LICENSE_WAIT

If all licenses are in use **MOSEK** returns with an error code. However, by turning on this parameter **MOSEK** will wait for an available license.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Overall solver, Optimization system, License manager*

MSK_IPAR_LOG

Controls the amount of log information. The value 0 implies that all log information is suppressed. A higher level implies that more information is logged.

Please note that if a task is employed to solve a sequence of optimization problems the value of this parameter is reduced by the value of *MSK_IPAR_LOG_CUT_SECOND_OPT* for the second and any subsequent optimizations.

Accepted Values: [0 ;+inf]

Default Value: 10

Groups: *Output information, Logging*

MSK_IPAR_LOG_ANA_PRO

Controls amount of output from the problem analyzer.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Analysis, Logging*

MSK_IPAR_LOG_BI

Controls the amount of output printed by the basis identification procedure. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 4

Groups: *Basis identification, Output information, Logging*

MSK_IPAR_LOG_BI_FREQ

Controls how frequent the optimizer outputs information about the basis identification and how frequent the user-defined call-back function is called.

Accepted Values: [0 ;+inf]

Default Value: 2500

Groups: *Basis identification, Output information, Logging*

MSK_IPAR_LOG_CHECK_CONVEXITY

Controls logging in convexity check on quadratic problems. Set to a positive value to turn logging on. If a quadratic coefficient matrix is found to violate the requirement of PSD (NSD) then a list of negative (positive) pivot elements is printed. The absolute value of the pivot elements is also shown.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Data check, Nonlinear convex method*

MSK_IPAR_LOG_CUT_SECOND_OPT

If a task is employed to solve a sequence of optimization problems, then the value of the log levels is reduced by the value of this parameter. E.g *MSK_IPAR_LOG* and *MSK_IPAR_LOG_SIM* are reduced by the value of this parameter for the second and any subsequent optimizations.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_EXPAND

Controls the amount of logging when a data item such as the maximum number constraints is expanded.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Output information, Logging*

MSK_IPAR_LOG_FACTOR

If turned on, then the factor log lines are added to the log.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_FEAS_REPAIR

Controls the amount of output printed when performing feasibility repair. A value higher than one means extensive logging.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_FILE

If turned on, then some log info is printed when a file is written or read.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Data input/output, Output information, Logging*

MSK_IPAR_LOG_HEAD

If turned on, then a header line is added to the log.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_INFEAS_ANA

Controls amount of output printed by the infeasibility analyzer procedures. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Infeasibility report, Output information, Logging*

MSK_IPAR_LOG_INTPNT

Controls amount of output printed by the interior-point optimizer. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 4

Groups: *Interior-point method, Output information, Logging*

MSK_IPAR_LOG_MIO

Controls the log level for the mixed-integer optimizer. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 4

Groups: *Mixed-integer optimization, Output information, Logging*

MSK_IPAR_LOG_MIO_FREQ

Controls how frequent the mixed-integer optimizer prints the log line. It will print line every time *MSK_IPAR_LOG_MIO_FREQ* relaxations have been solved.

Accepted Values: [-inf ;+inf]

Default Value: 10

Groups: *Mixed-integer optimization, Output information, Logging*

MSK_IPAR_LOG_OPTIMIZER

Controls the amount of general optimizer information that is logged.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_ORDER

If turned on, then factor lines are added to the log.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_PRESOLVE

Controls amount of output printed by the presolve procedure. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Interior-point method, Logging*

MSK_IPAR_LOG_RESPONSE

Controls amount of output printed when response codes are reported. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Output information, Logging*

MSK_IPAR_LOG_SENSITIVITY

Controls the amount of logging during the sensitivity analysis.

0.Means no logging information is produced.

1.Timing information is printed.

2.Sensitivity results are printed.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Output information, Logging*

MSK_IPAR_LOG_SENSITIVITY_OPT

Controls the amount of logging from the optimizers employed during the sensitivity analysis. 0 means no logging information is produced.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Output information, Logging*

MSK_IPAR_LOG_SIM

Controls amount of output printed by the simplex optimizer. A higher level implies that more information is logged.

Accepted Values: [0 ;+inf]

Default Value: 4

Groups: *Simplex optimizer, Output information, Logging*

MSK_IPAR_LOG_SIM_FREQ

Controls how frequent the simplex optimizer outputs information about the optimization and how frequent the user-defined call-back function is called.

Accepted Values: [0 ;+inf]

Default Value: 1000

Groups: *Simplex optimizer, Output information, Logging*

MSK_IPAR_LOG_SIM_MINOR

Currently not in use.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Simplex optimizer, Output information*

MSK_IPAR_LOG_STORAGE

When turned on, **MOSEK** prints messages regarding the storage usage and allocation.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Output information, Optimization system, Logging*

MSK_IPAR_MAX_NUM_WARNINGS

Each warning is shown a limit number times controlled by this parameter. A negative value is identical to infinite number of times.

Accepted Values: `[-inf ;+inf]`

Default Value: `10`

Groups: *Output information*

MSK_IPAR_MIO_BRANCH_DIR

Controls whether the mixed-integer optimizer is branching up or down by default.

Accepted Values: *MSKbranchdire*

Default Value: *MSK_BRANCH_DIR_FREE*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CONSTRUCT_SOL

If set to *MSK_ON* and all integer variables have been given a value for which a feasible mixed integer solution exists, then **MOSEK** generates an initial solution to the mixed integer problem by fixing all integer values and solving the remaining problem.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_CLIQUE

Controls whether clique cuts should be generated.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_CMIR

Controls whether mixed integer rounding cuts should be generated.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_GMI

Controls whether GMI cuts should be generated.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_IMPLIED_BOUND

Controls whether implied bound cuts should be generated.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_KNAPSACK_COVER

Controls whether knapsack cover cuts should be generated.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_CUT_SELECTION_LEVEL

Controls how aggressively generated cuts are selected to be included in the relaxation.

-1. The optimizer chooses the level of cut selection

0. Generated cuts less likely to be added to the relaxation

1. Cuts are more aggressively selected to be included in the relaxation

Accepted Values: `[-1 ; +1]`

Default Value: `-1`

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_HEURISTIC_LEVEL

Controls the heuristic employed by the mixed-integer optimizer to locate an initial good integer feasible solution. A value of zero means the heuristic is not used at all. A larger value than 0 means that a gradually more sophisticated heuristic is used which is computationally more expensive. A negative value implies that the optimizer chooses the heuristic. Normally a value around 3 to 5 should be optimal.

Accepted Values: `[-inf ; +inf]`

Default Value: `-1`

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_MAX_NUM_BRANCHES

Maximum number of branches allowed during the branch and bound search. A negative value means infinite.

Accepted Values: `[-inf ; +inf]`

Default Value: `-1`

Groups: *Mixed-integer optimization, Termination criterion*

MSK_IPAR_MIO_MAX_NUM_RELAXS

Maximum number of relaxations allowed during the branch and bound search. A negative value means infinite.

Accepted Values: `[-inf ; +inf]`

Default Value: `-1`

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_MAX_NUM_SOLUTIONS

The mixed-integer optimizer can be terminated after a certain number of different feasible solutions has been located. If this parameter has the value $n > 0$, then the mixed-integer optimizer will be terminated when n feasible solutions have been located.

Accepted Values: `[-inf ; +inf]`

Default Value: `-1`

Groups: *Mixed-integer optimization, Termination criterion*

MSK_IPAR_MIO_MODE

Controls whether the optimizer includes the integer restrictions when solving a (mixed) integer optimization problem.

Accepted Values: *MSKmiomodee*

Default Value: *MSK_MIO_MODE_SATISFIED*

Groups: *Overall solver*

MSK_IPAR_MIO_MT_USER_CB

It true user callbacks are called from each thread used by this optimizer. If false the user callback is only called from a single thread.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Optimization system*

MSK_IPAR_MIO_NODE_OPTIMIZER

Controls which optimizer is employed at the non-root nodes in the mixed-integer optimizer.

Accepted Values: *MSKoptimizertypee*

Default Value: *MSK_OPTIMIZER_FREE*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_NODE_SELECTION

Controls the node selection strategy employed by the mixed-integer optimizer.

Accepted Values: *MSKmionodeseltypee*

Default Value: *MSK_MIO_NODE_SELECTION_FREE*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_PERSPECTIVE_REFORMULATE

Enables or disables perspective reformulation in presolve.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_PROBING_LEVEL

Controls the amount of probing employed by the mixed-integer optimizer in presolve.

-1. The optimizer chooses the level of probing employed

0. Probing is disabled

1. A low amount of probing is employed

2. A medium amount of probing is employed

3. A high amount of probing is employed

Accepted Values: *[-inf ;+inf]*

Default Value: *-1*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_RINS_MAX_NODES

Controls the maximum number of nodes allowed in each call to the RINS heuristic. The default value of -1 means that the value is determined automatically. A value of zero turns off the heuristic.

Accepted Values: *[-1 ;+inf]*

Default Value: *-1*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_ROOT_OPTIMIZER

Controls which optimizer is employed at the root node in the mixed-integer optimizer.

Accepted Values: *MSKoptimizertypee*

Default Value: *MSK_OPTIMIZER_FREE*

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_ROOT_REPEAT_PRESOLVE_LEVEL

Controls whether presolve can be repeated at root node.

- 1 The optimizer chooses whether presolve is repeated
- 0 Never repeat presolve
- 1 Always repeat presolve

Accepted Values: [-1 ;1]

Default Value: -1

Groups: *Mixed-integer optimization*

MSK_IPAR_MIO_VB_DETECTION_LEVEL

Controls how much effort is put into detecting variable bounds.

- 1. The optimizer chooses
 - 0.No variable bounds are detected
 - 1.Only detect variable bounds that are directly represented in the problem
 - 2.Detect variable bounds in probing

Accepted Values: [-1 ;+2]

Default Value: -1

Groups: *Mixed-integer optimization*

MSK_IPAR_MT_SPINCOUNT

Set the number of iterations to spin before sleeping.

Accepted Values: [0 ;1000000000]

Default Value: 0

Groups: *Optimization system*

MSK_IPAR_NUM_THREADS

Controls the number of threads employed by the optimizer. If set to 0 the number of threads used will be equal to the number of cores detected on the machine.

Accepted Values: [0 ;+inf]

Default Value: 0

Groups: *Optimization system*

MSK_IPAR_OPF_MAX_TERMS_PER_LINE

The maximum number of terms (linear and quadratic) per line when an OPF file is written.

Accepted Values: [0 ;+inf]

Default Value: 5

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_HEADER

Write a text header with date and **MOSEK** version in an OPF file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_HINTS

Write a hint section with problem dimensions in the beginning of an OPF file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_PARAMETERS

Write a parameter section in an OPF file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_PROBLEM

Write objective, constraints, bounds etc. to an OPF file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_SOLUTIONS

Enable inclusion of solutions in the OPF files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_SOL_BAS

If *MSK_IPAR_OPF_WRITE_SOLUTIONS* is *MSK_ON* and a basic solution is defined, include the basic solution in OPF files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_SOL_ITG

If *MSK_IPAR_OPF_WRITE_SOLUTIONS* is *MSK_ON* and an integer solution is defined, write the integer solution in OPF files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPF_WRITE_SOL_ITR

If *MSK_IPAR_OPF_WRITE_SOLUTIONS* is *MSK_ON* and an interior solution is defined, write the interior solution in OPF files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_OPTIMIZER

The parameter controls which optimizer is used to optimize the task.

Accepted Values: *MSKoptimizertypee*

Default Value: *MSK_OPTIMIZER_FREE*

Groups: *Overall solver*

MSK_IPAR_PARAM_READ_CASE_NAME

If turned on, then names in the parameter file are case sensitive.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_PARAM_READ_IGN_ERROR

If turned on, then errors in parameter settings is ignored.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_PREOLVE_ELIMINATOR_MAX_FILL

Controls the maximum amount of fill-in that can be created by one pivot in the elimination phase of the presolve. A negative value means the parameter value is selected automatically.

Accepted Values: $[-inf ; +inf]$

Default Value: -1

Groups: *Presolve*

MSK_IPAR_PREOLVE_ELIMINATOR_MAX_NUM_TRIES

Control the maximum number of times the eliminator is tried.

Accepted Values: $[-inf ; +inf]$

Default Value: -1

Groups: *Presolve*

MSK_IPAR_PREOLVE_LEVEL

Currently not used.

Accepted Values: $[-inf ; +inf]$

Default Value: -1

Groups: *Overall solver, Presolve*

MSK_IPAR_PREOLVE_LINDEP_ABS_WORK_TRH

The linear dependency check is potentially computationally expensive.

Accepted Values: $[-inf ; +inf]$

Default Value: 100

Groups: *Presolve*

MSK_IPAR_PREOLVE_LINDEP_REL_WORK_TRH

The linear dependency check is potentially computationally expensive.

Accepted Values: $[-inf ; +inf]$

Default Value: 100

Groups: *Presolve*

MSK_IPAR_PREOLVE_LINDEP_USE

Controls whether the linear constraints are checked for linear dependencies.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_ON*

Groups: *Presolve*

MSK_IPAR_PREOLVE_MAX_NUM_REDUCTIONS

Controls the maximum number of reductions performed by the presolve. The value of the parameter is normally only changed in connection with debugging. A negative value implies that an infinite number of reductions are allowed.

Accepted Values: $[-inf ; +inf]$

Default Value: -1

MSK_IPAR_PRESOLVE_USE

Controls whether the presolve is applied to a problem before it is optimized.

Accepted Values: *MSKpresolvemodee*

Default Value: *MSK_PRESOLVE_MODE_FREE*

Groups: *Overall solver, Presolve*

MSK_IPAR_PRIMAL_REPAIR_OPTIMIZER

Controls which optimizer that is used to find the optimal repair.

Accepted Values: *MSKoptimizertypee*

Default Value: *MSK_OPTIMIZER_FREE*

Groups: *Overall solver*

MSK_IPAR_READ_DATA_COMPRESSED

If this option is turned on, it is assumed that the data file is compressed.

Accepted Values: *MSKcompresstypee*

Default Value: *MSK_COMPRESS_FREE*

Groups: *Data input/output*

MSK_IPAR_READ_DATA_FORMAT

Format of the data file to be read.

Accepted Values: *MSKdataformate*

Default Value: *MSK_DATA_FORMAT_EXTENSION*

Groups: *Data input/output*

MSK_IPAR_READ_DEBUG

Turns on additional debugging information when reading files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_READ_KEEP_FREE_CON

Controls whether the free constraints are included in the problem.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_READ_LP_DROP_NEW_VARS_IN_BOU

If this option is turned on, **MOSEK** will drop variables that are defined for the first time in the bounds section.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_READ_LP_QUOTED_NAMES

If a name is in quotes when reading an LP file, the quotes will be removed.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_READ_MPS_FORMAT

Controls how strictly the MPS file reader interprets the MPS format.

Accepted Values: *MSKmpsformat*

Default Value: *MSK_MPS_FORMAT_FREE*

Groups: *Data input/output*

MSK_IPAR_READ_MPS_WIDTH

Controls the maximal number of characters allowed in one line of the MPS file.

Accepted Values: *[80 ;+inf]*

Default Value: *1024*

Groups: *Data input/output*

MSK_IPAR_READ_TASK_IGNORE_PARAM

Controls whether **MOSEK** should ignore the parameter setting defined in the task file and use the default parameter setting instead.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_SENSITIVITY_ALL

Not applicable.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Overall solver*

MSK_IPAR_SENSITIVITY_OPTIMIZER

Controls which optimizer is used for optimal partition sensitivity analysis.

Accepted Values: *MSKoptimizertypee*

Default Value: *MSK_OPTIMIZER_FREE_SIMPLEX*

Groups: *Overall solver, Simplex optimizer*

MSK_IPAR_SENSITIVITY_TYPE

Controls which type of sensitivity analysis is to be performed.

Accepted Values: *MSKsensitivitytypee*

Default Value: *MSK_SENSITIVITY_TYPE_BASIS*

Groups: *Overall solver*

MSK_IPAR_SIM_BASIS_FACTOR_USE

Controls whether a (LU) factorization of the basis is used in a hot-start. Forcing a refactorization sometimes improves the stability of the simplex optimizers, but in most cases there is a performance penalty.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_DEGEN

Controls how aggressively degeneration is handled.

Accepted Values: *MSKsimdegene*

Default Value: *MSK_SIM_DEGEN_FREE*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_DUAL_CRASH

Controls whether crashing is performed in the dual simplex optimizer.

If this parameter is set to x , then a crash will be performed if a basis consists of more than $(100 - x) \bmod f_v$ entries, where f_v is the number of fixed variables.

Accepted Values: `[0 ; +inf]`

Default Value: `90`

Groups: *Dual simplex optimizer*

MSK_IPAR_SIM_DUAL_PHASEONE_METHOD

An experimental feature.

Accepted Values: `[0 ; 10]`

Default Value: `0`

Groups: *Simplex optimizer*

MSK_IPAR_SIM_DUAL_RESTRICT_SELECTION

The dual simplex optimizer can use a so-called restricted selection/pricing strategy to choose the outgoing variable. Hence, if restricted selection is applied, then the dual simplex optimizer first choose a subset of all the potential outgoing variables. Next, for some time it will choose the outgoing variable only among the subset. From time to time the subset is redefined.

A larger value of this parameter implies that the optimizer will be more aggressive in its restriction strategy, i.e. a value of 0 implies that the restriction strategy is not applied at all.

Accepted Values: `[0 ; 100]`

Default Value: `50`

Groups: *Dual simplex optimizer*

MSK_IPAR_SIM_DUAL_SELECTION

Controls the choice of the incoming variable, known as the selection strategy, in the dual simplex optimizer.

Accepted Values: *MSKsimseltypee*

Default Value: *MSK_SIM_SELECTION_FREE*

Groups: *Dual simplex optimizer*

MSK_IPAR_SIM_EXPLOIT_DUPVEC

Controls if the simplex optimizers are allowed to exploit duplicated columns.

Accepted Values: *MSKsimdupvece*

Default Value: *MSK_SIM_EXPLOIT_DUPVEC_OFF*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_HOTSTART

Controls the type of hot-start that the simplex optimizer perform.

Accepted Values: *MSKsimhotstarte*

Default Value: *MSK_SIM_HOTSTART_FREE*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_HOTSTART_LU

Determines if the simplex optimizer should exploit the initial factorization.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

MSK_IPAR_SIM_INTEGER

An experimental feature.

Accepted Values: [0 ;10]

Default Value: 0

Groups: *Simplex optimizer*

MSK_IPAR_SIM_MAX_ITERATIONS

Maximum number of iterations that can be used by a simplex optimizer.

Accepted Values: [0 ;+inf]

Default Value: 10000000

Groups: *Simplex optimizer, Termination criterion*

MSK_IPAR_SIM_MAX_NUM_SETBACKS

Controls how many set-backs are allowed within a simplex optimizer. A set-back is an event where the optimizer moves in the wrong direction. This is impossible in theory but may happen due to numerical problems.

Accepted Values: [0 ;+inf]

Default Value: 250

Groups: *Simplex optimizer*

MSK_IPAR_SIM_NON_SINGULAR

Controls if the simplex optimizer ensures a non-singular basis, if possible.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_PRIMAL_CRASH

Controls whether crashing is performed in the primal simplex optimizer.

In general, if a basis consists of more than (100-this parameter value)% fixed variables, then a crash will be performed.

Accepted Values: [0 ;+inf]

Default Value: 90

Groups: *Primal simplex optimizer*

MSK_IPAR_SIM_PRIMAL_PHASEONE_METHOD

An experimental feature.

Accepted Values: [0 ;10]

Default Value: 0

Groups: *Simplex optimizer*

MSK_IPAR_SIM_PRIMAL_RESTRICT_SELECTION

The primal simplex optimizer can use a so-called restricted selection/pricing strategy to choose the outgoing variable. Hence, if restricted selection is applied, then the primal simplex optimizer first choose a subset of all the potential incoming variables. Next, for some time it will choose the incoming variable only among the subset. From time to time the subset is redefined.

A larger value of this parameter implies that the optimizer will be more aggressive in its restriction strategy, i.e. a value of 0 implies that the restriction strategy is not applied at all.

Accepted Values: [0 ;100]

Default Value: 50

Groups: *Primal simplex optimizer*

MSK_IPAR_SIM_PRIMAL_SELECTION

Controls the choice of the incoming variable, known as the selection strategy, in the primal simplex optimizer.

Accepted Values: *MSKsimseltypee*

Default Value: *MSK_SIM_SELECTION_FREE*

Groups: *Primal simplex optimizer*

MSK_IPAR_SIM_REFACTOR_FREQ

Controls how frequent the basis is refactorized. The value 0 means that the optimizer determines the best point of refactorization.

It is strongly recommended NOT to change this parameter.

Accepted Values: *[0 ;+inf]*

Default Value: *0*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_REFORMULATION

Controls if the simplex optimizers are allowed to reformulate the problem.

Accepted Values: *MSKsimreforme*

Default Value: *MSK_SIM_REFORMULATION_OFF*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_SAVE_LU

Controls if the LU factorization stored should be replaced with the LU factorization corresponding to the initial basis.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_SCALING

Controls how much effort is used in scaling the problem before a simplex optimizer is used.

Accepted Values: *MSKscalingtypee*

Default Value: *MSK_SCALING_FREE*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_SCALING_METHOD

Controls how the problem is scaled before a simplex optimizer is used.

Accepted Values: *MSKscalingmethode*

Default Value: *MSK_SCALING_METHOD_POW2*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_SOLVE_FORM

Controls whether the primal or the dual problem is solved by the primal-/dual-simplex optimizer.

Accepted Values: *MSKsolveforme*

Default Value: *MSK_SOLVE_FREE*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_STABILITY_PRIORITY

Controls how high priority the numerical stability should be given.

Accepted Values: *[0 ;100]*

Default Value: *50*

Groups: *Simplex optimizer*

MSK_IPAR_SIM_SWITCH_OPTIMIZER

The simplex optimizer sometimes chooses to solve the dual problem instead of the primal problem. This implies that if you have chosen to use the dual simplex optimizer and the problem is dualized, then it actually makes sense to use the primal simplex optimizer instead. If this parameter is on and the problem is dualized and furthermore the simplex optimizer is chosen to be the primal (dual) one, then it is switched to the dual (primal).

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Simplex optimizer*

MSK_IPAR_SOLUTION_CALLBACK

Indicates whether solution call-backs will be performed during the optimization.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Progress call-back, Overall solver*

MSK_IPAR_SOL_FILTER_KEEP_BASIC

If turned on, then basic and super basic constraints and variables are written to the solution file independent of the filter setting.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Solution input/output*

MSK_IPAR_SOL_FILTER_KEEP_RANGED

If turned on, then ranged constraints and variables are written to the solution file independent of the filter setting.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Solution input/output*

MSK_IPAR_SOL_READ_NAME_WIDTH

When a solution is read by **MOSEK** and some constraint, variable or cone names contain blanks, then a maximum name width must be specified. A negative value implies that no name contain blanks.

Accepted Values: *[-inf ;+inf]*

Default Value: *-1*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_SOL_READ_WIDTH

Controls the maximal acceptable width of line in the solutions when read by **MOSEK**.

Accepted Values: *[0 ;+inf]*

Default Value: *1024*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_TIMING_LEVEL

Controls the amount of timing performed inside **MOSEK**.

Accepted Values: *[0 ;+inf]*

Default Value: *1*

Groups: *Optimization system*

MSK_IPAR_WRITE_BAS_CONSTRAINTS

Controls whether the constraint section is written to the basic solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_BAS_HEAD

Controls whether the header section is written to the basic solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_BAS_VARIABLES

Controls whether the variables section is written to the basic solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_DATA_COMPRESSED

Controls whether the data file is compressed while it is written. 0 means no compression while higher values mean more compression.

Accepted Values: *[0 ;+inf]*

Default Value: *0*

Groups: *Data input/output*

MSK_IPAR_WRITE_DATA_FORMAT

Controls the file format when writing task data to a file.

Accepted Values: *MSKdataformate*

Default Value: *MSK_DATA_FORMAT_EXTENSION*

Groups: *Data input/output*

MSK_IPAR_WRITE_DATA_PARAM

If this option is turned on the parameter settings are written to the data file as parameters.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_WRITE_FREE_CON

Controls whether the free constraints are written to the data file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_WRITE_GENERIC_NAMES

Controls whether the generic names or user-defined names are used in the data file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_WRITE_GENERIC_NAMES_IO

Index origin used in generic names.

Accepted Values: [0 ;+inf]

Default Value: 1

Groups: *Data input/output*

MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_ITEMS

Controls if the writer ignores incompatible problem items when writing files.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_WRITE_INT_CONSTRAINTS

Controls whether the constraint section is written to the integer solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_INT_HEAD

Controls whether the header section is written to the integer solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_INT_VARIABLES

Controls whether the variables section is written to the integer solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_LP_FULL_OBJ

Write all variables, including the ones with 0-coefficients, in the objective.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_WRITE_LP_LINE_WIDTH

Maximum width of line in an LP file written by **MOSEK**.

Accepted Values: [40 ;+inf]

Default Value: 80

Groups: *Data input/output*

MSK_IPAR_WRITE_LP_QUOTED_NAMES

If this option is turned on, then **MOSEK** will quote invalid LP names when writing an LP file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_WRITE_LP_STRICT_FORMAT

Controls whether LP output files satisfy the LP format strictly.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output*

MSK_IPAR_WRITE_LP_TERMS_PER_LINE

Maximum number of terms on a single line in an LP file written by **MOSEK**. 0 means unlimited.

Accepted Values: *[0 ;+inf]*

Default Value: *10*

Groups: *Data input/output*

MSK_IPAR_WRITE_MPS_FORMAT

Controls in which format the MPS is written.

Accepted Values: *MSKmpsformate*

Default Value: *MSK_MPS_FORMAT_FREE*

Groups: *Data input/output*

MSK_IPAR_WRITE_MPS_INT

Controls if marker records are written to the MPS file to indicate whether variables are integer restricted.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_WRITE_PRECISION

Controls the precision with which **double** numbers are printed in the MPS data file. In general it is not worthwhile to use a value higher than 15.

Accepted Values: *[0 ;+inf]*

Default Value: *15*

Groups: *Data input/output*

MSK_IPAR_WRITE_SOL_BARVARIABLES

Controls whether the symmetric matrix variables section is written to the solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_SOL_CONSTRAINTS

Controls whether the constraint section is written to the solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_SOL_HEAD

Controls whether the header section is written to the solution file.

Accepted Values: *MSKonoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_SOL_IGNORE_INVALID_NAMES

Even if the names are invalid MPS names, then they are employed when writing the solution file.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_OFF*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_SOL_VARIABLES

Controls whether the variables section is written to the solution file.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output, Solution input/output*

MSK_IPAR_WRITE_TASK_INC_SOL

Controls whether the solutions are stored in the task file too.

Accepted Values: *MSK_onoffkeye*

Default Value: *MSK_ON*

Groups: *Data input/output*

MSK_IPAR_WRITE_XML_MODE

Controls if linear coefficients should be written by row or column when writing in the XML file format.

Accepted Values: *MSK_xmlwriteroutputtypee*

Default Value: *MSK_WRITE_XML_MODE_ROW*

Groups: *Data input/output*

String Parameters

MSK_SPAR_BAS_SOL_FILE_NAME

Name of the bas solution file.

Accepted Values: Any valid file name.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_DATA_FILE_NAME

Data are read and written to this file.

Accepted Values: Any valid file name.

Groups: *Data input/output*

MSK_SPAR_DEBUG_FILE_NAME

MOSEK debug file.

Accepted Values: Any valid file name.

Groups: *Data input/output*

MSK_SPAR_INT_SOL_FILE_NAME

Name of the int solution file.

Accepted Values: Any valid file name.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_ITR_SOL_FILE_NAME

Name of the itr solution file.

Accepted Values: Any valid file name.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_MIO_DEBUG_STRING

For internal use only.

Accepted Values: Any valid string.

Groups: *Data input/output*

MSK_SPAR_PARAM_COMMENT_SIGN

Only the first character in this string is used. It is considered as a start of comment sign in the **MOSEK** parameter file. Spaces are ignored in the string.

Accepted Values: Any valid string.

Default Value: %%

Groups: *Data input/output*

MSK_SPAR_PARAM_READ_FILE_NAME

Modifications to the parameter database is read from this file.

Accepted Values: Any valid file name.

Groups: *Data input/output*

MSK_SPAR_PARAM_WRITE_FILE_NAME

The parameter database is written to this file.

Accepted Values: Any valid file name.

Groups: *Data input/output*

MSK_SPAR_READ_MPS_BOU_NAME

Name of the BOUNDS vector used. An empty name means that the first BOUNDS vector is used.

Accepted Values: Any valid MPS name.

Groups: *Data input/output*

MSK_SPAR_READ_MPS_OBJ_NAME

Name of the free constraint used as objective function. An empty name means that the first constraint is used as objective function.

Accepted Values: Any valid MPS name.

Groups: *Data input/output*

MSK_SPAR_READ_MPS_RAN_NAME

Name of the RANGE vector used. An empty name means that the first RANGE vector is used.

Accepted Values: Any valid MPS name.

Groups: *Data input/output*

MSK_SPAR_READ_MPS_RHS_NAME

Name of the RHS used. An empty name means that the first RHS vector is used.

Accepted Values: Any valid MPS name.

Groups: *Data input/output*

MSK_SPAR_REMOTE_ACCESS_TOKEN

An access token used to submit tasks to a remote **MOSEK** server. An access token is a random 32-byte string encoded in base64, i.e. it is a 44 character ASCII string.

Accepted Values: Any valid string.

MSK_SPAR_SENSITIVITY_FILE_NAME

Not applicable.

Accepted Values: Any valid string.

Groups: *Data input/output*

MSK_SPAR_SENSITIVITY_RES_FILE_NAME

Not applicable.

Accepted Values: Any valid string.

Groups: *Data input/output*

MSK_SPAR_SOL_FILTER_XC_LOW

A filter used to determine which constraints should be listed in the solution file. A value of 0.5 means that all constraints having $xc[i] > 0.5$ should be listed, whereas +0.5 means that all constraints having $xc[i] \geq blc[i] + 0.5$ should be listed. An empty filter means that no filter is applied.

Accepted Values: Any valid filter.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_SOL_FILTER_XC_UPR

A filter used to determine which constraints should be listed in the solution file. A value of 0.5 means that all constraints having $xc[i] < 0.5$ should be listed, whereas -0.5 means all constraints having $xc[i] \leq buc[i] - 0.5$ should be listed. An empty filter means that no filter is applied.

Accepted Values: Any valid filter.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_SOL_FILTER_XX_LOW

A filter used to determine which variables should be listed in the solution file. A value of "0.5" means that all constraints having $xx[j] \geq 0.5$ should be listed, whereas "+0.5" means that all constraints having $xx[j] \geq blx[j] + 0.5$ should be listed. An empty filter means no filter is applied.

Accepted Values: Any valid filter.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_SOL_FILTER_XX_UPR

A filter used to determine which variables should be listed in the solution file. A value of "0.5" means that all constraints having $xx[j] < 0.5$ should be printed, whereas "-0.5" means all constraints having $xx[j] \leq bux[j] - 0.5$ should be listed. An empty filter means no filter is applied.

Accepted Values: Any valid file name.

Groups: *Data input/output, Solution input/output*

MSK_SPAR_STAT_FILE_NAME

Statistics file name.

Accepted Values: Any valid file name.

Groups: *Data input/output*

MSK_SPAR_STAT_KEY

Key used when writing the summary file.

Accepted Values: Any valid XML string.

Groups: *Data input/output*

MSK_SPAR_STAT_NAME

Name used when writing the statistics file.

Accepted Values: Any valid XML string.

Groups: *Data input/output*

MSK_SPAR_WRITE_LP_GEN_VAR_NAME

Sometimes when an LP file is written additional variables must be inserted. They will have the prefix denoted by this parameter.

Accepted Values: Any valid string.

Default Value: `xmskgen`

Groups: `Data input/output`

11.1.2 Conic interior-point method parameters.

- `MSK_DPAR_INTPNT_CO_TOL_DFEAS`
- `MSK_DPAR_INTPNT_CO_TOL_INFEAS`
- `MSK_DPAR_INTPNT_CO_TOL_MU_RED`
- `MSK_DPAR_INTPNT_CO_TOL_NEAR_REL`
- `MSK_DPAR_INTPNT_CO_TOL_PFEAS`
- `MSK_DPAR_INTPNT_CO_TOL_REL_GAP`

11.1.3 License manager parameters.

- `MSK_IPAR_CACHE_LICENSE`
- `MSK_IPAR_LICENSE_DEBUG`
- `MSK_IPAR_LICENSE_PAUSE_TIME`
- `MSK_IPAR_LICENSE_SUPPRESS_EXPIRE_WRNS`
- `MSK_IPAR_LICENSE_WAIT`

11.1.4 Logging parameters.

- `MSK_IPAR_LOG`
- `MSK_IPAR_LOG_ANA_PRO`
- `MSK_IPAR_LOG_BI`
- `MSK_IPAR_LOG_BI_FREQ`
- `MSK_IPAR_LOG_CUT_SECOND_OPT`
- `MSK_IPAR_LOG_EXPAND`
- `MSK_IPAR_LOG_FACTOR`
- `MSK_IPAR_LOG_FEAS_REPAIR`
- `MSK_IPAR_LOG_FILE`
- `MSK_IPAR_LOG_HEAD`
- `MSK_IPAR_LOG_INFEAS_ANA`
- `MSK_IPAR_LOG_INTPNT`
- `MSK_IPAR_LOG_MIO`
- `MSK_IPAR_LOG_MIO_FREQ`
- `MSK_IPAR_LOG_OPTIMIZER`
- `MSK_IPAR_LOG_ORDER`
- `MSK_IPAR_LOG_PRESOLVE`
- `MSK_IPAR_LOG_RESPONSE`
- `MSK_IPAR_LOG_SENSITIVITY`

- *MSK_IPAR_LOG_SENSITIVITY_OPT*
- *MSK_IPAR_LOG_SIM*
- *MSK_IPAR_LOG_SIM_FREQ*
- *MSK_IPAR_LOG_STORAGE*

11.1.5 Presolve parameters.

- *MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_FILL*
- *MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_NUM_TRIES*
- *MSK_IPAR_PRESOLVE_LEVEL*
- *MSK_IPAR_PRESOLVE_LINDEP_ABS_WORK_TRH*
- *MSK_IPAR_PRESOLVE_LINDEP_REL_WORK_TRH*
- *MSK_IPAR_PRESOLVE_LINDEP_USE*
- *MSK_DPAR_PRESOLVE_TOL_ABS_LINDEP*
- *MSK_DPAR_PRESOLVE_TOL_AIJ*
- *MSK_DPAR_PRESOLVE_TOL_REL_LINDEP*
- *MSK_DPAR_PRESOLVE_TOL_S*
- *MSK_DPAR_PRESOLVE_TOL_X*
- *MSK_IPAR_PRESOLVE_USE*

11.1.6 Primal simplex optimizer parameters.

- *MSK_IPAR_SIM_PRIMAL_CRASH*
- *MSK_IPAR_SIM_PRIMAL_RESTRICT_SELECTION*
- *MSK_IPAR_SIM_PRIMAL_SELECTION*

11.1.7 Dual simplex optimizer parameters.

- *MSK_IPAR_SIM_DUAL_CRASH*
- *MSK_IPAR_SIM_DUAL_RESTRICT_SELECTION*
- *MSK_IPAR_SIM_DUAL_SELECTION*

11.1.8 Data input/output parameters.

- *MSK_SPAR_BAS_SOL_FILE_NAME*
- *MSK_SPAR_DATA_FILE_NAME*
- *MSK_SPAR_DEBUG_FILE_NAME*
- *MSK_IPAR_INFEAS_REPORT_AUTO*
- *MSK_SPAR_INT_SOL_FILE_NAME*
- *MSK_SPAR_ITR_SOL_FILE_NAME*
- *MSK_IPAR_LOG_FILE*
- *MSK_SPAR_MIO_DEBUG_STRING*

- *MSK_IPAR_OPF_MAX_TERMS_PER_LINE*
- *MSK_IPAR_OPF_WRITE_HEADER*
- *MSK_IPAR_OPF_WRITE_HINTS*
- *MSK_IPAR_OPF_WRITE_PARAMETERS*
- *MSK_IPAR_OPF_WRITE_PROBLEM*
- *MSK_IPAR_OPF_WRITE_SOL_BAS*
- *MSK_IPAR_OPF_WRITE_SOL_ITG*
- *MSK_IPAR_OPF_WRITE_SOL_ITR*
- *MSK_IPAR_OPF_WRITE_SOLUTIONS*
- *MSK_SPAR_PARAM_COMMENT_SIGN*
- *MSK_IPAR_PARAM_READ_CASE_NAME*
- *MSK_SPAR_PARAM_READ_FILE_NAME*
- *MSK_IPAR_PARAM_READ_IGN_ERROR*
- *MSK_SPAR_PARAM_WRITE_FILE_NAME*
- *MSK_IPAR_READ_DATA_COMPRESSED*
- *MSK_IPAR_READ_DATA_FORMAT*
- *MSK_IPAR_READ_DEBUG*
- *MSK_IPAR_READ_KEEP_FREE_CON*
- *MSK_IPAR_READ_LP_DROP_NEW_VARS_IN_BOU*
- *MSK_IPAR_READ_LP_QUOTED_NAMES*
- *MSK_SPAR_READ_MPS_BOU_NAME*
- *MSK_IPAR_READ_MPS_FORMAT*
- *MSK_SPAR_READ_MPS_OBJ_NAME*
- *MSK_SPAR_READ_MPS_RAN_NAME*
- *MSK_SPAR_READ_MPS_RHS_NAME*
- *MSK_IPAR_READ_MPS_WIDTH*
- *MSK_IPAR_READ_TASK_IGNORE_PARAM*
- *MSK_SPAR_SENSITIVITY_FILE_NAME*
- *MSK_SPAR_SENSITIVITY_RES_FILE_NAME*
- *MSK_SPAR_SOL_FILTER_XC_LOW*
- *MSK_SPAR_SOL_FILTER_XC_UPR*
- *MSK_SPAR_SOL_FILTER_XX_LOW*
- *MSK_SPAR_SOL_FILTER_XX_UPR*
- *MSK_IPAR_SOL_READ_NAME_WIDTH*
- *MSK_IPAR_SOL_READ_WIDTH*
- *MSK_SPAR_STAT_FILE_NAME*
- *MSK_SPAR_STAT_KEY*
- *MSK_SPAR_STAT_NAME*
- *MSK_IPAR_WRITE_BAS_CONSTRAINTS*

- *MSK_IPAR_WRITE_BAS_HEAD*
- *MSK_IPAR_WRITE_BAS_VARIABLES*
- *MSK_IPAR_WRITE_DATA_COMPRESSED*
- *MSK_IPAR_WRITE_DATA_FORMAT*
- *MSK_IPAR_WRITE_DATA_PARAM*
- *MSK_IPAR_WRITE_FREE_CON*
- *MSK_IPAR_WRITE_GENERIC_NAMES*
- *MSK_IPAR_WRITE_GENERIC_NAMES_IO*
- *MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_ITEMS*
- *MSK_IPAR_WRITE_INT_CONSTRAINTS*
- *MSK_IPAR_WRITE_INT_HEAD*
- *MSK_IPAR_WRITE_INT_VARIABLES*
- *MSK_IPAR_WRITE_LP_FULL_OBJ*
- *MSK_IPAR_WRITE_LP_GEN_VAR_NAME*
- *MSK_IPAR_WRITE_LP_LINE_WIDTH*
- *MSK_IPAR_WRITE_LP_QUOTED_NAMES*
- *MSK_IPAR_WRITE_LP_STRICT_FORMAT*
- *MSK_IPAR_WRITE_LP_TERMS_PER_LINE*
- *MSK_IPAR_WRITE_MPS_FORMAT*
- *MSK_IPAR_WRITE_MPS_INT*
- *MSK_IPAR_WRITE_PRECISION*
- *MSK_IPAR_WRITE_SOL_BARVARIABLES*
- *MSK_IPAR_WRITE_SOL_CONSTRAINTS*
- *MSK_IPAR_WRITE_SOL_HEAD*
- *MSK_IPAR_WRITE_SOL_IGNORE_INVALID_NAMES*
- *MSK_IPAR_WRITE_SOL_VARIABLES*
- *MSK_IPAR_WRITE_TASK_INC_SOL*
- *MSK_IPAR_WRITE_XML_MODE*

11.1.9 Overall solver parameters.

- *MSK_IPAR_BI_CLEAN_OPTIMIZER*
- *MSK_IPAR_INFEAS_PREFER_PRIMAL*
- *MSK_IPAR_LICENSE_WAIT*
- *MSK_IPAR_MIO_MODE*
- *MSK_IPAR_OPTIMIZER*
- *MSK_IPAR_PREOLVE_LEVEL*
- *MSK_IPAR_PREOLVE_USE*
- *MSK_IPAR_PRIMAL_REPAIR_OPTIMIZER*
- *MSK_IPAR_SENSITIVITY_ALL*

- *MSK_IPAR_SENSITIVITY_OPTIMIZER*
- *MSK_IPAR_SENSITIVITY_TYPE*
- *MSK_IPAR_SOLUTION_CALLBACK*

11.1.10 Data check parameters.

- *MSK_IPAR_CHECK_CONVEXITY*
- *MSK_DPAR_DATA_SYM_MAT_TOL*
- *MSK_DPAR_DATA_SYM_MAT_TOL_HUGE*
- *MSK_DPAR_DATA_SYM_MAT_TOL_LARGE*
- *MSK_DPAR_DATA_TOL_AIJ*
- *MSK_DPAR_DATA_TOL_AIJ_HUGE*
- *MSK_DPAR_DATA_TOL_AIJ_LARGE*
- *MSK_DPAR_DATA_TOL_BOUND_INF*
- *MSK_DPAR_DATA_TOL_BOUND_WRN*
- *MSK_DPAR_DATA_TOL_C_HUGE*
- *MSK_DPAR_DATA_TOL_CJ_LARGE*
- *MSK_DPAR_DATA_TOL_QIJ*
- *MSK_DPAR_DATA_TOL_X*
- *MSK_IPAR_LOG_CHECK_CONVEXITY*
- *MSK_DPAR_SEMIDEFINITE_TOL_APPROX*

11.1.11 Basis identification parameters.

- *MSK_IPAR_BI_CLEAN_OPTIMIZER*
- *MSK_IPAR_BI_IGNORE_MAX_ITER*
- *MSK_IPAR_BI_IGNORE_NUM_ERROR*
- *MSK_IPAR_BI_MAX_ITERATIONS*
- *MSK_IPAR_INTPNT_BASIS*
- *MSK_IPAR_LOG_BI*
- *MSK_IPAR_LOG_BI_FREQ*
- *MSK_DPAR_SIM_LU_TOL_REL_PIV*

11.1.12 Simplex optimizer parameters.

- *MSK_DPAR_BASIS_REL_TOL_S*
- *MSK_IPAR_BASIS_SOLVE_USE_PLUS_ONE*
- *MSK_DPAR_BASIS_TOL_S*
- *MSK_DPAR_BASIS_TOL_X*
- *MSK_IPAR_LOG_SIM*
- *MSK_IPAR_LOG_SIM_FREQ*

- *MSK_IPAR_LOG_SIM_MINOR*
- *MSK_IPAR_SENSITIVITY_OPTIMIZER*
- *MSK_IPAR_SIM_BASIS_FACTOR_USE*
- *MSK_IPAR_SIM_DEGEN*
- *MSK_IPAR_SIM_DUAL_PHASEONE_METHOD*
- *MSK_IPAR_SIM_EXPLOIT_DUPVEC*
- *MSK_IPAR_SIM_HOTSTART*
- *MSK_IPAR_SIM_INTEGER*
- *MSK_DPAR_SIM_LU_TOL_REL_PIV*
- *MSK_IPAR_SIM_MAX_ITERATIONS*
- *MSK_IPAR_SIM_MAX_NUM_SETBACKS*
- *MSK_IPAR_SIM_NON_SINGULAR*
- *MSK_IPAR_SIM_PRIMAL_PHASEONE_METHOD*
- *MSK_IPAR_SIM_REFACTOR_FREQ*
- *MSK_IPAR_SIM_REFORMULATION*
- *MSK_IPAR_SIM_SAVE_LU*
- *MSK_IPAR_SIM_SCALING*
- *MSK_IPAR_SIM_SCALING_METHOD*
- *MSK_IPAR_SIM_SOLVE_FORM*
- *MSK_IPAR_SIM_STABILITY_PRIORITY*
- *MSK_IPAR_SIM_SWITCH_OPTIMIZER*
- *MSK_DPAR_SIMPLEX_ABS_TOL_PIV*

11.1.13 Output information parameters.

- *MSK_IPAR_INFEAS_REPORT_LEVEL*
- *MSK_IPAR_LICENSE_SUPPRESS_EXPIRE_WRNS*
- *MSK_IPAR_LOG*
- *MSK_IPAR_LOG_BI*
- *MSK_IPAR_LOG_BI_FREQ*
- *MSK_IPAR_LOG_CUT_SECOND_OPT*
- *MSK_IPAR_LOG_EXPAND*
- *MSK_IPAR_LOG_FACTOR*
- *MSK_IPAR_LOG_FEAS_REPAIR*
- *MSK_IPAR_LOG_FILE*
- *MSK_IPAR_LOG_HEAD*
- *MSK_IPAR_LOG_INFEAS_ANA*
- *MSK_IPAR_LOG_INTPNT*
- *MSK_IPAR_LOG_MIO*
- *MSK_IPAR_LOG_MIO_FREQ*

- *MSK_IPAR_LOG_OPTIMIZER*
- *MSK_IPAR_LOG_ORDER*
- *MSK_IPAR_LOG_RESPONSE*
- *MSK_IPAR_LOG_SENSITIVITY*
- *MSK_IPAR_LOG_SENSITIVITY_OPT*
- *MSK_IPAR_LOG_SIM*
- *MSK_IPAR_LOG_SIM_FREQ*
- *MSK_IPAR_LOG_SIM_MINOR*
- *MSK_IPAR_LOG_STORAGE*
- *MSK_IPAR_MAX_NUM_WARNINGS*

11.1.14 Solution input/output parameters.

- *MSK_SPAR_BAS_SOL_FILE_NAME*
- *MSK_IPAR_INFEAS_REPORT_AUTO*
- *MSK_SPAR_INT_SOL_FILE_NAME*
- *MSK_SPAR_ITR_SOL_FILE_NAME*
- *MSK_IPAR_SOL_FILTER_KEEP_BASIC*
- *MSK_IPAR_SOL_FILTER_KEEP_RANGED*
- *MSK_SPAR_SOL_FILTER_XC_LOW*
- *MSK_SPAR_SOL_FILTER_XC_UPR*
- *MSK_SPAR_SOL_FILTER_XX_LOW*
- *MSK_SPAR_SOL_FILTER_XX_UPR*
- *MSK_IPAR_SOL_READ_NAME_WIDTH*
- *MSK_IPAR_SOL_READ_WIDTH*
- *MSK_IPAR_WRITE_BAS_CONSTRAINTS*
- *MSK_IPAR_WRITE_BAS_HEAD*
- *MSK_IPAR_WRITE_BAS_VARIABLES*
- *MSK_IPAR_WRITE_INT_CONSTRAINTS*
- *MSK_IPAR_WRITE_INT_HEAD*
- *MSK_IPAR_WRITE_INT_VARIABLES*
- *MSK_IPAR_WRITE_SOL_BARVARIABLES*
- *MSK_IPAR_WRITE_SOL_CONSTRAINTS*
- *MSK_IPAR_WRITE_SOL_HEAD*
- *MSK_IPAR_WRITE_SOL_IGNORE_INVALID_NAMES*
- *MSK_IPAR_WRITE_SOL_VARIABLES*

11.1.15 Infeasibility report parameters.

- *MSK_IPAR_INFEAS_GENERIC_NAMES*
- *MSK_IPAR_INFEAS_REPORT_LEVEL*
- *MSK_IPAR_LOG_INFEAS_ANA*

11.1.16 Nonlinear convex method parameters.

- *MSK_IPAR_CHECK_CONVEXITY*
- *MSK_DPAR_INTPNT_NL_MERIT_BAL*
- *MSK_DPAR_INTPNT_NL_TOL_DFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_MU_RED*
- *MSK_DPAR_INTPNT_NL_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_NL_TOL_PFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_REL_GAP*
- *MSK_DPAR_INTPNT_NL_TOL_REL_STEP*
- *MSK_DPAR_INTPNT_TOL_INFEAS*
- *MSK_IPAR_LOG_CHECK_CONVEXITY*

11.1.17 Analysis parameters.

- *MSK_IPAR_ANA_SOL_BASIS*
- *MSK_DPAR_ANA_SOL_INFEAS_TOL*
- *MSK_IPAR_ANA_SOL_PRINT_VIOLATED*
- *MSK_IPAR_LOG_ANA_PRO*

11.1.18 Mixed-integer optimization parameters.

- *MSK_IPAR_LOG_MIO*
- *MSK_IPAR_LOG_MIO_FREQ*
- *MSK_IPAR_MIO_BRANCH_DIR*
- *MSK_IPAR_MIO_CONSTRUCT_SOL*
- *MSK_IPAR_MIO_CUT_CLIQUE*
- *MSK_IPAR_MIO_CUT_CMIR*
- *MSK_IPAR_MIO_CUT_GMI*
- *MSK_IPAR_MIO_CUT_IMPLIED_BOUND*
- *MSK_IPAR_MIO_CUT_KNAPSACK_COVER*
- *MSK_IPAR_MIO_CUT_SELECTION_LEVEL*
- *MSK_DPAR_MIO_DISABLE_TERM_TIME*
- *MSK_IPAR_MIO_HEURISTIC_LEVEL*
- *MSK_IPAR_MIO_MAX_NUM_BRANCHES*
- *MSK_IPAR_MIO_MAX_NUM_RELAXS*

- *MSK_IPAR_MIO_MAX_NUM_SOLUTIONS*
- *MSK_DPAR_MIO_MAX_TIME*
- *MSK_DPAR_MIO_NEAR_TOL_ABS_GAP*
- *MSK_DPAR_MIO_NEAR_TOL_REL_GAP*
- *MSK_IPAR_MIO_NODE_OPTIMIZER*
- *MSK_IPAR_MIO_NODE_SELECTION*
- *MSK_IPAR_MIO_PERSPECTIVE_REFORMULATE*
- *MSK_IPAR_MIO_PROBING_LEVEL*
- *MSK_DPAR_MIO_REL_GAP_CONST*
- *MSK_IPAR_MIO_RINS_MAX_NODES*
- *MSK_IPAR_MIO_ROOT_OPTIMIZER*
- *MSK_IPAR_MIO_ROOT_REPEAT_PREOLVE_LEVEL*
- *MSK_DPAR_MIO_TOL_ABS_GAP*
- *MSK_DPAR_MIO_TOL_ABS_RELAX_INT*
- *MSK_DPAR_MIO_TOL_FEAS*
- *MSK_DPAR_MIO_TOL_REL_DUAL_BOUND_IMPROVEMENT*
- *MSK_DPAR_MIO_TOL_REL_GAP*
- *MSK_IPAR_MIO_VB_DETECTION_LEVEL*

11.1.19 Termination criterion parameters.

- *MSK_DPAR_BASIS_REL_TOL_S*
- *MSK_DPAR_BASIS_TOL_S*
- *MSK_DPAR_BASIS_TOL_X*
- *MSK_IPAR_BI_MAX_ITERATIONS*
- *MSK_DPAR_INTPNT_CO_TOL_DFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_INFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_MU_RED*
- *MSK_DPAR_INTPNT_CO_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_CO_TOL_PFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_REL_GAP*
- *MSK_IPAR_INTPNT_MAX_ITERATIONS*
- *MSK_DPAR_INTPNT_NL_TOL_DFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_MU_RED*
- *MSK_DPAR_INTPNT_NL_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_NL_TOL_PFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_REL_GAP*
- *MSK_DPAR_INTPNT_QO_TOL_DFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_INFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_MU_RED*

- *MSK_DPAR_INTPNT_QO_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_QO_TOL_PFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_REL_GAP*
- *MSK_DPAR_INTPNT_TOL_DFEAS*
- *MSK_DPAR_INTPNT_TOL_INFEAS*
- *MSK_DPAR_INTPNT_TOL_MU_RED*
- *MSK_DPAR_INTPNT_TOL_PFEAS*
- *MSK_DPAR_INTPNT_TOL_REL_GAP*
- *MSK_DPAR_LOWER_OBJ_CUT*
- *MSK_DPAR_LOWER_OBJ_CUT_FINITE_TRH*
- *MSK_DPAR_MIO_DISABLE_TERM_TIME*
- *MSK_IPAR_MIO_MAX_NUM_BRANCHES*
- *MSK_IPAR_MIO_MAX_NUM_SOLUTIONS*
- *MSK_DPAR_MIO_MAX_TIME*
- *MSK_DPAR_MIO_NEAR_TOL_REL_GAP*
- *MSK_DPAR_MIO_REL_GAP_CONST*
- *MSK_DPAR_MIO_TOL_REL_GAP*
- *MSK_DPAR_OPTIMIZER_MAX_TIME*
- *MSK_IPAR_SIM_MAX_ITERATIONS*
- *MSK_DPAR_UPPER_OBJ_CUT*
- *MSK_DPAR_UPPER_OBJ_CUT_FINITE_TRH*

11.1.20 Optimization system parameters.

- *MSK_IPAR_AUTO_UPDATE_SOL_INFO*
- *MSK_IPAR_INTPNT_MULTI_THREAD*
- *MSK_IPAR_LICENSE_WAIT*
- *MSK_IPAR_LOG_STORAGE*
- *MSK_IPAR_MIO_MT_USER_CB*
- *MSK_IPAR_MT_SPINCOUNT*
- *MSK_IPAR_NUM_THREADS*
- *MSK_IPAR_TIMING_LEVEL*

11.1.21 Progress call-back parameters.

- *MSK_IPAR_SOLUTION_CALLBACK*

11.1.22 Interior-point method parameters.

- *MSK_IPAR_BI_IGNORE_MAX_ITER*
- *MSK_IPAR_BI_IGNORE_NUM_ERROR*
- *MSK_DPAR_CHECK_CONVEXITY_REL_TOL*
- *MSK_IPAR_INTPNT_BASIS*
- *MSK_DPAR_INTPNT_CO_TOL_DFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_INFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_MU_RED*
- *MSK_DPAR_INTPNT_CO_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_CO_TOL_PFEAS*
- *MSK_DPAR_INTPNT_CO_TOL_REL_GAP*
- *MSK_IPAR_INTPNT_DIFF_STEP*
- *MSK_IPAR_INTPNT_HOTSTART*
- *MSK_IPAR_INTPNT_MAX_ITERATIONS*
- *MSK_IPAR_INTPNT_MAX_NUM_COR*
- *MSK_IPAR_INTPNT_MAX_NUM_REFINEMENT_STEPS*
- *MSK_DPAR_INTPNT_NL_MERIT_BAL*
- *MSK_DPAR_INTPNT_NL_TOL_DFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_MU_RED*
- *MSK_DPAR_INTPNT_NL_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_NL_TOL_PFEAS*
- *MSK_DPAR_INTPNT_NL_TOL_REL_GAP*
- *MSK_DPAR_INTPNT_NL_TOL_REL_STEP*
- *MSK_IPAR_INTPNT_OFF_COL_TRH*
- *MSK_IPAR_INTPNT_ORDER_METHOD*
- *MSK_DPAR_INTPNT_QO_TOL_DFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_INFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_MU_RED*
- *MSK_DPAR_INTPNT_QO_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_QO_TOL_PFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_REL_GAP*
- *MSK_IPAR_INTPNT_REGULARIZATION_USE*
- *MSK_IPAR_INTPNT_SCALING*
- *MSK_IPAR_INTPNT_SOLVE_FORM*
- *MSK_IPAR_INTPNT_STARTING_POINT*
- *MSK_DPAR_INTPNT_TOL_DFEAS*
- *MSK_DPAR_INTPNT_TOL_DSAFE*
- *MSK_DPAR_INTPNT_TOL_INFEAS*
- *MSK_DPAR_INTPNT_TOL_MU_RED*

- *MSK_DPAR_INTPNT_TOL_PATH*
- *MSK_DPAR_INTPNT_TOL_PFEAS*
- *MSK_DPAR_INTPNT_TOL_PSAFE*
- *MSK_DPAR_INTPNT_TOL_REL_GAP*
- *MSK_DPAR_INTPNT_TOL_REL_STEP*
- *MSK_DPAR_INTPNT_TOL_STEP_SIZE*
- *MSK_IPAR_LOG_INTPNT*
- *MSK_IPAR_LOG_PRESOLVE*
- *MSK_DPAR_QCQO_REFORMULATE_REL_DROP_TOL*

11.1.23 Debugging parameters.

- *MSK_IPAR_AUTO_SORT_A_BEFORE_OPT*

11.2 Response codes

- *Termination codes*
- *Error codes*
- *Warning codes*

11.2.1 Termination Codes

MSK_RES_OK (0)

No error occurred.

MSK_RES_TRM_INTERNAL (10030)

The optimizer terminated due to some internal reason. Please contact **MOSEK** support.

MSK_RES_TRM_INTERNAL_STOP (10031)

The optimizer terminated for internal reasons. Please contact **MOSEK** support.

MSK_RES_TRM_MAX_ITERATIONS (10000)

The optimizer terminated at the maximum number of iterations.

MSK_RES_TRM_MAX_NUM_SETBACKS (10020)

The optimizer terminated as the maximum number of set-backs was reached. This indicates % serious numerical problems and a possibly badly formulated problem.

MSK_RES_TRM_MAX_TIME (10001)

The optimizer terminated at the maximum amount of time.

MSK_RES_TRM_MIO_NEAR_ABS_GAP (10004)

The mixed-integer optimizer terminated because the near optimal absolute gap tolerance was satisfied.

MSK_RES_TRM_MIO_NEAR_REL_GAP (10003)

The mixed-integer optimizer terminated because the near optimal relative gap tolerance was satisfied.

MSK_RES_TRM_MIO_NUM_BRANCHES (10009)

The mixed-integer optimizer terminated as to the maximum number of branches was reached.

MSK_RES_TRM_MIO_NUM_RELAXS (10008)

The mixed-integer optimizer terminated as the maximum number of relaxations was reached.

MSK_RES_TRM_NUM_MAX_NUM_INT_SOLUTIONS (10015)

The mixed-integer optimizer terminated as the maximum number of feasible solutions was reached.

MSK_RES_TRM_NUMERICAL_PROBLEM (10025)

The optimizer terminated due to numerical problems.

MSK_RES_TRM_OBJECTIVE_RANGE (10002)

The optimizer terminated on the bound of the objective range.

MSK_RES_TRM_STALL (10006)

The optimizer is terminated due to slow progress.

Stalling means that numerical problems prevent the optimizer from making reasonable progress and that it make no sense to continue. In many cases this happens if the problem is badly scaled or otherwise ill-conditioned. There is no guarantee that the solution will be (near) feasible or near optimal. However, often stalling happens near the optimum, and the returned solution may be of good quality. Therefore, it is recommended to check the status of then solution. If the solution near optimal the solution is most likely good enough for most practical purposes.

Please note that if a linear optimization problem is solved using the interior-point optimizer with basis identification turned on, the returned basic solution likely to have high accuracy, even though the optimizer stalled.

Some common causes of stalling are a) badly scaled models, b) near feasible or near infeasible problems and c) a non-convex problems. Case c) is only relevant for general non-linear problems. It is not possible in general for **MOSEK** to check if a specific problems is convex since such a check would be NP hard in itself. This implies that care should be taken when solving problems involving general user defined functions.

MSK_RES_TRM_USER_CALLBACK (10007)

The optimizer terminated due to the return of the user-defined call-back function.

11.2.2 Error Codes

MSK_RES_ERR_AD_INVALID_CODELIST (3102)

The code list data was invalid.

MSK_RES_ERR_API_ARRAY_TOO_SMALL (3001)

An input array was too short.

MSK_RES_ERR_API_CB_CONNECT (3002)

Failed to connect a callback object.

MSK_RES_ERR_API_FATAL_ERROR (3005)

An internal error occurred in the API. Please report this problem.

MSK_RES_ERR_API_INTERNAL (3999)

An internal fatal error occurred in an interface function.

MSK_RES_ERR_ARG_IS_TOO_LARGE (1227)

The value of a argument is too small.

MSK_RES_ERR_ARG_IS_TOO_SMALL (1226)

The value of a argument is too small.

MSK_RES_ERR_ARGUMENT_DIMENSION (1201)

A function argument is of incorrect dimension.

MSK_RES_ERR_ARGUMENT_IS_TOO_LARGE (5005)

The value of a function argument is too large.

MSK_RES_ERR_ARGUMENT_LENNEQ (1197)

Incorrect length of arguments.

MSK_RES_ERR_ARGUMENT_PERM_ARRAY (1299)

An invalid permutation array is specified.

MSK_RES_ERR_ARGUMENT_TYPE (1198)	Incorrect argument type.
MSK_RES_ERR_BAR_VAR_DIM (3920)	The dimension of a symmetric matrix variable has to greater than 0.
MSK_RES_ERR_BASIS (1266)	An invalid basis is specified. Either too many or too few basis variables are specified.
MSK_RES_ERR_BASIS_FACTOR (1610)	The factorization of the basis is invalid.
MSK_RES_ERR_BASIS_SINGULAR (1615)	The basis is singular and hence cannot be factored.
MSK_RES_ERR_BLANK_NAME (1070)	An all blank name has been specified.
MSK_RES_ERR_CANNOT_CLONE_NL (2505)	A task with a nonlinear function call-back cannot be cloned.
MSK_RES_ERR_CANNOT_HANDLE_NL (2506)	A function cannot handle a task with nonlinear function call-backs.
MSK_RES_ERR_CBF_DUPLICATE_ACOORD (7116)	Duplicate index in ACOORD.
MSK_RES_ERR_CBF_DUPLICATE_BCOORD (7115)	Duplicate index in BCOORD.
MSK_RES_ERR_CBF_DUPLICATE_CON (7108)	Duplicate CON keyword.
MSK_RES_ERR_CBF_DUPLICATE_INT (7110)	Duplicate INT keyword.
MSK_RES_ERR_CBF_DUPLICATE_OBJ (7107)	Duplicate OBJ keyword.
MSK_RES_ERR_CBF_DUPLICATE_OBJACORD (7114)	Duplicate index in OBJCOORD.
MSK_RES_ERR_CBF_DUPLICATE_VAR (7109)	Duplicate VAR keyword.
MSK_RES_ERR_CBF_INVALID_CON_TYPE (7112)	Invalid constraint type.
MSK_RES_ERR_CBF_INVALID_DOMAIN_DIMENSION (7113)	Invalid domain dimension.
MSK_RES_ERR_CBF_INVALID_INT_INDEX (7121)	Invalid INT index.
MSK_RES_ERR_CBF_INVALID_VAR_TYPE (7111)	Invalid variable type.
MSK_RES_ERR_CBF_NO_VARIABLES (7102)	No variables are specified.
MSK_RES_ERR_CBF_NO_VERSION_SPECIFIED (7105)	No version specified.
MSK_RES_ERR_CBF_OBJ_SENSE (7101)	An invalid objective sense is specified.
MSK_RES_ERR_CBF_PARSE (7100)	An error occurred while parsing an CBF file.

MSK_RES_ERR_CBF_SYNTAX (7106)

Invalid syntax.

MSK_RES_ERR_CBF_TOO_FEW_CONSTRAINTS (7118)

Too few constraints defined.

MSK_RES_ERR_CBF_TOO_FEW_INTS (7119)

Too few ints are specified.

MSK_RES_ERR_CBF_TOO_FEW_VARIABLES (7117)

Too few variables defined.

MSK_RES_ERR_CBF_TOO_MANY_CONSTRAINTS (7103)

Too many constraints specified.

MSK_RES_ERR_CBF_TOO_MANY_INTS (7120)

Too many ints are specified.

MSK_RES_ERR_CBF_TOO_MANY_VARIABLES (7104)

Too many variables specified.

MSK_RES_ERR_CBF_UNSUPPORTED (7122)

Unsupported feature is present.

MSK_RES_ERR_CON_Q_NOT_NSD (1294)

The quadratic constraint matrix is not negative semidefinite as expected for a constraint with finite lower bound. This results in a nonconvex problem. The parameter *MSK_DPAR_CHECK_CONVEXITY_REL_TOL* can be used to relax the convexity check.

MSK_RES_ERR_CON_Q_NOT_PSD (1293)

The quadratic constraint matrix is not positive semidefinite as expected for a constraint with finite upper bound. This results in a nonconvex problem. The parameter *MSK_DPAR_CHECK_CONVEXITY_REL_TOL* can be used to relax the convexity check.

MSK_RES_ERR_CONE_INDEX (1300)

An index of a non-existing cone has been specified.

MSK_RES_ERR_CONE_OVERLAP (1302)

One or more of the variables in the cone to be added is already member of another cone. Now assume the variable is x_j then add a new variable say x_k and the constraint

$$x_j = x_k$$

and then let x_k be member of the cone to be appended.

MSK_RES_ERR_CONE_OVERLAP_APPEND (1307)

The cone to be appended has one variable which is already member of another cone.

MSK_RES_ERR_CONE_REP_VAR (1303)

A variable is included multiple times in the cone.

MSK_RES_ERR_CONE_SIZE (1301)

A cone with too few members is specified.

MSK_RES_ERR_CONE_TYPE (1305)

Invalid cone type specified.

MSK_RES_ERR_CONE_TYPE_STR (1306)

Invalid cone type specified.

MSK_RES_ERR_DATA_FILE_EXT (1055)

The data file format cannot be determined from the file name.

MSK_RES_ERR_DUP_NAME (1071)

The same name was used multiple times for the same problem item type.

MSK_RES_ERR_DUPLICATE_AIJ (1385)

An element in the A matrix is specified twice.

- MSK_RES_ERR_DUPLICATE_BARVARIABLE_NAMES (4502)
Two barvariable names are identical.
- MSK_RES_ERR_DUPLICATE_CONE_NAMES (4503)
Two cone names are identical.
- MSK_RES_ERR_DUPLICATE_CONSTRAINT_NAMES (4500)
Two constraint names are identical.
- MSK_RES_ERR_DUPLICATE_VARIABLE_NAMES (4501)
Two variable names are identical.
- MSK_RES_ERR_END_OF_FILE (1059)
End of file reached.
- MSK_RES_ERR_FACTOR (1650)
An error occurred while factorizing a matrix.
- MSK_RES_ERR_FEASREPAIR_CANNOT_RELAX (1700)
An optimization problem cannot be relaxed. This is the case e.g. for general nonlinear optimization problems.
- MSK_RES_ERR_FEASREPAIR_INCONSISTENT_BOUND (1702)
The upper bound is less than the lower bound for a variable or a constraint. Please correct this before running the feasibility repair.
- MSK_RES_ERR_FEASREPAIR_SOLVING_RELAXED (1701)
The relaxed problem could not be solved to optimality. Please consult the log file for further details.
- MSK_RES_ERR_FILE_LICENSE (1007)
Invalid license file.
- MSK_RES_ERR_FILE_OPEN (1052)
Error while opening a file.
- MSK_RES_ERR_FILE_READ (1053)
File read error.
- MSK_RES_ERR_FILE_WRITE (1054)
File write error.
- MSK_RES_ERR_FIRST (1261)
Invalid `first`.
- MSK_RES_ERR_FIRSTI (1285)
Invalid `firsti`.
- MSK_RES_ERR_FIRSTJ (1287)
Invalid `firstj`.
- MSK_RES_ERR_FIXED_BOUND_VALUES (1425)
A fixed constraint/variable has been specified using the bound keys but the numerical value of the lower and upper bound is different.
- MSK_RES_ERR_FLEXLM (1014)
The FLEXlm license manager reported an error.
- MSK_RES_ERR_GLOBAL_INV_CONIC_PROBLEM (1503)
The global optimizer can only be applied to problems without semidefinite variables.
- MSK_RES_ERR_HUGE_AIJ (1380)
A numerically huge value is specified for an $a_{i,j}$ element in A . The parameter `MSK_DPAR_DATA_TOL_AIJ_HUGE` controls when an $a_{i,j}$ is considered huge.
- MSK_RES_ERR_HUGE_C (1375)
A huge value in absolute size is specified for one c_j .
- MSK_RES_ERR_IDENTICAL_TASKS (3101)
Some tasks related to this function call were identical. Unique tasks were expected.

MSK_RES_ERR_IN_ARGUMENT (1200)
A function argument is incorrect.

MSK_RES_ERR_INDEX (1235)
An index is out of range.

MSK_RES_ERR_INDEX_ARR_IS_TOO_LARGE (1222)
An index in an array argument is too large.

MSK_RES_ERR_INDEX_ARR_IS_TOO_SMALL (1221)
An index in an array argument is too small.

MSK_RES_ERR_INDEX_IS_TOO_LARGE (1204)
An index in an argument is too large.

MSK_RES_ERR_INDEX_IS_TOO_SMALL (1203)
An index in an argument is too small.

MSK_RES_ERR_INF_DOU_INDEX (1219)
A double information index is out of range for the specified type.

MSK_RES_ERR_INF_DOU_NAME (1230)
A double information name is invalid.

MSK_RES_ERR_INF_INT_INDEX (1220)
An integer information index is out of range for the specified type.

MSK_RES_ERR_INF_INT_NAME (1231)
An integer information name is invalid.

MSK_RES_ERR_INF_LINT_INDEX (1225)
A long integer information index is out of range for the specified type.

MSK_RES_ERR_INF_LINT_NAME (1234)
A long integer information name is invalid.

MSK_RES_ERR_INF_TYPE (1232)
The information type is invalid.

MSK_RES_ERR_INFEAS_UNDEFINED (3910)
The requested value is not defined for this solution type.

MSK_RES_ERR_INFINITE_BOUND (1400)
A numerically huge bound value is specified.

MSK_RES_ERR_INT64_TO_INT32_CAST (3800)
An 32 bit integer could not cast to a 64 bit integer.

MSK_RES_ERR_INTERNAL (3000)
An internal error occurred. Please report this problem.

MSK_RES_ERR_INTERNAL_TEST_FAILED (3500)
An internal unit test function failed.

MSK_RES_ERR_INV_APTRE (1253)
`aptrb[j]` is strictly smaller than `aptrb[j]` for some `j`.

MSK_RES_ERR_INV_BK (1255)
Invalid bound key.

MSK_RES_ERR_INV_BKC (1256)
Invalid bound key is specified for a constraint.

MSK_RES_ERR_INV_BKX (1257)
An invalid bound key is specified for a variable.

MSK_RES_ERR_INV_CONE_TYPE (1272)
Invalid cone type code is encountered.

MSK_RES_ERR_INV_CONE_TYPE_STR (1271)
Invalid cone type string encountered.

MSK_RES_ERR_INV_MARKI (2501)
Invalid value in marki.

MSK_RES_ERR_INV_MARKJ (2502)
Invalid value in markj.

MSK_RES_ERR_INV_NAME_ITEM (1280)
An invalid name item code is used.

MSK_RES_ERR_INV_NUMI (2503)
Invalid numi.

MSK_RES_ERR_INV_NUMJ (2504)
Invalid numj.

MSK_RES_ERR_INV_OPTIMIZER (1550)
An invalid optimizer has been chosen for the problem. This means that the simplex or the conic optimizer is chosen to optimize a nonlinear problem.

MSK_RES_ERR_INV_PROBLEM (1500)
Invalid problem type. Probably a nonconvex problem has been specified.

MSK_RES_ERR_INV_QCON_SUBI (1405)
Invalid value in qcsubi.

MSK_RES_ERR_INV_QCON_SUBJ (1406)
Invalid value in qcsubj.

MSK_RES_ERR_INV_QCON_SUBK (1404)
Invalid value in qcsubk.

MSK_RES_ERR_INV_QCON_VAL (1407)
Invalid value in qcval.

MSK_RES_ERR_INV_QOBJ_SUBI (1401)
Invalid value in qosubi.

MSK_RES_ERR_INV_QOBJ_SUBJ (1402)
Invalid value in qosubj.

MSK_RES_ERR_INV_QOBJ_VAL (1403)
Invalid value in qoval.

MSK_RES_ERR_INV_SK (1270)
Invalid status key code.

MSK_RES_ERR_INV_SK_STR (1269)
Invalid status key string encountered.

MSK_RES_ERR_INV_SKC (1267)
Invalid value in skc.

MSK_RES_ERR_INV_SKN (1274)
Invalid value in skn.

MSK_RES_ERR_INV_SKX (1268)
Invalid value in skx.

MSK_RES_ERR_INV_VAR_TYPE (1258)
An invalid variable type is specified for a variable.

MSK_RES_ERR_INVALID_ACCMODE (2520)
An invalid access mode is specified.

MSK_RES_ERR_INVALID_AIJ (1473)
 $a_{i,j}$ contains an invalid floating point value, i.e. a NaN or an infinite value.

MSK_RES_ERR_INVALID_AMPL_STUB (3700)
Invalid AMPL stub.

MSK_RES_ERR_INVALID_BARVAR_NAME (1079)
An invalid symmetric matrix variable name is used.

MSK_RES_ERR_INVALID_COMPRESSION (1800)
Invalid compression type.

MSK_RES_ERR_INVALID_CON_NAME (1076)
An invalid constraint name is used.

MSK_RES_ERR_INVALID_CONE_NAME (1078)
An invalid cone name is used.

MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_CONES (4005)
The file format does not support a problem with conic constraints.

MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_GENERAL_NL (4010)
The file format does not support a problem with general nonlinear terms.

MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_SYM_MAT (4000)
The file format does not support a problem with symmetric matrix variables.

MSK_RES_ERR_INVALID_FILE_NAME (1056)
An invalid file name has been specified.

MSK_RES_ERR_INVALID_FORMAT_TYPE (1283)
Invalid format type.

MSK_RES_ERR_INVALID_IDX (1246)
A specified index is invalid.

MSK_RES_ERR_INVALID_IOMODE (1801)
Invalid io mode.

MSK_RES_ERR_INVALID_MAX_NUM (1247)
A specified index is invalid.

MSK_RES_ERR_INVALID_NAME_IN_SOL_FILE (1170)
An invalid name occurred in a solution file.

MSK_RES_ERR_INVALID_OBJ_NAME (1075)
An invalid objective name is specified.

MSK_RES_ERR_INVALID_OBJECTIVE_SENSE (1445)
An invalid objective sense is specified.

MSK_RES_ERR_INVALID_PROBLEM_TYPE (6000)
An invalid problem type.

MSK_RES_ERR_INVALID_SOL_FILE_NAME (1057)
An invalid file name has been specified.

MSK_RES_ERR_INVALID_STREAM (1062)
An invalid stream is referenced.

MSK_RES_ERR_INVALID_SURPLUS (1275)
Invalid surplus.

MSK_RES_ERR_INVALID_SYM_MAT_DIM (3950)
A sparse symmetric matrix of invalid dimension is specified.

MSK_RES_ERR_INVALID_TASK (1064)
The `task` is invalid.

MSK_RES_ERR_INVALID_UTF8 (2900)
An invalid UTF8 string is encountered.

MSK_RES_ERR_INVALID_VAR_NAME (1077)
An invalid variable name is used.

MSK_RES_ERR_INVALID_WCHAR (2901)
An invalid `wchar` string is encountered.

MSK_RES_ERR_INVALID_WHICHSOL (1228)
`whichsol` is invalid.

MSK_RES_ERR_JSON_DATA (1179)
Inconsistent data in JSON Task file

MSK_RES_ERR_JSON_FORMAT (1178)
Error in an JSON Task file

MSK_RES_ERR_JSON_MISSING_DATA (1180)
Missing data section in JSON task file.

MSK_RES_ERR_JSON_NUMBER_OVERFLOW (1177)
Invalid number entry - wrong type or value overflow.

MSK_RES_ERR_JSON_STRING (1176)
Error in JSON string.

MSK_RES_ERR_JSON_SYNTAX (1175)
Syntax error in an JSON data

MSK_RES_ERR_LAST (1262)
Invalid index `last`. A given index was out of expected range.

MSK_RES_ERR_LASTI (1286)
Invalid `lasti`.

MSK_RES_ERR_LASTJ (1288)
Invalid `lastj`.

MSK_RES_ERR_LAU_ARG_K (7012)
Invalid argument `k`.

MSK_RES_ERR_LAU_ARG_M (7010)
Invalid argument `m`.

MSK_RES_ERR_LAU_ARG_N (7011)
Invalid argument `n`.

MSK_RES_ERR_LAU_ARG_TRANS (7018)
Invalid argument `trans`.

MSK_RES_ERR_LAU_ARG_TRANSA (7015)
Invalid argument `transa`.

MSK_RES_ERR_LAU_ARG_TRANSB (7016)
Invalid argument `transb`.

MSK_RES_ERR_LAU_ARG_UPLO (7017)
Invalid argument `uplo`.

MSK_RES_ERR_LAU_INVALID_LOWER_TRIANGULAR_MATRIX (7002)
An invalid lower triangular matrix.

MSK_RES_ERR_LAU_INVALID_SPARSE_SYMMETRIC_MATRIX (7019)
An invalid sparse symmetric matrix is specified. Note only the lower triangular part with no duplicates is specified.

MSK_RES_ERR_LAU_NOT_POSITIVE_DEFINITE (7001)
A matrix is not positive definite.

MSK_RES_ERR_LAU_SINGULAR_MATRIX (7000)
A matrix is singular.

MSK_RES_ERR_LAU_UNKNOWN (7005)

An unknown error.

MSK_RES_ERR_LICENSE (1000)

Invalid license.

MSK_RES_ERR_LICENSE_CANNOT_ALLOCATE (1020)

The license system cannot allocate the memory required.

MSK_RES_ERR_LICENSE_CANNOT_CONNECT (1021)

MOSEK cannot connect to the license server. Most likely the license server is not up and running.

MSK_RES_ERR_LICENSE_EXPIRED (1001)

The license has expired.

MSK_RES_ERR_LICENSE_FEATURE (1018)

A requested feature is not available in the license file(s). Most likely due to an incorrect license system setup.

MSK_RES_ERR_LICENSE_INVALID_HOSTID (1025)

The host ID specified in the license file does not match the host ID of the computer.

MSK_RES_ERR_LICENSE_MAX (1016)

Maximum number of licenses is reached.

MSK_RES_ERR_LICENSE_MOSEKLM_DAEMON (1017)

The MOSEKLM license manager daemon is not up and running.

MSK_RES_ERR_LICENSE_NO_SERVER_LINE (1028)

There is no **SERVER** line in the license file. All non-zero license count features need at least one **SERVER** line.

MSK_RES_ERR_LICENSE_NO_SERVER_SUPPORT (1027)

The license server does not support the requested feature. Possible reasons for this error include:

- The feature has expired.
- The feature's start date is later than today's date.
- The version requested is higher than feature's the highest supported version.
- A corrupted license file.

Try restarting the license and inspect the license server debug file, usually called **lmgrd.log**.

MSK_RES_ERR_LICENSE_SERVER (1015)

The license server is not responding.

MSK_RES_ERR_LICENSE_SERVER_VERSION (1026)

The version specified in the checkout request is greater than the highest version number the daemon supports.

MSK_RES_ERR_LICENSE_VERSION (1002)

The license is valid for another version of **MOSEK**.

MSK_RES_ERR_LINK_FILE_DLL (1040)

A file cannot be linked to a stream in the DLL version.

MSK_RES_ERR_LIVING_TASKS (1066)

All tasks associated with an environment must be deleted before the environment is deleted. There are still some undeleted tasks.

MSK_RES_ERR_LOWER_BOUND_IS_A_NAN (1390)

The lower bound specified is not a number (nan).

MSK_RES_ERR_LP_DUP_SLACK_NAME (1152)

The name of the slack variable added to a ranged constraint already exists.

MSK_RES_ERR_LP_EMPTY (1151)

The problem cannot be written to an LP formatted file.

- MSK_RES_ERR_LP_FILE_FORMAT (1157)
Syntax error in an LP file.
- MSK_RES_ERR_LP_FORMAT (1160)
Syntax error in an LP file.
- MSK_RES_ERR_LP_FREE_CONSTRAINT (1155)
Free constraints cannot be written in LP file format.
- MSK_RES_ERR_LP_INCOMPATIBLE (1150)
The problem cannot be written to an LP formatted file.
- MSK_RES_ERR_LP_INVALID_CON_NAME (1171)
A constraint name is invalid when used in an LP formatted file.
- MSK_RES_ERR_LP_INVALID_VAR_NAME (1154)
A variable name is invalid when used in an LP formatted file.
- MSK_RES_ERR_LP_WRITE_CONIC_PROBLEM (1163)
The problem contains cones that cannot be written to an LP formatted file.
- MSK_RES_ERR_LP_WRITE_GECO_PROBLEM (1164)
The problem contains general convex terms that cannot be written to an LP formatted file.
- MSK_RES_ERR_LU_MAX_NUM_TRIES (2800)
Could not compute the LU factors of the matrix within the maximum number of allowed tries.
- MSK_RES_ERR_MAX_LEN_IS_TOO_SMALL (1289)
An maximum length that is too small has been specified.
- MSK_RES_ERR_MAXNUMBARVAR (1242)
The maximum number of semidefinite variables specified is smaller than the number of semidefinite variables in the task.
- MSK_RES_ERR_MAXNUMCON (1240)
The maximum number of constraints specified is smaller than the number of constraints in the task.
- MSK_RES_ERR_MAXNUMCONE (1304)
The value specified for `maxnumcone` is too small.
- MSK_RES_ERR_MAXNUMQNZ (1243)
The maximum number of non-zeros specified for the Q matrices is smaller than the number of non-zeros in the current Q matrices.
- MSK_RES_ERR_MAXNUMVAR (1241)
The maximum number of variables specified is smaller than the number of variables in the task.
- MSK_RES_ERR_MIO_INTERNAL (5010)
A fatal error occurred in the mixed integer optimizer. Please contact **MOSEK** support.
- MSK_RES_ERR_MIO_INVALID_NODE_OPTIMIZER (7131)
An invalid node optimizer was selected for the problem type.
- MSK_RES_ERR_MIO_INVALID_ROOT_OPTIMIZER (7130)
An invalid root optimizer was selected for the problem type.
- MSK_RES_ERR_MIO_NO_OPTIMIZER (1551)
No optimizer is available for the current class of integer optimization problems.
- MSK_RES_ERR_MIO_NOT_LOADED (1553)
The mixed-integer optimizer is not loaded.
- MSK_RES_ERR_MISSING_LICENSE_FILE (1008)
MOSEK cannot license file or a token server. See the **MOSEK** installation manual for details.
- MSK_RES_ERR_MIXED_CONIC_AND_NL (1501)
The problem contains nonlinear terms conic constraints. The requested operation cannot be applied to this type of problem.

MSK_RES_ERR_MPS_CONE_OVERLAP (1118)

A variable is specified to be a member of several cones.

MSK_RES_ERR_MPS_CONE_REPEAT (1119)

A variable is repeated within the CSECTION.

MSK_RES_ERR_MPS_CONE_TYPE (1117)

Invalid cone type specified in a CSECTION.

MSK_RES_ERR_MPS_DUPLICATE_Q_ELEMENT (1121)

Duplicate elements is specified in a Q matrix.

MSK_RES_ERR_MPS_FILE (1100)

An error occurred while reading an MPS file.

MSK_RES_ERR_MPS_INV_BOUND_KEY (1108)

An invalid bound key occurred in an MPS file.

MSK_RES_ERR_MPS_INV_CON_KEY (1107)

An invalid constraint key occurred in an MPS file.

MSK_RES_ERR_MPS_INV_FIELD (1101)

A field in the MPS file is invalid. Probably it is too wide.

MSK_RES_ERR_MPS_INV_MARKER (1102)

An invalid marker has been specified in the MPS file.

MSK_RES_ERR_MPS_INV_SEC_NAME (1109)

An invalid section name occurred in an MPS file.

MSK_RES_ERR_MPS_INV_SEC_ORDER (1115)

The sections in the MPS data file are not in the correct order.

MSK_RES_ERR_MPS_INVALID_OBJ_NAME (1128)

An invalid objective name is specified.

MSK_RES_ERR_MPS_INVALID_OBJSENSE (1122)

An invalid objective sense is specified.

MSK_RES_ERR_MPS_MUL_CON_NAME (1112)

A constraint name was specified multiple times in the ROWS section.

MSK_RES_ERR_MPS_MUL_CSEC (1116)

Multiple CSECTIONs are given the same name.

MSK_RES_ERR_MPS_MUL_QOBJ (1114)

The Q term in the objective is specified multiple times in the MPS data file.

MSK_RES_ERR_MPS_MUL_QSEC (1113)

Multiple QSECTIONs are specified for a constraint in the MPS data file.

MSK_RES_ERR_MPS_NO_OBJECTIVE (1110)

No objective is defined in an MPS file.

MSK_RES_ERR_MPS_NON_SYMMETRIC_Q (1120)

A non symmetric matrix has been specified.

MSK_RES_ERR_MPS_NULL_CON_NAME (1103)

An empty constraint name is used in an MPS file.

MSK_RES_ERR_MPS_NULL_VAR_NAME (1104)

An empty variable name is used in an MPS file.

MSK_RES_ERR_MPS_SPLITTED_VAR (1111)

All elements in a column of the A matrix must be specified consecutively. Hence, it is illegal to specify non-zero elements in A for variable 1, then for variable 2 and then variable 1 again.

MSK_RES_ERR_MPS_TAB_IN_FIELD2 (1125)

A tab char occurred in field 2.

- MSK_RES_ERR_MPS_TAB_IN_FIELD3 (1126)
A tab char occurred in field 3.
- MSK_RES_ERR_MPS_TAB_IN_FIELD5 (1127)
A tab char occurred in field 5.
- MSK_RES_ERR_MPS_UNDEF_CON_NAME (1105)
An undefined constraint name occurred in an MPS file.
- MSK_RES_ERR_MPS_UNDEF_VAR_NAME (1106)
An undefined variable name occurred in an MPS file.
- MSK_RES_ERR_MUL_A_ELEMENT (1254)
An element in A is defined multiple times.
- MSK_RES_ERR_NAME_IS_NULL (1760)
The name buffer is a NULL pointer.
- MSK_RES_ERR_NAME_MAX_LEN (1750)
A name is longer than the buffer that is supposed to hold it.
- MSK_RES_ERR_NAN_IN_BLC (1461)
 l^c contains an invalid floating point value, i.e. a NaN.
- MSK_RES_ERR_NAN_IN_BLC (1471)
 l^x contains an invalid floating point value, i.e. a NaN.
- MSK_RES_ERR_NAN_IN_BUC (1462)
 u^c contains an invalid floating point value, i.e. a NaN.
- MSK_RES_ERR_NAN_IN_BUC (1472)
 u^x contains an invalid floating point value, i.e. a NaN.
- MSK_RES_ERR_NAN_IN_C (1470)
 c contains an invalid floating point value, i.e. a NaN.
- MSK_RES_ERR_NAN_IN_DOUBLE_DATA (1450)
An invalid floating point value was used in some double data.
- MSK_RES_ERR_NEGATIVE_APPEND (1264)
Cannot append a negative number.
- MSK_RES_ERR_NEGATIVE_SURPLUS (1263)
Negative surplus.
- MSK_RES_ERR_NEWER_DLL (1036)
The dynamic link library is newer than the specified version.
- MSK_RES_ERR_NO_BARS_FOR_SOLUTION (3916)
There is no \bar{s} available for the solution specified. In particular note there are no \bar{s} defined for the basic and integer solutions.
- MSK_RES_ERR_NO_BARX_FOR_SOLUTION (3915)
There is no \bar{X} available for the solution specified. In particular note there are no \bar{X} defined for the basic and integer solutions.
- MSK_RES_ERR_NO_BASIS_SOL (1600)
No basic solution is defined.
- MSK_RES_ERR_NO_DUAL_FOR_ITG_SOL (2950)
No dual information is available for the integer solution.
- MSK_RES_ERR_NO_DUAL_INFEAS_CER (2001)
A certificate of infeasibility is not available.
- MSK_RES_ERR_NO_INIT_ENV (1063)
`env` is not initialized.

MSK_RES_ERR_NO_OPTIMIZER_VAR_TYPE (1552)

No optimizer is available for this class of optimization problems.

MSK_RES_ERR_NO_PRIMAL_INFEAS_CER (2000)

A certificate of primal infeasibility is not available.

MSK_RES_ERR_NO_SNX_FOR_BAS_SOL (2953)

s_n^x is not available for the basis solution.

MSK_RES_ERR_NO_SOLUTION_IN_CALLBACK (2500)

The required solution is not available.

MSK_RES_ERR_NON_UNIQUE_ARRAY (5000)

An array does not contain unique elements.

MSK_RES_ERR_NONCONVEX (1291)

The optimization problem is nonconvex.

MSK_RES_ERR_NONLINEAR_EQUALITY (1290)

The model contains a nonlinear equality which defines a nonconvex set.

MSK_RES_ERR_NONLINEAR_FUNCTIONS_NOT_ALLOWED (1428)

An operation that is invalid for problems with nonlinear functions defined has been attempted.

MSK_RES_ERR_NONLINEAR_RANGED (1292)

Nonlinear constraints with finite lower and upper bound always define a nonconvex feasible set.

MSK_RES_ERR_NR_ARGUMENTS (1199)

Incorrect number of function arguments.

MSK_RES_ERR_NULL_ENV (1060)

`env` is a NULL pointer.

MSK_RES_ERR_NULL_POINTER (1065)

An argument to a function is unexpectedly a NULL pointer.

MSK_RES_ERR_NULL_TASK (1061)

`task` is a NULL pointer.

MSK_RES_ERR_NUMCONLIM (1250)

Maximum number of constraints limit is exceeded.

MSK_RES_ERR_NUMVARLIM (1251)

Maximum number of variables limit is exceeded.

MSK_RES_ERR_OBJ_Q_NOT_NSD (1296)

The quadratic coefficient matrix in the objective is not negative semidefinite as expected for a maximization problem. The parameter `MSK_DPAR_CHECK_CONVEXITY_REL_TOL` can be used to relax the convexity check.

MSK_RES_ERR_OBJ_Q_NOT_PSD (1295)

The quadratic coefficient matrix in the objective is not positive semidefinite as expected for a minimization problem. The parameter `MSK_DPAR_CHECK_CONVEXITY_REL_TOL` can be used to relax the convexity check.

MSK_RES_ERR_OBJECTIVE_RANGE (1260)

Empty objective range.

MSK_RES_ERR_OLDER_DLL (1035)

The dynamic link library is older than the specified version.

MSK_RES_ERR_OPEN_DL (1030)

A dynamic link library could not be opened.

MSK_RES_ERR_OPF_FORMAT (1168)

Syntax error in an OPF file

- MSK_RES_ERR_OPF_NEW_VARIABLE (1169)
Introducing new variables is now allowed. When a [variables] section is present, it is not allowed to introduce new variables later in the problem.
- MSK_RES_ERR_OPF_PREMATURE_EOF (1172)
Premature end of file in an OPF file.
- MSK_RES_ERR_OPTIMIZER_LICENSE (1013)
The optimizer required is not licensed.
- MSK_RES_ERR_OVERFLOW (1590)
A computation produced an overflow i.e. a very large number.
- MSK_RES_ERR_PARAM_INDEX (1210)
Parameter index is out of range.
- MSK_RES_ERR_PARAM_IS_TOO_LARGE (1215)
The parameter value is too large.
- MSK_RES_ERR_PARAM_IS_TOO_SMALL (1216)
The parameter value is too small.
- MSK_RES_ERR_PARAM_NAME (1205)
The parameter name is not correct.
- MSK_RES_ERR_PARAM_NAME_DOUB (1206)
The parameter name is not correct for a double parameter.
- MSK_RES_ERR_PARAM_NAME_INT (1207)
The parameter name is not correct for an integer parameter.
- MSK_RES_ERR_PARAM_NAME_STR (1208)
The parameter name is not correct for a string parameter.
- MSK_RES_ERR_PARAM_TYPE (1218)
The parameter type is invalid.
- MSK_RES_ERR_PARAM_VALUE_STR (1217)
The parameter value string is incorrect.
- MSK_RES_ERR_PLATFORM_NOT_LICENSED (1019)
A requested license feature is not available for the required platform.
- MSK_RES_ERR_POSTSOLVE (1580)
An error occurred during the postsolve. Please contact **MOSEK** support.
- MSK_RES_ERR_PROBLEM_ITEM (1281)
An invalid problem is used.
- MSK_RES_ERR_PROB_LICENSE (1006)
The software is not licensed to solve the problem.
- MSK_RES_ERR_QCON_SUBI_TOO_LARGE (1409)
Invalid value in qconsubi.
- MSK_RES_ERR_QCON_SUBI_TOO_SMALL (1408)
Invalid value in qconsubi.
- MSK_RES_ERR_QCON_UPPER_TRIANGLE (1417)
An element in the upper triangle of a Q^k is specified. Only elements in the lower triangle should be specified.
- MSK_RES_ERR_QOBJ_UPPER_TRIANGLE (1415)
An element in the upper triangle of Q^o is specified. Only elements in the lower triangle should be specified.
- MSK_RES_ERR_READ_FORMAT (1090)
The specified format cannot be read.

MSK_RES_ERR_READ_LP_MISSING_END_TAG (1159)
Syntax error in LP file. Possibly missing End tag.

MSK_RES_ERR_READ_LP_NONEXISTING_NAME (1162)
A variable never occurred in objective or constraints.

MSK_RES_ERR_REMOVE_CONE_VARIABLE (1310)
A variable cannot be removed because it will make a cone invalid.

MSK_RES_ERR_REPAIR_INVALID_PROBLEM (1710)
The feasibility repair does not support the specified problem type.

MSK_RES_ERR_REPAIR_OPTIMIZATION_FAILED (1711)
Computation the optimal relaxation failed. The cause may have been numerical problems.

MSK_RES_ERR_SEN_BOUND_INVALID_LO (3054)
Analysis of lower bound requested for an index, where no lower bound exists.

MSK_RES_ERR_SEN_BOUND_INVALID_UP (3053)
Analysis of upper bound requested for an index, where no upper bound exists.

MSK_RES_ERR_SEN_FORMAT (3050)
Syntax error in sensitivity analysis file.

MSK_RES_ERR_SEN_INDEX_INVALID (3055)
Invalid range given in the sensitivity file.

MSK_RES_ERR_SEN_INDEX_RANGE (3052)
Index out of range in the sensitivity analysis file.

MSK_RES_ERR_SEN_INVALID_REGEXP (3056)
Syntax error in regexp or regexp longer than 1024.

MSK_RES_ERR_SEN_NUMERICAL (3058)
Numerical difficulties encountered performing the sensitivity analysis.

MSK_RES_ERR_SEN_SOLUTION_STATUS (3057)
No optimal solution found to the original problem given for sensitivity analysis.

MSK_RES_ERR_SEN_UNDEF_NAME (3051)
An undefined name was encountered in the sensitivity analysis file.

MSK_RES_ERR_SEN_UNHANDLED_PROBLEM_TYPE (3080)
Sensitivity analysis cannot be performed for the specified problem. Sensitivity analysis is only possible for linear problems.

MSK_RES_ERR_SERVER_CONNECT (8000)
Failed to connect to remote solver server. The server string or the port string were invalid, or the server did not accept connection.

MSK_RES_ERR_SERVER_PROTOCOL (8001)
Unexpected message or data from solver server.

MSK_RES_ERR_SERVER_STATUS (8002)
Server returned non-ok HTTP status code

MSK_RES_ERR_SERVER_TOKEN (8003)
The job ID specified is incorrect or invalid

MSK_RES_ERR_SIZE_LICENSE (1005)
The problem is bigger than the license.

MSK_RES_ERR_SIZE_LICENSE_CON (1010)
The problem has too many constraints to be solved with the available license.

MSK_RES_ERR_SIZE_LICENSE_INTVAR (1012)
The problem contains too many integer variables to be solved with the available license.

- MSK_RES_ERR_SIZE_LICENSE_NUMCORES (3900)**
The computer contains more cpu cores than the license allows for.
- MSK_RES_ERR_SIZE_LICENSE_VAR (1011)**
The problem has too many variables to be solved with the available license.
- MSK_RES_ERR_SOL_FILE_INVALID_NUMBER (1350)**
An invalid number is specified in a solution file.
- MSK_RES_ERR_SOLITEM (1237)**
The solution item number `solitem` is invalid. Please note that `MSK_SOL_ITEM_SNX` is invalid for the basic solution.
- MSK_RES_ERR_SOLVER_PROBTYPE (1259)**
Problem type does not match the chosen optimizer.
- MSK_RES_ERR_SPACE (1051)**
Out of space.
- MSK_RES_ERR_SPACE_LEAKING (1080)**
MOSEK is leaking memory. This can be due to either an incorrect use of **MOSEK** or a bug.
- MSK_RES_ERR_SPACE_NO_INFO (1081)**
No available information about the space usage.
- MSK_RES_ERR_SYM_MAT_DUPLICATE (3944)**
A value in a symmetric matrix has been specified more than once.
- MSK_RES_ERR_SYM_MAT_HUGE (1482)**
A symmetric matrix contains a huge value in absolute size. The parameter `MSK_DPAR_DATA_SYM_MAT_TOL_HUGE` controls when an $e_{i,j}$ is considered huge.
- MSK_RES_ERR_SYM_MAT_INVALID (1480)**
A symmetric matrix contains an invalid floating point value, i.e. a NaN or an infinite value.
- MSK_RES_ERR_SYM_MAT_INVALID_COL_INDEX (3941)**
A column index specified for sparse symmetric matrix is invalid.
- MSK_RES_ERR_SYM_MAT_INVALID_ROW_INDEX (3940)**
A row index specified for sparse symmetric matrix is invalid.
- MSK_RES_ERR_SYM_MAT_INVALID_VALUE (3943)**
The numerical value specified in a sparse symmetric matrix is not a valid floating value.
- MSK_RES_ERR_SYM_MAT_NOT_LOWER_TRINGULAR (3942)**
Only the lower triangular part of sparse symmetric matrix should be specified.
- MSK_RES_ERR_TASK_INCOMPATIBLE (2560)**
The Task file is incompatible with this platform. This results from reading a file on a 32 bit platform generated on a 64 bit platform.
- MSK_RES_ERR_TASK_INVALID (2561)**
The Task file is invalid.
- MSK_RES_ERR_TASK_WRITE (2562)**
Failed to write the task file.
- MSK_RES_ERR_THREAD_COND_INIT (1049)**
Could not initialize a condition.
- MSK_RES_ERR_THREAD_CREATE (1048)**
Could not create a thread. This error may occur if a large number of environments are created and not deleted again. In any case it is a good practice to minimize the number of environments created.
- MSK_RES_ERR_THREAD_MUTEX_INIT (1045)**
Could not initialize a mutex.

MSK_RES_ERR_THREAD_MUTEX_LOCK (1046)

Could not lock a mutex.

MSK_RES_ERR_THREAD_MUTEX_UNLOCK (1047)

Could not unlock a mutex.

MSK_RES_ERR_TOCONIC_CONSTR_NOT_CONIC (7153)

The constraint is not conic representable.

MSK_RES_ERR_TOCONIC_CONSTR_Q_NOT_PSD (7150)

The matrix defining the quadratic part of constraint is not positive semidefinite.

MSK_RES_ERR_TOCONIC_CONSTRAINT_FX (7151)

The quadratic constraint is an equality, thus not convex.

MSK_RES_ERR_TOCONIC_CONSTRAINT_RA (7152)

The quadratic constraint has finite lower and upper bound, and therefore it is not convex.

MSK_RES_ERR_TOCONIC_OBJECTIVE_NOT_PSD (7155)

The matrix defining the quadratic part of the objective function is not positive semidefinite.

MSK_RES_ERR_TOO_SMALL_MAX_NUM_NZ (1245)

The maximum number of non-zeros specified is too small.

MSK_RES_ERR_TOO_SMALL_MAXNUMANZ (1252)

The maximum number of non-zeros specified for A is smaller than the number of non-zeros in the current A .

MSK_RES_ERR_UNB_STEP_SIZE (3100)

A step size in an optimizer was unexpectedly unbounded. For instance, if the step-size becomes unbounded in phase 1 of the simplex algorithm then an error occurs. Normally this will happen only if the problem is badly formulated. Please contact **MOSEK** support if this error occurs.

MSK_RES_ERR_UNDEF_SOLUTION (1265)

MOSEK has the following solution types:

- an interior-point solution,
- an basic solution,
- and an integer solution.

Each optimizer may set one or more of these solutions; e.g by default a successful optimization with the interior-point optimizer defines the interior-point solution, and, for linear problems, also the basic solution. This error occurs when asking for a solution or for information about a solution that is not defined.

MSK_RES_ERR_UNDEFINED_OBJECTIVE_SENSE (1446)

The objective sense has not been specified before the optimization.

MSK_RES_ERR_UNHANDLED_SOLUTION_STATUS (6010)

Unhandled solution status.

MSK_RES_ERR_UNKNOWN (1050)

Unknown error.

MSK_RES_ERR_UPPER_BOUND_IS_A_NAN (1391)

The upper bound specified is not a number (nan).

MSK_RES_ERR_UPPER_TRIANGLE (6020)

An element in the upper triangle of a lower triangular matrix is specified.

MSK_RES_ERR_USER_FUNC_RET (1430)

An user function reported an error.

MSK_RES_ERR_USER_FUNC_RET_DATA (1431)

An user function returned invalid data.

MSK_RES_ERR_USER_NLO_EVAL (1433)

The user-defined nonlinear function reported an error.

MSK_RES_ERR_USER_NLO_EVAL_HESSUBI (1440)

The user-defined nonlinear function reported an invalid subscript in the Hessian.

MSK_RES_ERR_USER_NLO_EVAL_HESSUBJ (1441)

The user-defined nonlinear function reported an invalid subscript in the Hessian.

MSK_RES_ERR_USER_NLO_FUNC (1432)

The user-defined nonlinear function reported an error.

MSK_RES_ERR_WHICHITEM_NOT_ALLOWED (1238)

whichitem is unacceptable.

MSK_RES_ERR_WHICHSOL (1236)

The solution defined by *whchsol* does not exists.

MSK_RES_ERR_WRITE_LP_FORMAT (1158)

Problem cannot be written as an LP file.

MSK_RES_ERR_WRITE_LP_NON_UNIQUE_NAME (1161)

An auto-generated name is not unique.

MSK_RES_ERR_WRITE_MPS_INVALID_NAME (1153)

An invalid name is created while writing an MPS file. Usually this will make the MPS file unreadable.

MSK_RES_ERR_WRITE_OPF_INVALID_VAR_NAME (1156)

Empty variable names cannot be written to OPF files.

MSK_RES_ERR_WRITING_FILE (1166)

An error occurred while writing file

MSK_RES_ERR_XML_INVALID_PROBLEM_TYPE (3600)

The problem type is not supported by the XML format.

MSK_RES_ERR_Y_IS_UNDEFINED (1449)

The solution item *y* is undefined.

11.2.3 Warning Codes

MSK_RES_WRN_ANA_ALMOST_INT_BOUNDS (904)

This warning is issued by the problem analyzer if a constraint is bound nearly integral.

MSK_RES_WRN_ANA_C_ZERO (901)

This warning is issued by the problem analyzer, if the coefficients in the linear part of the objective are all zero.

MSK_RES_WRN_ANA_CLOSE_BOUNDS (903)

This warning is issued by problem analyzer, if ranged constraints or variables with very close upper and lower bounds are detected. One should consider treating such constraints as equalities and such variables as constants.

MSK_RES_WRN_ANA_EMPTY_COLS (902)

This warning is issued by the problem analyzer, if columns, in which all coefficients are zero, are found.

MSK_RES_WRN_ANA_LARGE_BOUNDS (900)

This warning is issued by the problem analyzer, if one or more constraint or variable bounds are very large. One should consider omitting these bounds entirely by setting them to $+\infty$ or $-\infty$.

MSK_RES_WRN_CONSTRUCT_INVALID_SOL_ITG (807)

The initial value for one or more of the integer variables is not feasible.

MSK_RES_WRN_CONSTRUCT_NO_SOL_ITG (810)

The construct solution requires an integer solution.

MSK_RES_WRN_CONSTRUCT_SOLUTION_INFEAS (805)

After fixing the integer variables at the suggested values then the problem is infeasible.

MSK_RES_WRN_DROPPED_NZ_QOBJ (201)

One or more non-zero elements were dropped in the Q matrix in the objective.

MSK_RES_WRN_DUPLICATE_BARVARIABLE_NAMES (852)

Two barvariable names are identical.

MSK_RES_WRN_DUPLICATE_CONE_NAMES (853)

Two cone names are identical.

MSK_RES_WRN_DUPLICATE_CONSTRAINT_NAMES (850)

Two constraint names are identical.

MSK_RES_WRN_DUPLICATE_VARIABLE_NAMES (851)

Two variable names are identical.

MSK_RES_WRN_ELIMINATOR_SPACE (801)

The eliminator is skipped at least once due to lack of space.

MSK_RES_WRN_EMPTY_NAME (502)

A variable or constraint name is empty. The output file may be invalid.

MSK_RES_WRN_IGNORE_INTEGER (250)

Ignored integer constraints.

MSK_RES_WRN_INCOMPLETE_LINEAR_DEPENDENCY_CHECK (800)

The linear dependency check(s) is incomplete. Normally this is not an important warning unless the optimization problem has been formulated with linear dependencies. Linear dependencies may prevent **MOSEK** from solving the problem.

MSK_RES_WRN_LARGE_AIJ (62)

A numerically large value is specified for an $a_{i,j}$ element in A . The parameter *MSK_DPAR_DATA_TOL_AIJ_LARGE* controls when an $a_{i,j}$ is considered large.

MSK_RES_WRN_LARGE_BOUND (51)

A numerically large bound value is specified.

MSK_RES_WRN_LARGE_CJ (57)

A numerically large value is specified for one c_j .

MSK_RES_WRN_LARGE_CON_FX (54)

An equality constraint is fixed to a numerically large value. This can cause numerical problems.

MSK_RES_WRN_LARGE_LO_BOUND (52)

A numerically large lower bound value is specified.

MSK_RES_WRN_LARGE_UP_BOUND (53)

A numerically large upper bound value is specified.

MSK_RES_WRN_LICENSE_EXPIRE (500)

The license expires.

MSK_RES_WRN_LICENSE_FEATURE_EXPIRE (505)

The license expires.

MSK_RES_WRN_LICENSE_SERVER (501)

The license server is not responding.

MSK_RES_WRN_LP_DROP_VARIABLE (85)

Ignored a variable because the variable was not previously defined. Usually this implies that a variable appears in the bound section but not in the objective or the constraints.

MSK_RES_WRN_LP_OLD_QUAD_FORMAT (80)

Missing ‘/2’ after quadratic expressions in bound or objective.

MSK_RES_WRN_MIO_INFEASIBLE_FINAL (270)

The final mixed-integer problem with all the integer variables fixed at their optimal values is infeasible.

MSK_RES_WRN_MPS_SPLIT_BOU_VECTOR (72)

A BOUNDS vector is split into several nonadjacent parts in an MPS file.

MSK_RES_WRN_MPS_SPLIT_RAN_VECTOR (71)

A RANGE vector is split into several nonadjacent parts in an MPS file.

MSK_RES_WRN_MPS_SPLIT_RHS_VECTOR (70)

An RHS vector is split into several nonadjacent parts in an MPS file.

MSK_RES_WRN_NAME_MAX_LEN (65)

A name is longer than the buffer that is supposed to hold it.

MSK_RES_WRN_NO_DUALIZER (950)

No automatic dualizer is available for the specified problem. The primal problem is solved.

MSK_RES_WRN_NO_GLOBAL_OPTIMIZER (251)

No global optimizer is available.

MSK_RES_WRN_NO_NONLINEAR_FUNCTION_WRITE (450)

The problem contains a general nonlinear function in either the objective or the constraints. Such a nonlinear function cannot be written to a disk file. Note that quadratic terms when inputted explicitly can be written to disk.

MSK_RES_WRN_NZ_IN_UPR_TRI (200)

Non-zero elements specified in the upper triangle of a matrix were ignored.

MSK_RES_WRN_OPEN_PARAM_FILE (50)

The parameter file could not be opened.

MSK_RES_WRN_PARAM_IGNORED_CMIO (516)

A parameter was ignored by the conic mixed integer optimizer.

MSK_RES_WRN_PARAM_NAME_DOU (510)

The parameter name is not recognized as a double parameter.

MSK_RES_WRN_PARAM_NAME_INT (511)

The parameter name is not recognized as an integer parameter.

MSK_RES_WRN_PARAM_NAME_STR (512)

The parameter name is not recognized as a string parameter.

MSK_RES_WRN_PARAM_STR_VALUE (515)

The string is not recognized as a symbolic value for the parameter.

MSK_RES_WRN_PRESOLVE_OUTOFSPACE (802)

The presolve is incomplete due to lack of space.

MSK_RES_WRN_QUAD_CONES_WITH_ROOT_FIXED_AT_ZERO (930)

For at least one quadratic cone the root is fixed at (nearly) zero. This may cause problems such as a very large dual solution. Therefore, it is recommended to remove such cones before optimizing the problems, or to fix all the variables in the cone to 0.

MSK_RES_WRN_RQUAD_CONES_WITH_ROOT_FIXED_AT_ZERO (931)

For at least one rotated quadratic cone at least one of the root variables are fixed at (nearly) zero. This may cause problems such as a very large dual solution. Therefore, it is recommended to remove such cones before optimizing the problems, or to fix all the variables in the cone to 0.

MSK_RES_WRN_SOL_FILE_IGNORED_CON (351)

One or more lines in the constraint section were ignored when reading a solution file.

MSK_RES_WRN_SOL_FILE_IGNORED_VAR (352)

One or more lines in the variable section were ignored when reading a solution file.

MSK_RES_WRN_SOL_FILTER (300)

Invalid solution filter is specified.

MSK_RES_WRN_SPAR_MAX_LEN (66)

A value for a string parameter is longer than the buffer that is supposed to hold it.

MSK_RES_WRN_SYM_MAT_LARGE (960)

A numerically large value is specified for an $e_{i,j}$ element in E . The parameter `MSK_DPAR_DATA_SYM_MAT_TOL_LARGE` controls when an $e_{i,j}$ is considered large.

MSK_RES_WRN_TOO_FEW_BASIS_VARS (400)

An incomplete basis has been specified. Too few basis variables are specified.

MSK_RES_WRN_TOO_MANY_BASIS_VARS (405)

A basis with too many variables has been specified.

MSK_RES_WRN_UNDEF_SOL_FILE_NAME (350)

Undefined name occurred in a solution.

MSK_RES_WRN_USING_GENERIC_NAMES (503)

Generic names are used because a name is not valid. For instance when writing an LP file the names must not contain blanks or start with a digit.

MSK_RES_WRN_WRITE_CHANGED_NAMES (803)

Some names were changed because they were invalid for the output file format.

MSK_RES_WRN_WRITE_DISCARDED_CFIX (804)

The fixed objective term could not be converted to a variable and was discarded in the output file.

MSK_RES_WRN_ZERO_AIJ (63)

One or more zero elements are specified in A .

MSK_RES_WRN_ZEROS_IN_SPARSE_COL (710)

One or more (near) zero elements are specified in a sparse column of a matrix. It is redundant to specify zero elements. Hence, it may indicate an error.

MSK_RES_WRN_ZEROS_IN_SPARSE_ROW (705)

One or more (near) zero elements are specified in a sparse row of a matrix. Since, it is redundant to specify zero elements then it may indicate an error.

11.3 Enumerations

MSKlanguagee

Language selection constants

MSK_LANG_ENG

English language selection

MSK_LANG_DAN

Danish language selection

MSKaccmodee

Constraint or variable access modes

MSK_ACC_VAR

Access data by columns (variable oriented)

MSK_ACC_CON

Access data by rows (constraint oriented)

MSKbasindtypee

Basis identification

MSK_BI_NEVER

Never do basis identification.

MSK_BI_ALWAYS

Basis identification is always performed even if the interior-point optimizer terminates abnormally.

MSK_BI_NO_ERROR

Basis identification is performed if the interior-point optimizer terminates without an error.

MSK_BI_IF_FEASIBLE

Basis identification is not performed if the interior-point optimizer terminates with a problem status saying that the problem is primal or dual infeasible.

MSK_BI_RESERVED

Not currently in use.

MSKboundkeye

Bound keys

MSK_BK_LO

The constraint or variable has a finite lower bound and an infinite upper bound.

MSK_BK_UP

The constraint or variable has an infinite lower bound and a finite upper bound.

MSK_BK_FX

The constraint or variable is fixed.

MSK_BK_FR

The constraint or variable is free.

MSK_BK_RA

The constraint or variable is ranged.

MSKmarke

Mark

MSK_MARK_LO

The lower bound is selected for sensitivity analysis.

MSK_MARK_UP

The upper bound is selected for sensitivity analysis.

MSKsimdegene

Degeneracy strategies

MSK_SIM_DEGEN_NONE

The simplex optimizer should use no degeneration strategy.

MSK_SIM_DEGEN_FREE

The simplex optimizer chooses the degeneration strategy.

MSK_SIM_DEGEN_AGGRESSIVE

The simplex optimizer should use an aggressive degeneration strategy.

MSK_SIM_DEGEN_MODERATE

The simplex optimizer should use a moderate degeneration strategy.

MSK_SIM_DEGEN_MINIMUM

The simplex optimizer should use a minimum degeneration strategy.

MSKtransposee

Transposed matrix.

MSK_TRANSPOSE_NO

No transpose is applied.

MSK_TRANSPOSE_YES

A transpose is applied.

MSKuploe

Triangular part of a symmetric matrix.

MSK_UPLO_LO

Lower part.

MSK_UPLO_UP

Upper part

MSKsimreforme

Problem reformulation.

MSK_SIM_REFORMULATION_ON

Allow the simplex optimizer to reformulate the problem.

MSK_SIM_REFORMULATION_OFF

Disallow the simplex optimizer to reformulate the problem.

MSK_SIM_REFORMULATION_FREE

The simplex optimizer can choose freely.

MSK_SIM_REFORMULATION_AGGRESSIVE

The simplex optimizer should use an aggressive reformulation strategy.

MSKsimdupvece

Exploit duplicate columns.

MSK_SIM_EXPLOIT_DUPVEC_ON

Allow the simplex optimizer to exploit duplicated columns.

MSK_SIM_EXPLOIT_DUPVEC_OFF

Disallow the simplex optimizer to exploit duplicated columns.

MSK_SIM_EXPLOIT_DUPVEC_FREE

The simplex optimizer can choose freely.

MSKsimhotstarte

Hot-start type employed by the simplex optimizer

MSK_SIM_HOTSTART_NONE

The simplex optimizer performs a coldstart.

MSK_SIM_HOTSTART_FREE

The simplex optimizer chooses the hot-start type.

MSK_SIM_HOTSTART_STATUS_KEYS

Only the status keys of the constraints and variables are used to choose the type of hot-start.

MSKintpntshotstarte

Hot-start type employed by the interior-point optimizers.

MSK_INTPNT_HOTSTART_NONE

The interior-point optimizer performs a coldstart.

MSK_INTPNT_HOTSTART_PRIMAL

The interior-point optimizer exploits the primal solution only.

MSK_INTPNT_HOTSTART_DUAL

The interior-point optimizer exploits the dual solution only.

MSK_INTPNT_HOTSTART_PRIMAL_DUAL

The interior-point optimizer exploits both the primal and dual solution.

MSKcallbackcodee

Progress call-back codes

MSK_CALLBACK_BEGIN_ROOT_CUTGEN

The call-back function is called when root cut generation is started.

MSK_CALLBACK_IM_ROOT_CUTGEN

The call-back is called from within root cut generation at an intermediate stage.

MSK_CALLBACK_END_ROOT_CUTGEN

The call-back function is called when root cut generation is terminated.

MSK_CALLBACK_BEGIN_OPTIMIZER

The call-back function is called when the optimizer is started.

MSK_CALLBACK_END_OPTIMIZER

The call-back function is called when the optimizer is terminated.

MSK_CALLBACK_BEGIN_PRESOLVE

The call-back function is called when the presolve is started.

MSK_CALLBACK_UPDATE_PRESOLVE

The call-back function is called from within the presolve procedure.

MSK_CALLBACK_IM_PRESOLVE

The call-back function is called from within the presolve procedure at an intermediate stage.

MSK_CALLBACK_END_PRESOLVE

The call-back function is called when the presolve is completed.

MSK_CALLBACK_BEGIN_INTPNT

The call-back function is called when the interior-point optimizer is started.

MSK_CALLBACK_INTPNT

The call-back function is called from within the interior-point optimizer after the information database has been updated.

MSK_CALLBACK_IM_INTPNT

The call-back function is called at an intermediate stage within the interior-point optimizer where the information database has not been updated.

MSK_CALLBACK_END_INTPNT

The call-back function is called when the interior-point optimizer is terminated.

MSK_CALLBACK_BEGIN_CONIC

The call-back function is called when the conic optimizer is started.

MSK_CALLBACK_CONIC

The call-back function is called from within the conic optimizer after the information database has been updated.

MSK_CALLBACK_IM_CONIC

The call-back function is called at an intermediate stage within the conic optimizer where the information database has not been updated.

MSK_CALLBACK_END_CONIC

The call-back function is called when the conic optimizer is terminated.

MSK_CALLBACK_PRIMAL_SIMPLEX

The call-back function is called from within the primal simplex optimizer.

MSK_CALLBACK_DUAL_SIMPLEX

The call-back function is called from within the dual simplex optimizer.

MSK_CALLBACK_BEGIN_BI

The basis identification procedure has been started.

MSK_CALLBACK_IM_BI

The call-back function is called from within the basis identification procedure at an intermediate point.

MSK_CALLBACK_END_BI

The call-back function is called when the basis identification procedure is terminated.

MSK_CALLBACK_BEGIN_PRIMAL_BI

The call-back function is called from within the basis identification procedure when the primal phase is started.

MSK_CALLBACK_IM_PRIMAL_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the primal phase.

MSK_CALLBACK_UPDATE_PRIMAL_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the primal phase.

MSK_CALLBACK_END_PRIMAL_BI

The call-back function is called from within the basis identification procedure when the primal phase is terminated.

MSK_CALLBACK_BEGIN_DUAL_BI

The call-back function is called from within the basis identification procedure when the dual phase is started.

MSK_CALLBACK_IM_DUAL_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the dual phase.

MSK_CALLBACK_UPDATE_DUAL_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the dual phase.

MSK_CALLBACK_END_DUAL_BI

The call-back function is called from within the basis identification procedure when the dual phase is terminated.

MSK_CALLBACK_BEGIN_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the simplex clean-up phase is started.

MSK_CALLBACK_IM_SIMPLEX_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the simplex clean-up phase. The frequency of the call-backs is controlled by the *MSK_IPAR_LOG_SIM_FREQ* parameter.

MSK_CALLBACK_BEGIN_PRIMAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the primal simplex clean-up phase is started.

MSK_CALLBACK_UPDATE_PRIMAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the primal simplex clean-up phase. The frequency of the call-backs is controlled by the *MSK_IPAR_LOG_SIM_FREQ* parameter.

MSK_CALLBACK_END_PRIMAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the primal clean-up phase is terminated.

MSK_CALLBACK_BEGIN_PRIMAL_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the primal-dual simplex clean-up phase is started.

MSK_CALLBACK_UPDATE_PRIMAL_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the primal-dual simplex clean-up phase. The frequency of the call-backs is controlled by the *MSK_IPAR_LOG_SIM_FREQ* parameter.

MSK_CALLBACK_END_PRIMAL_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the primal-dual clean-up phase is terminated.

MSK_CALLBACK_BEGIN_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the dual simplex clean-up phase is started.

MSK_CALLBACK_UPDATE_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure at an intermediate point in the dual simplex clean-up phase. The frequency of the call-backs is controlled by the *MSK_IPAR_LOG_SIM_FREQ* parameter.

MSK_CALLBACK_END_DUAL_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the dual clean-up phase is terminated.

MSK_CALLBACK_END_SIMPLEX_BI

The call-back function is called from within the basis identification procedure when the simplex clean-up phase is terminated.

MSK_CALLBACK_BEGIN_MIO

The call-back function is called when the mixed-integer optimizer is started.

MSK_CALLBACK_IM_MIO

The call-back function is called at an intermediate point in the mixed-integer optimizer.

MSK_CALLBACK_NEW_INT_MIO

The call-back function is called after a new integer solution has been located by the mixed-integer optimizer.

MSK_CALLBACK_END_MIO

The call-back function is called when the mixed-integer optimizer is terminated.

MSK_CALLBACK_BEGIN_SIMPLEX

The call-back function is called when the simplex optimizer is started.

MSK_CALLBACK_BEGIN_DUAL_SIMPLEX

The call-back function is called when the dual simplex optimizer started.

MSK_CALLBACK_IM_DUAL_SIMPLEX

The call-back function is called at an intermediate point in the dual simplex optimizer.

MSK_CALLBACK_UPDATE_DUAL_SIMPLEX

The call-back function is called in the dual simplex optimizer.

MSK_CALLBACK_END_DUAL_SIMPLEX

The call-back function is called when the dual simplex optimizer is terminated.

MSK_CALLBACK_BEGIN_PRIMAL_SIMPLEX

The call-back function is called when the primal simplex optimizer is started.

MSK_CALLBACK_IM_PRIMAL_SIMPLEX

The call-back function is called at an intermediate point in the primal simplex optimizer.

MSK_CALLBACK_UPDATE_PRIMAL_SIMPLEX

The call-back function is called in the primal simplex optimizer.

MSK_CALLBACK_END_PRIMAL_SIMPLEX

The call-back function is called when the primal simplex optimizer is terminated.

MSK_CALLBACK_BEGIN_PRIMAL_DUAL_SIMPLEX

The call-back function is called when the primal-dual simplex optimizer is started.

MSK_CALLBACK_IM_PRIMAL_DUAL_SIMPLEX

The call-back function is called at an intermediate point in the primal-dual simplex optimizer.

MSK_CALLBACK_UPDATE_PRIMAL_DUAL_SIMPLEX

The call-back function is called in the primal-dual simplex optimizer.

MSK_CALLBACK_END_PRIMAL_DUAL_SIMPLEX

The call-back function is called when the primal-dual simplex optimizer is terminated.

MSK_CALLBACK_END_SIMPLEX

The call-back function is called when the simplex optimizer is terminated.

MSK_CALLBACK_BEGIN_INFEAS_ANA

The call-back function is called when the infeasibility analyzer is started.

MSK_CALLBACK_END_INFEAS_ANA

The call-back function is called when the infeasibility analyzer is terminated.

MSK_CALLBACK_IM_PRIMAL_SENSIVITY

The call-back function is called at an intermediate stage of the primal sensitivity analysis.

MSK_CALLBACK_IM_DUAL_SENSIVITY

The call-back function is called at an intermediate stage of the dual sensitivity analysis.

MSK_CALLBACK_IM_MIO_INTPNT

The call-back function is called at an intermediate point in the mixed-integer optimizer while running the interior-point optimizer.

MSK_CALLBACK_IM_MIO_PRIMAL_SIMPLEX

The call-back function is called at an intermediate point in the mixed-integer optimizer while running the primal simplex optimizer.

MSK_CALLBACK_IM_MIO_DUAL_SIMPLEX

The call-back function is called at an intermediate point in the mixed-integer optimizer while running the dual simplex optimizer.

MSK_CALLBACK_BEGIN_PRIMAL_SETUP_BI

The call-back function is called when the primal BI setup is started.

MSK_CALLBACK_END_PRIMAL_SETUP_BI

The call-back function is called when the primal BI setup is terminated.

MSK_CALLBACK_BEGIN_DUAL_SETUP_BI

The call-back function is called when the dual BI phase is started.

MSK_CALLBACK_END_DUAL_SETUP_BI

The call-back function is called when the dual BI phase is terminated.

MSK_CALLBACK_BEGIN_PRIMAL_SENSITIVITY

Primal sensitivity analysis is started.

MSK_CALLBACK_END_PRIMAL_SENSITIVITY

Primal sensitivity analysis is terminated.

MSK_CALLBACK_BEGIN_DUAL_SENSITIVITY

Dual sensitivity analysis is started.

MSK_CALLBACK_END_DUAL_SENSITIVITY

Dual sensitivity analysis is terminated.

MSK_CALLBACK_BEGIN_LICENSE_WAIT

Begin waiting for license.

MSK_CALLBACK_END_LICENSE_WAIT

End waiting for license.

MSK_CALLBACK_IM_LICENSE_WAIT

MOSEK is waiting for a license.

MSK_CALLBACK_BEGIN_QCQO_REFORMULATE

Begin QCQO reformulation.

MSK_CALLBACK_END_QCQO_REFORMULATE

End QCQO reformulation.

MSK_CALLBACK_IM_QO_REFORMULATE

The call-back function is called at an intermediate stage of the conic quadratic reformulation.

MSK_CALLBACK_BEGIN_TO_CONIC
Begin conic reformulation.

MSK_CALLBACK_END_TO_CONIC
End conic reformulation.

MSK_CALLBACK_BEGIN_FULL_CONVEXITY_CHECK
Begin full convexity check.

MSK_CALLBACK_END_FULL_CONVEXITY_CHECK
End full convexity check.

MSK_CALLBACK_IM_FULL_CONVEXITY_CHECK
The call-back function is called at an intermediate stage of the full convexity check.

MSK_CALLBACK_BEGIN_PRIMAL_REPAIR
Begin primal feasibility repair.

MSK_CALLBACK_END_PRIMAL_REPAIR
End primal feasibility repair.

MSK_CALLBACK_BEGIN_READ
MOSEK has started reading a problem file.

MSK_CALLBACK_IM_READ
Intermediate stage in reading.

MSK_CALLBACK_END_READ
MOSEK has finished reading a problem file.

MSK_CALLBACK_BEGIN_WRITE
MOSEK has started writing a problem file.

MSK_CALLBACK_END_WRITE
MOSEK has finished writing a problem file.

MSK_CALLBACK_READ_OPF_SECTION
A chunk of Q non-zeros has been read from a problem file.

MSK_CALLBACK_IM_LU
The call-back function is called from within the LU factorization procedure at an intermediate point.

MSK_CALLBACK_IM_ORDER
The call-back function is called from within the matrix ordering procedure at an intermediate point.

MSK_CALLBACK_IM_SIMPLEX
The call-back function is called from within the simplex optimizer at an intermediate point.

MSK_CALLBACK_READ_OPF
The call-back function is called from the OPF reader.

MSK_CALLBACK_WRITE_OPF
The call-back function is called from the OPF writer.

MSK_CALLBACK_SOLVING_REMOTE
The call-back function is called while the task is being solved on a remote server.

MSKcheckconvexitytypee
Types of convexity checks.

MSK_CHECK_CONVEXITY_NONE
No convexity check.

MSK_CHECK_CONVEXITY_SIMPLE
Perform simple and fast convexity check.

MSK_CHECK_CONVEXITY_FULL

Perform a full convexity check.

MSKcompresstypee

Compression types

MSK_COMPRESS_NONE

No compression is used.

MSK_COMPRESS_FREE

The type of compression used is chosen automatically.

MSK_COMPRESS_GZIP

The type of compression used is gzip compatible.

MSKconetypee

Cone types

MSK_CT_QUAD

The cone is a quadratic cone.

MSK_CT_RQUAD

The cone is a rotated quadratic cone.

MSKnametypee

Name types

MSK_NAME_TYPE_GEN

General names. However, no duplicate and blank names are allowed.

MSK_NAME_TYPE_MPS

MPS type names.

MSK_NAME_TYPE_LP

LP type names.

MSKsymmattypee

Cone types

MSK_SYMMAT_TYPE_SPARSE

Sparse symmetric matrix.

MSKdataformate

Data format types

MSK_DATA_FORMAT_EXTENSION

The file extension is used to determine the data file format.

MSK_DATA_FORMAT_MPS

The data file is MPS formatted.

MSK_DATA_FORMAT_LP

The data file is LP formatted.

MSK_DATA_FORMAT_OP

The data file is an optimization problem formatted file.

MSK_DATA_FORMAT_XML

The data file is an XML formatted file.

MSK_DATA_FORMAT_FREE_MPS

The data a free MPS formatted file.

MSK_DATA_FORMAT_TASK

Generic task dump file.

MSK_DATA_FORMAT_CB

Conic benchmark format,

MSK_DATA_FORMAT_JSON_TASK
JSON based task format.

MSKdinfiteme

Double information items

MSK_DINF_BI_TIME
Time spent within the basis identification procedure since its invocation.

MSK_DINF_BI_PRIMAL_TIME
Time spent within the primal phase of the basis identification procedure since its invocation.

MSK_DINF_BI_DUAL_TIME
Time spent within the dual phase basis identification procedure since its invocation.

MSK_DINF_BI_CLEAN_TIME
Time spent within the clean-up phase of the basis identification procedure since its invocation.

MSK_DINF_BI_CLEAN_PRIMAL_TIME
Time spent within the primal clean-up optimizer of the basis identification procedure since its invocation.

MSK_DINF_BI_CLEAN_PRIMAL_DUAL_TIME
Time spent within the primal-dual clean-up optimizer of the basis identification procedure since its invocation.

MSK_DINF_BI_CLEAN_DUAL_TIME
Time spent within the dual clean-up optimizer of the basis identification procedure since its invocation.

MSK_DINF_INTPNT_TIME
Time spent within the interior-point optimizer since its invocation.

MSK_DINF_INTPNT_ORDER_TIME
Order time (in seconds).

MSK_DINF_INTPNT_PRIMAL_OBJ
Primal objective value reported by the interior-point optimizer.

MSK_DINF_INTPNT_DUAL_OBJ
Dual objective value reported by the interior-point optimizer.

MSK_DINF_INTPNT_PRIMAL_FEAS
Primal feasibility measure reported by the interior-point optimizers. (For the interior-point optimizer this measure does not directly related to the original problem because a homogeneous model is employed).

MSK_DINF_INTPNT_DUAL_FEAS
Dual feasibility measure reported by the interior-point optimizer. (For the interior-point optimizer this measure does not directly related to the original problem because a homogeneous model is employed.)

MSK_DINF_INTPNT_OPT_STATUS
This measure should converge to +1 if the problem has a primal-dual optimal solution, and converge to -1 if problem is (strictly) primal or dual infeasible. If the measure converges to another constant, or fails to settle, the problem is usually ill-posed.

MSK_DINF_SIM_TIME
Time spent in the simplex optimizer since invoking it.

MSK_DINF_SIM_PRIMAL_TIME
Time spent in the primal simplex optimizer since invoking it.

MSK_DINF_SIM_DUAL_TIME
Time spent in the dual simplex optimizer since invoking it.

MSK_DINF_SIM_PRIMAL_DUAL_TIME
Time spent in the primal-dual simplex optimizer since invoking it.

MSK_DINF_SIM_OBJ

Objective value reported by the simplex optimizer.

MSK_DINF_SIM_FEAS

Feasibility measure reported by the simplex optimizer.

MSK_DINF_MIO_TIME

Time spent in the mixed-integer optimizer.

MSK_DINF_MIO_ROOT_PRESOLVE_TIME

Time spent in while presolving the root relaxation.

MSK_DINF_MIO_ROOT_OPTIMIZER_TIME

Time spent in the optimizer while solving the root relaxation.

MSK_DINF_MIO_OPTIMIZER_TIME

Total time spent in the optimizer.

MSK_DINF_MIO_HEURISTIC_TIME

Total time spent in the optimizer.

MSK_DINF_TO_CONIC_TIME

Time spent in the last to conic reformulation.

MSK_DINF_MIO_CONSTRUCT_SOLUTION_OBJ

If **MOSEK** has successfully constructed an integer feasible solution, then this item contains the optimal objective value corresponding to the feasible solution.

MSK_DINF_MIO_OBJ_INT

The primal objective value corresponding to the best integer feasible solution. Please note that at least one integer feasible solution must have located i.e. check | [MSK_DINF_MIO_NUM_INT_SOLUTIONS](#) |.

MSK_DINF_MIO_OBJ_BOUND

The best known bound on the objective function. This value is undefined until at least one relaxation has been solved: To see if this is the case check that | [MSK_DINF_MIO_NUM_RELAX](#) | is strictly positive.

MSK_DINF_MIO_OBJ_REL_GAP

Given that the mixed-integer optimizer has computed a feasible solution and a bound on the optimal objective value, then this item contains the relative gap defined by

$$\frac{|(\text{objective value of feasible solution}) - (\text{objective bound})|}{\max(\delta, |(\text{objective value of feasible solution})|)}.$$

where δ is given by the parameter [MSK_DPAR_MIO_REL_GAP_CONST](#). Otherwise it has the value -1.0 .

MSK_DINF_MIO_OBJ_ABS_GAP

Given the mixed-integer optimizer has computed a feasible solution and a bound on the optimal objective value, then this item contains the absolute gap defined by

$$|(\text{objective value of feasible solution}) - (\text{objective bound})|.$$

Otherwise it has the value -1.0 .

MSK_DINF_MIO_USER_OBJ_CUT

If the objective cut is used, then this information item has the value of the cut.

MSK_DINF_MIO_CMIR_SEPARATION_TIME

Seperation time for CMIR cuts.

MSK_DINF_MIO_CLIQUÉ_SEPARATION_TIME

Seperation time for clique cuts.

MSK_DINF_MIO_KNAPSACK_COVER_SEPARATION_TIME

Seperation time for knapsack cover.

MSK_DINF_MIO_GMI_SEPARATION_TIME
 Separation time for GMI cuts.

MSK_DINF_MIO_IMPLIED_BOUND_TIME
 Separation time for implied bound cuts.

MSK_DINF_MIO_ROOT_CUTGEN_TIME
 Total time for cut generation.

MSK_DINF_MIO_PROBING_TIME
 Total time for probing.

MSK_DINF_OPTIMIZER_TIME
 Total time spent in the optimizer since it was invoked.

MSK_DINF_PRESOLVE_TIME
 Total time (in seconds) spent in the presolve since it was invoked.

MSK_DINF_MIO_DUAL_BOUND_AFTER_PRESOLVE
 Value of the dual bound after presolve but before cut generation.

MSK_DINF_PRESOLVE_ELI_TIME
 Total time spent in the eliminator since the presolve was invoked.

MSK_DINF_PRESOLVE_LINDEP_TIME
 Total time spent in the linear dependency checker since the presolve was invoked.

MSK_DINF_RD_TIME
 Time spent reading the data file.

MSK_DINF_SOL_ITR_PRIMAL_OBJ
 Primal objective value of the interior-point solution.

MSK_DINF_SOL_ITR_PVIOLCON
 Maximal primal bound violation for x^c in the interior-point solution.

MSK_DINF_SOL_ITR_PVIOLVAR
 Maximal primal bound violation for x^x in the interior-point solution.

MSK_DINF_SOL_ITR_PVIOLBARVAR
 Maximal primal bound violation for \overline{X} in the interior-point solution.

MSK_DINF_SOL_ITR_PVIOLCONES
 Maximal primal violation for primal conic constraints in the interior-point solution.

MSK_DINF_SOL_ITR_DUAL_OBJ
 Dual objective value of the interior-point solution.

MSK_DINF_SOL_ITR_DVIOLCON
 Maximal dual bound violation for x^c in the interior-point solution.

MSK_DINF_SOL_ITR_DVIOLVAR
 Maximal dual bound violation for x^x in the interior-point solution.

MSK_DINF_SOL_ITR_DVIOLBARVAR
 Maximal dual bound violation for \overline{X} in the interior-point solution.

MSK_DINF_SOL_ITR_DVIOLCONES
 Maximal dual violation for dual conic constraints in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_XC
 Infinity norm of x^c in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_XX
 Infinity norm of x^x in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_BARX
 Infinity norm of \overline{X} in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_Y
Infinity norm of y in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_SLC
Infinity norm of s_l^c in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_SUC
Infinity norm of s_u^c in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_SLX
Infinity norm of s_l^x in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_SUX
Infinity norm of s_u^X in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_SNX
Infinity norm of s_n^x in the interior-point solution.

MSK_DINF_SOL_ITR_NRM_BARS
Infinity norm of \bar{S} in the interior-point solution.

MSK_DINF_SOL_BAS_PRIMAL_OBJ
Primal objective value of the basic solution.

MSK_DINF_SOL_BAS_PVIOLCON
Maximal primal bound violation for x^c in the basic solution.

MSK_DINF_SOL_BAS_PVIOLVAR
Maximal primal bound violation for x^x in the basic solution.

MSK_DINF_SOL_BAS_DUAL_OBJ
Dual objective value of the basic solution.

MSK_DINF_SOL_BAS_DVIOLCON
Maximal dual bound violation for x^c in the basic solution.

MSK_DINF_SOL_BAS_DVIOLVAR
Maximal dual bound violation for x^x in the basic solution.

MSK_DINF_SOL_BAS_NRM_XC
Infinity norm of x^c in the basic solution.

MSK_DINF_SOL_BAS_NRM_XX
Infinity norm of x^x in the basic solution.

MSK_DINF_SOL_BAS_NRM_BARX
Infinity norm of \bar{X} in the basic solution.

MSK_DINF_SOL_BAS_NRM_Y
Infinity norm of y in the basic solution.

MSK_DINF_SOL_BAS_NRM_SLC
Infinity norm of s_l^c in the basic solution.

MSK_DINF_SOL_BAS_NRM_SUC
Infinity norm of s_u^c in the basic solution.

MSK_DINF_SOL_BAS_NRM_SLX
Infinity norm of s_l^x in the basic solution.

MSK_DINF_SOL_BAS_NRM_SUX
Infinity norm of s_u^X in the basic solution.

MSK_DINF_SOL_ITG_PRIMAL_OBJ
Primal objective value of the integer solution.

MSK_DINF_SOL_ITG_PVIOLCON
Maximal primal bound violation for x^c in the integer solution.

- MSK_DINF_SOL_ITG_PVIOLVAR**
Maximal primal bound violation for x^x in the integer solution.
- MSK_DINF_SOL_ITG_PVIOLBARVAR**
Maximal primal bound violation for \bar{X} in the integer solution.
- MSK_DINF_SOL_ITG_PVIOLCONES**
Maximal primal violation for primal conic constraints in the integer solution.
- MSK_DINF_SOL_ITG_PVIOLITG**
Maximal violation for the integer constraints in the integer solution.
- MSK_DINF_SOL_ITG_NRM_XC**
Infinity norm of x^c in the integer solution.
- MSK_DINF_SOL_ITG_NRM_XX**
Infinity norm of x^x in the integer solution.
- MSK_DINF_SOL_ITG_NRM_BARX**
Infinity norm of \bar{X} in the integer solution.
- MSK_DINF_INTPNT_FACTOR_NUM_FLOPS**
An estimate of the number of flops used in the factorization.
- MSK_DINF_QCQO_REFORMULATE_TIME**
Time spent with conic quadratic reformulation.
- MSK_DINF_QCQO_REFORMULATE_MAX_PERTURBATION**
Maximum absolute diagonal perturbation occurring during the QCQO reformulation.
- MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_DIAG_SCALING**
Worst Cholesky diagonal scaling.
- MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_COLUMN_SCALING**
Worst Cholesky column scaling.
- MSK_DINF_PRIMAL_REPAIR_PENALTY_OBJ**
The optimal objective value of the penalty function.
- MSKfeaturee**
License feature
- MSK_FEATURE_PTS**
Base system.
- MSK_FEATURE_PTON**
Nonlinear extension.
- MSKliinfiteme**
Long integer information items.
- MSK_LIINF_MIO_PRE SOLVED_ANZ**
Number of non-zero entries in the constraint matrix of presolved problem.
- MSK_LIINF_MIO_SIMPLEX_ITER**
Number of simplex iterations performed by the mixed-integer optimizer.
- MSK_LIINF_MIO_INTPNT_ITER**
Number of interior-point iterations performed by the mixed-integer optimizer.
- MSK_LIINF_BI_PRIMAL_ITER**
Number of primal pivots performed in the basis identification.
- MSK_LIINF_BI_DUAL_ITER**
Number of dual pivots performed in the basis identification.
- MSK_LIINF_BI_CLEAN_PRIMAL_ITER**
Number of primal clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_ITER

Number of primal-dual clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_DUAL_ITER

Number of dual clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_PRIMAL_DEG_ITER

Number of primal degenerate clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_SUB_ITER

Number of primal-dual subproblem clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_DEG_ITER

Number of primal-dual degenerate clean iterations performed in the basis identification.

MSK_LIINF_BI_CLEAN_DUAL_DEG_ITER

Number of dual degenerate clean iterations performed in the basis identification.

MSK_LIINF_INTPNT_FACTOR_NUM_NZ

Number of non-zeros in factorization.

MSK_LIINF_RD_NUMANZ

Number of non-zeros in A that is read.

MSK_LIINF_RD_NUMQNZ

Number of Q non-zeros.

MSK_LIINF_MIO_SIM_MAXITER_SETBACKS

Number of times the the simplex optimizer has hit the maximum iteration limit when re-optimizing.

MSKiinfiteme

Integer information items.

MSK_IINF_ANA_PRO_NUM_CON

Number of constraints in the problem.

MSK_IINF_ANA_PRO_NUM_CON_LO

Number of constraints with a lower bound and an infinite upper bound.

MSK_IINF_ANA_PRO_NUM_CON_UP

Number of constraints with an upper bound and an infinite lower bound.

MSK_IINF_ANA_PRO_NUM_CON_RA

Number of constraints with finite lower and upper bounds.

MSK_IINF_ANA_PRO_NUM_CON_EQ

Number of equality constraints.

MSK_IINF_ANA_PRO_NUM_CON_FR

Number of unbounded constraints.

MSK_IINF_ANA_PRO_NUM_VAR

Number of variables in the problem.

MSK_IINF_ANA_PRO_NUM_VAR_LO

Number of variables with a lower bound and an infinite upper bound.

MSK_IINF_ANA_PRO_NUM_VAR_UP

Number of variables with an upper bound and an infinite lower bound. This value is set by

MSK_IINF_ANA_PRO_NUM_VAR_RA

Number of variables with finite lower and upper bounds.

MSK_IINF_ANA_PRO_NUM_VAR_EQ

Number of fixed variables.

MSK_IINF_ANA_PRO_NUM_VAR_FR

Number of free variables.

MSK_IINF_ANA_PRO_NUM_VAR_CONT	Number of continuous variables.
MSK_IINF_ANA_PRO_NUM_VAR_BIN	Number of binary (0-1) variables.
MSK_IINF_ANA_PRO_NUM_VAR_INT	Number of general integer variables.
MSK_IINF_OPTIMIZE_RESPONSE	The response code returned by optimize.
MSK_IINF_INTPNT_ITER	Number of interior-point iterations since invoking the interior-point optimizer.
MSK_IINF_INTPNT_FACTOR_DIM_DENSE	Dimension of the dense sub system in factorization.
MSK_IINF_INTPNT_SOLVE_DUAL	Non-zero if the interior-point optimizer is solving the dual problem.
MSK_IINF_MIO_NODE_DEPTH	Depth of the last node solved.
MSK_IINF_MIO_NUMCON	Number of constraints in the problem solved by the mixed-integer optimizer.
MSK_IINF_MIO_NUMVAR	Number of variables in the problem solved by the mixed-integer optimizer.
MSK_IINF_MIO_NUMINT	Number of integer variables in the problem solved by the mixed-integer optimizer.
MSK_IINF_MIO_PRESOLVED_NUMCONT	Number of continuous variables in the problem solved by the mixed-integer optimizer.
MSK_IINF_MIO_PRESOLVED_NUMBIN	Number of binary variables in the problem solved by the mixed-integer optimizer.
MSK_IINF_MIO_PRESOLVED_NUMCON	Number of constraints in the presolved problem.
MSK_IINF_MIO_PRESOLVED_NUMVAR	Number of variables in the presolved problem.
MSK_IINF_MIO_PRESOLVED_NUMINT	Number of integer variables in the presolved problem.
MSK_IINF_MIO_CLIQUETABLE_SIZE	Size of the clique table.
MSK_IINF_MIO_CONSTRUCT_SOLUTION	If this item has the value 0, then MOSEK did not try to construct an initial integer feasible solution. If the item has a positive value, then MOSEK successfully constructed an initial integer feasible solution.
MSK_IINF_MIO_CONSTRUCT_NUM_ROUNDINGS	Number of values in the integer solution that is rounded to an integer value.
MSK_IINF_MIO_NUM_INT_SOLUTIONS	Number of integer feasible solutions that has been found.
MSK_IINF_MIO_OBJ_BOUND_DEFINED	Non-zero if a valid objective bound has been found, otherwise zero.
MSK_IINF_MIO_NUM_ACTIVE_NODES	Number of active branch bound nodes.

MSK_IINF_MIO_NUM_RELAX
Number of relaxations solved during the optimization.

MSK_IINF_MIO_NUM_BRANCH
Number of branches performed during the optimization.

MSK_IINF_MIO_TOTAL_NUM_CUTS
Total number of cuts generated by the mixed-integer optimizer.

MSK_IINF_MIO_NUM_CMIR_CUTS
Number of Complemented Mixed Integer Rounding (CMIR) cuts.

MSK_IINF_MIO_NUM_CLIQUE_CUTS
Number of clique cuts.

MSK_IINF_MIO_NUM_IMPLIED_BOUND_CUTS
Number of implied bound cuts.

MSK_IINF_MIO_NUM_KNAPSACK_COVER_CUTS
Number of clique cuts.

MSK_IINF_MIO_NUM_GOMORY_CUTS
Number of Gomory cuts.

MSK_IINF_MIO_NUM_REPEATED_PRESOLVE
Number of times presolve was repeated at root.

MSK_IINF_MIO_INITIAL_SOLUTION
Is non-zero if an initial integer solution is specified.

MSK_IINF_MIO_USER_OBJ_CUT
If it is non-zero, then the objective cut is used.

MSK_IINF_MIO_RELGAP_SATISFIED
Non-zero if relative gap is within tolerances.

MSK_IINF_MIO_ABSGAP_SATISFIED
Non-zero if absolute gap is within tolerances.

MSK_IINF_MIO_NEAR_RELGAP_SATISFIED
Non-zero if relative gap is within relaxed tolerances.

MSK_IINF_MIO_NEAR_ABSGAP_SATISFIED
Non-zero if absolute gap is within relaxed tolerances.

MSK_IINF_RD_PROTOTYPE
Problem type.

MSK_IINF_RD_NUMCON
Number of constraints read.

MSK_IINF_RD_NUMVAR
Number of variables read.

MSK_IINF_RD_NUMBARVAR
Number of variables read.

MSK_IINF_RD_NUMINTVAR
Number of integer-constrained variables read.

MSK_IINF_RD_NUMQ
Number of nonempty Q matrices read.

MSK_IINF_SIM_DUAL_DEG_ITER
The number of dual degenerate iterations.

MSK_IINF_SIM_DUAL_INF_ITER
The number of iterations taken with dual infeasibility.

MSK_IINF_SIM_DUAL_HOTSTART_LU	If 1 then a valid basis factorization of full rank was located and used by the dual simplex algorithm.
MSK_IINF_SIM_PRIMAL_ITER	Number of primal simplex iterations during the last optimization.
MSK_IINF_SIM_DUAL_ITER	Number of dual simplex iterations during the last optimization.
MSK_IINF_SIM_PRIMAL_DUAL_ITER	Number of primal dual simplex iterations during the last optimization.
MSK_IINF_INTPNT_NUM_THREADS	Number of threads that the interior-point optimizer is using.
MSK_IINF_SIM_PRIMAL_INF_ITER	The number of iterations taken with primal infeasibility.
MSK_IINF_SIM_PRIMAL_DUAL_INF_ITER	The number of master iterations with dual infeasibility taken by the primal dual simplex algorithm.
MSK_IINF_SIM_PRIMAL_DEG_ITER	The number of primal degenerate iterations.
MSK_IINF_SIM_PRIMAL_DUAL_DEG_ITER	The number of degenerate major iterations taken by the primal dual simplex algorithm.
MSK_IINF_SIM_PRIMAL_HOTSTART	If 1 then the primal simplex algorithm is solving from an advanced basis.
MSK_IINF_SIM_PRIMAL_HOTSTART_LU	If 1 then a valid basis factorization of full rank was located and used by the primal simplex algorithm.
MSK_IINF_SIM_DUAL_HOTSTART	If 1 then the dual simplex algorithm is solving from an advanced basis.
MSK_IINF_SIM_PRIMAL_DUAL_HOTSTART	If 1 then the primal dual simplex algorithm is solving from an advanced basis.
MSK_IINF_SIM_PRIMAL_DUAL_HOTSTART_LU	If 1 then a valid basis factorization of full rank was located and used by the primal dual simplex algorithm.
MSK_IINF_SOL_ITR_PROSTA	Problem status of the interior-point solution. Updated after each optimization.
MSK_IINF_SOL_ITR_SOLSTA	Solution status of the interior-point solution. Updated after each optimization.
MSK_IINF_SOL_BAS_PROSTA	Problem status of the basic solution. Updated after each optimization.
MSK_IINF_SOL_BAS_SOLSTA	Solution status of the basic solution. Updated after each optimization.
MSK_IINF_SOL_ITG_PROSTA	Problem status of the integer solution. Updated after each optimization.
MSK_IINF_SOL_ITG_SOLSTA	Solution status of the integer solution. Updated after each optimization.
MSK_IINF_SIM_NUMCON	Number of constraints in the problem solved by the simplex optimizer.
MSK_IINF_SIM_NUMVAR	Number of variables in the problem solved by the simplex optimizer.

MSK_IINF_OPT_NUMCON

Number of constraints in the problem solved when the optimizer is called.

MSK_IINF_OPT_NUMVAR

Number of variables in the problem solved when the optimizer is called

MSK_IINF_STO_NUM_A_REALLOC

Number of times the storage for storing A has been changed. A large value may indicates that memory fragmentation may occur.

MSK_IINF_RD_NUMCONE

Number of conic constraints read.

MSK_IINF_SIM_SOLVE_DUAL

Is non-zero if dual problem is solved.

MSKinfypee

Information item types

MSK_INF_DOU_TYPE

Is a double information type.

MSK_INF_INT_TYPE

Is an integer.

MSK_INF_LINT_TYPE

Is a long integer.

MSKiomodee

Input/output modes

MSK_IOMODE_READ

The file is read-only.

MSK_IOMODE_WRITE

The file is write-only. If the file exists then it is truncated when it is opened. Otherwise it is created when it is opened.

MSK_IOMODE_READWRITE

The file is to read and written.

MSKbranchdire

Specifies the branching direction.

MSK_BRANCH_DIR_FREE

The mixed-integer optimizer decides which branch to choose.

MSK_BRANCH_DIR_UP

The mixed-integer optimizer always chooses the up branch first.

MSK_BRANCH_DIR_DOWN

The mixed-integer optimizer always chooses the down branch first.

MSK_BRANCH_DIR_NEAR

Branch in direction nearest to selected fractional variable.

MSK_BRANCH_DIR_FAR

Branch in direction farthest from selected fractional variable.

MSK_BRANCH_DIR_ROOT_LP

Chose direction based on root lp value of selected variable.

MSK_BRANCH_DIR_GUIDED

Branch in direction of current incumbent.

MSK_BRANCH_DIR_PSEUDOCOST

Branch based on the pseudocost of the variable.

MSKmiocontsoltypee

Continuous mixed-integer solution type

MSK_MIO_CONT_SOL_NONE

No interior-point or basic solution are reported when the mixed-integer optimizer is used.

MSK_MIO_CONT_SOL_ROOT

The reported interior-point and basic solutions are a solution to the root node problem when mixed-integer optimizer is used.

MSK_MIO_CONT_SOL_ITG

The reported interior-point and basic solutions are a solution to the problem with all integer variables fixed at the value they have in the integer solution. A solution is only reported in case the problem has a primal feasible solution.

MSK_MIO_CONT_SOL_ITG_REL

In case the problem is primal feasible then the reported interior-point and basic solutions are a solution to the problem with all integer variables fixed at the value they have in the integer solution. If the problem is primal infeasible, then the solution to the root node problem is reported.

MSKmiomodee

Integer restrictions

MSK_MIO_MODE_IGNORED

The integer constraints are ignored and the problem is solved as a continuous problem.

MSK_MIO_MODE_SATISFIED

Integer restrictions should be satisfied.

MSKmionodeseltypee

Mixed-integer node selection types

MSK_MIO_NODE_SELECTION_FREE

The optimizer decides the node selection strategy.

MSK_MIO_NODE_SELECTION_FIRST

The optimizer employs a depth first node selection strategy.

MSK_MIO_NODE_SELECTION_BEST

The optimizer employs a best bound node selection strategy.

MSK_MIO_NODE_SELECTION_WORST

The optimizer employs a worst bound node selection strategy.

MSK_MIO_NODE_SELECTION_HYBRID

The optimizer employs a hybrid strategy.

MSK_MIO_NODE_SELECTION_PSEUDO

The optimizer employs selects the node based on a pseudo cost estimate.

MSKmpsformate

MPS file format type

MSK_MPS_FORMAT_STRICT

It is assumed that the input file satisfies the MPS format strictly.

MSK_MPS_FORMAT_RELAXED

It is assumed that the input file satisfies a slightly relaxed version of the MPS format.

MSK_MPS_FORMAT_FREE

It is assumed that the input file satisfies the free MPS format. This implies that spaces are not allowed in names. Otherwise the format is free.

MSK_MPS_FORMAT_CPLEX

The CPLEX compatible version of the MPS format is employed.

MSKmsgkeye

Message keys

MSK_MSG_READING_FILE

MSK_MSG_WRITING_FILE

MSK_MSG_MPS_SELECTED

MSKobjsensee

Objective sense types

MSK_OBJECTIVE_SENSE_MINIMIZE

The problem should be minimized.

MSK_OBJECTIVE_SENSE_MAXIMIZE

The problem should be maximized.

MSKonoffkeye

On/off

MSK_ON

Switch the option on.

MSK_OFF

Switch the option off.

MSKoptimizertypee

Optimizer types

MSK_OPTIMIZER_FREE

The optimizer is chosen automatically.

MSK_OPTIMIZER_INTPNT

The interior-point optimizer is used.

MSK_OPTIMIZER_CONIC

The optimizer for problems having conic constraints.

MSK_OPTIMIZER_PRIMAL_SIMPLEX

The primal simplex optimizer is used.

MSK_OPTIMIZER_DUAL_SIMPLEX

The dual simplex optimizer is used.

MSK_OPTIMIZER_FREE_SIMPLEX

One of the simplex optimizers is used.

MSK_OPTIMIZER_MIXED_INT

The mixed-integer optimizer.

MSKorderingtypee

Ordering strategies

MSK_ORDER_METHOD_FREE

The ordering method is chosen automatically.

MSK_ORDER_METHOD_APPMINLOC

Approximate minimum local fill-in ordering is employed.

MSK_ORDER_METHOD_EXPERIMENTAL

This option should not be used.

MSK_ORDER_METHOD_TRY_GRAPHPAR

Always try the graph partitioning based ordering.

MSK_ORDER_METHOD_FORCE_GRAPHPAR

Always use the graph partitioning based ordering even if it is worse than the approximate minimum local fill ordering.

MSK_ORDER_METHOD_NONE

No ordering is used.

MSKpresolvemodet

Presolve method.

MSK_PRESOLVE_MODE_OFF

The problem is not presolved before it is optimized.

MSK_PRESOLVE_MODE_ON

The problem is presolved before it is optimized.

MSK_PRESOLVE_MODE_FREE

It is decided automatically whether to presolve before the problem is optimized.

MSKparametertypet

Parameter type

MSK_PAR_INVALID_TYPE

Not a valid parameter.

MSK_PAR_DOUB_TYPE

Is a double parameter.

MSK_PAR_INT_TYPE

Is an integer parameter.

MSK_PAR_STR_TYPE

Is a string parameter.

MSKproblemitemet

Problem data items

MSK_PI_VAR

Item is a variable.

MSK_PI_CON

Item is a constraint.

MSK_PI_CONE

Item is a cone.

MSKproblemtypet

Problem types

MSK_PROBTYPE_LO

The problem is a linear optimization problem.

MSK_PROBTYPE_QO

The problem is a quadratic optimization problem.

MSK_PROBTYPE_QCQO

The problem is a quadratically constrained optimization problem.

MSK_PROBTYPE_GECO

General convex optimization.

MSK_PROBTYPE_CONIC

A conic optimization.

MSK_PROBTYPE_MIXED

General nonlinear constraints and conic constraints. This combination can not be solved by **MOSEK**.

MSKprostaet

Problem status keys

MSK_PRO_STA_UNKNOWN

Unknown problem status.

MSK_PRO_STA_PRIM_AND_DUAL_FEAS

The problem is primal and dual feasible.

MSK_PRO_STA_PRIM_FEAS

The problem is primal feasible.

MSK_PRO_STA_DUAL_FEAS

The problem is dual feasible.

MSK_PRO_STA_NEAR_PRIM_AND_DUAL_FEAS

The problem is at least nearly primal and dual feasible.

MSK_PRO_STA_NEAR_PRIM_FEAS

The problem is at least nearly primal feasible.

MSK_PRO_STA_NEAR_DUAL_FEAS

The problem is at least nearly dual feasible.

MSK_PRO_STA_PRIM_INFEAS

The problem is primal infeasible.

MSK_PRO_STA_DUAL_INFEAS

The problem is dual infeasible.

MSK_PRO_STA_PRIM_AND_DUAL_INFEAS

The problem is primal and dual infeasible.

MSK_PRO_STA_ILL_POSED

The problem is ill-posed. For example, it may be primal and dual feasible but have a positive duality gap.

MSK_PRO_STA_PRIM_INFEAS_OR_UNBOUNDED

The problem is either primal infeasible or unbounded. This may occur for mixed-integer problems.

MSKxmlwriteroutputtypee

XML writer output mode

MSK_WRITE_XML_MODE_ROW

Write in row order.

MSK_WRITE_XML_MODE_COL

Write in column order.

MSKrescodetypee

Response code type

MSK_RESPONSE_OK

The response code is OK.

MSK_RESPONSE_WRN

The response code is a warning.

MSK_RESPONSE_TRM

The response code is an optimizer termination status.

MSK_RESPONSE_ERR

The response code is an error.

MSK_RESPONSE_UNK

The response code does not belong to any class.

MSKscalingtypee

Scaling type

MSK_SCALING_FREE

The optimizer chooses the scaling heuristic.

MSK_SCALING_NONE

No scaling is performed.

MSK_SCALING_MODERATE

A conservative scaling is performed.

MSK_SCALING_AGGRESSIVE

A very aggressive scaling is performed.

MSKscalingmethode

Scaling method

MSK_SCALING_METHOD_POW2

Scales only with power of 2 leaving the mantissa untouched.

MSK_SCALING_METHOD_FREE

The optimizer chooses the scaling heuristic.

MSKsensitivitytypee

Sensitivity types

MSK_SENSITIVITY_TYPE_BASIS

Basis sensitivity analysis is performed.

MSK_SENSITIVITY_TYPE_OPTIMAL_PARTITION

Optimal partition sensitivity analysis is performed.

MSKsimselftypee

Simplex selection strategy

MSK_SIM_SELECTION_FREE

The optimizer chooses the pricing strategy.

MSK_SIM_SELECTION_FULL

The optimizer uses full pricing.

MSK_SIM_SELECTION_ASE

The optimizer uses approximate steepest-edge pricing.

MSK_SIM_SELECTION_DEVEX

The optimizer uses devex steepest-edge pricing (or if it is not available an approximate steep-edge selection).

MSK_SIM_SELECTION_SE

The optimizer uses steepest-edge selection (or if it is not available an approximate steep-edge selection).

MSK_SIM_SELECTION_PARTIAL

The optimizer uses a partial selection approach. The approach is usually beneficial if the number of variables is much larger than the number of constraints.

MSKsoliteme

Solution items

MSK_SOL_ITEM_XC

Solution for the constraints.

MSK_SOL_ITEM_XX

Variable solution.

MSK_SOL_ITEM_Y

Lagrange multipliers for equations.

MSK_SOL_ITEM_SLC

Lagrange multipliers for lower bounds on the constraints.

MSK_SOL_ITEM_SUC

Lagrange multipliers for upper bounds on the constraints.

MSK_SOL_ITEM_SLX

Lagrange multipliers for lower bounds on the variables.

MSK_SOL_ITEM_SUX

Lagrange multipliers for upper bounds on the variables.

MSK_SOL_ITEM_SNX

Lagrange multipliers corresponding to the conic constraints on the variables.

MSKsolstae

Solution status keys

MSK_SOL_STA_UNKNOWN

Status of the solution is unknown.

MSK_SOL_STA_OPTIMAL

The solution is optimal.

MSK_SOL_STA_PRIM_FEAS

The solution is primal feasible.

MSK_SOL_STA_DUAL_FEAS

The solution is dual feasible.

MSK_SOL_STA_PRIM_AND_DUAL_FEAS

The solution is both primal and dual feasible.

MSK_SOL_STA_NEAR_OPTIMAL

The solution is nearly optimal.

MSK_SOL_STA_NEAR_PRIM_FEAS

The solution is nearly primal feasible.

MSK_SOL_STA_NEAR_DUAL_FEAS

The solution is nearly dual feasible.

MSK_SOL_STA_NEAR_PRIM_AND_DUAL_FEAS

The solution is nearly both primal and dual feasible.

MSK_SOL_STA_PRIM_INFEAS_CER

The solution is a certificate of primal infeasibility.

MSK_SOL_STA_DUAL_INFEAS_CER

The solution is a certificate of dual infeasibility.

MSK_SOL_STA_NEAR_PRIM_INFEAS_CER

The solution is almost a certificate of primal infeasibility.

MSK_SOL_STA_NEAR_DUAL_INFEAS_CER

The solution is almost a certificate of dual infeasibility.

MSK_SOL_STA_PRIM_ILLPOSED_CER

The solution is a certificate that the primal problem is illposed.

MSK_SOL_STA_DUAL_ILLPOSED_CER

The solution is a certificate that the dual problem is illposed.

MSK_SOL_STA_INTEGER_OPTIMAL

The primal solution is integer optimal.

MSK_SOL_STA_NEAR_INTEGER_OPTIMAL

The primal solution is near integer optimal.

MSKsoltypee

Solution types

MSK_SOL_BAS

The basic solution.

MSK_SOL_ITR
The interior solution.

MSK_SOL_ITG
The integer solution.

MSKsolveforme
Solve primal or dual form

MSK_SOLVE_FREE
The optimizer is free to solve either the primal or the dual problem.

MSK_SOLVE_PRIMAL
The optimizer should solve the primal problem.

MSK_SOLVE_DUAL
The optimizer should solve the dual problem.

MSKstakeye
Status keys

MSK_SK_UNK
The status for the constraint or variable is unknown.

MSK_SK_BAS
The constraint or variable is in the basis.

MSK_SK_SUPBAS
The constraint or variable is super basic.

MSK_SK_LOW
The constraint or variable is at its lower bound.

MSK_SK_UPR
The constraint or variable is at its upper bound.

MSK_SK_FIX
The constraint or variable is fixed.

MSK_SK_INF
The constraint or variable is infeasible in the bounds.

MSKstartpointtypee
Starting point types

MSK_STARTING_POINT_FREE
The starting point is chosen automatically.

MSK_STARTING_POINT_GUESS
The optimizer guesses a starting point.

MSK_STARTING_POINT_CONSTANT
The optimizer constructs a starting point by assigning a constant value to all primal and dual variables. This starting point is normally robust.

MSK_STARTING_POINT_SATISFY_BOUNDS
The starting point is chosen to satisfy all the simple bounds on nonlinear variables. If this starting point is employed, then more care than usual should be employed when choosing the bounds on the nonlinear variables. In particular very tight bounds should be avoided.

MSKstreamtypee
Stream types

MSK_STREAM_LOG
Log stream. Contains the aggregated contents of all other streams. This means that a message written to any other stream will also be written to this stream.

MSK_STREAM_MSG

Message stream. Log information relating to performance and progress of the optimization is written to this stream.

MSK_STREAM_ERR

Error stream. Error messages are written to this stream.

MSK_STREAM_WRN

Warning stream. Warning messages are written to this stream.

MSKvaluee

Integer values

MSK_MAX_STR_LEN

Maximum string length allowed in **MOSEK**.

MSK_LICENSE_BUFFER_LENGTH

The length of a license key buffer.

MSKvariabletypee

Variable types

MSK_VAR_TYPE_CONT

Is a continuous variable.

MSK_VAR_TYPE_INT

Is an integer variable.

SUPPORTED FILE FORMATS

MOSEK supports a range of problem and solution formats listed in [Table 12.1](#) and [Table 12.2](#). The **Task format** is **MOSEK**'s native binary format and it supports all features that **MOSEK** supports. The **OPF format** is **MOSEK**'s human-readable alternative that supports nearly all features (everything except semidefinite problems). In general, text formats are significantly slower to read, but can be examined and edited directly in any text editor.

Problem formats

See [Table 12.1](#).

Table 12.1: List of supported file formats for optimization problems.

Format Type	Ext.	Binary/Text	LP	QP	CQO	SDP
<i>LP</i>	lp	plain text	X	X		
<i>MPS</i>	mps	plain text	X	X		
<i>OPF</i>	opf	plain text	X	X	X	
<i>CBF</i>	cbf	plain text	X		X	X
<i>Osil</i>	xml	xml text	X	X		
<i>Task format</i>	task	binary	X	X	X	X
<i>Jtask format</i>	jtask	text	X	X	X	X

Solution formats

See [Table 12.2](#).

Table 12.2: List of supported solution formats.

Format Type	Ext.	Binary/Text	Description
<i>SOL</i>	sol	plain text	Interior Solution
	bas	plain text	Basic Solution
	int	plain text	Integer
<i>Jsol format</i>	jsol	text	Solution

Compression

MOSEK supports GZIP compression of files. Problem files with an additional `.gz` extension are assumed to be compressed when read, and are automatically compressed when written. For example, a file called

problem.mps.gz

will be considered as a GZIP compressed MPS file.

12.1 The LP File Format

MOSEK supports the LP file format with some extensions. The LP format is not a completely well-defined standard and hence different optimization packages may interpret the same LP file in slightly different ways. **MOSEK** tries to emulate as closely as possible CPLEX's behavior, but tries to stay backward compatible.

The LP file format can specify problems on the form

$$\begin{array}{ll} \text{minimize/maximize} & c^T x + \frac{1}{2} q^o(x) \\ \text{subject to} & \begin{array}{lll} l^c \leq & Ax + \frac{1}{2} q(x) & \leq u^c, \\ l^x \leq & x & \leq u^x, \\ & x_{\mathcal{J}} \text{ integer,} \end{array} \end{array}$$

where

- $x \in \mathbb{R}^n$ is the vector of decision variables.
- $c \in \mathbb{R}^n$ is the linear term in the objective.
- $q^o : \mathbb{R}^n \rightarrow \mathbb{R}$ is the quadratic term in the objective where

$$q^o(x) = x^T Q^o x$$

and it is assumed that

$$Q^o = (Q^o)^T.$$

- $A \in \mathbb{R}^{m \times n}$ is the constraint matrix.
- $l^c \in \mathbb{R}^m$ is the lower limit on the activity for the constraints.
- $u^c \in \mathbb{R}^m$ is the upper limit on the activity for the constraints.
- $l^x \in \mathbb{R}^n$ is the lower limit on the activity for the variables.
- $u^x \in \mathbb{R}^n$ is the upper limit on the activity for the variables.
- $q : \mathbb{R}^n \rightarrow \mathbb{R}$ is a vector of quadratic functions. Hence,

$$q_i(x) = x^T Q^i x$$

where it is assumed that

$$Q^i = (Q^i)^T.$$

- $\mathcal{J} \subseteq \{1, 2, \dots, n\}$ is an index set of the integer constrained variables.

12.1.1 File Sections

An LP formatted file contains a number of sections specifying the objective, constraints, variable bounds, and variable types. The section keywords may be any mix of upper and lower case letters.

Objective Function

The first section beginning with one of the keywords

```
max
maximum
maximize
min
minimum
minimize
```

defines the objective sense and the objective function, i.e.

$$c^T x + \frac{1}{2} x^T Q^o x.$$

The objective may be given a name by writing

```
myname:
```

before the expressions. If no name is given, then the objective is named `obj`.

The objective function contains linear and quadratic terms. The linear terms are written as:

```
4 x1 + x2 - 0.1 x3
```

and so forth. The quadratic terms are written in square brackets (`[]`) and are either squared or multiplied as in the examples

```
x1^2
```

and

```
x1 * x2
```

There may be zero or more pairs of brackets containing quadratic expressions.

An example of an objective section is

```
minimize
myobj: 4 x1 + x2 - 0.1 x3 + [ x1^2 + 2.1 x1 * x2 ]/2
```

Please note that the quadratic expressions are multiplied with $\frac{1}{2}$, so that the above expression means

$$\text{minimize } 4x_1 + x_2 - 0.1 \cdot x_3 + \frac{1}{2}(x_1^2 + 2.1 \cdot x_1 \cdot x_2)$$

If the same variable occurs more than once in the linear part, the coefficients are added, so that `4 x1 + 2 x1` is equivalent to `6 x1`. In the quadratic expressions `x1 * x2` is equivalent to `x2 * x1` and, as in the linear part, if the same variables multiplied or squared occur several times their coefficients are added.

Constraints

The second section beginning with one of the keywords

```
subj to
subject to
s.t.
st
```

defines the linear constraint matrix A and the quadratic matrices Q^i .

A constraint contains a name (optional), expressions adhering to the same rules as in the objective and a bound:

```
subject to
con1: x1 + x2 + [ x3^2 ]/2 <= 5.1
```

The bound type (here \leq) may be any of $<$, \leq , $=$, $>$, \geq ($<$ and \leq mean the same), and the bound may be any number.

In the standard LP format it is not possible to define more than one bound, but **MOSEK** supports defining ranged constraints by using double-colon ($::$) instead of a single-colon ($:$) after the constraint name, i.e.

$$-5 \leq x_1 + x_2 \leq 5 \tag{12.1}$$

may be written as

```
con:: -5 < x_1 + x_2 < 5
```

By default **MOSEK** writes ranged constraints this way.

If the files must adhere to the LP standard, ranged constraints must either be split into upper bounded and lower bounded constraints or be written as an equality with a slack variable. For example the expression (12.1) may be written as

$$x_1 + x_2 - sl_1 = 0, \quad -5 \leq sl_1 \leq 5.$$

Bounds

Bounds on the variables can be specified in the bound section beginning with one of the keywords

```
bound
bounds
```

The bounds section is optional but should, if present, follow the **subject to** section. All variables listed in the bounds section must occur in either the objective or a constraint.

The default lower and upper bounds are 0 and $+\infty$. A variable may be declared free with the keyword **free**, which means that the lower bound is $-\infty$ and the upper bound is $+\infty$. Furthermore it may be assigned a finite lower and upper bound. The bound definitions for a given variable may be written in one or two lines, and bounds can be any number or $\pm\infty$ (written as **+inf/-inf/+infinity/-infinity**) as in the example

```
bounds
x1 free
x2 <= 5
0.1 <= x2
x3 = 42
2 <= x4 < +inf
```

Variable Types

The final two sections are optional and must begin with one of the keywords

```
bin
binaries
binary
```

and

```
gen
general
```

Under **general** all integer variables are listed, and under **binary** all binary (integer variables with bounds 0 and 1) are listed:

```

general
x1 x2
binary
x3 x4

```

Again, all variables listed in the binary or general sections must occur in either the objective or a constraint.

Terminating Section

Finally, an LP formatted file must be terminated with the keyword

```
end
```

12.1.2 LP File Examples

Linear example lo1.lp

```

\ File: lo1.lp
maximize
obj: 3 x1 + x2 + 5 x3 + x4
subject to
c1: 3 x1 + x2 + 2 x3 = 30
c2: 2 x1 + x2 + 3 x3 + x4 >= 15
c3: 2 x2 + 3 x4 <= 25
bounds
0 <= x1 <= +infinity
0 <= x2 <= 10
0 <= x3 <= +infinity
0 <= x4 <= +infinity
end

```

Mixed integer example milo1.lp

```

maximize
obj: x1 + 6.4e-01 x2
subject to
c1: 5e+01 x1 + 3.1e+01 x2 <= 2.5e+02
c2: 3e+00 x1 - 2e+00 x2 >= -4e+00
bounds
0 <= x1 <= +infinity
0 <= x2 <= +infinity
general
x1 x2
end

```

12.1.3 LP Format peculiarities

Comments

Anything on a line after a \ is ignored and is treated as a comment.

Names

A name for an objective, a constraint or a variable may contain the letters *a-z*, *A-Z*, the digits *0-9* and the characters

!"#\$%&()/,.;?@_`'|~

The first character in a name must not be a number, a period or the letter *e* or *E*. Keywords must not be used as names.

MOSEK accepts any character as valid for names, except \0. A name that is not allowed in LP file will be changed and a warning will be issued.

The algorithm for making names LP valid works as follows: The name is interpreted as an **utf-8** string. For a unicode character *c*:

- If *c*==_ (underscore), the output is __ (two underscores).
- If *c* is a valid LP name character, the output is just *c*.
- If *c* is another character in the ASCII range, the output is _XX, where XX is the hexadecimal code for the character.
- If *c* is a character in the range *127-65535*, the output is _uXXXX, where XXXX is the hexadecimal code for the character.
- If *c* is a character above 65535, the output is _UXXXXXXXX, where XXXXXXXX is the hexadecimal code for the character.

Invalid **utf-8** substrings are escaped as _XX', and if a name starts with a period, *e* or *E*, that character is escaped as _XX.

Variable Bounds

Specifying several upper or lower bounds on one variable is possible but **MOSEK** uses only the tightest bounds. If a variable is fixed (with =), then it is considered the tightest bound.

MOSEK Extensions to the LP Format

Some optimization software packages employ a more strict definition of the LP format than the one used by **MOSEK**. The limitations imposed by the strict LP format are the following:

- Quadratic terms in the constraints are not allowed.
- Names can be only 16 characters long.
- Lines must not exceed 255 characters in length.

If an LP formatted file created by **MOSEK** should satisfy the strict definition, then the parameter

- *MSK_IPAR_WRITE_LP_STRICT_FORMAT*

should be set; note, however, that some problems cannot be written correctly as a strict LP formatted file. For instance, all names are truncated to 16 characters and hence they may lose their uniqueness and change the problem.

To get around some of the inconveniences converting from other problem formats, **MOSEK** allows lines to contain 1024 characters and names may have any length (shorter than the 1024 characters).

Internally in **MOSEK** names may contain any (printable) character, many of which cannot be used in LP names. Setting the parameters

- *MSK_IPAR_READ_LP_QUOTED_NAMES* and
- *MSK_IPAR_WRITE_LP_QUOTED_NAMES*

allows **MOSEK** to use quoted names. The first parameter tells **MOSEK** to remove quotes from quoted names e.g, "x1", when reading LP formatted files. The second parameter tells **MOSEK** to put quotes around any semi-illegal name (names beginning with a number or a period) and fully illegal name (containing illegal characters). As double quote is a legal character in the LP format, quoting semi-illegal names makes them legal in the pure LP format as long as they are still shorter than 16 characters. Fully illegal names are still illegal in a pure LP file.

12.1.4 The strict LP format

The LP format is not a formal standard and different vendors have slightly different interpretations of the LP format. To make **MOSEK**'s definition of the LP format more compatible with the definitions of other vendors, use the parameter setting

- `MSK_IPAR_WRITE_LP_STRICT_FORMAT = MSK_ON`

This setting may lead to truncation of some names and hence to an invalid LP file. The simple solution to this problem is to use the parameter setting

- `MSK_IPAR_WRITE_GENERIC_NAMES = MSK_ON`

which will cause all names to be renamed systematically in the output file.

12.1.5 Formatting of an LP File

A few parameters control the visual formatting of LP files written by **MOSEK** in order to make it easier to read the files. These parameters are

- `MSK_IPAR_WRITE_LP_LINE_WIDTH`
- `MSK_IPAR_WRITE_LP_TERMS_PER_LINE`

The first parameter sets the maximum number of characters on a single line. The default value is 80 corresponding roughly to the width of a standard text document.

The second parameter sets the maximum number of terms per line; a term means a sign, a coefficient, and a name (for example + 42 elephants). The default value is 0, meaning that there is no maximum.

Unnamed Constraints

Reading and writing an LP file with **MOSEK** may change it superficially. If an LP file contains unnamed constraints or objective these are given their generic names when the file is read (however unnamed constraints in **MOSEK** are written without names).

12.2 The MPS File Format

MOSEK supports the standard MPS format with some extensions. For a detailed description of the MPS format see the book by Nazareth [Naz87].

12.2.1 MPS File Structure

The version of the MPS format supported by **MOSEK** allows specification of an optimization problem of the form

$$\begin{aligned} l^c &\leq Ax + q(x) &&\leq u^c, \\ l^x &\leq x &&\leq u^x, \\ &x \in \mathcal{K}, \\ &x_{\mathcal{J}} \text{ integer}, \end{aligned} \tag{12.2}$$

where

- $x \in \mathbb{R}^n$ is the vector of decision variables.
- $A \in \mathbb{R}^{m \times n}$ is the constraint matrix.
- $l^c \in \mathbb{R}^m$ is the lower limit on the activity for the constraints.
- $u^c \in \mathbb{R}^m$ is the upper limit on the activity for the constraints.
- $l^x \in \mathbb{R}^n$ is the lower limit on the activity for the variables.
- $u^x \in \mathbb{R}^n$ is the upper limit on the activity for the variables.
- $q : \mathbb{R}^n \rightarrow \mathbb{R}$ is a vector of quadratic functions. Hence,

$$q_i(x) = \frac{1}{2} x^T Q^i x$$

where it is assumed that

$$Q^i = (Q^i)^T.$$

Please note the explicit $\frac{1}{2}$ in the quadratic term and that Q^i is required to be symmetric.

- \mathcal{K} is a convex cone.
- $\mathcal{J} \subseteq \{1, 2, \dots, n\}$ is an index set of the integer-constrained variables.

An MPS file with one row and one column can be illustrated like this:

```
*          1          2          3          4          5          6
*23456789012345678901234567890123456789012345678901234567890
NAME          [name]
OBJSENSE
[objsense]
OBJNAME
[objname]
ROWS
? [cname1]
COLUMNS
[vname1] [cname1] [value1] [vname3] [value2]
RHS
[name] [cname1] [value1] [cname2] [value2]
RANGES
[name] [cname1] [value1] [cname2] [value2]
QSECTION      [cname1]
[vname1] [vname2] [value1] [vname3] [value2]
QMATRIX
[vname1] [vname2] [value1]
QUADOBJ
[vname1] [vname2] [value1]
QCMATRIX      [cname1]
[vname1] [vname2] [value1]
BOUNDS
?? [name] [vname1] [value1]
CSECTION      [kname1] [value1] [ktype]
[vname1]
ENDATA
```

Here the names in capitals are keywords of the MPS format and names in brackets are custom defined names or values. A couple of notes on the structure:

- Fields: All items surrounded by brackets appear in *fields*. The fields named “valueN” are numerical values. Hence, they must have the format

```
[+|-]XXXXXXXX.XXXXXX[[e|E][+|-]XXX]
```

where

```
.. code-block:: text
```

```
X = [0|1|2|3|4|5|6|7|8|9].
```

- Sections: The MPS file consists of several sections where the names in capitals indicate the beginning of a new section. For example, COLUMNS denotes the beginning of the columns section.
- Comments: Lines starting with an * are comment lines and are ignored by **MOSEK**.
- Keys: The question marks represent keys to be specified later.
- Extensions: The sections QSECTION and CSECTION are specific **MOSEK** extensions of the MPS format. The sections QMATRIX, QUADOBJ and QCMATRIX are included for sake of compatibility with other vendors extensions to the MPS format.

The standard MPS format is a fixed format, i.e. everything in the MPS file must be within certain fixed positions. **MOSEK** also supports a *free format*. See Section 12.2.9 for details.

Linear example lo1.mps

A concrete example of a MPS file is presented below:

```
* File: lo1.mps
NAME          lo1
OBJSENSE
    MAX
ROWS
N  obj
E  c1
G  c2
L  c3
COLUMNS
    x1      obj      3
    x1      c1       3
    x1      c2       2
    x2      obj      1
    x2      c1       1
    x2      c2       1
    x2      c3       2
    x3      obj      5
    x3      c1       2
    x3      c2       3
    x4      obj      1
    x4      c2       1
    x4      c3       3
RHS
    rhs      c1      30
    rhs      c2      15
    rhs      c3      25
RANGES
BOUNDS
UP bound    x2      10
ENDATA
```

Subsequently each individual section in the MPS format is discussed.

Section NAME

In this section a name ([name]) is assigned to the problem.

OBJSENSE (optional)

This is an optional section that can be used to specify the sense of the objective function. The **OBJSENSE** section contains one line at most which can be one of the following

```
MIN
MINIMIZE
MAX
MAXIMIZE
```

It should be obvious what the implication is of each of these four lines.

OBJNAME (optional)

This is an optional section that can be used to specify the name of the row that is used as objective function. The **OBJNAME** section contains one line at most which has the form

```
objname
```

`objname` should be a valid row name.

ROWS

A record in the **ROWS** section has the form

```
? [cname1]
```

where the requirements for the fields are as follows:

Field	Starting Position	Max Width	required	Description
?	2	1	Yes	Constraint key
[cname1]	5	8	Yes	Constraint name

Hence, in this section each constraint is assigned an unique name denoted by `[cname1]`. Please note that `[cname1]` starts in position 5 and the field can be at most 8 characters wide. An initial key `?` must be present to specify the type of the constraint. The key can have the values E, G, L, or N with the following interpretation:

Constraint type	l_i^c	u_i^c
E	finite	l_i^c
G	finite	∞
L	$-\infty$	finite
N	$-\infty$	∞

In the MPS format an objective vector is not specified explicitly, but one of the constraints having the key N will be used as the objective vector c . In general, if multiple N type constraints are specified, then the first will be used as the objective vector c .

COLUMNS

In this section the elements of A are specified using one or more records having the form:

```
[vname1] [cname1] [value1] [cname2] [value2]
```

where the requirements for each field are as follows:

Field	Starting Position	Max Width	required	Description
[vname1]	5	8	Yes	Variable name
[cname1]	15	8	Yes	Constraint name
[value1]	25	12	Yes	Numerical value
[cname2]	40	8	No	Constraint name
[value2]	50	12	No	Numerical value

Hence, a record specifies one or two elements a_{ij} of A using the principle that [vname1] and [cname1] determines j and i respectively. Please note that [cname1] must be a constraint name specified in the ROWS section. Finally, [value1] denotes the numerical value of a_{ij} . Another optional element is specified by [cname2], and [value2] for the variable specified by [vname1]. Some important comments are:

- All elements belonging to one variable must be grouped together.
- Zero elements of A should not be specified.
- At least one element for each variable should be specified.

RHS (optional)

A record in this section has the format

[name]	[cname1]	[value1]	[cname2]	[value2]
--------	----------	----------	----------	----------

where the requirements for each field are as follows:

Field	Starting Position	Max Width	required	Description
[name]	5	8	Yes	Name of the RHS vector
[cname1]	15	8	Yes	Constraint name
[value1]	25	12	Yes	Numerical value
[cname2]	40	8	No	Constraint name
[value2]	50	12	No	Numerical value

The interpretation of a record is that [name] is the name of the RHS vector to be specified. In general, several vectors can be specified. [cname1] denotes a constraint name previously specified in the ROWS section. Now, assume that this name has been assigned to the i th constraint and v_1 denotes the value specified by [value1], then the interpretation of v_1 is:

Constraint	l_i^c	u_i^c
type		
E	v_1	v_1
G	v_1	
L		v_1
N		

An optional second element is specified by [cname2] and [value2] and is interpreted in the same way. Please note that it is not necessary to specify zero elements, because elements are assumed to be zero.

RANGES (optional)

A record in this section has the form

[name]	[cname1]	[value1]	[cname2]	[value2]
--------	----------	----------	----------	----------

where the requirements for each fields are as follows:

Field	Starting Position	Max Width	required	Description
[name]	5	8	Yes	Name of the RANGE vector
[cname1]	15	8	Yes	Constraint name
[value1]	25	12	Yes	Numerical value
[cname2]	40	8	No	Constraint name
[value2]	50	12	No	Numerical value

The records in this section are used to modify the bound vectors for the constraints, i.e. the values in l^c and u^c . A record has the following interpretation: [name] is the name of the RANGE vector and [cname1] is a valid constraint name. Assume that [cname1] is assigned to the i th constraint and let v_1 be the value specified by [value1], then a record has the interpretation:

Constraint type	Sign of v_1	l_i^c	u_i^c
E	—	$u_i^c + v_1$	
E	+		$l_i^c + v_1$
G	— or +	$l_i^c + v_1 $	
L	— or +	$u_i^c - v_1 $	
N			

QSECTION (optional)

Within the QSECTION the label [cname1] must be a constraint name previously specified in the ROWS section. The label [cname1] denotes the constraint to which the quadratic term belongs. A record in the QSECTION has the form

[vname1]	[vname2]	[value1]	[vname3]	[value2]
----------	----------	----------	----------	----------

where the requirements for each field are:

Field	Starting Position	Max Width	required	Description
[vname1]	5	8	Yes	Variable name
[vname2]	15	8	Yes	Variable name
[value1]	25	12	Yes	Numerical value
[vname3]	40	8	No	Variable name
[value2]	50	12	No	Numerical value

A record specifies one or two elements in the lower triangular part of the Q^i matrix where [cname1] specifies the i . Hence, if the names [vname1] and [vname2] have been assigned to the k th and j th variable, then Q_{kj}^i is assigned the value given by [value1]. An optional second element is specified in the same way by the fields [vname1], [vname3], and [value2].

The example

$$\begin{array}{ll} \text{minimize} & -x_2 + \frac{1}{2}(2x_1^2 - 2x_1x_3 + 0.2x_2^2 + 2x_3^2) \\ \text{subject to} & x_1 + x_2 + x_3 \geq 1, \\ & x \geq 0 \end{array}$$

has the following MPS file representation

```
* File: qo1.mps
NAME          qo1
ROWS
N  obj
G  c1
COLUMNS
x1      c1      1.0
x2      obj     -1.0
x2      c1      1.0
x3      c1      1.0
RHS
rhs      c1      1.0
QSECTION      obj
x1      x1      2.0
x1      x3     -1.0
x2      x2      0.2
x3      x3      2.0
ENDATA
```

Regarding the QSECTIONS please note that:

- Only one QSECTION is allowed for each constraint.
- The QSECTIONS can appear in an arbitrary order after the COLUMNS section.
- All variable names occurring in the QSECTION must already be specified in the COLUMNS section.
- All entries specified in a QSECTION are assumed to belong to the lower triangular part of the quadratic term of Q .

QMATRIX/QUADOBJ (optional)

The QMATRIX and QUADOBJ sections allow to define the quadratic term of the objective function. They differ in how the quadratic term of the objective function is stored:

- QMATRIX It stores all the nonzeros coefficients, without taking advantage of the symmetry of the Q matrix.
- QUADOBJ It only store the upper diagonal nonzero elements of the Q matrix.

A record in both sections has the form:

[vname1]	[vname2]	[value1]
----------	----------	----------

where the requirements for each field are:

Field	Starting Position	Max Width	required	Description
[vname1]	5	8	Yes	Variable name
[vname2]	15	8	Yes	Variable name
[value1]	25	12	Yes	Numerical value

A record specifies one elements of the Q matrix in the objective function. Hence, if the names [vname1] and [vname2] have been assigned to the k th and j th variable, then Q_{kj} is assigned the value given by [value1]. Note that a line must appear for each off-diagonal coefficient if using a QMATRIX section, while only one entry is required in a QUADOBJ section. The quadratic part of the objective function will be evaluated as $1/2x^T Qx$.

The example

$$\begin{aligned}
 &\text{minimize} && -x_2 + \frac{1}{2}(2x_1^2 - 2x_1x_3 + 0.2x_2^2 + 2x_3^2) \\
 &\text{subject to} && x_1 + x_2 + x_3 \geq 1, \\
 &&& x \geq 0
 \end{aligned}$$

has the following MPS file representation using QMATRIX

```

* File: qo1_matrix.mps
NAME          qo1_qmatrix
ROWS
  N  obj
  G  c1
COLUMNS
  x1      c1      1.0
  x2      obj     -1.0
  x2      c1      1.0
  x3      c1      1.0
RHS
  rhs     c1      1.0
QMATRIX
  x1      x1      2.0
  x1      x3     -1.0
  x3      x1     -1.0
  x2      x2      0.2
  x3      x3      2.0
ENDATA

```

or the following using QUADOBJ

```
* File: qo1_quadobj.mps
NAME          qo1_quadobj
ROWS
  N  obj
  G  c1
COLUMNS
  x1      c1      1.0
  x2      obj     -1.0
  x2      c1      1.0
  x3      c1      1.0
RHS
  rhs     c1      1.0
QUADOBJ
  x1      x1      2.0
  x1      x3     -1.0
  x2      x2      0.2
  x3      x3      2.0
ENDATA
```

Please also note that:

- A QMATRIX/QUADOBJ section can appear in an arbitrary order after the COLUMNS section.
- All variable names occurring in the QMATRIX/QUADOBJ section must already be specified in the COLUMNS section.

12.2.2 QCMATRIX (optional)

A QCMATRIX section allows to specify the quadratic part of a given constraints. Within the QCMATRIX the label [cname1] must be a constraint name previously specified in the ROWS section. The label [cname1] denotes the constraint to which the quadratic term belongs. A record in the QSECTION has the form

[vname1]	[vname2]	[value1]
----------	----------	----------

where the requirements for each field are:

Field	Starting Position	Max Width	required	Description
[vname1]	5	8	Yes	Variable name
[vname2]	15	8	Yes	Variable name
[value1]	25	12	Yes	Numerical value

A record specifies an entry of the Q^i matrix where [cname1] specifies the i . Hence, if the names [vname1] and [vname2] have been assigned to the k th and j th variable, then Q_{kj}^i is assigned the value given by [value1]. Moreover, the quadratic term is represented as $1/2x^T Qx$.

The example

$$\begin{aligned}
 &\text{minimize} && x_2 \\
 &\text{subject to} && x_1 + x_2 + x_3 \geq 1, \\
 & && \frac{1}{2}(-2x_1x_3 + 0.2x_2^2 + 2x_3^2) \leq 10, \\
 & && x \geq 0
 \end{aligned}$$

has the following MPS file representation

```
* File: qo1.mps
NAME          qo1
ROWS
  N  obj
  G  c1
  L  q1
COLUMNS
```


x1	c1	1.0
x2	obj	-1.0
x2	c1	1.0
x3	c1	1.0
RHS		
rhs	c1	1.0
rhs	q1	10.0
QCMATRIX		
	q1	
x1	x1	2.0
x1	x3	-1.0
x3	x1	-1.0
x2	x2	0.2
x3	x3	2.0
ENDATA		

Regarding the QCMATRIXs please note that:

- Only one QCMATRIX is allowed for each constraint.
- The QCMATRIXs can appear in an arbitrary order after the COLUMNS section.
- All variable names occurring in the QSECTION must already be specified in the COLUMNS section.
- A QCMATRIX does not exploit the symmetry of Q : an off-diagonal entry (i, j) should appear twice.

12.2.3 BOUNDS (optional)

In the BOUNDS section changes to the default bounds vectors l^x and u^x are specified. The default bounds vectors are $l^x = 0$ and $u^x = \infty$. Moreover, it is possible to specify several sets of bound vectors. A record in this section has the form

??	[name]	[vname1]	[value1]
----	--------	----------	----------

where the requirements for each field are:

Field	Starting Position	Max Width	Required	Description
??	2	2	Yes	Bound key
[name]	5	8	Yes	Name of the BOUNDS vector
[vname1]	15	8	Yes	Variable name
[value1]	25	12	No	Numerical value

Hence, a record in the BOUNDS section has the following interpretation: [name] is the name of the bound vector and [vname1] is the name of the variable which bounds are modified by the record. ?? and [value1] are used to modify the bound vectors according to the following table:

??	l_j^x	u_j^x	Made integer (added to \mathcal{J})
FR	$-\infty$	∞	No
FX	v_1	v_1	No
LO	v_1	unchanged	No
MI	$-\infty$	unchanged	No
PL	unchanged	∞	No
UP	unchanged	v_1	No
BV	0	1	Yes
LI	$\lceil v_1 \rceil$	unchanged	Yes
UI	unchanged	$\lfloor v_1 \rfloor$	Yes

v_1 is the value specified by [value1].

12.2.4 CSECTION (optional)

The purpose of the CSECTION is to specify the constraint

$$x \in \mathcal{K}.$$

in (12.2). It is assumed that \mathcal{K} satisfies the following requirements. Let

$$x^t \in \mathbb{R}^{n^t}, \quad t = 1, \dots, k$$

be vectors comprised of parts of the decision variables x so that each decision variable is a member of exactly **one** vector x^t , for example

$$x^1 = \begin{bmatrix} x_1 \\ x_4 \\ x_7 \end{bmatrix} \quad \text{and} \quad x^2 = \begin{bmatrix} x_6 \\ x_5 \\ x_3 \\ x_2 \end{bmatrix}.$$

Next define

$$\mathcal{K} := \{x \in \mathbb{R}^n : \quad x^t \in \mathcal{K}_t, \quad t = 1, \dots, k\}$$

where \mathcal{K}_t must have one of the following forms

- \mathbb{R} set:

$$\mathcal{K}_t = \{x \in \mathbb{R}^{n^t}\}.$$

- Quadratic cone:

$$\mathcal{K}_t = \left\{ x \in \mathbb{R}^{n^t} : x_1 \geq \sqrt{\sum_{j=2}^{n^t} x_j^2} \right\}. \quad (12.3)$$

- Rotated quadratic cone:

$$\mathcal{K}_t = \left\{ x \in \mathbb{R}^{n^t} : 2x_1x_2 \geq \sum_{j=3}^{n^t} x_j^2, \quad x_1, x_2 \geq 0 \right\}. \quad (12.4)$$

In general, only quadratic and rotated quadratic cones are specified in the MPS file whereas membership of the \mathbb{R} set is not. If a variable is not a member of any other cone then it is assumed to be a member of an \mathbb{R} cone.

Next, let us study an example. Assume that the quadratic cone

$$x_4 \geq \sqrt{x_5^2 + x_8^2}$$

and the rotated quadratic cone

$$x_3x_7 \geq x_1^2 + x_0^2, \quad x_3, x_7 \geq 0,$$

should be specified in the MPS file. One CSECTION is required for each cone and they are specified as follows:

```

*          1          2          3          4          5          6
*23456789012345678901234567890123456789012345678901234567890
CSECTION      konea      0.0      QUAD
x4
x5
x8
CSECTION      koneb      0.0      RQUAD
x7
x3
x1
x0

```

This first CSECTION specifies the cone (12.3) which is given the name `konea`. This is a quadratic cone which is specified by the keyword `QUAD` in the CSECTION header. The 0.0 value in the CSECTION header is not used by the `QUAD` cone.

The second CSECTION specifies the rotated quadratic cone (12.4). Please note the keyword `RQUAD` in the CSECTION which is used to specify that the cone is a rotated quadratic cone instead of a quadratic cone. The 0.0 value in the CSECTION header is not used by the `RQUAD` cone.

In general, a CSECTION header has the format

```
CSECTION      [kname1]      [value1]      [ktype]
```

where the requirement for each field are as follows:

Field	Starting Position	Max Width	Required	Description
[kname1]	5	8	Yes	Name of the cone
[value1]	15	12	No	Cone parameter
[ktype]	25		Yes	Type of the cone.

The possible cone type keys are:

Cone type key	Members	Interpretation.
QUAD	≤ 1	Quadratic cone i.e. (12.3).
RQUAD	≤ 2	Rotated quadratic cone i.e. (12.4).

Please note that a quadratic cone must have at least one member whereas a rotated quadratic cone must have at least two members. A record in the CSECTION has the format

```
[vname1]
```

where the requirements for each field are

Field	Starting Position	Max Width	required	Description
[vname1]	2	8	Yes	A valid variable name

The most important restriction with respect to the CSECTION is that a variable must occur in only one CSECTION.

12.2.5 ENDATA

This keyword denotes the end of the MPS file.

12.2.6 Integer Variables

Using special bound keys in the BOUNDS section it is possible to specify that some or all of the variables should be integer-constrained i.e. be members of \mathcal{J} . However, an alternative method is available.

This method is available only for backward compatibility and we recommend that it is not used. This method requires that markers are placed in the COLUMNS section as in the example:

```
COLUMNS
x1      obj      -10.0      c1      0.7
x1      c2        0.5      c3      1.0
x1      c4        0.1
* Start of integer-constrained variables.
MARK000 'MARKER'          'INTORG'
x2      obj      -9.0      c1      1.0
x2      c2      0.8333333333 c3      0.66666667
x2      c4        0.25
x3      obj      1.0      c6      2.0
MARK001 'MARKER'          'INTEND'
```

- End of integer-constrained variables.

Please note that special marker lines are used to indicate the start and the end of the integer variables. Furthermore be aware of the following

- **IMPORTANT:** All variables between the markers are assigned a default lower bound of 0 and a default upper bound of 1. **This may not be what is intended.** If it is not intended, the correct bounds should be defined in the `BOUNDS` section of the MPS formatted file.
- **MOSEK** ignores field 1, i.e. `MARK0001` and `MARK001`, however, other optimization systems require them.
- Field 2, i.e. `MARKER`, must be specified including the single quotes. This implies that no row can be assigned the name `MARKER`.
- Field 3 is ignored and should be left blank.
- Field 4, i.e. `INTORG` and `INTEND`, must be specified.
- It is possible to specify several such integer marker sections within the `COLUMNS` section.

12.2.7 General Limitations

- An MPS file should be an ASCII file.

12.2.8 Interpretation of the MPS Format

Several issues related to the MPS format are not well-defined by the industry standard. However, **MOSEK** uses the following interpretation:

- If a matrix element in the `COLUMNS` section is specified multiple times, then the multiple entries are added together.
- If a matrix element in a `QSECTION` section is specified multiple times, then the multiple entries are added together.

12.2.9 The Free MPS Format

MOSEK supports a free format variation of the MPS format. The free format is similar to the MPS file format but less restrictive, e.g. it allows longer names. However, it also presents two main limitations:

- A name must not contain any blanks.
- By default a line in the MPS file must not contain more than 1024 characters. However, by modifying the parameter `MSK_IPAR_READ_MPS_WIDTH` an arbitrary large line width will be accepted.

To use the free MPS format instead of the default MPS format the **MOSEK** parameter `MSK_IPAR_READ_MPS_FORMAT` should be changed.

12.3 The OPF Format

The *Optimization Problem Format (OPF)* is an alternative to LP and MPS files for specifying optimization problems. It is row-oriented, inspired by the CPLEX LP format.

Apart from containing objective, constraints, bounds etc. it may contain complete or partial solutions, comments and extra information relevant for solving the problem. It is designed to be easily read and modified by hand and to be forward compatible with possible future extensions.

Intended use

The OPF file format is meant to replace several other files:

- The LP file format: Any problem that can be written as an LP file can be written as an OPF file too; furthermore it naturally accommodates ranged constraints and variables as well as arbitrary characters in names, fixed expressions in the objective, empty constraints, and conic constraints.
- Parameter files: It is possible to specify integer, double and string parameters along with the problem (or in a separate OPF file).
- Solution files: It is possible to store a full or a partial solution in an OPF file and later reload it.

12.3.1 The File Format

The format uses tags to structure data. A simple example with the basic sections may look like this:

```
[comment]
This is a comment. You may write almost anything here...
[/comment]

# This is a single-line comment.

[objective min 'myobj']
x + 3 y + x^2 + 3 y^2 + z + 1
[/objective]

[constraints]
[con 'con01'] 4 <= x + y  [/con]
[/constraints]

[bounds]
[b] -10 <= x,y <= 10  [/b]

[cone quad] x,y,z [/cone]
[/bounds]
```

A scope is opened by a tag of the form `[tag]` and closed by a tag of the form `[/tag]`. An opening tag may accept a list of unnamed and named arguments, for examples:

```
[tag value] tag with one unnamed argument [/tag]
[tag arg=value] tag with one named argument in quotes [/tag]
```

Unnamed arguments are identified by their order, while named arguments may appear in any order, but never before an unnamed argument. The `value` can be a quoted, single-quoted or double-quoted text string, i.e.

```
[tag 'value']      single-quoted value [/tag]
[tag arg='value']  single-quoted value [/tag]
[tag "value"]      double-quoted value [/tag]
[tag arg="value"]  double-quoted value [/tag]
```

Sections

The recognized tags are

[comment]

A comment section. This can contain *almost* any text: Between single quotes (') or double quotes (") any text may appear. Outside quotes the markup characters ([and]) must be prefixed by backslashes. Both single and double quotes may appear alone or inside a pair of quotes if it is prefixed by a backslash.

[objective]

The objective function: This accepts one or two parameters, where the first one (in the above example `min`) is either `min` or `max` (regardless of case) and defines the objective sense, and the second one (above `myobj`), if present, is the objective name. The section may contain linear and quadratic expressions. If several objectives are specified, all but the last are ignored.

[constraints]

This does not directly contain any data, but may contain the subsection `con` defining a linear constraint.

[`con`] defines a single constraint; if an argument is present ([`con NAME`]) this is used as the name of the constraint, otherwise it is given a null-name. The section contains a constraint definition written as linear and quadratic expressions with a lower bound, an upper bound, with both or with an equality. Examples:

```
[constraints]
[con 'con1'] 0 <= x + y      [/con]
[con 'con2'] 0 >= x + y      [/con]
[con 'con3'] 0 <= x + y <= 10 [/con]
[con 'con4']      x + y = 10 [/con]
[/constraints]
```

Constraint names are unique. If a constraint is specified which has the same name as a previously defined constraint, the new constraint replaces the existing one.

[bounds]

This does not directly contain any data, but may contain the subsections `b` (linear bounds on variables) and `cone` (quadratic cone).

[`b`]. Bound definition on one or several variables separated by comma (,). An upper or lower bound on a variable replaces any earlier defined bound on that variable. If only one bound (upper or lower) is given only this bound is replaced. This means that upper and lower bounds can be specified separately. So the OPF bound definition:

```
[b] x,y >= -10 [/b]
[b] x,y <= 10  [/b]
```

results in the bound $-10 \leq x, y \leq 10$.

[`cone`]. currently supports the *quadratic cone* and the *rotated quadratic cone*.

A conic constraint is defined as a set of variables which belong to a single unique cone.

- A quadratic cone of n variables x_1, \dots, x_n defines a constraint of the form

$$x_1^2 > \sum_{i=2}^n x_i^2.$$

- A rotated quadratic cone of n variables x_1, \dots, x_n defines a constraint of the form

$$x_1 x_2 > \sum_{i=3}^n x_i^2.$$

A `[bounds]`-section example:

```
[bounds]
[b]  0 <= x,y <= 10  [/b] # ranged bound
[b] 10 >= x,y >=  0  [/b] # ranged bound
[b]  0 <= x,y <= inf [/b] # using inf
[b]      x,y free    [/b] # free variables
# Let (x,y,z,w) belong to the cone K
[cone quad] x,y,z,w  [/cone] # quadratic cone
[cone rquad] x,y,z,w [/cone] # rotated quadratic cone
[/bounds]
```

By default all variables are free.

`[variables]`

This defines an ordering of variables as they should appear in the problem. This is simply a space-separated list of variable names.

`[integer]`

This contains a space-separated list of variables and defines the constraint that the listed variables must be integer values.

`[hints]`

This may contain only non-essential data; for example estimates of the number of variables, constraints and non-zeros. Placed before all other sections containing data this may reduce the time spent reading the file.

In the `hints` section, any subsection which is not recognized by **MOSEK** is simply ignored. In this section a hint in a subsection is defined as follows:

```
[hint ITEM] value [/hint]
```

where `ITEM` may be replaced by `numvar` (number of variables), `numcon` (number of linear/quadratic constraints), `numanz` (number of linear non-zeros in constraints) and `numqnz` (number of quadratic non-zeros in constraints).

`[solutions]`

This section can contain a set of full or partial solutions to a problem. Each solution must be specified using a `[solution]`-section, i.e.

```
[solutions]
[solution]...[/solution] #solution 1
[solution]...[/solution] #solution 2
#other solutions....
[solution]...[/solution] #solution n
[/solutions]
```

Note that a `[solution]`-section must be always specified inside a `[solutions]`-section. The syntax of a `[solution]`-section is the following:

```
[solution SOLTYPE status=STATUS]...[/solution]
```

where `SOLTYPE` is one of the strings

- `interior`, a non-basic solution,
- `basic`, a basic solution,
- `integer`, an integer solution,

and `STATUS` is one of the strings

- `UNKNOWN`,
- `OPTIMAL`,
- `INTEGER_OPTIMAL`,
- `PRIM_FEAS`,
- `DUAL_FEAS`,
- `PRIM_AND_DUAL_FEAS`,
- `NEAR_OPTIMAL`,
- `NEAR_PRIM_FEAS`,
- `NEAR_DUAL_FEAS`,
- `NEAR_PRIM_AND_DUAL_FEAS`,
- `PRIM_INFEAS_CER`,
- `DUAL_INFEAS_CER`,
- `NEAR_PRIM_INFEAS_CER`,
- `NEAR_DUAL_INFEAS_CER`,
- `NEAR_INTEGER_OPTIMAL`.

Most of these values are irrelevant for input solutions; when constructing a solution for simplex hot-start or an initial solution for a mixed integer problem the safe setting is `UNKNOWN`.

A `[solution]`-section contains `[con]` and `[var]` sections. Each `[con]` and `[var]` section defines solution information for a single variable or constraint, specified as list of `KEYWORD/value` pairs, in any order, written as

```
KEYWORD=value
```

Allowed keywords are as follows:

- `sk`. The status of the item, where the `value` is one of the following strings:
 - `LOW`, the item is on its lower bound.
 - `UPR`, the item is on its upper bound.
 - `FIX`, it is a fixed item.
 - `BAS`, the item is in the basis.

- SUPBAS, the item is super basic.
- UNK, the status is unknown.
- INF, the item is outside its bounds (infeasible).
- **lv1** Defines the level of the item.
- **s1** Defines the level of the dual variable associated with its lower bound.
- **su** Defines the level of the dual variable associated with its upper bound.
- **sn** Defines the level of the variable associated with its cone.
- **y** Defines the level of the corresponding dual variable (for constraints only).

A **[var]** section should always contain the items **sk**, **lv1**, **s1** and **su**. Items **s1** and **su** are not required for **integer** solutions.

A **[con]** section should always contain **sk**, **lv1**, **s1**, **su** and **y**.

An example of a solution section

```
[solution basic status=UNKNOWN]
[var x0] sk=LOW    lv1=5.0      [/var]
[var x1] sk=UPR    lv1=10.0     [/var]
[var x2] sk=SUPBAS lv1=2.0    s1=1.5 su=0.0 [/var]

[con c0] sk=LOW    lv1=3.0 y=0.0 [/con]
[con c0] sk=UPR    lv1=0.0 y=5.0 [/con]
[/solution]
```

- **[vendor]** This contains solver/vendor specific data. It accepts one argument, which is a vendor ID – for **MOSEK** the ID is simply **mosek** – and the section contains the subsection **parameters** defining solver parameters. When reading a vendor section, any unknown vendor can be safely ignored. This is described later.

Comments using the **#** may appear anywhere in the file. Between the **#** and the following line-break any text may be written, including markup characters.

Numbers

Numbers, when used for parameter values or coefficients, are written in the usual way by the **printf** function. That is, they may be prefixed by a sign (+ or -) and may contain an integer part, decimal part and an exponent. The decimal point is always **.** (a dot). Some examples are

```
1
1.0
.0
1.
1e10
1e+10
1e-10
```

Some *invalid* examples are

```
e10 # invalid, must contain either integer or decimal part
.   # invalid
.e10 # invalid
```

More formally, the following standard regular expression describes numbers as used:

```
[+|-]?([0-9]+[.][0-9]*|.[0-9]+)([eE][+|-]?[0-9]+)?
```

Names

Variable names, constraint names and objective name may contain arbitrary characters, which in some cases must be enclosed by quotes (single or double) that in turn must be preceded by a backslash. Unquoted names must begin with a letter (a-z or A-Z) and contain only the following characters: the letters a-z and A-Z, the digits 0-9, braces { and } and underscore (_).

Some examples of legal names:

```
an_unquoted_name
another_name{123}
'single quoted name'
"double quoted name"
"name with \"quote\" in it"
"name with []s in it"
```

12.3.2 Parameters Section

In the `vendor` section solver parameters are defined inside the `parameters` subsection. Each parameter is written as

```
[p PARAMETER_NAME] value [/p]
```

where `PARAMETER_NAME` is replaced by a **MOSEK** parameter name, usually of the form `MSK_IPAR_...`, `MSK_DPAR_...` or `MSK_SPAR_...`, and the `value` is replaced by the value of that parameter; both integer values and named values may be used. Some simple examples are

```
[vendor mosek]
[parameters]
[p MSK_IPAR_OPF_MAX_TERMS_PER_LINE] 10      [/p]
[p MSK_IPAR_OPF_WRITE_PARAMETERS]    MSK_ON [/p]
[p MSK_DPAR_DATA_TOL_BOUND_INF]      1.0e18 [/p]
[/parameters]
[/vendor]
```

12.3.3 Writing OPF Files from MOSEK

To write an OPF file set the parameter `MSK_IPAR_WRITE_DATA_FORMAT` to `MSK_DATA_FORMAT_OP` as this ensures that OPF format is used.

Then modify the following parameters to define what the file should contain:

<code>MSK_IPAR_OPF_WRITE_SOL_BAS</code>	Include basic solution, if defined.
<code>MSK_IPAR_OPF_WRITE_SOL_ITG</code>	Include integer solution, if defined.
<code>MSK_IPAR_OPF_WRITE_SOL_ITR</code>	Include interior solution, if defined.
<code>MSK_IPAR_OPF_WRITE_SOLUTIONS</code>	Include solutions if they are defined. If this is off, no solutions are included.
<code>MSK_IPAR_OPF_WRITE_HEADER</code>	Include a small header with comments.
<code>MSK_IPAR_OPF_WRITE_PROBLEM</code>	Include the problem itself — objective, constraints and bounds.
<code>MSK_IPAR_OPF_WRITE_PARAMETERS</code>	Include all parameter settings.
<code>MSK_IPAR_OPF_WRITE_HINTS</code>	Include hints about the size of the problem.

12.3.4 Examples

This section contains a set of small examples written in OPF and describing how to formulate linear, quadratic and conic problems.

Linear Example lo1.opf

Consider the example:

$$\begin{array}{llllll} \text{maximize} & 3x_0 & + & 1x_1 & + & 5x_2 & + & 1x_3 \\ \text{subject to} & 3x_0 & + & 1x_1 & + & 2x_2 & & = & 30, \\ & 2x_0 & + & 1x_1 & + & 3x_2 & + & 1x_3 & \geq & 15, \\ & & & 2x_1 & & & + & 3x_3 & \leq & 25, \end{array}$$

having the bounds

$$\begin{array}{llll} 0 & \leq & x_0 & \leq \infty, \\ 0 & \leq & x_1 & \leq 10, \\ 0 & \leq & x_2 & \leq \infty, \\ 0 & \leq & x_3 & \leq \infty. \end{array}$$

In the OPF format the example is displayed as shown in [Listing 12.1](#).

Listing 12.1: Example of an OPF file for a linear problem.

```
[comment]
  The lo1 example in OPF format
[/comment]

[hints]
  [hint NUMVAR] 4 [/hint]
  [hint NUMCON] 3 [/hint]
  [hint NUMANZ] 9 [/hint]
[/hints]

[variables disallow_new_variables]
  x1 x2 x3 x4
[/variables]

[objective maximize 'obj']
  3 x1 + x2 + 5 x3 + x4
[/objective]

[constraints]
  [con 'c1'] 3 x1 + x2 + 2 x3 = 30 [/con]
  [con 'c2'] 2 x1 + x2 + 3 x3 + x4 >= 15 [/con]
  [con 'c3'] 2 x2 + 3 x4 <= 25 [/con]
[/constraints]

[bounds]
  [b] 0 <= * [/b]
  [b] 0 <= x2 <= 10 [/b]
[/bounds]
```

Quadratic Example qo1.opf

An example of a quadratic optimization problem is

$$\begin{array}{ll} \text{minimize} & x_1^2 + 0.1x_2^2 + x_3^2 - x_1x_3 - x_2 \\ \text{subject to} & 1 \leq x_1 + x_2 + x_3, \\ & x \geq 0. \end{array}$$

This can be formulated in opf as shown below.

Listing 12.2: Example of an OPF file for a quadratic problem.

```
[comment]
  The qo1 example in OPF format
[/comment]

[hints]
  [hint NUMVAR] 3 [/hint]
  [hint NUMCON] 1 [/hint]
  [hint NUMANZ] 3 [/hint]
  [hint NUMQNZ] 4 [/hint]
[/hints]

[variables disallow_new_variables]
  x1 x2 x3
[/variables]

[objective minimize 'obj']
  # The quadratic terms are often written with a factor of 1/2 as here,
  # but this is not required.

  - x2 + 0.5 ( 2.0 x1 ^ 2 - 2.0 x3 * x1 + 0.2 x2 ^ 2 + 2.0 x3 ^ 2 )
[/objective]

[constraints]
  [con 'c1'] 1.0 <= x1 + x2 + x3 [/con]
[/constraints]

[bounds]
  [b] 0 <= * [/b]
[/bounds]
```

Conic Quadratic Example cqo1.opf

Consider the example:

$$\begin{aligned}
 &\text{minimize} && x_3 + x_4 + x_5 \\
 &\text{subject to} && x_0 + x_1 + 2x_2 = 1, \\
 & && x_0, x_1, x_2 \geq 0, \\
 & && x_3 \geq \sqrt{x_0^2 + x_1^2}, \\
 & && 2x_4x_5 \geq x_2^2.
 \end{aligned}$$

Please note that the type of the cones is defined by the parameter to `[cone ...]`; the content of the cone-section is the names of variables that belong to the cone. The resulting OPF file is in [Listing 12.3](#).

Listing 12.3: Example of an OPF file for a conic quadratic problem.

```
[comment]
  The cqo1 example in OPF format.
[/comment]

[hints]
  [hint NUMVAR] 6 [/hint]
  [hint NUMCON] 1 [/hint]
  [hint NUMANZ] 3 [/hint]
[/hints]

[variables disallow_new_variables]
  x1 x2 x3 x4 x5 x6
[/variables]
```

```

[objective minimize 'obj']
  x4 + x5 + x6
[/objective]

[constraints]
  [con 'c1']  x1 + x2 + 2e+00 x3 = 1e+00 [/con]
[/constraints]

[bounds]
  # We let all variables default to the positive orthant
  [b] 0 <= * [/b]

  # ...and change those that differ from the default
  [b] x4,x5,x6 free [/b]

  # Define quadratic cone:  $x_4 \geq \sqrt{x_1^2 + x_2^2}$ 
  [cone quad 'k1'] x4, x1, x2 [/cone]

  # Define rotated quadratic cone:  $2 x_5 x_6 \geq x_3^2$ 
  [cone rquad 'k2'] x5, x6, x3 [/cone]
[/bounds]

```

Mixed Integer Example `mil01.opf`

Consider the mixed integer problem:

$$\begin{aligned}
 &\text{maximize} && x_0 + 0.64x_1 \\
 &\text{subject to} && 50x_0 + 31x_1 \leq 250, \\
 & && 3x_0 - 2x_1 \geq -4, \\
 & && x_0, x_1 \geq 0 \quad \text{and integer}
 \end{aligned}$$

This can be implemented in OPF with the file in [Listing 12.4](#).

Listing 12.4: Example of an OPF file for a mixed-integer linear problem.

```

[comment]
  The mil01 example in OPF format
[/comment]

[hints]
  [hint NUMVAR] 2 [/hint]
  [hint NUMCON] 2 [/hint]
  [hint NUMANZ] 4 [/hint]
[/hints]

[variables disallow_new_variables]
  x1 x2
[/variables]

[objective maximize 'obj']
  x1 + 6.4e-1 x2
[/objective]

[constraints]
  [con 'c1'] 5e+1 x1 + 3.1e+1 x2 <= 2.5e+2 [/con]
  [con 'c2'] -4 <= 3 x1 - 2 x2 [/con]
[/constraints]

[bounds]
  [b] 0 <= * [/b]
[/bounds]

```

```
[integer]
  x1 x2
[/integer]
```

12.4 The CBF Format

This document constitutes the technical reference manual of the *Conic Benchmark Format* with file extension: `.cbf` or `.CBF`. It unifies linear, second-order cone (also known as conic quadratic) and semidefinite optimization with mixed-integer variables. The format has been designed with benchmark libraries in mind, and therefore focuses on compact and easily parsable representations. The problem structure is separated from the problem data, and the format moreover facilitates benchmarking of hotstart capability through sequences of changes.

12.4.1 How Instances Are Specified

This section defines the spectrum of conic optimization problems that can be formulated in terms of the keywords of the CBF format.

In the CBF format, conic optimization problems are considered in the following form:

$$\begin{aligned}
 & \min / \max && g^{obj} \\
 & \text{s.t.} && \begin{aligned} & g_i \in \mathcal{K}_i, & i \in \mathcal{I}, \\ & G_i \in \mathcal{K}_i, & i \in \mathcal{I}^{PSD}, \\ & x_j \in \mathcal{K}_j, & j \in \mathcal{J}, \\ & \bar{X}_j \in \mathcal{K}_j, & j \in \mathcal{J}^{PSD}. \end{aligned}
 \end{aligned} \tag{12.5}$$

- **Variables** are either scalar variables, x_j for $j \in \mathcal{J}$, or variables, \bar{X}_j for $j \in \mathcal{J}^{PSD}$. Scalar variables can also be declared as integer.
- **Constraints** are affine expressions of the variables, either scalar-valued g_i for $i \in \mathcal{I}$, or matrix-valued G_i for $i \in \mathcal{I}^{PSD}$

$$\begin{aligned}
 g_i &= \sum_{j \in \mathcal{J}^{PSD}} \langle F_{ij}, X_j \rangle + \sum_{j \in \mathcal{J}} a_{ij} x_j + b_i, \\
 G_i &= \sum_{j \in \mathcal{J}} x_j H_{ij} + D_i.
 \end{aligned}$$

- The **objective function** is a scalar-valued affine expression of the variables, either to be minimized or maximized. We refer to this expression as g^{obj}

$$g^{obj} = \sum_{j \in \mathcal{J}^{PSD}} \langle F_j^{obj}, X_j \rangle + \sum_{j \in \mathcal{J}} a_j^{obj} x_j + b^{obj}.$$

CBF format can represent the following cones \mathcal{K} :

- **Free domain** - A cone in the linear family defined by

$$\{x \in \mathbb{R}^n\}, \text{ for } n \geq 1.$$

- **Positive orthant** - A cone in the linear family defined by

$$\{x \in \mathbb{R}^n \mid x_j \geq 0 \text{ for } j = 1, \dots, n\}, \text{ for } n \geq 1.$$

- **Negative orthant** - A cone in the linear family defined by

$$\{x \in \mathbb{R}^n \mid x_j \leq 0 \text{ for } j = 1, \dots, n\}, \text{ for } n \geq 1.$$

- **Fixpoint zero** - A cone in the linear family defined by

$$\{x \in \mathbb{R}^n \mid x_j = 0 \text{ for } j = 1, \dots, n\}, \text{ for } n \geq 1.$$

- **Quadratic cone** - A cone in the second-order cone family defined by

$$\left\{ \begin{pmatrix} p \\ x \end{pmatrix} \in \mathbb{R} \times \mathbb{R}^{n-1}, p^2 \geq x^T x, p \geq 0 \right\}, \text{ for } n \geq 2.$$

- **Rotated quadratic cone** - A cone in the second-order cone family defined by

$$\left\{ \begin{pmatrix} p \\ q \\ x \end{pmatrix} \in \mathbb{R} \times \mathbb{R} \times \mathbb{R}^{n-2}, 2pq \geq x^T x, p \geq 0, q \geq 0 \right\}, \text{ for } n \geq 3.$$

12.4.2 The Structure of CBF Files

This section defines how information is written in the CBF format, without being specific about the type of information being communicated.

All information items belong to exactly one of the three groups of information. These information groups, and the order they must appear in, are:

1. File format.
2. Problem structure.
3. Problem data.

The first group, file format, provides information on how to interpret the file. The second group, problem structure, provides the information needed to deduce the type and size of the problem instance. Finally, the third group, problem data, specifies the coefficients and constants of the problem instance.

Information items

The format is composed as a list of information items. The first line of an information item is the **KEYWORD**, revealing the type of information provided. The second line - of some keywords only - is the **HEADER**, typically revealing the size of information that follows. The remaining lines are the **BODY** holding the actual information to be specified.

KEYWORD
BODY
KEYWORD
HEADER
BODY

The **KEYWORD** determines how each line in the **HEADER** and **BODY** is structured. Moreover, the number of lines in the **BODY** follows either from the **KEYWORD**, the **HEADER**, or from another information item required to precede it.

Embedded hotstart-sequences

A sequence of problem instances, based on the same problem structure, is within a single file. This is facilitated via the **CHANGE** within the problem data information group, as a separator between the information items of each instance. The information items following a **CHANGE** keyword are appending to, or changing (e.g., setting coefficients back to their default value of zero), the problem data of the preceding instance.

The sequence is intended for benchmarking of hotstart capability, where the solvers can reuse their internal state and solution (subject to the achieved accuracy) as warmpoint for the succeeding instance. Whenever this feature is unsupported or undesired, the keyword **CHANGE** should be interpreted as the end of file.

File encoding and line width restrictions

The format is based on the US-ASCII printable character set with two extensions as listed below. Note, by definition, that none of these extensions can be misinterpreted as printable US-ASCII characters:

- A line feed marks the end of a line, carriage returns are ignored.
- Comment-lines may contain unicode characters in UTF-8 encoding.

The line width is restricted to 512 bytes, with 3 bytes reserved for the potential carriage return, line feed and null-terminator.

Integers and floating point numbers must follow the ISO C decimal string representation in the standard C locale. The format does not impose restrictions on the magnitude of, or number of significant digits in numeric data, but the use of 64-bit integers and 64-bit IEEE 754 floating point numbers should be sufficient to avoid loss of precision.

Comment-line and whitespace rules

The format allows single-line comments respecting the following rule:

- Lines having first byte equal to '#' (US-ASCII 35) are comments, and should be ignored. Comments are only allowed between information items.

Given that a line is not a comment-line, whitespace characters should be handled according to the following rules:

- Leading and trailing whitespace characters should be ignored.
 - The separator between multiple pieces of information on one line, is either one or more whitespace characters.
- Lines containing only whitespace characters are empty, and should be ignored. Empty lines are only allowed between information items.

12.4.3 Problem Specification

The problem structure

The problem structure defines the objective sense, whether it is minimization and maximization. It also defines the index sets, \mathcal{J} , \mathcal{J}^{PSD} , \mathcal{I} and \mathcal{I}^{PSD} , which are all numbered from zero, $\{0, 1, \dots\}$, and empty until explicitly constructed.

- **Scalar variables** are constructed in vectors restricted to a conic domain, such as $(x_0, x_1) \in \mathbb{R}_+^2$, $(x_2, x_3, x_4) \in \mathcal{Q}^3$, etc. In terms of the Cartesian product, this generalizes to

$$x \in \mathcal{K}_1^{n_1} \times \mathcal{K}_2^{n_2} \times \dots \times \mathcal{K}_k^{n_k}$$

which in the CBF format becomes:

```
VAR
n k
K1 n1
K2 n2
...
Kk nk
```

where $\sum_i n_i = n$ is the total number of scalar variables. The list of supported cones is found in [Table 12.3](#). Integrality of scalar variables can be specified afterwards.

- **PSD variables** are constructed one-by-one. That is, $X_j \succeq \mathbf{0}^{n_j \times n_j}$ for $j \in \mathcal{J}^{PSD}$, constructs a matrix-valued variable of size $n_j \times n_j$ restricted to be symmetric positive semidefinite. In the CBF format, this list of constructions becomes:

```
PSDVAR
N
n1
n2
...
nN
```

where N is the total number of PSD variables.

- **Scalar constraints** are constructed in vectors restricted to a conic domain, such as $(g_0, g_1) \in \mathbb{R}_+^2$, $(g_2, g_3, g_4) \in \mathcal{Q}^3$, etc. In terms of the Cartesian product, this generalizes to

$$g \in \mathcal{K}_1^{m_1} \times \mathcal{K}_2^{m_2} \times \dots \times \mathcal{K}_k^{m_k}$$

which in the CBF format becomes:

```
CON
m k
K1 m1
K2 m2
..
Kk mk
```

where $\sum_i m_i = m$ is the total number of scalar constraints. The list of supported cones is found in [Table 12.3](#).

- **PSD constraints** are constructed one-by-one. That is, $G_i \succeq \mathbf{0}^{m_i \times m_i}$ for $i \in \mathcal{I}^{PSD}$, constructs a matrix-valued affine expressions of size $m_i \times m_i$ restricted to be symmetric positive semidefinite. In the CBF format, this list of constructions becomes

```
PSDCON
M
m1
m2
..
mM
```

where M is the total number of PSD constraints.

With the objective sense, variables (with integer indications) and constraints, the definitions of the many affine expressions follow in problem data.

Problem data

The problem data defines the coefficients and constants of the affine expressions of the problem instance. These are considered zero until explicitly defined, implying that instances with no keywords from this

information group are, in fact, valid. Duplicating or conflicting information is a failure to comply with the standard. Consequently, two coefficients written to the same position in a matrix (or to transposed positions in a symmetric matrix) is an error.

The affine expressions of the objective, g^{obj} , of the scalar constraints, g_i , and of the PSD constraints, G_i , are defined separately. The following notation uses the standard trace inner product for matrices, $\langle X, Y \rangle = \sum_{i,j} X_{ij}Y_{ij}$.

- The affine expression of the objective is defined as

$$g^{obj} = \sum_{j \in \mathcal{J}^{PSD}} \langle F_j^{obj}, X_j \rangle + \sum_{j \in \mathcal{J}} a_j^{obj} x_j + b^{obj},$$

in terms of the symmetric matrices, F_j^{obj} , and scalars, a_j^{obj} and b^{obj} .

- The affine expressions of the scalar constraints are defined, for $i \in \mathcal{I}$, as

$$g_i = \sum_{j \in \mathcal{J}^{PSD}} \langle F_{ij}, X_j \rangle + \sum_{j \in \mathcal{J}} a_{ij} x_j + b_i,$$

in terms of the symmetric matrices, F_{ij} , and scalars, a_{ij} and b_i .

- The affine expressions of the PSD constraints are defined, for $i \in \mathcal{I}^{PSD}$, as

$$G_i = \sum_{j \in \mathcal{J}} x_j H_{ij} + D_i,$$

in terms of the symmetric matrices, H_{ij} and D_i .

List of cones

The format uses an explicit syntax for symmetric positive semidefinite cones as shown above. For scalar variables and constraints, constructed in vectors, the supported conic domains and their minimum sizes are given as follows.

Table 12.3: Cones available in the CBF format

Name	CBF keyword	Cone family
Free domain	F	linear
Positive orthant	L+	linear
Negative orthant	L-	linear
Fixpoint zero	L=	linear
Quadratic cone	Q	second-order
Rotated quadratic cone	QR	second-order

12.4.4 File Format Keywords

VER

Description: The version of the Conic Benchmark Format used to write the file.

HEADER: None

BODY: One line formatted as:

INT

This is the version number.

Must appear exactly once in a file, as the first keyword.

OBJSENSE

Description: Define the objective sense.

HEADER: None

BODY: One line formatted as:

STR

having MIN indicates minimize, and MAX indicates maximize. Capital letters are required.

Must appear exactly once in a file.

PSDVAR

Description: Construct the PSD variables.

HEADER: One line formatted as:

INT

This is the number of PSD variables in the problem.

BODY: A list of lines formatted as:

INT

This indicates the number of rows (equal to the number of columns) in the matrix-valued PSD variable. The number of lines should match the number stated in the header.

VAR

Description: Construct the scalar variables.

HEADER: One line formatted as:

INT INT

This is the number of scalar variables, followed by the number of conic domains they are restricted to.

BODY: A list of lines formatted as:

STR INT

This indicates the cone name (see [Table 12.3](#)), and the number of scalar variables restricted to this cone. These numbers should add up to the number of scalar variables stated first in the header. The number of lines should match the second number stated in the header.

INT

Description: Declare integer requirements on a selected subset of scalar variables.

HEADER: one line formatted as:

INT

This is the number of integer scalar variables in the problem.

BODY: a list of lines formatted as:

INT

This indicates the scalar variable index $j \in \mathcal{J}$. The number of lines should match the number stated in the header.

Can only be used after the keyword **VAR**.

PSDCON

Description: Construct the PSD constraints.

HEADER: One line formatted as:

INT

This is the number of PSD constraints in the problem.

BODY: A list of lines formatted as:

INT

This indicates the number of rows (equal to the number of columns) in the matrix-valued affine expression of the PSD constraint. The number of lines should match the number stated in the header.

Can only be used after these keywords: **PSDVAR**, **VAR**.

CON

Description: Construct the scalar constraints.

HEADER: One line formatted as:

INT INT

This is the number of scalar constraints, followed by the number of conic domains they restrict to.

BODY: A list of lines formatted as:

STR INT

This indicates the cone name (see [Table 12.3](#)), and the number of affine expressions restricted to this cone. These numbers should add up to the number of scalar constraints stated first in the header. The number of lines should match the second number stated in the header.

Can only be used after these keywords: **PSDVAR**, **VAR**

OBJFCOORD

Description: Input sparse coordinates (quadruplets) to define the symmetric matrices F_j^{obj} , as used in the objective.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT INT INT REAL

This indicates the PSD variable index $j \in \mathcal{J}^{PSD}$, the row index, the column index and the coefficient value. The number of lines should match the number stated in the header.

OBJACOORD

Description: Input sparse coordinates (pairs) to define the scalars, a_j^{obj} , as used in the objective.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT REAL

This indicates the scalar variable index $j \in \mathcal{J}$ and the coefficient value. The number of lines should match the number stated in the header.

OBJBCOORD

Description: Input the scalar, b^{obj} , as used in the objective.

HEADER: None.

BODY: One line formatted as:

REAL

This indicates the coefficient value.

FCOORD

Description: Input sparse coordinates (quintuplets) to define the symmetric matrices, F_{ij} , as used in the scalar constraints.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT INT INT INT REAL

This indicates the scalar constraint index $i \in \mathcal{I}$, the PSD variable index $j \in \mathcal{J}^{PSD}$, the row index, the column index and the coefficient value. The number of lines should match the number stated in the header.

ACOORD

Description: Input sparse coordinates (triplets) to define the scalars, a_{ij} , as used in the scalar constraints.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT INT REAL

This indicates the scalar constraint index $i \in \mathcal{I}$, the scalar variable index $j \in \mathcal{J}$ and the coefficient value. The number of lines should match the number stated in the header.

BCOORD

Description: Input sparse coordinates (pairs) to define the scalars, b_i , as used in the scalar constraints.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT REAL

This indicates the scalar constraint index $i \in \mathcal{I}$ and the coefficient value. The number of lines should match the number stated in the header.

HCOORD

Description: Input sparse coordinates (quintuplets) to define the symmetric matrices, H_{ij} , as used in the PSD constraints.

HEADER: One line formatted as:

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as

INT INT INT INT REAL

This indicates the PSD constraint index $i \in \mathcal{I}^{PSD}$, the scalar variable index $j \in \mathcal{J}$, the row index, the column index and the coefficient value. The number of lines should match the number stated in the header.

DCOORD

Description: Input sparse coordinates (quadruplets) to define the symmetric matrices, D_i , as used in the PSD constraints.

HEADER: One line formatted as

INT

This is the number of coordinates to be specified.

BODY: A list of lines formatted as:

INT INT INT REAL

This indicates the PSD constraint index $i \in \mathcal{I}^{PSD}$, the row index, the column index and the coefficient value. The number of lines should match the number stated in the header.

CHANGE

Start of a new instance specification based on changes to the previous. Can be interpreted as the end of file when the hotstart-sequence is unsupported or undesired.

BODY: None

Header: None

12.4.5 CBF Format Examples

Minimal Working Example

The conic optimization problem (12.6), has three variables in a quadratic cone - first one is integer - and an affine expression in domain 0 (equality constraint).

$$\begin{aligned} & \text{minimize} && 5.1 x_0 \\ & \text{subject to} && 6.2 x_1 + 7.3 x_2 - 8.4 \in \{0\} \\ & && x \in \mathcal{Q}^3, x_0 \in \mathbb{Z}. \end{aligned} \tag{12.6}$$

Its formulation in the Conic Benchmark Format begins with the version of the CBF format used, to safeguard against later revisions.

```
VER
1
```

Next follows the problem structure, consisting of the objective sense, the number and domain of variables, the indices of integer variables, and the number and domain of scalar-valued affine expressions (i.e., the equality constraint).

```
OBJSENSE
MIN

VAR
3 1
Q 3

INT
1
0

CON
1 1
L= 1
```

Finally follows the problem data, consisting of the coefficients of the objective, the coefficients of the constraints, and the constant terms of the constraints. All data is specified on a sparse coordinate form.

```
OBJACOORD
1
0 5.1

ACOORD
2
0 1 6.2
0 2 7.3

BCOORD
1
0 -8.4
```

This concludes the example.

Mixing Linear, Second-order and Semidefinite Cones

The conic optimization problem (12.7), has a semidefinite cone, a quadratic cone over unordered subindices, and two equality constraints.

$$\begin{aligned}
 & \text{minimize} && \left\langle \begin{bmatrix} 2 & 1 & 0 \\ 1 & 2 & 1 \\ 0 & 1 & 2 \end{bmatrix}, X_1 \right\rangle + x_1 \\
 & \text{subject to} && \left\langle \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}, X_1 \right\rangle + x_1 &= 1.0, \\
 & && \left\langle \begin{bmatrix} 1 & 1 & 1 \\ 1 & 1 & 1 \\ 1 & 1 & 1 \end{bmatrix}, X_1 \right\rangle + x_0 + x_2 &= 0.5, \\
 & && x_1 \geq \sqrt{x_0^2 + x_2^2}, \\
 & && X_1 \succeq \mathbf{0}.
 \end{aligned} \tag{12.7}$$

The equality constraints are easily rewritten to the conic form, $(g_0, g_1) \in \{0\}^2$, by moving constants such that the right-hand-side becomes zero. The quadratic cone does not fit under the `VAR` keyword in this variable permutation. Instead, it takes a scalar constraint $(g_2, g_3, g_4) = (x_1, x_0, x_2) \in \mathcal{Q}^3$, with scalar variables constructed as $(x_0, x_1, x_2) \in \mathbb{R}^3$. Its formulation in the CBF format is reported in the following list

```

# File written using this version of the Conic Benchmark Format:
#   | Version 1.
VER
1

# The sense of the objective is:
#   | Minimize.
OBJSENSE
MIN

# One PSD variable of this size:
#   | Three times three.
PSDVAR
1
3

# Three scalar variables in this one conic domain:
#   | Three are free.
VAR
3 1
F 3

# Five scalar constraints with affine expressions in two conic domains:
#   | Two are fixed to zero.
#   | Three are in conic quadratic domain.
CON
5 2
L= 2
Q 3

# Five coordinates in F^{obj}_j coefficients:
#   | F^{obj}[0][0,0] = 2.0
#   | F^{obj}[0][1,0] = 1.0
#   | and more...
OBJFCOORD
5
0 0 0 2.0
0 1 0 1.0
0 1 1 2.0

```



```

0 2 1 1.0
0 2 2 2.0

# One coordinate in a^{obj}_j coefficients:
#   | a^{obj}[1] = 1.0
OBJCOORD
1
1 1.0

# Nine coordinates in F_ij coefficients:
#   | F[0,0][0,0] = 1.0
#   | F[0,0][1,1] = 1.0
#   | and more...
FCOORD
9
0 0 0 0 1.0
0 0 1 1 1.0
0 0 2 2 1.0
1 0 0 0 1.0
1 0 1 0 1.0
1 0 2 0 1.0
1 0 1 1 1.0
1 0 2 1 1.0
1 0 2 2 1.0

# Six coordinates in a_ij coefficients:
#   | a[0,1] = 1.0
#   | a[1,0] = 1.0
#   | and more...
ACCOORD
6
0 1 1.0
1 0 1.0
1 2 1.0
2 1 1.0
3 0 1.0
4 2 1.0

# Two coordinates in b_i coefficients:
#   | b[0] = -1.0
#   | b[1] = -0.5
BCCOORD
2
0 -1.0
1 -0.5

```

Mixing Semidefinite Variables and Linear Matrix Inequalities

The standard forms in semidefinite optimization are usually based either on semidefinite variables or linear matrix inequalities. In the CBF format, both forms are supported and can even be mixed as shown in.

$$\begin{aligned}
 & \text{minimize} && \left\langle \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}, X_1 \right\rangle + x_1 + x_2 + 1 \\
 & \text{subject to} && \left\langle \begin{bmatrix} 0 & 1 \\ 1 & 0 \end{bmatrix}, X_1 \right\rangle - x_1 - x_2 \geq 0.0, \\
 & && x_1 \begin{bmatrix} 0 & 1 \\ 1 & 3 \end{bmatrix} + x_2 \begin{bmatrix} 3 & 1 \\ 1 & 0 \end{bmatrix} - \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix} \succeq \mathbf{0}, \\
 & && X_1 \succeq \mathbf{0}.
 \end{aligned} \tag{12.8}$$

Its formulation in the CBF format is written in what follows

```
# File written using this version of the Conic Benchmark Format:
#       | Version 1.
VER
1

# The sense of the objective is:
#       | Minimize.
OBJSENSE
MIN

# One PSD variable of this size:
#       | Two times two.
PSDVAR
1
2

# Two scalar variables in this one conic domain:
#       | Two are free.
VAR
2 1
F 2

# One PSD constraint of this size:
#       | Two times two.
PSDCON
1
2

# One scalar constraint with an affine expression in this one conic domain:
#       | One is greater than or equal to zero.
CON
1 1
L+ 1

# Two coordinates in  $F^{\text{obj}}_j$  coefficients:
#       |  $F^{\text{obj}}[0][0,0] = 1.0$ 
#       |  $F^{\text{obj}}[0][1,1] = 1.0$ 
OBJFCOORD
2
0 0 0 1.0
0 1 1 1.0

# Two coordinates in  $a^{\text{obj}}_j$  coefficients:
#       |  $a^{\text{obj}}[0] = 1.0$ 
#       |  $a^{\text{obj}}[1] = 1.0$ 
OBJACOORD
2
0 1.0
1 1.0

# One coordinate in  $b^{\text{obj}}$  coefficient:
#       |  $b^{\text{obj}} = 1.0$ 
OBJBCOORD
1.0

# One coordinate in  $F_{ij}$  coefficients:
#       |  $F[0,0][1,0] = 1.0$ 
FCOORD
1
0 0 1 0 1.0

# Two coordinates in  $a_{ij}$  coefficients:
#       |  $a[0,0] = -1.0$ 
```

```
#      | a[0,1] = -1.0
ACCOORD
2
0 0 -1.0
0 1 -1.0

# Four coordinates in H_ij coefficients:
#      | H[0,0][1,0] = 1.0
#      | H[0,0][1,1] = 3.0
#      | and more...
HCOORD
4
0 0 1 0 1.0
0 0 1 1 3.0
0 1 0 0 3.0
0 1 1 0 1.0

# Two coordinates in D_i coefficients:
#      | D[0][0,0] = -1.0
#      | D[0][1,1] = -1.0
DCCOORD
2
0 0 0 -1.0
0 1 1 -1.0
```

Optimization Over a Sequence of Objectives

The linear optimization problem (12.9), is defined for a sequence of objectives such that hotstarting from one to the next might be advantages.

$$\begin{aligned}
 & \text{maximize}_k && g_k^{obj} \\
 & \text{subject to} && 50x_0 + 31 \leq 250, \\
 & && 3x_0 - 2x_1 \geq -4, \\
 & && x \in \mathbb{R}_+^2,
 \end{aligned} \tag{12.9}$$

given,

1. $g_0^{obj} = x_0 + 0.64x_1$.
2. $g_1^{obj} = 1.11x_0 + 0.76x_1$.
3. $g_2^{obj} = 1.11x_0 + 0.85x_1$.

Its formulation in the CBF format is reported in [Listing 12.5](#).

Listing 12.5: Problem (12.9) in CBF format.

```
# File written using this version of the Conic Benchmark Format:
#      | Version 1.
VER
1

# The sense of the objective is:
#      | Maximize.
OBJSENSE
MAX

# Two scalar variables in this one conic domain:
#      | Two are nonnegative.
VAR
2 1
L+ 2
```

```
# Two scalar constraints with affine expressions in these two conic domains:
#   | One is in the nonpositive domain.
#   | One is in the nonnegative domain.
CON
2 2
L- 1
L+ 1

# Two coordinates in a^{obj}_j coefficients:
#   | a^{obj}[0] = 1.0
#   | a^{obj}[1] = 0.64
OBJACCOORD
2
0 1.0
1 0.64

# Four coordinates in a_ij coefficients:
#   | a[0,0] = 50.0
#   | a[1,0] = 3.0
#   | and more...
ACCOORD
4
0 0 50.0
1 0 3.0
0 1 31.0
1 1 -2.0

# Two coordinates in b_i coefficients:
#   | b[0] = -250.0
#   | b[1] = 4.0
BCCOORD
2
0 -250.0
1 4.0

# New problem instance defined in terms of changes.
CHANGE

# Two coordinate changes in a^{obj}_j coefficients. Now it is:
#   | a^{obj}[0] = 1.11
#   | a^{obj}[1] = 0.76
OBJACCOORD
2
0 1.11
1 0.76

# New problem instance defined in terms of changes.
CHANGE

# One coordinate change in a^{obj}_j coefficients. Now it is:
#   | a^{obj}[0] = 1.11
#   | a^{obj}[1] = 0.85
OBJACCOORD
1
1 0.85
```

12.5 The XML (OSiL) Format

MOSEK can write data in the standard OSiL xml format. For a definition of the OSiL format please see <http://www.optimizationservices.org/>.

Only linear constraints (possibly with integer variables) are supported. By default output files with the extension `.xml` are written in the OSiL format.

The parameter `MSK_IPAR_WRITE_XML_MODE` controls if the linear coefficients in the A matrix are written in row or column order.

12.6 The Task Format

The Task format is **MOSEK**'s native binary format. It contains a complete image of a **MOSEK** task, i.e.

- Problem data: Linear, conic quadratic, semidefinite and quadratic data
- Problem item names: Variable names, constraints names, cone names etc.
- Parameter settings
- Solutions

There are a few things to be aware of:

- The task format *does not* support General Convex problems since these are defined by arbitrary user-defined functions.
- Status of a solution read from a file will *always* be unknown.

The format is based on the *TAR* (USTar) file format. This means that the individual pieces of data in a `.task` file can be examined by unpacking it as a *TAR* file. Please note that the inverse may not work: Creating a file using *TAR* will most probably not create a valid **MOSEK** Task file since the order of the entries is important.

12.7 The JSON Format

MOSEK provides the possibility to read/write problems in valid JSON format.

JSON (JavaScript Object Notation) is a lightweight data-interchange format. It is easy for humans to read and write. It is easy for machines to parse and generate. It is based on a subset of the JavaScript Programming Language, Standard ECMA-262 3rd Edition - December 1999. JSON is a text format that is completely language independent but uses conventions that are familiar to programmers of the C-family of languages, including C, C++, C#, Java, JavaScript, Perl, Python, and many others. These properties make JSON an ideal data-interchange language.

The official JSON website <http://www.json.org> provides plenty of information along with the format definition.

MOSEK defines two JSON-like formats:

- *jtask*
- *jsol*

Warning: Despite being text-based human-readable formats, *jtask* and *jsol* files will include no indentation and no new-lines, in order to keep the files as compact as possible. We therefore strongly advise to use JSON viewer tools to inspect *jtask* and *jsol* files.

12.7.1 *jtask* format

It stores a problem instance. The *jtask* format contains the same information as a *task format*.

Even though a *jtask* file is human-readable, we do not recommend users to create it by hand, but to rely on MOSEK.

12.7.2 *jsol* format

It stores a problem solution. The *jsol* format contains all solutions and information items.

12.7.3 A *jtask* example

In Listing 12.6 we present a file in the *jtask* format that corresponds to the sample problem from `lo1.lp`. The listing has been formatted for readability.

Listing 12.6: A formatted *jtask* file for the `lo1.lp` example.

```
{
  "$schema": "http://mosek.com/json/schema#",
  "Task/INFO": {
    "taskname": "lo1",
    "numvar": 4,
    "numcon": 3,
    "numcone": 0,
    "numbarvar": 0,
    "numanz": 9,
    "numsymmat": 0,
    "mosekver": [
      8,
      0,
      0,
      9
    ]
  },
  "Task/data": {
    "var": {
      "name": [
        "x1",
        "x2",
        "x3",
        "x4"
      ],
      "bk": [
        "lo",
        "ra",
        "lo",
        "lo"
      ],
      "b1": [
        0.0,
        0.0,
        0.0,
        0.0
      ],
      "bu": [
        1e+30,
        1e+1,
        1e+30,
        1e+30
      ]
    },
  },
}
```

```

        "type": [
            "cont",
            "cont",
            "cont",
            "cont"
        ],
    },
    "con": {
        "name": [
            "c1",
            "c2",
            "c3"
        ],
        "bk": [
            "fx",
            "lo",
            "up"
        ],
        "bl": [
            3e+1,
            1.5e+1,
            -1e+30
        ],
        "bu": [
            3e+1,
            1e+30,
            2.5e+1
        ]
    },
    "objective": {
        "sense": "max",
        "name": "obj",
        "c": {
            "subj": [
                0,
                1,
                2,
                3
            ],
            "val": [
                3e+0,
                1e+0,
                5e+0,
                1e+0
            ]
        }
    },
    "cfix": 0.0
},
"A": {
    "subi": [
        0,
        0,
        0,
        1,
        1,
        1,
        1,
        1,
        2,
        2
    ],
    "subj": [
        0,
        1,

```

```

        2,
        0,
        1,
        2,
        3,
        1,
        3
    ],
    "val": [
        3e+0,
        1e+0,
        2e+0,
        2e+0,
        1e+0,
        3e+0,
        1e+0,
        2e+0,
        3e+0
    ]
}
},
"Task/parameters": {
    "iparam": {
        "ANA_SOL_BASIS": "ON",
        "ANA_SOL_PRINT_VIOLATED": "OFF",
        "AUTO_SORT_A_BEFORE_OPT": "OFF",
        "AUTO_UPDATE_SOL_INFO": "OFF",
        "BASIS_SOLVE_USE_PLUS_ONE": "OFF",
        "BI_CLEAN_OPTIMIZER": "OPTIMIZER_FREE",
        "BI_IGNORE_MAX_ITER": "OFF",
        "BI_IGNORE_NUM_ERROR": "OFF",
        "BI_MAX_ITERATIONS": 1000000,
        "CACHE_LICENSE": "ON",
        "CHECK_CONVEXITY": "CHECK_CONVEXITY_FULL",
        "COMPRESS_STATFILE": "ON",
        "CONCURRENT_NUM_OPTIMIZERS": 2,
        "CONCURRENT_PRIORITY_DUAL_SIMPLEX": 2,
        "CONCURRENT_PRIORITY_FREE_SIMPLEX": 3,
        "CONCURRENT_PRIORITY_INTPNT": 4,
        "CONCURRENT_PRIORITY_PRIMAL_SIMPLEX": 1,
        "FEASREPAIR_OPTIMIZE": "FEASREPAIR_OPTIMIZE_NONE",
        "INFEAS_GENERIC_NAMES": "OFF",
        "INFEAS_PREFER_PRIMAL": "ON",
        "INFEAS_REPORT_AUTO": "OFF",
        "INFEAS_REPORT_LEVEL": 1,
        "INTPNT_BASIS": "BI_ALWAYS",
        "INTPNT_DIFF_STEP": "ON",
        "INTPNT_FACTOR_DEBUG_LVL": 0,
        "INTPNT_FACTOR_METHOD": 0,
        "INTPNT_HOTSTART": "INTPNT_HOTSTART_NONE",
        "INTPNT_MAX_ITERATIONS": 400,
        "INTPNT_MAX_NUM_COR": -1,
        "INTPNT_MAX_NUM_REFINEMENT_STEPS": -1,
        "INTPNT_OFF_COL_TRH": 40,
        "INTPNT_ORDER_METHOD": "ORDER_METHOD_FREE",
        "INTPNT_REGULARIZATION_USE": "ON",
        "INTPNT_SCALING": "SCALING_FREE",
        "INTPNT_SOLVE_FORM": "SOLVE_FREE",
        "INTPNT_STARTING_POINT": "STARTING_POINT_FREE",
        "LIC_TRH_EXPIRY_WRN": 7,
        "LICENSE_DEBUG": "OFF",
        "LICENSE_PAUSE_TIME": 0,
        "LICENSE_SUPPRESS_EXPIRE_WRNS": "OFF",
    }
}

```



```

"LICENSE_WAIT": "OFF",
"LOG": 10,
"LOG_ANA_PRO": 1,
"LOG_BI": 4,
"LOG_BI_FREQ": 2500,
"LOG_CHECK_CONVEXITY": 0,
"LOG_CONCURRENT": 1,
"LOG_CUT_SECOND_OPT": 1,
"LOG_EXPAND": 0,
"LOG_FACTOR": 1,
"LOG_FEAS_REPAIR": 1,
"LOG_FILE": 1,
"LOG_HEAD": 1,
"LOG_INFEAS_ANA": 1,
"LOG_INTPNT": 4,
"LOG_MIO": 4,
"LOG_MIO_FREQ": 1000,
"LOG_OPTIMIZER": 1,
"LOG_ORDER": 1,
"LOG_PRESOLVE": 1,
"LOG_RESPONSE": 0,
"LOG_SENSITIVITY": 1,
"LOG_SENSITIVITY_OPT": 0,
"LOG_SIM": 4,
"LOG_SIM_FREQ": 1000,
"LOG_SIM_MINOR": 1,
"LOG_STORAGE": 1,
"MAX_NUM_WARNINGS": 10,
"MIO_BRANCH_DIR": "BRANCH_DIR_FREE",
"MIO_CONSTRUCT_SOL": "OFF",
"MIO_CUT_CLIQUE": "ON",
"MIO_CUT_CMIR": "ON",
"MIO_CUT_GMI": "ON",
"MIO_CUT_KNAPSACK_COVER": "OFF",
"MIO_HEURISTIC_LEVEL": -1,
"MIO_MAX_NUM_BRANCHES": -1,
"MIO_MAX_NUM_RELAXS": -1,
"MIO_MAX_NUM_SOLUTIONS": -1,
"MIO_MODE": "MIO_MODE_SATISFIED",
"MIO_MT_USER_CB": "ON",
"MIO_NODE_OPTIMIZER": "OPTIMIZER_FREE",
"MIO_NODE_SELECTION": "MIO_NODE_SELECTION_FREE",
"MIO_PERSPECTIVE_REFORMULATE": "ON",
"MIO_PROBING_LEVEL": -1,
"MIO_RINS_MAX_NODES": -1,
"MIO_ROOT_OPTIMIZER": "OPTIMIZER_FREE",
"MIO_ROOT_REPEAT_PRESOLVE_LEVEL": -1,
"MT_SPINCOUNT": 0,
"NUM_THREADS": 0,
"OPF_MAX_TERMS_PER_LINE": 5,
"OPF_WRITE_HEADER": "ON",
"OPF_WRITE_HINTS": "ON",
"OPF_WRITE_PARAMETERS": "OFF",
"OPF_WRITE_PROBLEM": "ON",
"OPF_WRITE_SOL_BAS": "ON",
"OPF_WRITE_SOL_ITG": "ON",
"OPF_WRITE_SOL_ITR": "ON",
"OPF_WRITE_SOLUTIONS": "OFF",
"OPTIMIZER": "OPTIMIZER_FREE",
"PARAM_READ_CASE_NAME": "ON",
"PARAM_READ_IGN_ERROR": "OFF",
"PRESOLVE_ELIMINATOR_MAX_FILL": -1,
"PRESOLVE_ELIMINATOR_MAX_NUM_TRIES": -1,

```

```

"PRESOLVE_LEVEL":-1,
"PRESOLVE_LINDEP_ABS_WORK_TRH":100,
"PRESOLVE_LINDEP_REL_WORK_TRH":100,
"PRESOLVE_LINDEP_USE":"ON",
"PRESOLVE_MAX_NUM_REDUCATIONS":-1,
"PRESOLVE_USE":"PRESOLVE_MODE_FREE",
"PRIMAL_REPAIR_OPTIMIZER":"OPTIMIZER_FREE",
"QO_SEPARABLE_REFORMULATION":"OFF",
"READ_DATA_COMPRESSED":"COMPRESS_FREE",
"READ_DATA_FORMAT":"DATA_FORMAT_EXTENSION",
"READ_DEBUG":"OFF",
"READ_KEEP_FREE_CON":"OFF",
"READ_LP_DROP_NEW_VARS_IN_BOU":"OFF",
"READ_LP_QUOTED_NAMES":"ON",
"READ_MPS_FORMAT":"MPS_FORMAT_FREE",
"READ_MPS_WIDTH":1024,
"READ_TASK_IGNORE_PARAM":"OFF",
"SENSITIVITY_ALL":"OFF",
"SENSITIVITY_OPTIMIZER":"OPTIMIZER_FREE_SIMPLEX",
"SENSITIVITY_TYPE":"SENSITIVITY_TYPE_BASIS",
"SIM_BASIS_FACTOR_USE":"ON",
"SIM_DEGEN":"SIM_DEGEN_FREE",
"SIM_DUAL_CRASH":90,
"SIM_DUAL_PHASEONE_METHOD":0,
"SIM_DUAL_RESTRICT_SELECTION":50,
"SIM_DUAL_SELECTION":"SIM_SELECTION_FREE",
"SIM_EXPLOIT_DUPVEC":"SIM_EXPLOIT_DUPVEC_OFF",
"SIM_HOTSTART":"SIM_HOTSTART_FREE",
"SIM_HOTSTART_LU":"ON",
"SIM_INTEGER":0,
"SIM_MAX_ITERATIONS":10000000,
"SIM_MAX_NUM_SETBACKS":250,
"SIM_NON_SINGULAR":"ON",
"SIM_PRIMAL_CRASH":90,
"SIM_PRIMAL_PHASEONE_METHOD":0,
"SIM_PRIMAL_RESTRICT_SELECTION":50,
"SIM_PRIMAL_SELECTION":"SIM_SELECTION_FREE",
"SIM_REFACTOR_FREQ":0,
"SIM_REFORMULATION":"SIM_REFORMULATION_OFF",
"SIM_SAVE_LU":"OFF",
"SIM_SCALING":"SCALING_FREE",
"SIM_SCALING_METHOD":"SCALING_METHOD_POW2",
"SIM_SOLVE_FORM":"SOLVE_FREE",
"SIM_STABILITY_PRIORITY":50,
"SIM_SWITCH_OPTIMIZER":"OFF",
"SOL_FILTER_KEEP_BASIC":"OFF",
"SOL_FILTER_KEEP_RANGED":"OFF",
"SOL_READ_NAME_WIDTH":-1,
"SOL_READ_WIDTH":1024,
"SOLUTION_CALLBACK":"OFF",
"TIMING_LEVEL":1,
"WRITE_BAS_CONSTRAINTS":"ON",
"WRITE_BAS_HEAD":"ON",
"WRITE_BAS_VARIABLES":"ON",
"WRITE_DATA_COMPRESSED":0,
"WRITE_DATA_FORMAT":"DATA_FORMAT_EXTENSION",
"WRITE_DATA_PARAM":"OFF",
"WRITE_FREE_CON":"OFF",
"WRITE_GENERIC_NAMES":"OFF",
"WRITE_GENERIC_NAMES_IO":1,
"WRITE_IGNORE_INCOMPATIBLE_CONIC_ITEMS":"OFF",
"WRITE_IGNORE_INCOMPATIBLE_ITEMS":"OFF",
"WRITE_IGNORE_INCOMPATIBLE_NL_ITEMS":"OFF",

```

```

    "WRITE_IGNORE_INCOMPATIBLE_PSD_ITEMS": "OFF",
    "WRITE_INT_CONSTRAINTS": "ON",
    "WRITE_INT_HEAD": "ON",
    "WRITE_INT_VARIABLES": "ON",
    "WRITE_LP_FULL_OBJ": "ON",
    "WRITE_LP_LINE_WIDTH": 80,
    "WRITE_LP_QUOTED_NAMES": "ON",
    "WRITE_LP_STRICT_FORMAT": "OFF",
    "WRITE_LP_TERMS_PER_LINE": 10,
    "WRITE_MPS_FORMAT": "MPS_FORMAT_FREE",
    "WRITE_MPS_INT": "ON",
    "WRITE_PRECISION": 15,
    "WRITE_SOL_BARVARIABLES": "ON",
    "WRITE_SOL_CONSTRAINTS": "ON",
    "WRITE_SOL_HEAD": "ON",
    "WRITE_SOL_IGNORE_INVALID_NAMES": "OFF",
    "WRITE_SOL_VARIABLES": "ON",
    "WRITE_TASK_INC_SOL": "ON",
    "WRITE_XML_MODE": "WRITE_XML_MODE_ROW"
  },
  "dparam": {
    "ANA_SOL_INFEAS_TOL": 1e-6,
    "BASIS_REL_TOL_S": 1e-12,
    "BASIS_TOL_S": 1e-6,
    "BASIS_TOL_X": 1e-6,
    "CHECK_CONVEXITY_REL_TOL": 1e-10,
    "DATA_TOL_AIJ": 1e-12,
    "DATA_TOL_AIJ_HUGE": 1e+20,
    "DATA_TOL_AIJ_LARGE": 1e+10,
    "DATA_TOL_BOUND_INF": 1e+16,
    "DATA_TOL_BOUND_WRN": 1e+8,
    "DATA_TOL_C_HUGE": 1e+16,
    "DATA_TOL_CJ_LARGE": 1e+8,
    "DATA_TOL_QIJ": 1e-16,
    "DATA_TOL_X": 1e-8,
    "FEASREPAIR_TOL": 1e-10,
    "INTPNT_CO_TOL_DFEAS": 1e-8,
    "INTPNT_CO_TOL_INFEAS": 1e-10,
    "INTPNT_CO_TOL_MU_RED": 1e-8,
    "INTPNT_CO_TOL_NEAR_REL": 1e+3,
    "INTPNT_CO_TOL_PFEAS": 1e-8,
    "INTPNT_CO_TOL_REL_GAP": 1e-7,
    "INTPNT_NL_MERIT_BAL": 1e-4,
    "INTPNT_NL_TOL_DFEAS": 1e-8,
    "INTPNT_NL_TOL_MU_RED": 1e-12,
    "INTPNT_NL_TOL_NEAR_REL": 1e+3,
    "INTPNT_NL_TOL_PFEAS": 1e-8,
    "INTPNT_NL_TOL_REL_GAP": 1e-6,
    "INTPNT_NL_TOL_REL_STEP": 9.95e-1,
    "INTPNT_QO_TOL_DFEAS": 1e-8,
    "INTPNT_QO_TOL_INFEAS": 1e-10,
    "INTPNT_QO_TOL_MU_RED": 1e-8,
    "INTPNT_QO_TOL_NEAR_REL": 1e+3,
    "INTPNT_QO_TOL_PFEAS": 1e-8,
    "INTPNT_QO_TOL_REL_GAP": 1e-8,
    "INTPNT_TOL_DFEAS": 1e-8,
    "INTPNT_TOL_DSAFE": 1e+0,
    "INTPNT_TOL_INFEAS": 1e-10,
    "INTPNT_TOL_MU_RED": 1e-16,
    "INTPNT_TOL_PATH": 1e-8,
    "INTPNT_TOL_PFEAS": 1e-8,
    "INTPNT_TOL_PSAFE": 1e+0,
    "INTPNT_TOL_REL_GAP": 1e-8,

```

```

    "INTPNT_TOL_REL_STEP":9.999e-1,
    "INTPNT_TOL_STEP_SIZE":1e-6,
    "LOWER_OBJ_CUT":-1e+30,
    "LOWER_OBJ_CUT_FINITE_TRH":-5e+29,
    "MIO_DISABLE_TERM_TIME":-1e+0,
    "MIO_MAX_TIME":-1e+0,
    "MIO_MAX_TIME_APRX_OPT":6e+1,
    "MIO_NEAR_TOL_ABS_GAP":0.0,
    "MIO_NEAR_TOL_REL_GAP":1e-3,
    "MIO_REL_GAP_CONST":1e-10,
    "MIO_TOL_ABS_GAP":0.0,
    "MIO_TOL_ABS_RELAX_INT":1e-5,
    "MIO_TOL_FEAS":1e-6,
    "MIO_TOL_REL_DUAL_BOUND_IMPROVEMENT":0.0,
    "MIO_TOL_REL_GAP":1e-4,
    "MIO_TOL_X":1e-6,
    "OPTIMIZER_MAX_TIME":-1e+0,
    "PRESOLVE_TOL_ABS_LINDEP":1e-6,
    "PRESOLVE_TOL_AIJ":1e-12,
    "PRESOLVE_TOL_REL_LINDEP":1e-10,
    "PRESOLVE_TOL_S":1e-8,
    "PRESOLVE_TOL_X":1e-8,
    "QCQO_REFORMULATE_REL_DROP_TOL":1e-15,
    "SEMIDEFINITE_TOL_APPROX":1e-10,
    "SIM_LU_TOL_REL_PIV":1e-2,
    "SIMPLEX_ABS_TOL_PIV":1e-7,
    "UPPER_OBJ_CUT":1e+30,
    "UPPER_OBJ_CUT_FINITE_TRH":5e+29
  },
  "sparam":{
    "BAS_SOL_FILE_NAME":"",
    "DATA_FILE_NAME":"examples/tools/data/lo1.mps",
    "DEBUG_FILE_NAME":"",
    "INT_SOL_FILE_NAME":"",
    "ITR_SOL_FILE_NAME":"",
    "MIO_DEBUG_STRING":"",
    "PARAM_COMMENT_SIGN": "%%",
    "PARAM_READ_FILE_NAME":"",
    "PARAM_WRITE_FILE_NAME":"",
    "READ_MPS_BOU_NAME":"",
    "READ_MPS_OBJ_NAME":"",
    "READ_MPS_RAN_NAME":"",
    "READ_MPS_RHS_NAME":"",
    "SENSITIVITY_FILE_NAME":"",
    "SENSITIVITY_RES_FILE_NAME":"",
    "SOL_FILTER_XC_LOW":"",
    "SOL_FILTER_XC_UPR":"",
    "SOL_FILTER_XX_LOW":"",
    "SOL_FILTER_XX_UPR":"",
    "STAT_FILE_NAME":"",
    "STAT_KEY":"",
    "STAT_NAME":"",
    "WRITE_LP_GEN_VAR_NAME":"XMSKGEN"
  }
}

```

12.8 The Solution File Format

MOSEK provides several solution files depending on the problem type and the optimizer used:

- *basis solution file* (extension `.bas`) if the problem is optimized using the simplex optimizer or basis identification is performed,
- *interior solution file* (extension `.sol`) if a problem is optimized using the interior-point optimizer and no basis identification is required,
- *integer solution file* (extension `.int`) if the problem contains integer constrained variables.

All solution files have the format:

NAME	:	<problem name>						
PROBLEM STATUS	:	<status of the problem>						
SOLUTION STATUS	:	<status of the solution>						
OBJECTIVE NAME	:	<name of the objective function>						
PRIMAL OBJECTIVE	:	<primal objective value corresponding to the solution>						
DUAL OBJECTIVE	:	<dual objective value corresponding to the solution>						
CONSTRAINTS								
INDEX	NAME	AT	ACTIVITY	LOWER LIMIT	UPPER LIMIT	DUAL LOWER	DUAL UPPER	
?	<name>	??	<a value>	<a value>	<a value>	<a value>	<a value>	
VARIABLES								
INDEX	NAME	AT	ACTIVITY	LOWER LIMIT	UPPER LIMIT	DUAL LOWER	DUAL UPPER	CONIC
↪DUAL								
?	<name>	??	<a value>	<a value>	<a value>	<a value>	<a value>	<a value>

In the example the fields ? and <> will be filled with problem and solution specific information. As can be observed a solution report consists of three sections, i.e.

- **HEADER** In this section, first the name of the problem is listed and afterwards the problem and solution status are shown. Next the primal and dual objective values are displayed.
- **CONSTRAINTS** For each constraint i of the form

$$l_i^c \leq \sum_{j=1}^n a_{ij}x_j \leq u_i^c, \quad (12.10)$$

the following information is listed:

- **INDEX**: A sequential index assigned to the constraint by **MOSEK**
- **NAME**: The name of the constraint assigned by the user.
- **AT**: The status of the constraint. In Table 12.4 the possible values of the status keys and their interpretation are shown.

Table 12.4: Status keys.

Status key	Interpretation
UN	Unknown status
BS	Is basic
SB	Is superbasic
LL	Is at the lower limit (bound)
UL	Is at the upper limit (bound)
EQ	Lower limit is identical to upper limit
**	Is infeasible i.e. the lower limit is greater than the upper limit.

- **ACTIVITY**: the quantity $\sum_{j=1}^n a_{ij}x_j^*$, where x^* is the value of the primal solution.
- **LOWER LIMIT**: the quantity l_i^c (see (12.10).)
- **UPPER LIMIT**: the quantity u_i^c (see (12.10).)
- **DUAL LOWER**: the dual multiplier corresponding to the lower limit on the constraint.
- **DUAL UPPER**: the dual multiplier corresponding to the upper limit on the constraint.

- **VARIABLES** The last section of the solution report lists information about the variables. This information has a similar interpretation as for the constraints. However, the column with the header CONIC DUAL is included for problems having one or more conic constraints. This column shows the dual variables corresponding to the conic constraints.

Example: lo1.sol

In Listing 12.7 we show the solution file for the lo1.opf problem.

Listing 12.7: An example of .sol file.

NAME	:				
PROBLEM STATUS	:	PRIMAL_AND_DUAL_FEASIBLE			
SOLUTION STATUS	:	OPTIMAL			
OBJECTIVE NAME	:	obj			
PRIMAL OBJECTIVE	:	8.33333333e+01			
DUAL OBJECTIVE	:	8.33333332e+01			
CONSTRAINTS					
INDEX	NAME	AT ACTIVITY	LOWER LIMIT	UPPER LIMIT	
	→DUAL LOWER	DUAL UPPER			
0	c1	EQ 3.00000000000000e+01	3.00000000e+01	3.00000000e+01	-0.
	→00000000000000e+00	-2.49999999741654e+00			
1	c2	SB 5.33333333049188e+01	1.50000000e+01	NONE	2.
	→09157603759397e-10	-0.00000000000000e+00			
2	c3	UL 2.49999999842049e+01	NONE	2.50000000e+01	-0.
	→00000000000000e+00	-3.33333332895110e-01			
VARIABLES					
INDEX	NAME	AT ACTIVITY	LOWER LIMIT	UPPER LIMIT	
	→DUAL LOWER	DUAL UPPER			
0	x1	LL 1.67020427073508e-09	0.00000000e+00	NONE	-4.
	→49999999528055e+00	-0.00000000000000e+00			
1	x2	LL 2.93510446280504e-09	0.00000000e+00	1.00000000e+01	-2.
	→16666666494916e+00	6.20863861687316e-10			
2	x3	SB 1.49999999899425e+01	0.00000000e+00	NONE	-8.
	→79123177454657e-10	-0.00000000000000e+00			
3	x4	SB 8.33333332273116e+00	0.00000000e+00	NONE	-1.
	→69795978899185e-09	-0.00000000000000e+00			

INTERFACE CHANGES

The section show interface-specific changes to the **MOSEK** Command Line Tools in version 8. See the [release notes](#) for general changes and new features of the **MOSEK** Optimization Suite.

13.1 Compatibility

13.2 Parameters

Added

- *MSK_DPAR_DATA_SYM_MAT_TOL*
- *MSK_DPAR_DATA_SYM_MAT_TOL_HUGE*
- *MSK_DPAR_DATA_SYM_MAT_TOL_LARGE*
- *MSK_DPAR_INTPNT_QO_TOL_DFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_INFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_MU_RED*
- *MSK_DPAR_INTPNT_QO_TOL_NEAR_REL*
- *MSK_DPAR_INTPNT_QO_TOL_PFEAS*
- *MSK_DPAR_INTPNT_QO_TOL_REL_GAP*
- *MSK_DPAR_SEMIDEFINITE_TOL_APPROX*
- *MSK_IPAR_INTPNT_MULTI_THREAD*
- *MSK_IPAR_LICENSE_TRH_EXPIRY_WRN*
- *MSK_IPAR_LOG_ANA_PRO*
- *MSK_IPAR_MIO_CUT_CLIQUE*
- *MSK_IPAR_MIO_CUT_GMI*
- *MSK_IPAR_MIO_CUT_IMPLIED_BOUND*
- *MSK_IPAR_MIO_CUT_KNAPSACK_COVER*
- *MSK_IPAR_MIO_CUT_SELECTION_LEVEL*
- *MSK_IPAR_MIO_PERSPECTIVE_REFORMULATE*
- *MSK_IPAR_MIO_ROOT_REPEAT_PRESOLVE_LEVEL*
- *MSK_IPAR_MIO_VB_DETECTION_LEVEL*
- *MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_FILL*

Removed

- MSK_DPAR_FEASREPAIR_TOL
- MSK_DPAR_MIO_HEURISTIC_TIME
- MSK_DPAR_MIO_MAX_TIME_APRX_OPT
- MSK_DPAR_MIO_REL_ADD_CUT_LIMITED
- MSK_DPAR_MIO_TOL_MAX_CUT_FRAC_RHS
- MSK_DPAR_MIO_TOL_MIN_CUT_FRAC_RHS
- MSK_DPAR_MIO_TOL_REL_RELAX_INT
- MSK_DPAR_MIO_TOL_X
- MSK_DPAR_NONCONVEX_TOL_FEAS
- MSK_DPAR_NONCONVEX_TOL_OPT
- MSK_IPAR_ALLOC_ADD_QNZ
- MSK_IPAR_CONCURRENT_NUM_OPTIMIZERS
- MSK_IPAR_CONCURRENT_PRIORITY_DUAL_SIMPLEX
- MSK_IPAR_CONCURRENT_PRIORITY_FREE_SIMPLEX
- MSK_IPAR_CONCURRENT_PRIORITY_INTPNT
- MSK_IPAR_CONCURRENT_PRIORITY_PRIMAL_SIMPLEX
- MSK_IPAR_FEASREPAIR_OPTIMIZE
- MSK_IPAR_INTPNT_FACTOR_DEBUG_LVL
- MSK_IPAR_INTPNT_FACTOR_METHOD
- MSK_IPAR_LIC_TRH_EXPIRY_WRN
- MSK_IPAR_LOG_CONCURRENT
- MSK_IPAR_LOG_NONCONVEX
- MSK_IPAR_LOG_PARAM
- MSK_IPAR_LOG_SIM_NETWORK_FREQ
- MSK_IPAR_MIO_BRANCH_PRIORITIES_USE
- MSK_IPAR_MIO_CONT_SOL
- MSK_IPAR_MIO_CUT_CG
- MSK_IPAR_MIO_CUT_LEVEL_ROOT
- MSK_IPAR_MIO_CUT_LEVEL_TREE
- MSK_IPAR_MIO_FEASPUMP_LEVEL
- MSK_IPAR_MIO_HOTSTART
- MSK_IPAR_MIO_KEEP_BASIS
- MSK_IPAR_MIO_LOCAL_BRANCH_NUMBER
- MSK_IPAR_MIO_OPTIMIZER_MODE
- MSK_IPAR_MIO_PRESOLVE_AGGREGATE
- MSK_IPAR_MIO_PRESOLVE_PROBING
- MSK_IPAR_MIO_PRESOLVE_USE

- MSK_IPAR_MIO_STRONG_BRANCH
- MSK_IPAR_MIO_USE_MULTITHREADED_OPTIMIZER
- MSK_IPAR_NONCONVEX_MAX_ITERATIONS
- MSK_IPAR_PREOLVE_ELIM_FILL
- MSK_IPAR_PREOLVE_ELIMINATOR_USE
- MSK_IPAR_QO_SEPARABLE_REFORMULATION
- MSK_IPAR_READ_ANZ
- MSK_IPAR_READ_CON
- MSK_IPAR_READ_CONE
- MSK_IPAR_READ_MPS_KEEP_INT
- MSK_IPAR_READ_MPS_OBJ_SENSE
- MSK_IPAR_READ_MPS_RELAX
- MSK_IPAR_READ_QNZ
- MSK_IPAR_READ_VAR
- MSK_IPAR_WARNING_LEVEL
- MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_CONIC_ITEMS
- MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_NL_ITEMS
- MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_PSD_ITEMS
- MSK_SPAR_FEASREPAIR_NAME_PREFIX
- MSK_SPAR_FEASREPAIR_NAME_SEPARATOR
- MSK_SPAR_FEASREPAIR_NAME_WSUMVIOL

13.3 Constants

Added

- *MSK_BRANCH_DIR_FAR*
- *MSK_BRANCH_DIR_GUIDED*
- *MSK_BRANCH_DIR_NEAR*
- *MSK_BRANCH_DIR_PSEUDOCOST*
- *MSK_BRANCH_DIR_ROOT_LP*
- *MSK_CALLBACK_BEGIN_ROOT_CUTGEN*
- *MSK_CALLBACK_BEGIN_TO_CONIC*
- *MSK_CALLBACK_END_ROOT_CUTGEN*
- *MSK_CALLBACK_END_TO_CONIC*
- *MSK_CALLBACK_IM_ROOT_CUTGEN*
- *MSK_CALLBACK_SOLVING_REMOTE*
- *MSK_DATA_FORMAT_JSON_TASK*
- *MSK_DINF_MIO_CLIQUÉ_SEPARATION_TIME*

- *MSK_DINF_MIO_CMIR_SEPARATION_TIME*
- *MSK_DINF_MIO_GMI_SEPARATION_TIME*
- *MSK_DINF_MIO_IMPLIED_BOUND_TIME*
- *MSK_DINF_MIO_KNAPSACK_COVER_SEPARATION_TIME*
- *MSK_DINF_QCQO_REFORMULATE_MAX_PERTURBATION*
- *MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_COLUMN_SCALING*
- *MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_DIAG_SCALING*
- *MSK_DINF_SOL_BAS_NRM_BARX*
- *MSK_DINF_SOL_BAS_NRM_SLC*
- *MSK_DINF_SOL_BAS_NRM_SLX*
- *MSK_DINF_SOL_BAS_NRM_SUC*
- *MSK_DINF_SOL_BAS_NRM_SUX*
- *MSK_DINF_SOL_BAS_NRM_XC*
- *MSK_DINF_SOL_BAS_NRM_XX*
- *MSK_DINF_SOL_BAS_NRM_Y*
- *MSK_DINF_SOL_ITG_NRM_BARX*
- *MSK_DINF_SOL_ITG_NRM_XC*
- *MSK_DINF_SOL_ITG_NRM_XX*
- *MSK_DINF_SOL_ITR_NRM_BARS*
- *MSK_DINF_SOL_ITR_NRM_BARX*
- *MSK_DINF_SOL_ITR_NRM_SLC*
- *MSK_DINF_SOL_ITR_NRM_SLX*
- *MSK_DINF_SOL_ITR_NRM_SNX*
- *MSK_DINF_SOL_ITR_NRM_SUC*
- *MSK_DINF_SOL_ITR_NRM_SUX*
- *MSK_DINF_SOL_ITR_NRM_XC*
- *MSK_DINF_SOL_ITR_NRM_XX*
- *MSK_DINF_SOL_ITR_NRM_Y*
- *MSK_DINF_TO_CONIC_TIME*
- *MSK_IINF_MIO_ABSGAP_SATISFIED*
- *MSK_IINF_MIO_CLIQUETABLE_SIZE*
- *MSK_IINF_MIO_NEAR_ABSGAP_SATISFIED*
- *MSK_IINF_MIO_NEAR_RELGAP_SATISFIED*
- *MSK_IINF_MIO_NODE_DEPTH*
- *MSK_IINF_MIO_NUM_CMIR_CUTS*
- *MSK_IINF_MIO_NUM_IMPLIED_BOUND_CUTS*
- *MSK_IINF_MIO_NUM_KNAPSACK_COVER_CUTS*
- *MSK_IINF_MIO_NUM_REPEATED_PRESOLVE*
- *MSK_IINF_MIO_PRESOLVED_NUMBIN*

- *MSK_IINF_MIO_PRE SOLVED_NUMCON*
- *MSK_IINF_MIO_PRE SOLVED_NUMCONT*
- *MSK_IINF_MIO_PRE SOLVED_NUMINT*
- *MSK_IINF_MIO_PRE SOLVED_NUMVAR*
- *MSK_IINF_MIO_RELGAP_SATISFIED*
- *MSK_LIINF_MIO_PRE SOLVED_ANZ*
- *MSK_LIINF_MIO_SIM_MAXITER_SETBACKS*
- *MSK_MPS_FORMAT_CPLEX*
- *MSK_SOL_STA_DUAL_ILLPOSED_CER*
- *MSK_SOL_STA_PRIM_ILLPOSED_CER*

Changed

- *MSK_SOL_STA_INTEGER_OPTIMAL*
- *MSK_SOL_STA_NEAR_INTEGER_OPTIMAL*
- *MSK_LICENSE_BUFFER_LENGTH*

Removed

- *MSK_CALLBACKCODE_BEGIN_CONCURRENT*
- *MSK_CALLBACKCODE_BEGIN_NETWORK_DUAL_SIMPLEX*
- *MSK_CALLBACKCODE_BEGIN_NETWORK_PRIMAL_SIMPLEX*
- *MSK_CALLBACKCODE_BEGIN_NETWORK_SIMPLEX*
- *MSK_CALLBACKCODE_BEGIN_NONCONVEX*
- *MSK_CALLBACKCODE_BEGIN_SIMPLEX_NETWORK_DETECT*
- *MSK_CALLBACKCODE_END_CONCURRENT*
- *MSK_CALLBACKCODE_END_NETWORK_DUAL_SIMPLEX*
- *MSK_CALLBACKCODE_END_NETWORK_PRIMAL_SIMPLEX*
- *MSK_CALLBACKCODE_END_NETWORK_SIMPLEX*
- *MSK_CALLBACKCODE_END_NONCONVEX*
- *MSK_CALLBACKCODE_END_SIMPLEX_NETWORK_DETECT*
- *MSK_CALLBACKCODE_IM_MIO_PRE SOLVE*
- *MSK_CALLBACKCODE_IM_NETWORK_DUAL_SIMPLEX*
- *MSK_CALLBACKCODE_IM_NETWORK_PRIMAL_SIMPLEX*
- *MSK_CALLBACKCODE_IM_NONCONVEX*
- *MSK_CALLBACKCODE_NONCOVEX*
- *MSK_CALLBACKCODE_UPDATE_NETWORK_DUAL_SIMPLEX*
- *MSK_CALLBACKCODE_UPDATE_NETWORK_PRIMAL_SIMPLEX*
- *MSK_CALLBACKCODE_UPDATE_NONCONVEX*
- *MSK_DINFITEM_CONCURRENT_TIME*

- MSK_DINFITEM_MIO_CG_SEPERATION_TIME
- MSK_DINFITEM_MIO_CMIR_SEPERATION_TIME
- MSK_DINFITEM_SIM_NETWORK_DUAL_TIME
- MSK_DINFITEM_SIM_NETWORK_PRIMAL_TIME
- MSK_DINFITEM_SIM_NETWORK_TIME
- MSK_FEATURE_PTOM
- MSK_FEATURE_PTOX
- MSK_IINFITEM_CONCURRENT_FASTEST_OPTIMIZER
- MSK_IINFITEM_MIO_NUM_BASIS_CUTS
- MSK_IINFITEM_MIO_NUM_CARDGUB_CUTS
- MSK_IINFITEM_MIO_NUM_COEF_REDC_CUTS
- MSK_IINFITEM_MIO_NUM_CONTRA_CUTS
- MSK_IINFITEM_MIO_NUM_DISAGG_CUTS
- MSK_IINFITEM_MIO_NUM_FLOW_COVER_CUTS
- MSK_IINFITEM_MIO_NUM_GCD_CUTS
- MSK_IINFITEM_MIO_NUM_GUB_COVER_CUTS
- MSK_IINFITEM_MIO_NUM_KNAPSUR_COVER_CUTS
- MSK_IINFITEM_MIO_NUM_LATTICE_CUTS
- MSK_IINFITEM_MIO_NUM_LIFT_CUTS
- MSK_IINFITEM_MIO_NUM_OBJ_CUTS
- MSK_IINFITEM_MIO_NUM_PLAN_LOC_CUTS
- MSK_IINFITEM_SIM_NETWORK_DUAL_DEG_ITER
- MSK_IINFITEM_SIM_NETWORK_DUAL_HOTSTART
- MSK_IINFITEM_SIM_NETWORK_DUAL_HOTSTART_LU
- MSK_IINFITEM_SIM_NETWORK_DUAL_INF_ITER
- MSK_IINFITEM_SIM_NETWORK_DUAL_ITER
- MSK_IINFITEM_SIM_NETWORK_PRIMAL_DEG_ITER
- MSK_IINFITEM_SIM_NETWORK_PRIMAL_HOTSTART
- MSK_IINFITEM_SIM_NETWORK_PRIMAL_HOTSTART_LU
- MSK_IINFITEM_SIM_NETWORK_PRIMAL_INF_ITER
- MSK_IINFITEM_SIM_NETWORK_PRIMAL_ITER
- MSK_IINFITEM_SOL_INT_PROSTA
- MSK_IINFITEM_SOL_INT_SOLSTA
- MSK_IINFITEM_STO_NUM_A_CACHE_FLUSHES
- MSK_IINFITEM_STO_NUM_A_TRANSPOSES
- MSK_MIOMODE_LAZY
- MSK_OPTIMIZERTYPE_CONCURRENT
- MSK_OPTIMIZERTYPE_MIXED_INT_CONIC
- MSK_OPTIMIZERTYPE_NETWORK_PRIMAL_SIMPLEX

- `MSK_OPTIMIZERTYPE_NONCONVEX`
- `MSK_OPTIMIZERTYPE_PRIMAL_DUAL_SIMPLEX`

13.4 Response Codes

Added

- `MSK_RES_ERR_DUPLICATE_AIJ (1385)`
- `MSK_RES_ERR_JSON_DATA (1179)`
- `MSK_RES_ERR_JSON_FORMAT (1178)`
- `MSK_RES_ERR_JSON_MISSING_DATA (1180)`
- `MSK_RES_ERR_JSON_NUMBER_OVERFLOW (1177)`
- `MSK_RES_ERR_JSON_STRING (1176)`
- `MSK_RES_ERR_JSON_SYNTAX (1175)`
- `MSK_RES_ERR_LAU_INVALID_LOWER_TRIANGULAR_MATRIX (7002)`
- `MSK_RES_ERR_LAU_INVALID_SPARSE_SYMMETRIC_MATRIX (7019)`
- `MSK_RES_ERR_LAU_NOT_POSITIVE_DEFINITE (7001)`
- `MSK_RES_ERR_MIXED_CONIC_AND_NL (1501)`
- `MSK_RES_ERR_SERVER_CONNECT (8000)`
- `MSK_RES_ERR_SERVER_PROTOCOL (8001)`
- `MSK_RES_ERR_SERVER_STATUS (8002)`
- `MSK_RES_ERR_SERVER_TOKEN (8003)`
- `MSK_RES_ERR_SYM_MAT_HUGE (1482)`
- `MSK_RES_ERR_SYM_MAT_INVALID (1480)`
- `MSK_RES_ERR_TASK_WRITE (2562)`
- `MSK_RES_ERR_TOCONIC_CONSTR_NOT_CONIC (7153)`
- `MSK_RES_ERR_TOCONIC_CONSTR_Q_NOT_PSD (7150)`
- `MSK_RES_ERR_TOCONIC_CONSTRAINT_FX (7151)`
- `MSK_RES_ERR_TOCONIC_CONSTRAINT_RA (7152)`
- `MSK_RES_ERR_TOCONIC_OBJECTIVE_NOT_PSD (7155)`
- `MSK_RES_WRN_SYM_MAT_LARGE (960)`

Removed

- `MSK_RES_ERR_AD_INVALID_OPERAND`
- `MSK_RES_ERR_AD_INVALID_OPERATOR`
- `MSK_RES_ERR_AD_MISSING_OPERAND`
- `MSK_RES_ERR_AD_MISSING_RETURN`
- `MSK_RES_ERR_CONCURRENT_OPTIMIZER`
- `MSK_RES_ERR_INV_CONIC_PROBLEM`

- MSK_RES_ERR_INVALID_BRANCH_DIRECTION
- MSK_RES_ERR_INVALID_BRANCH_PRIORITY
- MSK_RES_ERR_INVALID_NETWORK_PROBLEM
- MSK_RES_ERR_MBT_INCOMPATIBLE
- MSK_RES_ERR_MBT_INVALID
- MSK_RES_ERR_MIXED_PROBLEM
- MSK_RES_ERR_NO_DUAL_INFO_FOR_ITG_SOL
- MSK_RES_ERR_ORD_INVALID
- MSK_RES_ERR_ORD_INVALID_BRANCH_DIR
- MSK_RES_ERR_TOCONIC_CONVERSION_FAIL
- MSK_RES_ERR_TOO_MANY_CONCURRENT_TASKS
- MSK_RES_WRN_TOO_MANY_THREADS_CONCURRENT

BIBLIOGRAPHY

- [AA95] E. D. Andersen and K. D. Andersen. Presolving in linear programming. *Math. Programming*, 71(2):221–245, 1995.
- [AGMX96] E. D. Andersen, J. Gondzio, Cs. Mészáros, and X. Xu. Implementation of interior point methods for large scale linear programming. In T. Terlaky, editor, *Interior-point methods of mathematical programming*, pages 189–252. Kluwer Academic Publishers, 1996.
- [ART03] E. D. Andersen, C. Roos, and T. Terlaky. On implementing a primal-dual interior-point method for conic quadratic optimization. *Math. Programming*, February 2003.
- [AY96] E. D. Andersen and Y. Ye. Combining interior-point and pivoting algorithms. *Management Sci.*, 42(12):1719–1731, December 1996.
- [AY98] E. D. Andersen and Y. Ye. A computational study of the homogeneous algorithm for large-scale convex optimization. *Computational Optimization and Applications*, 10:243–269, 1998.
- [AY99] E. D. Andersen and Y. Ye. On a homogeneous algorithm for the monotone complementarity problem. *Math. Programming*, 84(2):375–399, February 1999.
- [And09] Erling D. Andersen. The homogeneous and self-dual model and algorithm for linear optimization. Technical Report TR-1-2009, MOSEK ApS, 2009. URL: <http://docs.mosek.com/whitepapers/homolo.pdf>.
- [And13] Erling D. Andersen. On formulating quadratic functions in optimization models. Technical Report TR-1-2013, MOSEK ApS, 2013. Last revised 23-feb-2016. URL: <http://docs.mosek.com/whitepapers/qmodel.pdf>.
- [Chv83] V. Chvátal. *Linear programming*. W.H. Freeman and Company, 1983.
- [FGK03] R. Fourer, D. M. Gay, and B. W. Kernighan. *AMPL. A modeling language for mathematical programming*. Thomson, 2nd edition, 2003.
- [Naz87] J. L. Nazareth. *Computer Solution of Linear Programs*. Oxford University Press, New York, 1987.
- [RTV97] C. Roos, T. Terlaky, and J. -Ph. Vial. *Theory and algorithms for linear optimization: an interior point approach*. John Wiley and Sons, New York, 1997.
- [Wal00] S. W. Wallace. Decision making under uncertainty: is sensitivity of any use. *Oper. Res.*, 48(1):20–25, January 2000.
- [Wol98] L. A. Wolsey. *Integer programming*. John Wiley and Sons, 1998.
- [MOSEKApS12] MOSEK ApS. *The MOSEK Modeling Cookbook*. MOSEK ApS, Fruebjergvej 3, Boks 16, 2100 Copenhagen O, 2012. Last revised September 2015. URL: <http://docs.mosek.com/generic/modeling-a4.pdf>.

Enumerations

MSKaccmodee, 140
 MSK_ACC_CON, 140
 MSK_ACC_VAR, 140
 MSKbasindtypee, 140
 MSK_BI_ALWAYS, 140
 MSK_BI_IF_FEASIBLE, 141
 MSK_BI_NEVER, 140
 MSK_BI_NO_ERROR, 141
 MSK_BI_RESERVED, 141
 MSKboundkeye, 141
 MSK_BK_FR, 141
 MSK_BK_FX, 141
 MSK_BK_LO, 141
 MSK_BK_RA, 141
 MSK_BK_UP, 141
 MSKbranchdire, 158
 MSK_BRANCH_DIR_DOWN, 158
 MSK_BRANCH_DIR_FAR, 158
 MSK_BRANCH_DIR_FREE, 158
 MSK_BRANCH_DIR_GUIDED, 158
 MSK_BRANCH_DIR_NEAR, 158
 MSK_BRANCH_DIR_PSEUDOCOST, 158
 MSK_BRANCH_DIR_ROOT_LP, 158
 MSK_BRANCH_DIR_UP, 158
 MSKcallbackcodee, 142
 MSK_CALLBACK_BEGIN_BI, 143
 MSK_CALLBACK_BEGIN_CONIC, 143
 MSK_CALLBACK_BEGIN_DUAL_BI, 144
 MSK_CALLBACK_BEGIN_DUAL_SENSITIVITY, 146
 MSK_CALLBACK_BEGIN_DUAL_SETUP_BI, 146
 MSK_CALLBACK_BEGIN_DUAL_SIMPLEX, 145
 MSK_CALLBACK_BEGIN_DUAL_SIMPLEX_BI, 145
 MSK_CALLBACK_BEGIN_FULL_CONVEXITY_CHECK, 147
 MSK_CALLBACK_BEGIN_INFEAS_ANA, 146
 MSK_CALLBACK_BEGIN_INTPNT, 143
 MSK_CALLBACK_BEGIN_LICENSE_WAIT, 146
 MSK_CALLBACK_BEGIN_MIO, 145
 MSK_CALLBACK_BEGIN_OPTIMIZER, 143
 MSK_CALLBACK_BEGIN_PRESOLVE, 143
 MSK_CALLBACK_BEGIN_PRIMAL_BI, 143
 MSK_CALLBACK_BEGIN_PRIMAL_DUAL_SIMPLEX, 145
 MSK_CALLBACK_BEGIN_PRIMAL_DUAL_SIMPLEX_BI, 144
 MSK_CALLBACK_BEGIN_PRIMAL_REPAIR, 147
 MSK_CALLBACK_BEGIN_PRIMAL_SENSITIVITY, 146
 MSK_CALLBACK_BEGIN_PRIMAL_SETUP_BI, 146
 MSK_CALLBACK_BEGIN_PRIMAL_SIMPLEX, 145
 MSK_CALLBACK_BEGIN_PRIMAL_SIMPLEX_BI, 144
 MSK_CALLBACK_BEGIN_QCQO_REFORMULATE, 146
 MSK_CALLBACK_BEGIN_READ, 147
 MSK_CALLBACK_BEGIN_ROOT_CUTGEN, 142
 MSK_CALLBACK_BEGIN_SIMPLEX, 145
 MSK_CALLBACK_BEGIN_SIMPLEX_BI, 144
 MSK_CALLBACK_BEGIN_TO_CONIC, 146
 MSK_CALLBACK_BEGIN_WRITE, 147
 MSK_CALLBACK_CONIC, 143
 MSK_CALLBACK_DUAL_SIMPLEX, 143
 MSK_CALLBACK_END_BI, 143
 MSK_CALLBACK_END_CONIC, 143
 MSK_CALLBACK_END_DUAL_BI, 144
 MSK_CALLBACK_END_DUAL_SENSITIVITY, 146
 MSK_CALLBACK_END_DUAL_SETUP_BI, 146
 MSK_CALLBACK_END_DUAL_SIMPLEX, 145
 MSK_CALLBACK_END_DUAL_SIMPLEX_BI, 145
 MSK_CALLBACK_END_FULL_CONVEXITY_CHECK, 147
 MSK_CALLBACK_END_INFEAS_ANA, 146
 MSK_CALLBACK_END_INTPNT, 143
 MSK_CALLBACK_END_LICENSE_WAIT, 146
 MSK_CALLBACK_END_MIO, 145
 MSK_CALLBACK_END_OPTIMIZER, 143
 MSK_CALLBACK_END_PRESOLVE, 143
 MSK_CALLBACK_END_PRIMAL_BI, 144
 MSK_CALLBACK_END_PRIMAL_DUAL_SIMPLEX, 145
 MSK_CALLBACK_END_PRIMAL_DUAL_SIMPLEX_BI, 144
 MSK_CALLBACK_END_PRIMAL_REPAIR, 147
 MSK_CALLBACK_END_PRIMAL_SENSITIVITY, 146
 MSK_CALLBACK_END_PRIMAL_SETUP_BI, 146
 MSK_CALLBACK_END_PRIMAL_SIMPLEX, 145
 MSK_CALLBACK_END_PRIMAL_SIMPLEX_BI, 144
 MSK_CALLBACK_END_QCQO_REFORMULATE, 146
 MSK_CALLBACK_END_READ, 147
 MSK_CALLBACK_END_ROOT_CUTGEN, 143
 MSK_CALLBACK_END_SIMPLEX, 145
 MSK_CALLBACK_END_SIMPLEX_BI, 145
 MSK_CALLBACK_END_TO_CONIC, 147
 MSK_CALLBACK_END_WRITE, 147
 MSK_CALLBACK_IM_BI, 143
 MSK_CALLBACK_IM_CONIC, 143
 MSK_CALLBACK_IM_DUAL_BI, 144
 MSK_CALLBACK_IM_DUAL_SENSITIVITY, 146

MSK_CALLBACK_IM_DUAL_SIMPLEX, 145
MSK_CALLBACK_IM_FULL_CONVEXITY_CHECK, 147
MSK_CALLBACK_IM_INTPNT, 143
MSK_CALLBACK_IM_LICENSE_WAIT, 146
MSK_CALLBACK_IM_LU, 147
MSK_CALLBACK_IM_MIO, 145
MSK_CALLBACK_IM_MIO_DUAL_SIMPLEX, 146
MSK_CALLBACK_IM_MIO_INTPNT, 146
MSK_CALLBACK_IM_MIO_PRIMAL_SIMPLEX, 146
MSK_CALLBACK_IM_ORDER, 147
MSK_CALLBACK_IM_PRESOLVE, 143
MSK_CALLBACK_IM_PRIMAL_BI, 144
MSK_CALLBACK_IM_PRIMAL_DUAL_SIMPLEX, 145
MSK_CALLBACK_IM_PRIMAL_SENSIVITY, 146
MSK_CALLBACK_IM_PRIMAL_SIMPLEX, 145
MSK_CALLBACK_IM_QO_REFORMULATE, 146
MSK_CALLBACK_IM_READ, 147
MSK_CALLBACK_IM_ROOT_CUTGEN, 142
MSK_CALLBACK_IM_SIMPLEX, 147
MSK_CALLBACK_IM_SIMPLEX_BI, 144
MSK_CALLBACK_INTPNT, 143
MSK_CALLBACK_NEW_INT_MIO, 145
MSK_CALLBACK_PRIMAL_SIMPLEX, 143
MSK_CALLBACK_READ_OPF, 147
MSK_CALLBACK_READ_OPF_SECTION, 147
MSK_CALLBACK_SOLVING_REMOTE, 147
MSK_CALLBACK_UPDATE_DUAL_BI, 144
MSK_CALLBACK_UPDATE_DUAL_SIMPLEX, 145
MSK_CALLBACK_UPDATE_DUAL_SIMPLEX_BI, 145
MSK_CALLBACK_UPDATE_PRESOLVE, 143
MSK_CALLBACK_UPDATE_PRIMAL_BI, 144
MSK_CALLBACK_UPDATE_PRIMAL_DUAL_SIMPLEX, 145
MSK_CALLBACK_UPDATE_PRIMAL_DUAL_SIMPLEX_BI, 144
MSK_CALLBACK_UPDATE_PRIMAL_SIMPLEX, 145
MSK_CALLBACK_UPDATE_PRIMAL_SIMPLEX_BI, 144
MSK_CALLBACK_WRITE_OPF, 147
MSKcheckconvexitytypee, 147
MSK_CHECK_CONVEXITY_FULL, 147
MSK_CHECK_CONVEXITY_NONE, 147
MSK_CHECK_CONVEXITY_SIMPLE, 147
MSKcompresstypee, 148
MSK_COMPRESS_FREE, 148
MSK_COMPRESS_GZIP, 148
MSK_COMPRESS_NONE, 148
MSKconetypee, 148
MSK_CT_QUAD, 148
MSK_CT_RQUAD, 148
MSKdataformate, 148
MSK_DATA_FORMAT_CB, 148
MSK_DATA_FORMAT_EXTENSION, 148
MSK_DATA_FORMAT_FREE_MPS, 148
MSK_DATA_FORMAT_JSON_TASK, 148
MSK_DATA_FORMAT_LP, 148
MSK_DATA_FORMAT_MPS, 148
MSK_DATA_FORMAT_OP, 148
MSK_DATA_FORMAT_TASK, 148
MSK_DATA_FORMAT_XML, 148
MSKdinfiteme, 149
MSK_DINF_BI_CLEAN_DUAL_TIME, 149
MSK_DINF_BI_CLEAN_PRIMAL_DUAL_TIME, 149
MSK_DINF_BI_CLEAN_PRIMAL_TIME, 149
MSK_DINF_BI_CLEAN_TIME, 149
MSK_DINF_BI_DUAL_TIME, 149
MSK_DINF_BI_PRIMAL_TIME, 149
MSK_DINF_BI_TIME, 149
MSK_DINF_INTPNT_DUAL_FEAS, 149
MSK_DINF_INTPNT_DUAL_OBJ, 149
MSK_DINF_INTPNT_FACTOR_NUM_FLOPS, 153
MSK_DINF_INTPNT_OPT_STATUS, 149
MSK_DINF_INTPNT_ORDER_TIME, 149
MSK_DINF_INTPNT_PRIMAL_FEAS, 149
MSK_DINF_INTPNT_PRIMAL_OBJ, 149
MSK_DINF_INTPNT_TIME, 149
MSK_DINF_MIO_CLIQUE_SEPARATION_TIME, 150
MSK_DINF_MIO_CMIR_SEPARATION_TIME, 150
MSK_DINF_MIO_CONSTRUCT_SOLUTION_OBJ, 150
MSK_DINF_MIO_DUAL_BOUND_AFTER_PRESOLVE, 151
MSK_DINF_MIO_GMI_SEPARATION_TIME, 150
MSK_DINF_MIO_HEURISTIC_TIME, 150
MSK_DINF_MIO_IMPLIED_BOUND_TIME, 151
MSK_DINF_MIO_KNAPSACK_COVER_SEPARATION_TIME, 150
MSK_DINF_MIO_OBJ_ABS_GAP, 150
MSK_DINF_MIO_OBJ_BOUND, 150
MSK_DINF_MIO_OBJ_INT, 150
MSK_DINF_MIO_OBJ_REL_GAP, 150
MSK_DINF_MIO_OPTIMIZER_TIME, 150
MSK_DINF_MIO_PROBING_TIME, 151
MSK_DINF_MIO_ROOT_CUTGEN_TIME, 151
MSK_DINF_MIO_ROOT_OPTIMIZER_TIME, 150
MSK_DINF_MIO_ROOT_PRESOLVE_TIME, 150
MSK_DINF_MIO_TIME, 150
MSK_DINF_MIO_USER_OBJ_CUT, 150
MSK_DINF_OPTIMIZER_TIME, 151
MSK_DINF_PRESOLVE_ELI_TIME, 151
MSK_DINF_PRESOLVE_LINDEP_TIME, 151
MSK_DINF_PRESOLVE_TIME, 151
MSK_DINF_PRIMAL_REPAIR_PENALTY_OBJ, 153
MSK_DINF_QCQO_REFORMULATE_MAX_PERTURBATION, 153
MSK_DINF_QCQO_REFORMULATE_TIME, 153
MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_COLUMN_SCALING, 153
MSK_DINF_QCQO_REFORMULATE_WORST_CHOLESKY_DIAG_SCALING, 153
MSK_DINF_RD_TIME, 151
MSK_DINF_SIM_DUAL_TIME, 149
MSK_DINF_SIM_FEAS, 150
MSK_DINF_SIM_OBJ, 150
MSK_DINF_SIM_PRIMAL_DUAL_TIME, 149
MSK_DINF_SIM_PRIMAL_TIME, 149
MSK_DINF_SIM_TIME, 149
MSK_DINF_SOL_BAS_DUAL_OBJ, 152
MSK_DINF_SOL_BAS_DVIOLCON, 152

MSK_DINF_SOL_BAS_DVIOLVAR, 152
 MSK_DINF_SOL_BAS_NRM_BARX, 152
 MSK_DINF_SOL_BAS_NRM_SLC, 152
 MSK_DINF_SOL_BAS_NRM_SLX, 152
 MSK_DINF_SOL_BAS_NRM_SUC, 152
 MSK_DINF_SOL_BAS_NRM_SUX, 152
 MSK_DINF_SOL_BAS_NRM_XC, 152
 MSK_DINF_SOL_BAS_NRM_XX, 152
 MSK_DINF_SOL_BAS_NRM_Y, 152
 MSK_DINF_SOL_BAS_PRIMAL_OBJ, 152
 MSK_DINF_SOL_BAS_PVIOLCON, 152
 MSK_DINF_SOL_BAS_PVIOLVAR, 152
 MSK_DINF_SOL_ITG_NRM_BARX, 153
 MSK_DINF_SOL_ITG_NRM_XC, 153
 MSK_DINF_SOL_ITG_NRM_XX, 153
 MSK_DINF_SOL_ITG_PRIMAL_OBJ, 152
 MSK_DINF_SOL_ITG_PVIOLBARVAR, 153
 MSK_DINF_SOL_ITG_PVIOLCON, 152
 MSK_DINF_SOL_ITG_PVIOLCONES, 153
 MSK_DINF_SOL_ITG_PVIOLITG, 153
 MSK_DINF_SOL_ITG_PVIOLVAR, 152
 MSK_DINF_SOL_ITR_DUAL_OBJ, 151
 MSK_DINF_SOL_ITR_DVIOLBARVAR, 151
 MSK_DINF_SOL_ITR_DVIOLCON, 151
 MSK_DINF_SOL_ITR_DVIOLCONES, 151
 MSK_DINF_SOL_ITR_DVIOLVAR, 151
 MSK_DINF_SOL_ITR_NRM_BARS, 152
 MSK_DINF_SOL_ITR_NRM_BARX, 151
 MSK_DINF_SOL_ITR_NRM_SLC, 152
 MSK_DINF_SOL_ITR_NRM_SLX, 152
 MSK_DINF_SOL_ITR_NRM_SNX, 152
 MSK_DINF_SOL_ITR_NRM_SUC, 152
 MSK_DINF_SOL_ITR_NRM_SUX, 152
 MSK_DINF_SOL_ITR_NRM_XC, 151
 MSK_DINF_SOL_ITR_NRM_XX, 151
 MSK_DINF_SOL_ITR_NRM_Y, 151
 MSK_DINF_SOL_ITR_PRIMAL_OBJ, 151
 MSK_DINF_SOL_ITR_PVIOLBARVAR, 151
 MSK_DINF_SOL_ITR_PVIOLCON, 151
 MSK_DINF_SOL_ITR_PVIOLCONES, 151
 MSK_DINF_SOL_ITR_PVIOLVAR, 151
 MSK_DINF_TO_CONIC_TIME, 150
 MSKfeaturee, 153
 MSK_FEATURE_PTON, 153
 MSK_FEATURE_PTS, 153
 MSKiinfiteme, 154
 MSK_IINF_ANA_PRO_NUM_CON, 154
 MSK_IINF_ANA_PRO_NUM_CON_EQ, 154
 MSK_IINF_ANA_PRO_NUM_CON_FR, 154
 MSK_IINF_ANA_PRO_NUM_CON_LO, 154
 MSK_IINF_ANA_PRO_NUM_CON_RA, 154
 MSK_IINF_ANA_PRO_NUM_CON_UP, 154
 MSK_IINF_ANA_PRO_NUM_VAR, 154
 MSK_IINF_ANA_PRO_NUM_VAR_BIN, 155
 MSK_IINF_ANA_PRO_NUM_VAR_CONT, 154
 MSK_IINF_ANA_PRO_NUM_VAR_EQ, 154
 MSK_IINF_ANA_PRO_NUM_VAR_FR, 154
 MSK_IINF_ANA_PRO_NUM_VAR_INT, 155
 MSK_IINF_ANA_PRO_NUM_VAR_LO, 154
 MSK_IINF_ANA_PRO_NUM_VAR_RA, 154
 MSK_IINF_ANA_PRO_NUM_VAR_UP, 154
 MSK_IINF_INTPNT_FACTOR_DIM_DENSE, 155
 MSK_IINF_INTPNT_ITER, 155
 MSK_IINF_INTPNT_NUM_THREADS, 157
 MSK_IINF_INTPNT_SOLVE_DUAL, 155
 MSK_IINF_MIO_ABSGAP_SATISFIED, 156
 MSK_IINF_MIO_CLIQUE_TABLE_SIZE, 155
 MSK_IINF_MIO_CONSTRUCT_NUM_ROUNDINGS, 155
 MSK_IINF_MIO_CONSTRUCT_SOLUTION, 155
 MSK_IINF_MIO_INITIAL_SOLUTION, 156
 MSK_IINF_MIO_NEAR_ABSGAP_SATISFIED, 156
 MSK_IINF_MIO_NEAR_RELGAP_SATISFIED, 156
 MSK_IINF_MIO_NODE_DEPTH, 155
 MSK_IINF_MIO_NUM_ACTIVE_NODES, 155
 MSK_IINF_MIO_NUM_BRANCH, 156
 MSK_IINF_MIO_NUM_CLIQUE_CUTS, 156
 MSK_IINF_MIO_NUM_CMIR_CUTS, 156
 MSK_IINF_MIO_NUM_GOMORY_CUTS, 156
 MSK_IINF_MIO_NUM IMPLIED_BOUND_CUTS, 156
 MSK_IINF_MIO_NUM_INT_SOLUTIONS, 155
 MSK_IINF_MIO_NUM_KNAPSACK_COVER_CUTS, 156
 MSK_IINF_MIO_NUM_RELAX, 155
 MSK_IINF_MIO_NUM_REPEATED_PRESOLVE, 156
 MSK_IINF_MIO_NUMCON, 155
 MSK_IINF_MIO_NUMINT, 155
 MSK_IINF_MIO_NUMVAR, 155
 MSK_IINF_MIO_OBJ_BOUND_DEFINED, 155
 MSK_IINF_MIO_PRESOLVED_NUMBIN, 155
 MSK_IINF_MIO_PRESOLVED_NUMCON, 155
 MSK_IINF_MIO_PRESOLVED_NUMCONT, 155
 MSK_IINF_MIO_PRESOLVED_NUMINT, 155
 MSK_IINF_MIO_PRESOLVED_NUMVAR, 155
 MSK_IINF_MIO_RELGAP_SATISFIED, 156
 MSK_IINF_MIO_TOTAL_NUM_CUTS, 156
 MSK_IINF_MIO_USER_OBJ_CUT, 156
 MSK_IINF_OPT_NUMCON, 158
 MSK_IINF_OPT_NUMVAR, 158
 MSK_IINF_OPTIMIZE_RESPONSE, 155
 MSK_IINF_RD_NUMBARVAR, 156
 MSK_IINF_RD_NUMCON, 156
 MSK_IINF_RD_NUMCONE, 158
 MSK_IINF_RD_NUMINTVAR, 156
 MSK_IINF_RD_NUMQ, 156
 MSK_IINF_RD_NUMVAR, 156
 MSK_IINF_RD_PROTOTYPE, 156
 MSK_IINF_SIM_DUAL_DEG_ITER, 156
 MSK_IINF_SIM_DUAL_HOTSTART, 157
 MSK_IINF_SIM_DUAL_HOTSTART_LU, 156
 MSK_IINF_SIM_DUAL_INF_ITER, 156
 MSK_IINF_SIM_DUAL_ITER, 157
 MSK_IINF_SIM_NUMCON, 157
 MSK_IINF_SIM_NUMVAR, 157
 MSK_IINF_SIM_PRIMAL_DEG_ITER, 157
 MSK_IINF_SIM_PRIMAL_DUAL_DEG_ITER, 157
 MSK_IINF_SIM_PRIMAL_DUAL_HOTSTART, 157
 MSK_IINF_SIM_PRIMAL_DUAL_HOTSTART_LU, 157

MSK_IINF_SIM_PRIMAL_DUAL_INF_ITER, 157
MSK_IINF_SIM_PRIMAL_DUAL_ITER, 157
MSK_IINF_SIM_PRIMAL_HOTSTART, 157
MSK_IINF_SIM_PRIMAL_HOTSTART_LU, 157
MSK_IINF_SIM_PRIMAL_INF_ITER, 157
MSK_IINF_SIM_PRIMAL_ITER, 157
MSK_IINF_SIM_SOLVE_DUAL, 158
MSK_IINF_SOL_BAS_PROSTA, 157
MSK_IINF_SOL_BAS_SOLSTA, 157
MSK_IINF_SOL_ITG_PROSTA, 157
MSK_IINF_SOL_ITG_SOLSTA, 157
MSK_IINF_SOL_ITR_PROSTA, 157
MSK_IINF_SOL_ITR_SOLSTA, 157
MSK_IINF_STO_NUM_A_REALLOC, 158
MSKinfypee, 158
MSK_INF_DOU_TYPE, 158
MSK_INF_INT_TYPE, 158
MSK_INF_LINT_TYPE, 158
MSKintpnthotstarte, 142
MSK_INTPNT_HOTSTART_DUAL, 142
MSK_INTPNT_HOTSTART_NONE, 142
MSK_INTPNT_HOTSTART_PRIMAL, 142
MSK_INTPNT_HOTSTART_PRIMAL_DUAL, 142
MSKiomodee, 158
MSK_IOMODE_READ, 158
MSK_IOMODE_READWRITE, 158
MSK_IOMODE_WRITE, 158
MSKlanguagee, 140
MSK_LANG_DAN, 140
MSK_LANG_ENG, 140
MSKliinfiteme, 153
MSK_LIINF_BI_CLEAN_DUAL_DEG_ITER, 154
MSK_LIINF_BI_CLEAN_DUAL_ITER, 154
MSK_LIINF_BI_CLEAN_PRIMAL_DEG_ITER, 154
MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_DEG_ITER, 154
MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_ITER, 153
MSK_LIINF_BI_CLEAN_PRIMAL_DUAL_SUB_ITER, 154
MSK_LIINF_BI_CLEAN_PRIMAL_ITER, 153
MSK_LIINF_BI_DUAL_ITER, 153
MSK_LIINF_BI_PRIMAL_ITER, 153
MSK_LIINF_INTPNT_FACTOR_NUM_NZ, 154
MSK_LIINF_MIO_INTPNT_ITER, 153
MSK_LIINF_MIO_PRE SOLVED_ANZ, 153
MSK_LIINF_MIO_SIM_MAXITER_SETBACKS, 154
MSK_LIINF_MIO_SIMPLEX_ITER, 153
MSK_LIINF_RD_NUMANZ, 154
MSK_LIINF_RD_NUMQNZ, 154
MSKmarke, 141
MSK_MARK_LO, 141
MSK_MARK_UP, 141
MSKmiocontsoltypee, 158
MSK_MIO_CONT_SOL_ITG, 159
MSK_MIO_CONT_SOL_ITG_REL, 159
MSK_MIO_CONT_SOL_NONE, 159
MSK_MIO_CONT_SOL_ROOT, 159
MSKmioemodee, 159
MSK_MIO_MODE_IGNORED, 159
MSK_MIO_MODE_SATISFIED, 159
MSKmionodeseltypee, 159
MSK_MIO_NODE_SELECTION_BEST, 159
MSK_MIO_NODE_SELECTION_FIRST, 159
MSK_MIO_NODE_SELECTION_FREE, 159
MSK_MIO_NODE_SELECTION_HYBRID, 159
MSK_MIO_NODE_SELECTION_PSEUDO, 159
MSK_MIO_NODE_SELECTION_WORST, 159
MSKmpsformate, 159
MSK_MPS_FORMAT_CPLEX, 159
MSK_MPS_FORMAT_FREE, 159
MSK_MPS_FORMAT_RELAXED, 159
MSK_MPS_FORMAT_STRICT, 159
MSKmsgkeye, 159
MSK_MSG_MPS_SELECTED, 160
MSK_MSG_READING_FILE, 160
MSK_MSG_WRITING_FILE, 160
MSKnametypee, 148
MSK_NAME_TYPE_GEN, 148
MSK_NAME_TYPE_LP, 148
MSK_NAME_TYPE_MPS, 148
MSKobjsensee, 160
MSK_OBJECTIVE_SENSE_MAXIMIZE, 160
MSK_OBJECTIVE_SENSE_MINIMIZE, 160
MSKonoffkeye, 160
MSK_OFF, 160
MSK_ON, 160
MSKoptimizertypee, 160
MSK_OPTIMIZER_CONIC, 160
MSK_OPTIMIZER_DUAL_SIMPLEX, 160
MSK_OPTIMIZER_FREE, 160
MSK_OPTIMIZER_FREE_SIMPLEX, 160
MSK_OPTIMIZER_INTPNT, 160
MSK_OPTIMIZER_MIXED_INT, 160
MSK_OPTIMIZER_PRIMAL_SIMPLEX, 160
MSKorderingtypee, 160
MSK_ORDER_METHOD_APPMINLOC, 160
MSK_ORDER_METHOD_EXPERIMENTAL, 160
MSK_ORDER_METHOD_FORCE_GRAPHPAR, 160
MSK_ORDER_METHOD_FREE, 160
MSK_ORDER_METHOD_NONE, 160
MSK_ORDER_METHOD_TRY_GRAPHPAR, 160
MSKparametertypee, 161
MSK_PAR_DOU_TYPE, 161
MSK_PAR_INT_TYPE, 161
MSK_PAR_INVALID_TYPE, 161
MSK_PAR_STR_TYPE, 161
MSKpresolvemodee, 161
MSK_PRE SOLVE_MODE_FREE, 161
MSK_PRE SOLVE_MODE_OFF, 161
MSK_PRE SOLVE_MODE_ON, 161
MSKproblemiteme, 161
MSK_PI_CON, 161
MSK_PI_CONE, 161
MSK_PI_VAR, 161
MSKproblemtypee, 161
MSK_PROBTYPE_CONIC, 161

MSK_PROBTYPE_GECO, 161
 MSK_PROBTYPE_LO, 161
 MSK_PROBTYPE_MIXED, 161
 MSK_PROBTYPE_QCQO, 161
 MSK_PROBTYPE_QO, 161
 MSKprostae, 161
 MSK_PRO_STA_DUAL_FEAS, 162
 MSK_PRO_STA_DUAL_INFEAS, 162
 MSK_PRO_STA_ILL_POSED, 162
 MSK_PRO_STA_NEAR_DUAL_FEAS, 162
 MSK_PRO_STA_NEAR_PRIM_AND_DUAL_FEAS, 162
 MSK_PRO_STA_NEAR_PRIM_FEAS, 162
 MSK_PRO_STA_PRIM_AND_DUAL_FEAS, 161
 MSK_PRO_STA_PRIM_AND_DUAL_INFEAS, 162
 MSK_PRO_STA_PRIM_FEAS, 162
 MSK_PRO_STA_PRIM_INFEAS, 162
 MSK_PRO_STA_PRIM_INFEAS_OR_UNBOUNDED, 162
 MSK_PRO_STA_UNKNOWN, 161
 MSKrescodetypee, 162
 MSK_RESPONSE_ERR, 162
 MSK_RESPONSE_OK, 162
 MSK_RESPONSE_TRM, 162
 MSK_RESPONSE_UNK, 162
 MSK_RESPONSE_WRN, 162
 MSKscalingmethode, 163
 MSK_SCALING_METHOD_FREE, 163
 MSK_SCALING_METHOD_POW2, 163
 MSKscalingtypee, 162
 MSK_SCALING_AGGRESSIVE, 163
 MSK_SCALING_FREE, 162
 MSK_SCALING_MODERATE, 163
 MSK_SCALING_NONE, 162
 MSKsensitivitytypee, 163
 MSK_SENSITIVITY_TYPE_BASIS, 163
 MSK_SENSITIVITY_TYPE_OPTIMAL_PARTITION, 163
 MSKsimdegene, 141
 MSK_SIM_DEGEN_AGGRESSIVE, 141
 MSK_SIM_DEGEN_FREE, 141
 MSK_SIM_DEGEN_MINIMUM, 141
 MSK_SIM_DEGEN_MODERATE, 141
 MSK_SIM_DEGEN_NONE, 141
 MSKsimdupvece, 142
 MSK_SIM_EXPLOIT_DUPVEC_FREE, 142
 MSK_SIM_EXPLOIT_DUPVEC_OFF, 142
 MSK_SIM_EXPLOIT_DUPVEC_ON, 142
 MSKsimhotstarte, 142
 MSK_SIM_HOTSTART_FREE, 142
 MSK_SIM_HOTSTART_NONE, 142
 MSK_SIM_HOTSTART_STATUS_KEYS, 142
 MSKsimreforme, 142
 MSK_SIM_REFORMULATION_AGGRESSIVE, 142
 MSK_SIM_REFORMULATION_FREE, 142
 MSK_SIM_REFORMULATION_OFF, 142
 MSK_SIM_REFORMULATION_ON, 142
 MSKsimseltypee, 163
 MSK_SIM_SELECTION_ASE, 163
 MSK_SIM_SELECTION_DEVEX, 163
 MSK_SIM_SELECTION_FREE, 163
 MSK_SIM_SELECTION_FULL, 163
 MSK_SIM_SELECTION_PARTIAL, 163
 MSK_SIM_SELECTION_SE, 163
 MSKsoliteme, 163
 MSK_SOL_ITEM_SLC, 163
 MSK_SOL_ITEM_SLX, 163
 MSK_SOL_ITEM_SNX, 164
 MSK_SOL_ITEM_SUC, 163
 MSK_SOL_ITEM_SUX, 164
 MSK_SOL_ITEM_XC, 163
 MSK_SOL_ITEM_XX, 163
 MSK_SOL_ITEM_Y, 163
 MSKsolstae, 164
 MSK_SOL_STA_DUAL_FEAS, 164
 MSK_SOL_STA_DUAL_ILLPOSED_CER, 164
 MSK_SOL_STA_DUAL_INFEAS_CER, 164
 MSK_SOL_STA_INTEGER_OPTIMAL, 164
 MSK_SOL_STA_NEAR_DUAL_FEAS, 164
 MSK_SOL_STA_NEAR_DUAL_INFEAS_CER, 164
 MSK_SOL_STA_NEAR_INTEGER_OPTIMAL, 164
 MSK_SOL_STA_NEAR_OPTIMAL, 164
 MSK_SOL_STA_NEAR_PRIM_AND_DUAL_FEAS, 164
 MSK_SOL_STA_NEAR_PRIM_FEAS, 164
 MSK_SOL_STA_NEAR_PRIM_INFEAS_CER, 164
 MSK_SOL_STA_OPTIMAL, 164
 MSK_SOL_STA_PRIM_AND_DUAL_FEAS, 164
 MSK_SOL_STA_PRIM_FEAS, 164
 MSK_SOL_STA_PRIM_ILLPOSED_CER, 164
 MSK_SOL_STA_PRIM_INFEAS_CER, 164
 MSK_SOL_STA_UNKNOWN, 164
 MSKsoltypee, 164
 MSK_SOL_BAS, 164
 MSK_SOL_ITG, 165
 MSK_SOL_ITR, 164
 MSKsolveforme, 165
 MSK_SOLVE_DUAL, 165
 MSK_SOLVE_FREE, 165
 MSK_SOLVE_PRIMAL, 165
 MSKstakeye, 165
 MSK_SK_BAS, 165
 MSK_SK_FIX, 165
 MSK_SK_INF, 165
 MSK_SK_LOW, 165
 MSK_SK_SUPBAS, 165
 MSK_SK_UNK, 165
 MSK_SK_UPR, 165
 MSKstartpointtypee, 165
 MSK_STARTING_POINT_CONSTANT, 165
 MSK_STARTING_POINT_FREE, 165
 MSK_STARTING_POINT_GUESS, 165
 MSK_STARTING_POINT_SATISFY_BOUNDS, 165
 MSKstreamtypee, 165
 MSK_STREAM_ERR, 166
 MSK_STREAM_LOG, 165
 MSK_STREAM_MSG, 165
 MSK_STREAM_WRN, 166
 MSKsymmattypee, 148
 MSK_SYMMAT_TYPE_SPARSE, 148

MSKtranspose, 141
MSK_TRANSPOSE_NO, 141
MSK_TRANSPOSE_YES, 141
MSKuploe, 141
MSK_UPLO_LO, 142
MSK_UPLO_UP, 142
MSKvaluee, 166
MSK_LICENSE_BUFFER_LENGTH, 166
MSK_MAX_STR_LEN, 166
MSKvariabletypee, 166
MSK_VAR_TYPE_CONT, 166
MSK_VAR_TYPE_INT, 166
MSKxmlwriteroutputtypee, 162
MSK_WRITE_XML_MODE_COL, 162
MSK_WRITE_XML_MODE_ROW, 162

Functions

Parameters

Double params, 72
MSK_DPAR_ANA_SOL_INFEAS_TOL, 72
MSK_DPAR_BASIS_REL_TOL_S, 72
MSK_DPAR_BASIS_TOL_S, 72
MSK_DPAR_BASIS_TOL_X, 72
MSK_DPAR_CHECK_CONVEXITY_REL_TOL, 72
MSK_DPAR_DATA_SYM_MAT_TOL, 72
MSK_DPAR_DATA_SYM_MAT_TOL_HUGE, 73
MSK_DPAR_DATA_SYM_MAT_TOL_LARGE, 73
MSK_DPAR_DATA_TOL_AIJ, 73
MSK_DPAR_DATA_TOL_AIJ_HUGE, 73
MSK_DPAR_DATA_TOL_AIJ_LARGE, 73
MSK_DPAR_DATA_TOL_BOUND_INF, 73
MSK_DPAR_DATA_TOL_BOUND_WRN, 73
MSK_DPAR_DATA_TOL_C_HUGE, 74
MSK_DPAR_DATA_TOL_CJ_LARGE, 73
MSK_DPAR_DATA_TOL_QIJ, 74
MSK_DPAR_DATA_TOL_X, 74
MSK_DPAR_INTPNT_CO_TOL_DFEAS, 74
MSK_DPAR_INTPNT_CO_TOL_INFEAS, 74
MSK_DPAR_INTPNT_CO_TOL_MU_RED, 74
MSK_DPAR_INTPNT_CO_TOL_NEAR_REL, 74
MSK_DPAR_INTPNT_CO_TOL_PFEAS, 74
MSK_DPAR_INTPNT_CO_TOL_REL_GAP, 75
MSK_DPAR_INTPNT_NL_MERIT_BAL, 75
MSK_DPAR_INTPNT_NL_TOL_DFEAS, 75
MSK_DPAR_INTPNT_NL_TOL_MU_RED, 75
MSK_DPAR_INTPNT_NL_TOL_NEAR_REL, 75
MSK_DPAR_INTPNT_NL_TOL_PFEAS, 75
MSK_DPAR_INTPNT_NL_TOL_REL_GAP, 75
MSK_DPAR_INTPNT_NL_TOL_REL_STEP, 76
MSK_DPAR_INTPNT_QO_TOL_DFEAS, 76
MSK_DPAR_INTPNT_QO_TOL_INFEAS, 76
MSK_DPAR_INTPNT_QO_TOL_MU_RED, 76
MSK_DPAR_INTPNT_QO_TOL_NEAR_REL, 76
MSK_DPAR_INTPNT_QO_TOL_PFEAS, 76
MSK_DPAR_INTPNT_QO_TOL_REL_GAP, 76
MSK_DPAR_INTPNT_TOL_DFEAS, 76
MSK_DPAR_INTPNT_TOL_DSAFE, 77

MSK_DPAR_INTPNT_TOL_INFEAS, 77
MSK_DPAR_INTPNT_TOL_MU_RED, 77
MSK_DPAR_INTPNT_TOL_PATH, 77
MSK_DPAR_INTPNT_TOL_PFEAS, 77
MSK_DPAR_INTPNT_TOL_PSAFE, 77
MSK_DPAR_INTPNT_TOL_REL_GAP, 77
MSK_DPAR_INTPNT_TOL_REL_STEP, 78
MSK_DPAR_INTPNT_TOL_STEP_SIZE, 78
MSK_DPAR_LOWER_OBJ_CUT, 78
MSK_DPAR_LOWER_OBJ_CUT_FINITE_TRH, 78
MSK_DPAR_MIO_DISABLE_TERM_TIME, 78
MSK_DPAR_MIO_MAX_TIME, 78
MSK_DPAR_MIO_NEAR_TOL_ABS_GAP, 79
MSK_DPAR_MIO_NEAR_TOL_REL_GAP, 79
MSK_DPAR_MIO_REL_GAP_CONST, 79
MSK_DPAR_MIO_TOL_ABS_GAP, 79
MSK_DPAR_MIO_TOL_ABS_RELAX_INT, 79
MSK_DPAR_MIO_TOL_FEAS, 79
MSK_DPAR_MIO_TOL_REL_DUAL_BOUND_IMPROVEMENT, 79
MSK_DPAR_MIO_TOL_REL_GAP, 80
MSK_DPAR_OPTIMIZER_MAX_TIME, 80
MSK_DPAR_PREOLVE_TOL_ABS_LINDEP, 80
MSK_DPAR_PREOLVE_TOL_AIJ, 80
MSK_DPAR_PREOLVE_TOL_REL_LINDEP, 80
MSK_DPAR_PREOLVE_TOL_S, 80
MSK_DPAR_PREOLVE_TOL_X, 80
MSK_DPAR_QCQO_REFORMULATE_REL_DROP_TOL, 80
MSK_DPAR_SEMIDEFINITE_TOL_APPROX, 81
MSK_DPAR_SIM_LU_TOL_REL_PIV, 81
MSK_DPAR_SIMPLEX_ABS_TOL_PIV, 81
MSK_DPAR_UPPER_OBJ_CUT, 81
MSK_DPAR_UPPER_OBJ_CUT_FINITE_TRH, 81
Integer params, 81
MSK_IPAR_ANA_SOL_BASIS, 81
MSK_IPAR_ANA_SOL_PRINT_VIOLATED, 81
MSK_IPAR_AUTO_SORT_A_BEFORE_OPT, 82
MSK_IPAR_AUTO_UPDATE_SOL_INFO, 82
MSK_IPAR_BASIS_SOLVE_USE_PLUS_ONE, 82
MSK_IPAR_BI_CLEAN_OPTIMIZER, 82
MSK_IPAR_BI_IGNORE_MAX_ITER, 82
MSK_IPAR_BI_IGNORE_NUM_ERROR, 82
MSK_IPAR_BI_MAX_ITERATIONS, 82
MSK_IPAR_CACHE_LICENSE, 83
MSK_IPAR_CHECK_CONVEXITY, 83
MSK_IPAR_COMPRESS_STATFILE, 83
MSK_IPAR_INFEAS_GENERIC_NAMES, 83
MSK_IPAR_INFEAS_PREFER_PRIMAL, 83
MSK_IPAR_INFEAS_REPORT_AUTO, 83
MSK_IPAR_INFEAS_REPORT_LEVEL, 83
MSK_IPAR_INTPNT_BASIS, 84
MSK_IPAR_INTPNT_DIFF_STEP, 84
MSK_IPAR_INTPNT_HOTSTART, 84
MSK_IPAR_INTPNT_MAX_ITERATIONS, 84
MSK_IPAR_INTPNT_MAX_NUM_COR, 84
MSK_IPAR_INTPNT_MAX_NUM_REFINEMENT_STEPS, 84
MSK_IPAR_INTPNT_MULTI_THREAD, 84

MSK_IPAR_INTPNT_OFF_COL_TRH, 85
 MSK_IPAR_INTPNT_ORDER_METHOD, 85
 MSK_IPAR_INTPNT_REGULARIZATION_USE, 85
 MSK_IPAR_INTPNT_SCALING, 85
 MSK_IPAR_INTPNT_SOLVE_FORM, 85
 MSK_IPAR_INTPNT_STARTING_POINT, 85
 MSK_IPAR_LICENSE_DEBUG, 85
 MSK_IPAR_LICENSE_PAUSE_TIME, 85
 MSK_IPAR_LICENSE_SUPPRESS_EXPIRE_WRNS, 86
 MSK_IPAR_LICENSE_TRH_EXPIRY_WRN, 86
 MSK_IPAR_LICENSE_WAIT, 86
 MSK_IPAR_LOG, 86
 MSK_IPAR_LOG_ANA_PRO, 86
 MSK_IPAR_LOG_BI, 86
 MSK_IPAR_LOG_BI_FREQ, 86
 MSK_IPAR_LOG_CHECK_CONVEXITY, 87
 MSK_IPAR_LOG_CUT_SECOND_OPT, 87
 MSK_IPAR_LOG_EXPAND, 87
 MSK_IPAR_LOG_FACTOR, 87
 MSK_IPAR_LOG_FEAS_REPAIR, 87
 MSK_IPAR_LOG_FILE, 87
 MSK_IPAR_LOG_HEAD, 87
 MSK_IPAR_LOG_INFEAS_ANA, 88
 MSK_IPAR_LOG_INTPNT, 88
 MSK_IPAR_LOG_MIO, 88
 MSK_IPAR_LOG_MIO_FREQ, 88
 MSK_IPAR_LOG_OPTIMIZER, 88
 MSK_IPAR_LOG_ORDER, 88
 MSK_IPAR_LOG PRESOLVE, 88
 MSK_IPAR_LOG_RESPONSE, 89
 MSK_IPAR_LOG_SENSITIVITY, 89
 MSK_IPAR_LOG_SENSITIVITY_OPT, 89
 MSK_IPAR_LOG_SIM, 89
 MSK_IPAR_LOG_SIM_FREQ, 89
 MSK_IPAR_LOG_SIM_MINOR, 89
 MSK_IPAR_LOG_STORAGE, 89
 MSK_IPAR_MAX_NUM_WARNINGS, 90
 MSK_IPAR_MIO_BRANCH_DIR, 90
 MSK_IPAR_MIO_CONSTRUCT_SOL, 90
 MSK_IPAR_MIO_CUT_CLIQUE, 90
 MSK_IPAR_MIO_CUT_CMIR, 90
 MSK_IPAR_MIO_CUT_GMI, 90
 MSK_IPAR_MIO_CUT_IMPLIED_BOUND, 90
 MSK_IPAR_MIO_CUT_KNAPSACK_COVER, 90
 MSK_IPAR_MIO_CUT_SELECTION_LEVEL, 91
 MSK_IPAR_MIO_HEURISTIC_LEVEL, 91
 MSK_IPAR_MIO_MAX_NUM_BRANCHES, 91
 MSK_IPAR_MIO_MAX_NUM_RELAXS, 91
 MSK_IPAR_MIO_MAX_NUM_SOLUTIONS, 91
 MSK_IPAR_MIO_MODE, 91
 MSK_IPAR_MIO_MT_USER_CB, 91
 MSK_IPAR_MIO_NODE_OPTIMIZER, 92
 MSK_IPAR_MIO_NODE_SELECTION, 92
 MSK_IPAR_MIO_PERSPECTIVE_REFORMULATE, 92
 MSK_IPAR_MIO_PROBING_LEVEL, 92
 MSK_IPAR_MIO_RINS_MAX_NODES, 92
 MSK_IPAR_MIO_ROOT_OPTIMIZER, 92
 MSK_IPAR_MIO_ROOT_REPEAT_PRESOLVE_LEVEL, 92
 MSK_IPAR_MIO_VB_DETECTION_LEVEL, 93
 MSK_IPAR_MT_SPINCOUNT, 93
 MSK_IPAR_NUM_THREADS, 93
 MSK_IPAR_OPF_MAX_TERMS_PER_LINE, 93
 MSK_IPAR_OPF_WRITE_HEADER, 93
 MSK_IPAR_OPF_WRITE_HINTS, 93
 MSK_IPAR_OPF_WRITE_PARAMETERS, 94
 MSK_IPAR_OPF_WRITE_PROBLEM, 94
 MSK_IPAR_OPF_WRITE_SOL_BAS, 94
 MSK_IPAR_OPF_WRITE_SOL_ITG, 94
 MSK_IPAR_OPF_WRITE_SOL_ITR, 94
 MSK_IPAR_OPF_WRITE_SOLUTIONS, 94
 MSK_IPAR_OPTIMIZER, 94
 MSK_IPAR_PARAM_READ_CASE_NAME, 94
 MSK_IPAR_PARAM_READ_IGN_ERROR, 95
 MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_FILL, 95
 MSK_IPAR_PRESOLVE_ELIMINATOR_MAX_NUM_TRIES, 95
 MSK_IPAR_PRESOLVE_LEVEL, 95
 MSK_IPAR_PRESOLVE_LINDEP_ABS_WORK_TRH, 95
 MSK_IPAR_PRESOLVE_LINDEP_REL_WORK_TRH, 95
 MSK_IPAR_PRESOLVE_LINDEP_USE, 95
 MSK_IPAR_PRESOLVE_MAX_NUM_REDUCTIONS, 95
 MSK_IPAR_PRESOLVE_USE, 95
 MSK_IPAR_PRIMAL_REPAIR_OPTIMIZER, 96
 MSK_IPAR_READ_DATA_COMPRESSED, 96
 MSK_IPAR_READ_DATA_FORMAT, 96
 MSK_IPAR_READ_DEBUG, 96
 MSK_IPAR_READ_KEEP_FREE_CON, 96
 MSK_IPAR_READ_LP_DROP_NEW_VARS_IN_BOU, 96
 MSK_IPAR_READ_LP_QUOTED_NAMES, 96
 MSK_IPAR_READ_MPS_FORMAT, 96
 MSK_IPAR_READ_MPS_WIDTH, 97
 MSK_IPAR_READ_TASK_IGNORE_PARAM, 97
 MSK_IPAR_SENSITIVITY_ALL, 97
 MSK_IPAR_SENSITIVITY_OPTIMIZER, 97
 MSK_IPAR_SENSITIVITY_TYPE, 97
 MSK_IPAR_SIM_BASIS_FACTOR_USE, 97
 MSK_IPAR_SIM_DEGEN, 97
 MSK_IPAR_SIM_DUAL_CRASH, 98
 MSK_IPAR_SIM_DUAL_PHASEONE_METHOD, 98
 MSK_IPAR_SIM_DUAL_RESTRICT_SELECTION, 98
 MSK_IPAR_SIM_DUAL_SELECTION, 98
 MSK_IPAR_SIM_EXPLOIT_DUPVEC, 98
 MSK_IPAR_SIM_HOTSTART, 98
 MSK_IPAR_SIM_HOTSTART_LU, 98
 MSK_IPAR_SIM_INTEGER, 98
 MSK_IPAR_SIM_MAX_ITERATIONS, 99
 MSK_IPAR_SIM_MAX_NUM_SETBACKS, 99
 MSK_IPAR_SIM_NON_SINGULAR, 99
 MSK_IPAR_SIM_PRIMAL_CRASH, 99
 MSK_IPAR_SIM_PRIMAL_PHASEONE_METHOD, 99
 MSK_IPAR_SIM_PRIMAL_RESTRICT_SELECTION, 99
 MSK_IPAR_SIM_PRIMAL_SELECTION, 100
 MSK_IPAR_SIM_REFACTOR_FREQ, 100
 MSK_IPAR_SIM_REFORMULATION, 100
 MSK_IPAR_SIM_SAVE_LU, 100
 MSK_IPAR_SIM_SCALING, 100

MSK_IPAR_SIM_SCALING_METHOD, 100
MSK_IPAR_SIM_SOLVE_FORM, 100
MSK_IPAR_SIM_STABILITY_PRIORITY, 100
MSK_IPAR_SIM_SWITCH_OPTIMIZER, 101
MSK_IPAR_SOL_FILTER_KEEP_BASIC, 101
MSK_IPAR_SOL_FILTER_KEEP_RANGED, 101
MSK_IPAR_SOL_READ_NAME_WIDTH, 101
MSK_IPAR_SOL_READ_WIDTH, 101
MSK_IPAR_SOLUTION_CALLBACK, 101
MSK_IPAR_TIMING_LEVEL, 101
MSK_IPAR_WRITE_BAS_CONSTRAINTS, 101
MSK_IPAR_WRITE_BAS_HEAD, 102
MSK_IPAR_WRITE_BAS_VARIABLES, 102
MSK_IPAR_WRITE_DATA_COMPRESSED, 102
MSK_IPAR_WRITE_DATA_FORMAT, 102
MSK_IPAR_WRITE_DATA_PARAM, 102
MSK_IPAR_WRITE_FREE_CON, 102
MSK_IPAR_WRITE_GENERIC_NAMES, 102
MSK_IPAR_WRITE_GENERIC_NAMES_IO, 102
MSK_IPAR_WRITE_IGNORE_INCOMPATIBLE_ITEMS,
103
MSK_IPAR_WRITE_INT_CONSTRAINTS, 103
MSK_IPAR_WRITE_INT_HEAD, 103
MSK_IPAR_WRITE_INT_VARIABLES, 103
MSK_IPAR_WRITE_LP_FULL_OBJ, 103
MSK_IPAR_WRITE_LP_LINE_WIDTH, 103
MSK_IPAR_WRITE_LP_QUOTED_NAMES, 103
MSK_IPAR_WRITE_LP_STRICT_FORMAT, 103
MSK_IPAR_WRITE_LP_TERMS_PER_LINE, 104
MSK_IPAR_WRITE_MPS_FORMAT, 104
MSK_IPAR_WRITE_MPS_INT, 104
MSK_IPAR_WRITE_PRECISION, 104
MSK_IPAR_WRITE_SOL_BARVARIABLES, 104
MSK_IPAR_WRITE_SOL_CONSTRAINTS, 104
MSK_IPAR_WRITE_SOL_HEAD, 104
MSK_IPAR_WRITE_SOL_IGNORE_INVALID_NAMES,
104
MSK_IPAR_WRITE_SOL_VARIABLES, 105
MSK_IPAR_WRITE_TASK_INC_SOL, 105
MSK_IPAR_WRITE_XML_MODE, 105
String params, 105
MSK_SPAR_BAS_SOL_FILE_NAME, 105
MSK_SPAR_DATA_FILE_NAME, 105
MSK_SPAR_DEBUG_FILE_NAME, 105
MSK_SPAR_INT_SOL_FILE_NAME, 105
MSK_SPAR_ITR_SOL_FILE_NAME, 105
MSK_SPAR_MIO_DEBUG_STRING, 106
MSK_SPAR_PARAM_COMMENT_SIGN, 106
MSK_SPAR_PARAM_READ_FILE_NAME, 106
MSK_SPAR_PARAM_WRITE_FILE_NAME, 106
MSK_SPAR_READ_MPS_BOU_NAME, 106
MSK_SPAR_READ_MPS_OBJ_NAME, 106
MSK_SPAR_READ_MPS_RAN_NAME, 106
MSK_SPAR_READ_MPS_RHS_NAME, 106
MSK_SPAR_REMOTE_ACCESS_TOKEN, 106
MSK_SPAR_SENSITIVITY_FILE_NAME, 106
MSK_SPAR_SENSITIVITY_RES_FILE_NAME, 107
MSK_SPAR_SOL_FILTER_XC_LOW, 107

MSK_SPAR_SOL_FILTER_XC_UPR, 107
MSK_SPAR_SOL_FILTER_XX_LOW, 107
MSK_SPAR_SOL_FILTER_XX_UPR, 107
MSK_SPAR_STAT_FILE_NAME, 107
MSK_SPAR_STAT_KEY, 107
MSK_SPAR_STAT_NAME, 107
MSK_SPAR_WRITE_LP_GEN_VAR_NAME, 107

Response codes

MSK_RES_OK (*ok*), 119
MSK_RES_TRM_INTERNAL (*trm_internal*), 119
MSK_RES_TRM_INTERNAL_STOP
(*trm_internal_stop*), 119
MSK_RES_TRM_MAX_ITERATIONS
(*trm_max_iterations*), 119
MSK_RES_TRM_MAX_NUM_SETBACKS
(*trm_max_num_setbacks*), 119
MSK_RES_TRM_MAX_TIME (*trm_max_time*), 119
MSK_RES_TRM_MIO_NEAR_ABS_GAP
(*trm_mio_near_abs_gap*), 119
MSK_RES_TRM_MIO_NEAR_REL_GAP
(*trm_mio_near_rel_gap*), 119
MSK_RES_TRM_MIO_NUM_BRANCHES
(*trm_mio_num_branches*), 119
MSK_RES_TRM_MIO_NUM_RELAXS
(*trm_mio_num_relaxs*), 119
MSK_RES_TRM_NUM_MAX_NUM_INT_SOLUTIONS
(*trm_num_max_num_int_solutions*),
119
MSK_RES_TRM_NUMERICAL_PROBLEM
(*trm_numerical_problem*), 120
MSK_RES_TRM_OBJECTIVE_RANGE
(*trm_objective_range*), 120
MSK_RES_TRM_STALL (*trm_stall*), 120
MSK_RES_TRM_USER_CALLBACK
(*trm_user_callback*), 120
MSK_RES_WRN_ANA_ALMOST_INT_BOUNDS
(*wrn_ana_almost_int_bounds*), 137
MSK_RES_WRN_ANA_C_ZERO (*wrn_ana_c_zero*),
137
MSK_RES_WRN_ANA_CLOSE_BOUNDS
(*wrn_ana_close_bounds*), 137
MSK_RES_WRN_ANA_EMPTY_COLS
(*wrn_ana_empty_cols*), 137
MSK_RES_WRN_ANA_LARGE_BOUNDS
(*wrn_ana_large_bounds*), 137
MSK_RES_WRN_CONSTRUCT_INVALID_SOL_ITG
(*wrn_construct_invalid_sol_itg*), 137
MSK_RES_WRN_CONSTRUCT_NO_SOL_ITG
(*wrn_construct_no_sol_itg*), 137
MSK_RES_WRN_CONSTRUCT_SOLUTION_INFEAS
(*wrn_construct_solution_infeas*), 138
MSK_RES_WRN_DROPPED_NZ_QOBJ
(*wrn_dropped_nz_qobj*), 138
MSK_RES_WRN_DUPLICATE_BARVARIABLE_NAMES
(*wrn_duplicate_barvariable_names*),
138

MSK_RES_WRN_DUPLICATE_CONE_NAMES (<i>wrn_duplicate_cone_names</i>), 138	MSK_RES_WRN_PARAM_NAME_DOU (<i>wrn_param_name_dou</i>), 139
MSK_RES_WRN_DUPLICATE_CONSTRAINT_NAMES (<i>wrn_duplicate_constraint_names</i>), 138	MSK_RES_WRN_PARAM_NAME_INT (<i>wrn_param_name_int</i>), 139
MSK_RES_WRN_DUPLICATE_VARIABLE_NAMES (<i>wrn_duplicate_variable_names</i>), 138	MSK_RES_WRN_PARAM_NAME_STR (<i>wrn_param_name_str</i>), 139
MSK_RES_WRN_ELIMINATOR_SPACE (<i>wrn_eliminator_space</i>), 138	MSK_RES_WRN_PARAM_STR_VALUE (<i>wrn_param_str_value</i>), 139
MSK_RES_WRN_EMPTY_NAME (<i>wrn_empty_name</i>), 138	MSK_RES_WRN_PRESOLVE_OUTOFSPACE (<i>wrn_presolve_outofspace</i>), 139
MSK_RES_WRN_IGNORE_INTEGER (<i>wrn_ignore_integer</i>), 138	MSK_RES_WRN_QUAD_CONES_WITH_ROOT_FIXED_AT_ZERO (<i>wrn_quad_cones_with_root_fixed_at_zero</i>), 139
MSK_RES_WRN_INCOMPLETE_LINEAR_DEPENDENCY_CHECK (<i>wrn_incomplete_linear_dependency_check</i>), 138	MSK_RES_WRN_RQUAD_CONES_WITH_ROOT_FIXED_AT_ZERO (<i>wrn_rquad_cones_with_root_fixed_at_zero</i>), 139
MSK_RES_WRN_LARGE_AIJ (<i>wrn_large_aij</i>), 138	MSK_RES_WRN_SOL_FILE_IGNORED_CON (<i>wrn_sol_file_ignored_con</i>), 139
MSK_RES_WRN_LARGE_BOUND (<i>wrn_large_bound</i>), 138	MSK_RES_WRN_SOL_FILE_IGNORED_VAR (<i>wrn_sol_file_ignored_var</i>), 139
MSK_RES_WRN_LARGE_CJ (<i>wrn_large_cj</i>), 138	MSK_RES_WRN_SOL_FILTER (<i>wrn_sol_filter</i>), 139
MSK_RES_WRN_LARGE_CON_FX (<i>wrn_large_con_fx</i>), 138	MSK_RES_WRN_SPAR_MAX_LEN (<i>wrn_spar_max_len</i>), 140
MSK_RES_WRN_LARGE_LO_BOUND (<i>wrn_large_lo_bound</i>), 138	MSK_RES_WRN_SYM_MAT_LARGE (<i>wrn_sym_mat_large</i>), 140
MSK_RES_WRN_LARGE_UP_BOUND (<i>wrn_large_up_bound</i>), 138	MSK_RES_WRN_TOO_FEW_BASIS_VARS (<i>wrn_too_few_basis_vars</i>), 140
MSK_RES_WRN_LICENSE_EXPIRE (<i>wrn_license_expire</i>), 138	MSK_RES_WRN_TOO_MANY_BASIS_VARS (<i>wrn_too_many_basis_vars</i>), 140
MSK_RES_WRN_LICENSE_FEATURE_EXPIRE (<i>wrn_license_feature_expire</i>), 138	MSK_RES_WRN_UNDEF_SOL_FILE_NAME (<i>wrn_undef_sol_file_name</i>), 140
MSK_RES_WRN_LICENSE_SERVER (<i>wrn_license_server</i>), 138	MSK_RES_WRN_USING_GENERIC_NAMES (<i>wrn_using_generic_names</i>), 140
MSK_RES_WRN_LP_DROP_VARIABLE (<i>wrn_lp_drop_variable</i>), 138	MSK_RES_WRN_WRITE_CHANGED_NAMES (<i>wrn_write_changed_names</i>), 140
MSK_RES_WRN_LP_OLD_QUAD_FORMAT (<i>wrn_lp_old_quad_format</i>), 138	MSK_RES_WRN_WRITE_DISCARDED_CFIX (<i>wrn_write_discarded_cfix</i>), 140
MSK_RES_WRN_MIO_INFEASIBLE_FINAL (<i>wrn_mio_infeasible_final</i>), 139	MSK_RES_WRN_ZERO_AIJ (<i>wrn_zero_aij</i>), 140
MSK_RES_WRN_MPS_SPLIT_BOU_VECTOR (<i>wrn_mps_split_bou_vector</i>), 139	MSK_RES_WRN_ZEROS_IN_SPARSE_COL (<i>wrn_zeros_in_sparse_col</i>), 140
MSK_RES_WRN_MPS_SPLIT_RAN_VECTOR (<i>wrn_mps_split_ran_vector</i>), 139	MSK_RES_WRN_ZEROS_IN_SPARSE_ROW (<i>wrn_zeros_in_sparse_row</i>), 140
MSK_RES_WRN_MPS_SPLIT_RHS_VECTOR (<i>wrn_mps_split_rhs_vector</i>), 139	MSK_RES_ERR_AD_INVALID_CODELIST (<i>err_ad_invalid_codelist</i>), 120
MSK_RES_WRN_NAME_MAX_LEN (<i>wrn_name_max_len</i>), 139	MSK_RES_ERR_API_ARRAY_TOO_SMALL (<i>err_api_array_too_small</i>), 120
MSK_RES_WRN_NO_DUALIZER (<i>wrn_no_dualizer</i>), 139	MSK_RES_ERR_API_CB_CONNECT (<i>err_api_cb_connect</i>), 120
MSK_RES_WRN_NO_GLOBAL_OPTIMIZER (<i>wrn_no_global_optimizer</i>), 139	MSK_RES_ERR_API_FATAL_ERROR (<i>err_api_fatal_error</i>), 120
MSK_RES_WRN_NO_NONLINEAR_FUNCTION_WRITE (<i>wrn_no_nonlinear_function_write</i>), 139	MSK_RES_ERR_API_INTERNAL (<i>err_api_internal</i>), 120
MSK_RES_WRN_NZ_IN_UPR_TRI (<i>wrn_nz_in_upr_tri</i>), 139	MSK_RES_ERR_ARG_IS_TOO_LARGE (<i>err_arg_is_too_large</i>), 120
MSK_RES_WRN_OPEN_PARAM_FILE (<i>wrn_open_param_file</i>), 139	MSK_RES_ERR_ARG_IS_TOO_SMALL (<i>err_arg_is_too_small</i>), 120
MSK_RES_WRN_PARAM_IGNORED_CMIO (<i>wrn_param_ignored_cmio</i>), 139	MSK_RES_ERR_ARGUMENT_DIMENSION (<i>err_argument_dimension</i>), 120

MSK_RES_ERR_ARGUMENT_IS_TOO_LARGE
(*err_argument_is_too_large*), 120

MSK_RES_ERR_ARGUMENT_LENNEQ
(*err_argument_lenneq*), 120

MSK_RES_ERR_ARGUMENT_PERM_ARRAY
(*err_argument_perm_array*), 120

MSK_RES_ERR_ARGUMENT_TYPE
(*err_argument_type*), 120

MSK_RES_ERR_BAR_VAR_DIM (*err_bar_var_dim*),
121

MSK_RES_ERR_BASIS (*err_basis*), 121

MSK_RES_ERR_BASIS_FACTOR (*err_basis_factor*),
121

MSK_RES_ERR_BASIS_SINGULAR
(*err_basis_singular*), 121

MSK_RES_ERR_BLANK_NAME (*err_blank_name*), 121

MSK_RES_ERR_CANNOT_CLONE_NL
(*err_cannot_clone_nl*), 121

MSK_RES_ERR_CANNOT_HANDLE_NL
(*err_cannot_handle_nl*), 121

MSK_RES_ERR_CBF_DUPLICATE_ACOORD
(*err_cbf_duplicate_acoord*), 121

MSK_RES_ERR_CBF_DUPLICATE_BCOORD
(*err_cbf_duplicate_bcoord*), 121

MSK_RES_ERR_CBF_DUPLICATE_CON
(*err_cbf_duplicate_con*), 121

MSK_RES_ERR_CBF_DUPLICATE_INT
(*err_cbf_duplicate_int*), 121

MSK_RES_ERR_CBF_DUPLICATE_OBJ
(*err_cbf_duplicate_obj*), 121

MSK_RES_ERR_CBF_DUPLICATE_OBJACCOORD
(*err_cbf_duplicate_objacoord*), 121

MSK_RES_ERR_CBF_DUPLICATE_VAR
(*err_cbf_duplicate_var*), 121

MSK_RES_ERR_CBF_INVALID_CON_TYPE
(*err_cbf_invalid_con_type*), 121

MSK_RES_ERR_CBF_INVALID_DOMAIN_DIMENSION
(*err_cbf_invalid_domain_dimension*),
121

MSK_RES_ERR_CBF_INVALID_INT_INDEX
(*err_cbf_invalid_int_index*), 121

MSK_RES_ERR_CBF_INVALID_VAR_TYPE
(*err_cbf_invalid_var_type*), 121

MSK_RES_ERR_CBF_NO_VARIABLES
(*err_cbf_no_variables*), 121

MSK_RES_ERR_CBF_NO_VERSION_SPECIFIED
(*err_cbf_no_version_specified*), 121

MSK_RES_ERR_CBF_OBJ_SENSE
(*err_cbf_obj_sense*), 121

MSK_RES_ERR_CBF_PARSE (*err_cbf_parse*), 121

MSK_RES_ERR_CBF_SYNTAX (*err_cbf_syntax*), 121

MSK_RES_ERR_CBF_TOO_FEW_CONSTRAINTS
(*err_cbf_too_few_constraints*), 122

MSK_RES_ERR_CBF_TOO_FEW_INTS
(*err_cbf_too_few_ints*), 122

MSK_RES_ERR_CBF_TOO_FEW_VARIABLES
(*err_cbf_too_few_variables*), 122

MSK_RES_ERR_CBF_TOO_MANY_CONSTRAINTS
(*err_cbf_too_many_constraints*), 122

MSK_RES_ERR_CBF_TOO_MANY_INTS
(*err_cbf_too_many_ints*), 122

MSK_RES_ERR_CBF_TOO_MANY_VARIABLES
(*err_cbf_too_many_variables*), 122

MSK_RES_ERR_CBF_UNSUPPORTED
(*err_cbf_unsupported*), 122

MSK_RES_ERR_CON_Q_NOT_NSD
(*err_con_q_not_nsd*), 122

MSK_RES_ERR_CON_Q_NOT_PSD
(*err_con_q_not_psd*), 122

MSK_RES_ERR_CONE_INDEX (*err_cone_index*), 122

MSK_RES_ERR_CONE_OVERLAP (*err_cone_overlap*),
122

MSK_RES_ERR_CONE_OVERLAP_APPEND
(*err_cone_overlap_append*), 122

MSK_RES_ERR_CONE_REP_VAR
(*err_cone_rep_var*), 122

MSK_RES_ERR_CONE_SIZE (*err_cone_size*), 122

MSK_RES_ERR_CONE_TYPE (*err_cone_type*), 122

MSK_RES_ERR_CONE_TYPE_STR
(*err_cone_type_str*), 122

MSK_RES_ERR_DATA_FILE_EXT
(*err_data_file_ext*), 122

MSK_RES_ERR_DUP_NAME (*err_dup_name*), 122

MSK_RES_ERR_DUPLICATE_AIJ
(*err_duplicate_aij*), 122

MSK_RES_ERR_DUPLICATE_BARVARIABLE_NAMES
(*err_duplicate_barvariable_names*), 122

MSK_RES_ERR_DUPLICATE_CONE_NAMES
(*err_duplicate_cone_names*), 123

MSK_RES_ERR_DUPLICATE_CONSTRAINT_NAMES
(*err_duplicate_constraint_names*), 123

MSK_RES_ERR_DUPLICATE_VARIABLE_NAMES
(*err_duplicate_variable_names*), 123

MSK_RES_ERR_END_OF_FILE (*err_end_of_file*),
123

MSK_RES_ERR_FACTOR (*err_factor*), 123

MSK_RES_ERR_FEASREPAIR_CANNOT_RELAX
(*err_feasrepair_cannot_relax*), 123

MSK_RES_ERR_FEASREPAIR_INCONSISTENT_BOUND
(*err_feasrepair_inconsistent_bound*),
123

MSK_RES_ERR_FEASREPAIR_SOLVING_RELAXED
(*err_feasrepair_solving_relaxed*), 123

MSK_RES_ERR_FILE_LICENSE (*err_file_license*),
123

MSK_RES_ERR_FILE_OPEN (*err_file_open*), 123

MSK_RES_ERR_FILE_READ (*err_file_read*), 123

MSK_RES_ERR_FILE_WRITE (*err_file_write*), 123

MSK_RES_ERR_FIRST (*err_first*), 123

MSK_RES_ERR_FIRSTI (*err_firsti*), 123

MSK_RES_ERR_FIRSTJ (*err_firstj*), 123

MSK_RES_ERR_FIXED_BOUND_VALUES
(*err_fixed_bound_values*), 123

MSK_RES_ERR_FLEXLM (*err_flexlm*), 123

MSK_RES_ERR_GLOBAL_INV_CONIC_PROBLEM (<i>err_global_inv_conic_problem</i>), 123	MSK_RES_ERR_INV_QCON_SUBI (<i>err_inv_qcon_subi</i>), 125
MSK_RES_ERR_HUGE_AIJ (<i>err_huge_aij</i>), 123	MSK_RES_ERR_INV_QCON_SUBJ (<i>err_inv_qcon_subj</i>), 125
MSK_RES_ERR_HUGE_C (<i>err_huge_c</i>), 123	MSK_RES_ERR_INV_QCON_SUBK (<i>err_inv_qcon_subk</i>), 125
MSK_RES_ERR_IDENTICAL_TASKS (<i>err_identical_tasks</i>), 123	MSK_RES_ERR_INV_QCON_VAL (<i>err_inv_qcon_val</i>), 125
MSK_RES_ERR_IN_ARGUMENT (<i>err_in_argument</i>), 124	MSK_RES_ERR_INV_QOBJ_SUBI (<i>err_inv_qobj_subi</i>), 125
MSK_RES_ERR_INDEX (<i>err_index</i>), 124	MSK_RES_ERR_INV_QOBJ_SUBJ (<i>err_inv_qobj_subj</i>), 125
MSK_RES_ERR_INDEX_ARR_IS_TOO_LARGE (<i>err_index_arr_is_too_large</i>), 124	MSK_RES_ERR_INV_QOBJ_VAL (<i>err_inv_qobj_val</i>), 125
MSK_RES_ERR_INDEX_ARR_IS_TOO_SMALL (<i>err_index_arr_is_too_small</i>), 124	MSK_RES_ERR_INV_SK (<i>err_inv_sk</i>), 125
MSK_RES_ERR_INDEX_IS_TOO_LARGE (<i>err_index_is_too_large</i>), 124	MSK_RES_ERR_INV_SK_STR (<i>err_inv_sk_str</i>), 125
MSK_RES_ERR_INDEX_IS_TOO_SMALL (<i>err_index_is_too_small</i>), 124	MSK_RES_ERR_INV_SKC (<i>err_inv_skc</i>), 125
MSK_RES_ERR_INF_DOU_INDEX (<i>err_inf_dou_index</i>), 124	MSK_RES_ERR_INV_SKN (<i>err_inv_skn</i>), 125
MSK_RES_ERR_INF_DOU_NAME (<i>err_inf_dou_name</i>), 124	MSK_RES_ERR_INV_SKX (<i>err_inv_skc</i>), 125
MSK_RES_ERR_INF_INT_INDEX (<i>err_inf_int_index</i>), 124	MSK_RES_ERR_INV_VAR_TYPE (<i>err_inv_var_type</i>), 125
MSK_RES_ERR_INF_INT_NAME (<i>err_inf_int_name</i>), 124	MSK_RES_ERR_INVALID_ACCMODE (<i>err_invalid_accmode</i>), 125
MSK_RES_ERR_INF_LINT_INDEX (<i>err_inf_lint_index</i>), 124	MSK_RES_ERR_INVALID_AIJ (<i>err_invalid_aij</i>), 125
MSK_RES_ERR_INF_LINT_NAME (<i>err_inf_lint_name</i>), 124	MSK_RES_ERR_INVALID_AMPL_STUB (<i>err_invalid_ampl_stub</i>), 125
MSK_RES_ERR_INF_TYPE (<i>err_inf_type</i>), 124	MSK_RES_ERR_INVALID_BARVAR_NAME (<i>err_invalid_barvar_name</i>), 126
MSK_RES_ERR_INFEAS_UNDEFINED (<i>err_infeas_undefined</i>), 124	MSK_RES_ERR_INVALID_COMPRESSION (<i>err_invalid_compression</i>), 126
MSK_RES_ERR_INFINITE_BOUND (<i>err_infinite_bound</i>), 124	MSK_RES_ERR_INVALID_CON_NAME (<i>err_invalid_con_name</i>), 126
MSK_RES_ERR_INT64_TO_INT32_CAST (<i>err_int64_to_int32_cast</i>), 124	MSK_RES_ERR_INVALID_CONE_NAME (<i>err_invalid_cone_name</i>), 126
MSK_RES_ERR_INTERNAL (<i>err_internal</i>), 124	MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_CONES (<i>err_invalid_file_format_for_cones</i>), 126
MSK_RES_ERR_INTERNAL_TEST_FAILED (<i>err_internal_test_failed</i>), 124	MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_GENERAL_NL (<i>err_invalid_file_format_for_general_nl</i>), 126
MSK_RES_ERR_INV_APTRE (<i>err_inv_aptre</i>), 124	MSK_RES_ERR_INVALID_FILE_FORMAT_FOR_SYM_MAT (<i>err_invalid_file_format_for_sym_mat</i>), 126
MSK_RES_ERR_INV_BK (<i>err_inv_bk</i>), 124	MSK_RES_ERR_INVALID_FILE_NAME (<i>err_invalid_file_name</i>), 126
MSK_RES_ERR_INV_BKC (<i>err_inv_bkc</i>), 124	MSK_RES_ERR_INVALID_FORMAT_TYPE (<i>err_invalid_format_type</i>), 126
MSK_RES_ERR_INV_BKX (<i>err_inv_bkx</i>), 124	MSK_RES_ERR_INVALID_IDX (<i>err_invalid_idx</i>), 126
MSK_RES_ERR_INV_CONE_TYPE (<i>err_inv_cone_type</i>), 124	MSK_RES_ERR_INVALID_IOMODE (<i>err_invalid_iomode</i>), 126
MSK_RES_ERR_INV_CONE_TYPE_STR (<i>err_inv_cone_type_str</i>), 124	MSK_RES_ERR_INVALID_MAX_NUM (<i>err_invalid_max_num</i>), 126
MSK_RES_ERR_INV_MARKI (<i>err_inv_marki</i>), 125	MSK_RES_ERR_INVALID_NAME_IN_SOL_FILE (<i>err_invalid_name_in_sol_file</i>), 126
MSK_RES_ERR_INV_MARKJ (<i>err_inv_markj</i>), 125	MSK_RES_ERR_INVALID_OBJ_NAME (<i>err_invalid_obj_name</i>), 126
MSK_RES_ERR_INV_NAME_ITEM (<i>err_inv_name_item</i>), 125	
MSK_RES_ERR_INV_NUMI (<i>err_inv_numi</i>), 125	
MSK_RES_ERR_INV_NUMJ (<i>err_inv_numj</i>), 125	
MSK_RES_ERR_INV_OPTIMIZER (<i>err_inv_optimizer</i>), 125	
MSK_RES_ERR_INV_PROBLEM (<i>err_inv_problem</i>), 125	

MSK_RES_ERR_INVALID_OBJECTIVE_SENSE
(*err_invalid_objective_sense*), 126

MSK_RES_ERR_INVALID_PROBLEM_TYPE
(*err_invalid_problem_type*), 126

MSK_RES_ERR_INVALID_SOL_FILE_NAME
(*err_invalid_sol_file_name*), 126

MSK_RES_ERR_INVALID_STREAM
(*err_invalid_stream*), 126

MSK_RES_ERR_INVALID_SURPLUS
(*err_invalid_surplus*), 126

MSK_RES_ERR_INVALID_SYM_MAT_DIM
(*err_invalid_sym_mat_dim*), 126

MSK_RES_ERR_INVALID_TASK (*err_invalid_task*),
126

MSK_RES_ERR_INVALID_UTF8 (*err_invalid_utf8*),
126

MSK_RES_ERR_INVALID_VAR_NAME
(*err_invalid_var_name*), 126

MSK_RES_ERR_INVALID_WCHAR
(*err_invalid_wchar*), 127

MSK_RES_ERR_INVALID_WHICH_SOL
(*err_invalid_whichsol*), 127

MSK_RES_ERR_JSON_DATA (*err_json_data*), 127

MSK_RES_ERR_JSON_FORMAT (*err_json_format*),
127

MSK_RES_ERR_JSON_MISSING_DATA
(*err_json_missing_data*), 127

MSK_RES_ERR_JSON_NUMBER_OVERFLOW
(*err_json_number_overflow*), 127

MSK_RES_ERR_JSON_STRING (*err_json_string*),
127

MSK_RES_ERR_JSON_SYNTAX (*err_json_syntax*),
127

MSK_RES_ERR_LAST (*err_last*), 127

MSK_RES_ERR_LAST_I (*err_lasti*), 127

MSK_RES_ERR_LAST_J (*err_lastj*), 127

MSK_RES_ERR_LAU_ARG_K (*err_lau_arg_k*), 127

MSK_RES_ERR_LAU_ARG_M (*err_lau_arg_m*), 127

MSK_RES_ERR_LAU_ARG_N (*err_lau_arg_n*), 127

MSK_RES_ERR_LAU_ARG_TRANS
(*err_lau_arg_trans*), 127

MSK_RES_ERR_LAU_ARG_TRANSA
(*err_lau_arg_transa*), 127

MSK_RES_ERR_LAU_ARG_TRANSB
(*err_lau_arg_transb*), 127

MSK_RES_ERR_LAU_ARG_UPLO (*err_lau_arg_uplo*),
127

MSK_RES_ERR_LAU_INVALID_LOWER_TRIANGULAR_MATRIX
(*err_lau_invalid_lower_triangular_matrix*),
127

MSK_RES_ERR_LAU_INVALID_SPARSE_SYMMETRIC_MATRIX
(*err_lau_invalid_sparse_symmetric_matrix*),
127

MSK_RES_ERR_LAU_NOT_POSITIVE_DEFINITE
(*err_lau_not_positive_definite*), 127

MSK_RES_ERR_LAU_SINGULAR_MATRIX
(*err_lau_singular_matrix*), 127

MSK_RES_ERR_LAU_UNKNOWN (*err_lau_unknown*),
127

MSK_RES_ERR_LICENSE (*err_license*), 128

MSK_RES_ERR_LICENSE_CANNOT_ALLOCATE
(*err_license_cannot_allocate*), 128

MSK_RES_ERR_LICENSE_CANNOT_CONNECT
(*err_license_cannot_connect*), 128

MSK_RES_ERR_LICENSE_EXPIRED
(*err_license_expired*), 128

MSK_RES_ERR_LICENSE_FEATURE
(*err_license_feature*), 128

MSK_RES_ERR_LICENSE_INVALID_HOSTID
(*err_license_invalid_hostid*), 128

MSK_RES_ERR_LICENSE_MAX (*err_license_max*),
128

MSK_RES_ERR_LICENSE_MOSEKLM_DAEMON
(*err_license_moseklm_daemon*), 128

MSK_RES_ERR_LICENSE_NO_SERVER_LINE
(*err_license_no_server_line*), 128

MSK_RES_ERR_LICENSE_NO_SERVER_SUPPORT
(*err_license_no_server_support*), 128

MSK_RES_ERR_LICENSE_SERVER
(*err_license_server*), 128

MSK_RES_ERR_LICENSE_SERVER_VERSION
(*err_license_server_version*), 128

MSK_RES_ERR_LICENSE_VERSION
(*err_license_version*), 128

MSK_RES_ERR_LINK_FILE_DLL (*err_link_file_dll*),
128

MSK_RES_ERR_LIVING_TASKS (*err_living_tasks*),
128

MSK_RES_ERR_LOWER_BOUND_IS_A_NAN
(*err_lower_bound_is_a_nan*), 128

MSK_RES_ERR_LP_DUP_SLACK_NAME
(*err_lp_dup_slack_name*), 128

MSK_RES_ERR_LP_EMPTY (*err_lp_empty*), 128

MSK_RES_ERR_LP_FILE_FORMAT
(*err_lp_file_format*), 129

MSK_RES_ERR_LP_FORMAT (*err_lp_format*), 129

MSK_RES_ERR_LP_FREE_CONSTRAINT
(*err_lp_free_constraint*), 129

MSK_RES_ERR_LP_INCOMPATIBLE
(*err_lp_incompatible*), 129

MSK_RES_ERR_LP_INVALID_CON_NAME
(*err_lp_invalid_con_name*), 129

MSK_RES_ERR_LP_INVALID_VAR_NAME
(*err_lp_invalid_var_name*), 129

MSK_RES_ERR_LP_WRITE_CONIC_PROBLEM
(*err_lp_write_conic_problem*), 129

MSK_RES_ERR_LP_WRITE_GECO_PROBLEM
(*err_lp_write_geco_problem*), 129

MSK_RES_ERR_LU_MAX_NUM_TRIES
(*err_lu_max_num_tries*), 129

MSK_RES_ERR_MAX_LEN_IS_TOO_SMALL
(*err_max_len_is_too_small*), 129

MSK_RES_ERR_MAXNUMBARVAR
(*err_maxnumbarvar*), 129

MSK_RES_ERR_MAXNUMCON (*err_maxnumcon*), 129

MSK_RES_ERR_MAXNUMCONE (<i>err_maxnumcone</i>), 129	MSK_RES_ERR_MPS_NULL_VAR_NAME (<i>err_mps_null_var_name</i>), 130
MSK_RES_ERR_MAXNUMQNZ (<i>err_maxnumqnz</i>), 129	MSK_RES_ERR_MPS_SPLITTED_VAR (<i>err_mps_splitted_var</i>), 130
MSK_RES_ERR_MAXNUMVAR (<i>err_maxnumvar</i>), 129	MSK_RES_ERR_MPS_TAB_IN_FIELD2 (<i>err_mps_tab_in_field2</i>), 130
MSK_RES_ERR_MIO_INTERNAL (<i>err_mio_internal</i>), 129	MSK_RES_ERR_MPS_TAB_IN_FIELD3 (<i>err_mps_tab_in_field3</i>), 130
MSK_RES_ERR_MIO_INVALID_NODE_OPTIMIZER (<i>err_mio_invalid_node_optimizer</i>), 129	MSK_RES_ERR_MPS_TAB_IN_FIELD5 (<i>err_mps_tab_in_field5</i>), 131
MSK_RES_ERR_MIO_INVALID_ROOT_OPTIMIZER (<i>err_mio_invalid_root_optimizer</i>), 129	MSK_RES_ERR_MPS_UNDEF_CON_NAME (<i>err_mps_undef_con_name</i>), 131
MSK_RES_ERR_MIO_NO_OPTIMIZER (<i>err_mio_no_optimizer</i>), 129	MSK_RES_ERR_MPS_UNDEF_VAR_NAME (<i>err_mps_undef_var_name</i>), 131
MSK_RES_ERR_MIO_NOT_LOADED (<i>err_mio_not_loaded</i>), 129	MSK_RES_ERR_MUL_A_ELEMENT (<i>err_mul_a_element</i>), 131
MSK_RES_ERR_MISSING_LICENSE_FILE (<i>err_missing_license_file</i>), 129	MSK_RES_ERR_NAME_IS_NULL (<i>err_name_is_null</i>), 131
MSK_RES_ERR_MIXED_CONIC_AND_NL (<i>err_mixed_conic_and_nl</i>), 129	MSK_RES_ERR_NAME_MAX_LEN (<i>err_name_max_len</i>), 131
MSK_RES_ERR_MPS_CONE_OVERLAP (<i>err_mps_cone_overlap</i>), 130	MSK_RES_ERR_NAN_IN_BLC (<i>err_nan_in_blc</i>), 131
MSK_RES_ERR_MPS_CONE_REPEAT (<i>err_mps_cone_repeat</i>), 130	MSK_RES_ERR_NAN_IN_BLX (<i>err_nan_in_blx</i>), 131
MSK_RES_ERR_MPS_CONE_TYPE (<i>err_mps_cone_type</i>), 130	MSK_RES_ERR_NAN_IN_BUC (<i>err_nan_in_buc</i>), 131
MSK_RES_ERR_MPS_DUPLICATE_Q_ELEMENT (<i>err_mps_duplicate_q_element</i>), 130	MSK_RES_ERR_NAN_IN_BUX (<i>err_nan_in_bux</i>), 131
MSK_RES_ERR_MPS_FILE (<i>err_mps_file</i>), 130	MSK_RES_ERR_NAN_IN_C (<i>err_nan_in_c</i>), 131
MSK_RES_ERR_MPS_INV_BOUND_KEY (<i>err_mps_inv_bound_key</i>), 130	MSK_RES_ERR_NAN_IN_DOUBLE_DATA (<i>err_nan_in_double_data</i>), 131
MSK_RES_ERR_MPS_INV_CON_KEY (<i>err_mps_inv_con_key</i>), 130	MSK_RES_ERR_NEGATIVE_APPEND (<i>err_negative_append</i>), 131
MSK_RES_ERR_MPS_INV_FIELD (<i>err_mps_inv_field</i>), 130	MSK_RES_ERR_NEGATIVE_SURPLUS (<i>err_negative_surplus</i>), 131
MSK_RES_ERR_MPS_INV_MARKER (<i>err_mps_inv_marker</i>), 130	MSK_RES_ERR_NEWER_DLL (<i>err_newer_dll</i>), 131
MSK_RES_ERR_MPS_INV_SEC_NAME (<i>err_mps_inv_sec_name</i>), 130	MSK_RES_ERR_NO_BARS_FOR_SOLUTION (<i>err_no_bars_for_solution</i>), 131
MSK_RES_ERR_MPS_INV_SEC_ORDER (<i>err_mps_inv_sec_order</i>), 130	MSK_RES_ERR_NO_BARX_FOR_SOLUTION (<i>err_no_barx_for_solution</i>), 131
MSK_RES_ERR_MPS_INVALID_OBJ_NAME (<i>err_mps_invalid_obj_name</i>), 130	MSK_RES_ERR_NO_BASIS_SOL (<i>err_no_basis_sol</i>), 131
MSK_RES_ERR_MPS_INVALID_OBJSENSE (<i>err_mps_invalid_objsense</i>), 130	MSK_RES_ERR_NO_DUAL_FOR_ITG_SOL (<i>err_no_dual_for_itg_sol</i>), 131
MSK_RES_ERR_MPS_MUL_CON_NAME (<i>err_mps_mul_con_name</i>), 130	MSK_RES_ERR_NO_DUAL_INFEAS_CER (<i>err_no_dual_infeas_cer</i>), 131
MSK_RES_ERR_MPS_MUL_CSEC (<i>err_mps_mul_csec</i>), 130	MSK_RES_ERR_NO_INIT_ENV (<i>err_no_init_env</i>), 131
MSK_RES_ERR_MPS_MUL_QOBJ (<i>err_mps_mul_qobj</i>), 130	MSK_RES_ERR_NO_OPTIMIZER_VAR_TYPE (<i>err_no_optimizer_var_type</i>), 131
MSK_RES_ERR_MPS_MUL_QSEC (<i>err_mps_mul_qsec</i>), 130	MSK_RES_ERR_NO_PRIMAL_INFEAS_CER (<i>err_no_primal_infeas_cer</i>), 132
MSK_RES_ERR_MPS_NO_OBJECTIVE (<i>err_mps_no_objective</i>), 130	MSK_RES_ERR_NO_SNX_FOR_BAS_SOL (<i>err_no_snx_for_bas_sol</i>), 132
MSK_RES_ERR_MPS_NON_SYMMETRIC_Q (<i>err_mps_non_symmetric_q</i>), 130	MSK_RES_ERR_NO_SOLUTION_IN_CALLBACK (<i>err_no_solution_in_callback</i>), 132
MSK_RES_ERR_MPS_NULL_CON_NAME (<i>err_mps_null_con_name</i>), 130	MSK_RES_ERR_NON_UNIQUE_ARRAY (<i>err_non_unique_array</i>), 132
	MSK_RES_ERR_NONCONVEX (<i>err_nonconvex</i>), 132

MSK_RES_ERR_NONLINEAR_EQUALITY
(*err_nonlinear_equality*), 132

MSK_RES_ERR_NONLINEAR_FUNCTIONS_NOT_ALLOWED
(*err_nonlinear_functions_not_allowed*),
132

MSK_RES_ERR_NONLINEAR_RANGED
(*err_nonlinear_ranged*), 132

MSK_RES_ERR_NR_ARGUMENTS
(*err_nr_arguments*), 132

MSK_RES_ERR_NULL_ENV (*err_null_env*), 132

MSK_RES_ERR_NULL_POINTER (*err_null_pointer*),
132

MSK_RES_ERR_NULL_TASK (*err_null_task*), 132

MSK_RES_ERR_NUMCONLIM (*err_numconlim*), 132

MSK_RES_ERR_NUMVARLIM (*err_numvarlim*), 132

MSK_RES_ERR_OBJ_Q_NOT_NSD
(*err_obj_q_not_nsd*), 132

MSK_RES_ERR_OBJ_Q_NOT_PSD
(*err_obj_q_not_psd*), 132

MSK_RES_ERR_OBJECTIVE_RANGE
(*err_objective_range*), 132

MSK_RES_ERR_OLDER_DLL (*err_older_dll*), 132

MSK_RES_ERR_OPEN_DL (*err_open_dl*), 132

MSK_RES_ERR_OPF_FORMAT (*err_opf_format*), 132

MSK_RES_ERR_OPF_NEW_VARIABLE
(*err_opf_new_variable*), 132

MSK_RES_ERR_OPF_PREMATURE_EOF
(*err_opf_premature_eof*), 133

MSK_RES_ERR_OPTIMIZER_LICENSE
(*err_optimizer_license*), 133

MSK_RES_ERR_OVERFLOW (*err_overflow*), 133

MSK_RES_ERR_PARAM_INDEX (*err_param_index*),
133

MSK_RES_ERR_PARAM_IS_TOO_LARGE
(*err_param_is_too_large*), 133

MSK_RES_ERR_PARAM_IS_TOO_SMALL
(*err_param_is_too_small*), 133

MSK_RES_ERR_PARAM_NAME (*err_param_name*),
133

MSK_RES_ERR_PARAM_NAME_DOU
(*err_param_name_dou*), 133

MSK_RES_ERR_PARAM_NAME_INT
(*err_param_name_int*), 133

MSK_RES_ERR_PARAM_NAME_STR
(*err_param_name_str*), 133

MSK_RES_ERR_PARAM_TYPE (*err_param_type*), 133

MSK_RES_ERR_PARAM_VALUE_STR
(*err_param_value_str*), 133

MSK_RES_ERR_PLATFORM_NOT_LICENSED
(*err_platform_not_licensed*), 133

MSK_RES_ERR_POSTSOLVE (*err_postsolve*), 133

MSK_RES_ERR_PRO_ITEM (*err_pro_item*), 133

MSK_RES_ERR_PROB_LICENSE (*err_prob_license*),
133

MSK_RES_ERR_QCON_SUBI_TOO_LARGE
(*err_qcon_subi_too_large*), 133

MSK_RES_ERR_QCON_SUBI_TOO_SMALL
(*err_qcon_subi_too_small*), 133

MSK_RES_ERR_QCON_UPPER_TRIANGLE
(*err_qcon_upper_triangle*), 133

MSK_RES_ERR_QOBJ_UPPER_TRIANGLE
(*err_qobj_upper_triangle*), 133

MSK_RES_ERR_READ_FORMAT (*err_read_format*),
133

MSK_RES_ERR_READ_LP_MISSING_END_TAG
(*err_read_lp_missing_end_tag*), 133

MSK_RES_ERR_READ_LP_NONEXISTING_NAME
(*err_read_lp_nonexisting_name*),
134

MSK_RES_ERR_REMOVE_CONE_VARIABLE
(*err_remove_cone_variable*), 134

MSK_RES_ERR_REPAIR_INVALID_PROBLEM
(*err_repair_invalid_problem*), 134

MSK_RES_ERR_REPAIR_OPTIMIZATION_FAILED
(*err_repair_optimization_failed*), 134

MSK_RES_ERR_SEN_BOUND_INVALID_LO
(*err_sen_bound_invalid_lo*), 134

MSK_RES_ERR_SEN_BOUND_INVALID_UP
(*err_sen_bound_invalid_up*), 134

MSK_RES_ERR_SEN_FORMAT (*err_sen_format*), 134

MSK_RES_ERR_SEN_INDEX_INVALID
(*err_sen_index_invalid*), 134

MSK_RES_ERR_SEN_INDEX_RANGE
(*err_sen_index_range*), 134

MSK_RES_ERR_SEN_INVALID_REGEXP
(*err_sen_invalid_regexp*), 134

MSK_RES_ERR_SEN_NUMERICAL
(*err_sen_numerical*), 134

MSK_RES_ERR_SEN_SOLUTION_STATUS
(*err_sen_solution_status*), 134

MSK_RES_ERR_SEN_UNDEF_NAME
(*err_sen_undef_name*), 134

MSK_RES_ERR_SEN_UNHANDLED_PROBLEM_TYPE
(*err_sen_unhandled_problem_type*),
134

MSK_RES_ERR_SERVER_CONNECT
(*err_server_connect*), 134

MSK_RES_ERR_SERVER_PROTOCOL
(*err_server_protocol*), 134

MSK_RES_ERR_SERVER_STATUS
(*err_server_status*), 134

MSK_RES_ERR_SERVER_TOKEN (*err_server_token*),
134

MSK_RES_ERR_SIZE_LICENSE (*err_size_license*),
134

MSK_RES_ERR_SIZE_LICENSE_CON
(*err_size_license_con*), 134

MSK_RES_ERR_SIZE_LICENSE_INTVAR
(*err_size_license_intvar*), 134

MSK_RES_ERR_SIZE_LICENSE_NUMCORES
(*err_size_license_numcores*), 134

MSK_RES_ERR_SIZE_LICENSE_VAR
(*err_size_license_var*), 135

MSK_RES_ERR_SOL_FILE_INVALID_NUMBER
(*err_sol_file_invalid_number*), 135

MSK_RES_ERR_SOLITEM (*err_solitem*), 135

MSK_RES_ERR_SOLVER_PROBTYPE (<i>err_solver_probtype</i>), 135	MSK_RES_ERR_UNHANDLED_SOLUTION_STATUS (<i>err_unhandled_solution_status</i>), 136
MSK_RES_ERR_SPACE (<i>err_space</i>), 135	MSK_RES_ERR_UNKNOWN (<i>err_unknown</i>), 136
MSK_RES_ERR_SPACE_LEAKING (<i>err_space_leaking</i>), 135	MSK_RES_ERR_UPPER_BOUND_IS_A_NAN (<i>err_upper_bound_is_a_nan</i>), 136
MSK_RES_ERR_SPACE_NO_INFO (<i>err_space_no_info</i>), 135	MSK_RES_ERR_UPPER_TRIANGLE (<i>err_upper_triangle</i>), 136
MSK_RES_ERR_SYM_MAT_DUPLICATE (<i>err_sym_mat_duplicate</i>), 135	MSK_RES_ERR_USER_FUNC_RET (<i>err_user_func_ret</i>), 136
MSK_RES_ERR_SYM_MAT_HUGE (<i>err_sym_mat_huge</i>), 135	MSK_RES_ERR_USER_FUNC_RET_DATA (<i>err_user_func_ret_data</i>), 136
MSK_RES_ERR_SYM_MAT_INVALID (<i>err_sym_mat_invalid</i>), 135	MSK_RES_ERR_USER_NLO_EVAL (<i>err_user_nlo_eval</i>), 136
MSK_RES_ERR_SYM_MAT_INVALID_COL_INDEX (<i>err_sym_mat_invalid_col_index</i>), 135	MSK_RES_ERR_USER_NLO_EVAL_HESSUBI (<i>err_user_nlo_eval_hessubi</i>), 137
MSK_RES_ERR_SYM_MAT_INVALID_ROW_INDEX (<i>err_sym_mat_invalid_row_index</i>), 135	MSK_RES_ERR_USER_NLO_EVAL_HESSUBJ (<i>err_user_nlo_eval_hessubj</i>), 137
MSK_RES_ERR_SYM_MAT_INVALID_VALUE (<i>err_sym_mat_invalid_value</i>), 135	MSK_RES_ERR_USER_NLO_FUNC (<i>err_user_nlo_func</i>), 137
MSK_RES_ERR_SYM_MAT_NOT_LOWER_TRINGULAR (<i>err_sym_mat_not_lower_tringular</i>), 135	MSK_RES_ERR_WHICHITEM_NOT_ALLOWED (<i>err_whichitem_not_allowed</i>), 137
MSK_RES_ERR_TASK_INCOMPATIBLE (<i>err_task_incompatible</i>), 135	MSK_RES_ERR_WHICHSOL (<i>err_whichsol</i>), 137
MSK_RES_ERR_TASK_INVALID (<i>err_task_invalid</i>), 135	MSK_RES_ERR_WRITE_LP_FORMAT (<i>err_write_lp_format</i>), 137
MSK_RES_ERR_TASK_WRITE (<i>err_task_write</i>), 135	MSK_RES_ERR_WRITE_LP_NON_UNIQUE_NAME (<i>err_write_lp_non_unique_name</i>), 137
MSK_RES_ERR_THREAD_COND_INIT (<i>err_thread_cond_init</i>), 135	MSK_RES_ERR_WRITE_MPS_INVALID_NAME (<i>err_write_mps_invalid_name</i>), 137
MSK_RES_ERR_THREAD_CREATE (<i>err_thread_create</i>), 135	MSK_RES_ERR_WRITE_OPF_INVALID_VAR_NAME (<i>err_write_opf_invalid_var_name</i>), 137
MSK_RES_ERR_THREAD_MUTEX_INIT (<i>err_thread_mutex_init</i>), 135	MSK_RES_ERR_WRITING_FILE (<i>err_writing_file</i>), 137
MSK_RES_ERR_THREAD_MUTEX_LOCK (<i>err_thread_mutex_lock</i>), 135	MSK_RES_ERR_XML_INVALID_PROBLEM_TYPE (<i>err_xml_invalid_problem_type</i>), 137
MSK_RES_ERR_THREAD_MUTEX_UNLOCK (<i>err_thread_mutex_unlock</i>), 136	MSK_RES_ERR_Y_IS_UNDEFINED (<i>err_y_is_undefined</i>), 137
MSK_RES_ERR_TOCONIC_CONSTR_NOT_CONIC (<i>err_toconic_constr_not_conic</i>), 136	
MSK_RES_ERR_TOCONIC_CONSTR_Q_NOT_PSD (<i>err_toconic_constr_q_not_psd</i>), 136	
MSK_RES_ERR_TOCONIC_CONSTRAINT_FX (<i>err_toconic_constraint_fx</i>), 136	
MSK_RES_ERR_TOCONIC_CONSTRAINT_RA (<i>err_toconic_constraint_ra</i>), 136	
MSK_RES_ERR_TOCONIC_OBJECTIVE_NOT_PSD (<i>err_toconic_objective_not_psd</i>), 136	
MSK_RES_ERR_TOO_SMALL_MAX_NUM_NZ (<i>err_too_small_max_num_nz</i>), 136	
MSK_RES_ERR_TOO_SMALL_MAXNUMANZ (<i>err_too_small_maxnumanz</i>), 136	
MSK_RES_ERR_UNB_STEP_SIZE (<i>err_unb_step_size</i>), 136	
MSK_RES_ERR_UNDEF_SOLUTION (<i>err_undef_solution</i>), 136	
MSK_RES_ERR_UNDEFINED_OBJECTIVE_SENSE (<i>err_undefined_objective_sense</i>), 136	